

















CONTENTS	
PAGE NO.	SCHEMATIC PAGE
1	01_COVER
2	02_CORE
3	03_NBIOT
4	04_RADER
5	05_POWER

REV	Description	DATE	BY
1.0	First Design	2017-10-09	Yunjie-K of MVB
	去除外部8M晶振，修改C5封装为Cap6mm	2017-10-16	Yunjie-K of MVB
1.1	sx1208替换为si4438	2017-11-30	Yunjie-K of MVB
	去除移远BC95直插座，去除霍尔元件，增加蜂鸣器		
1.2	蜂鸣器供电使用电池电压，雷达模块增加自设计接口，增加贴片SIM卡支持	2018-01-08	Yunjie-K of MVB
1.3	修改NB串口直接连接J10排针，不通过1K电阻	2018-01-22	Yunjie-K of MVB
1.4	修改电源供电方案，车位锁采用6V供电，用DCDC（MP2451）替换XC6202，输出3.3V提供MCU与NB、QMC、RF供电。 雷达运放供电采用HT7550降压至5V 移除NB模组DBG接口，和模组程序下载接口	2018-04-16	Yunjie-K of MVB
1.5	MP2359的输出加个8x12mm尺寸的电解电容 电源接口改为3.96间距的接插件 增加JDY-08蓝牙模块接口 增加(正转,反转,VBAT,COM,K3,COM,K2,K1).8个脚 MP2359替换MP2451	2018-05-29	Yunjie-K of MVB












MoveBroad


Title		
01_COVER		
Size	Document Number	Rev
B	<Doc>	1.5
Date: Tuesday, May 29, 2018		Sheet 1 of 5



MoveBroad

Title		02_CORE	
Size		Document Number	
B		<Doc>	
Date:		Thursday, May 31, 2018	
Sheet		2 of 5	
Rev		1.5	





MoveBroad

Title

03_NBIOT

Size

Document Number

Rev

B

<Doc>

1.5

Date:




Tuesday, May 29, 2018

Sheet

3

of

5



MoveBroad

Title

04_RADER

Size

Document Number

B





<Doc>

Rev

1.5

Date: Tuesday, May 29, 2018

Sheet 4 of 5



MoveBroad

Title

05_POWER

Size

Document Number

Rev

B

<Doc>

1.5

Date: Thursday, May 31, 2018

Sheet 5 of 5