

Tips and tricks

Classification metrics

- Confusion matrix
- Accuracy
- Precision, recall
- F1 score
- ROC

Regression metrics

- R squared
- Mallow's CP
- AIC, BIC

Model selection

- Cross-validation
- Regularization

Diagnostics

- Bias/variance tradeoff
- Error/ablative analysis

Want more content like this? [Subscribe here](#) to be notified of new releases!

CS 229 - Machine Learning

English

Supervised Learning	Unsupervised Learning	Deep Learning	Tips and tricks
---------------------	-----------------------	---------------	-----------------

Machine Learning tips and tricks cheatsheet

Star 17,275

By [Afshine Amidi](#) and [Shervine Amidi](#)

Classification metrics

In a context of a binary classification, here are the main metrics that are important to track in order to assess the performance of the model.

▣ **Confusion matrix** — The confusion matrix is used to have a more complete picture when assessing the performance of a model. It is defined as follows:

		Predicted class	
		+	-
Actual class	+	TP True Positives	FN False Negatives Type II error
	-	FP False Positives Type I error	TN True Negatives


▣ **Main metrics** — The following metrics are commonly used to assess the performance of classification models:

Metric	Formula	Interpretation
Accuracy	$\frac{TP + TN}{TP + TN + FP + FN}$	Overall performance of model
Precision	$\frac{TP}{TP + FP}$	How accurate the positive predictions are
Recall Sensitivity	$\frac{TP}{TP + FN}$	Coverage of actual positive sample
Specificity	$\frac{TN}{TN + FP}$	Coverage of actual negative sample
F1 score	$\frac{2TP}{2TP + FP + FN}$	Hybrid metric useful for unbalanced classes

▣ **ROC** — The receiver operating curve, also noted ROC, is the plot of TPR versus FPR by varying the threshold. These metrics are summed up in the table below:

Metric	Formula	Equivalent
True Positive Rate TPR	$\frac{TP}{TP + FN}$	Recall, sensitivity
False Positive Rate FPR	$\frac{FP}{TN + FP}$	1-specificity

▣ **AUC** — The area under the receiving operating curve, also noted AUC or AUROC, is the area below the ROC as shown in the following figure:



Regression metrics

▣ **Basic metrics** — Given a regression model f , the following metrics are commonly used to assess the performance of the model:

Total sum of squares	Explained sum of squares	Residual sum of squares
$SS_{\text{tot}} = \sum_{i=1}^m (y_i - \bar{y})^2$	$SS_{\text{reg}} = \sum_{i=1}^m (f(x_i) - \bar{y})^2$	$SS_{\text{res}} = \sum_{i=1}^m (y_i - f(x_i))^2$

▣ **Coefficient of determination** — The coefficient of determination, often noted R^2 or r^2 , provides a measure of how well the observed outcomes are replicated by the model and is defined as follows:

$$R^2 = 1 - \frac{SS_{\text{res}}}{SS_{\text{tot}}}$$

▣ **Main metrics** — The following metrics are commonly used to assess the performance of regression models, by taking into account the number of variables n that they take into consideration:

Mallow's Cp	AIC	BIC	Adjusted R^2
$\frac{SS_{\text{res}} + 2(n+1)\hat{\sigma}^2}{m}$	$2[(n+2) - \log(L)]$	$\log(m)(n+2) - 2\log(L)$	$1 - \frac{(1-R^2)(m-1)}{m-n-1}$


where L is the likelihood and $\hat{\sigma}^2$ is an estimate of the variance associated with each response.

Model selection

▣ **Vocabulary** — When selecting a model, we distinguish 3 different parts of the data that we have as follows:

Training set	Validation set	Testing set
<ul style="list-style-type: none">Model is trainedUsually 80% of the dataset	<ul style="list-style-type: none">Model is assessedUsually 20% of the datasetAlso called hold-out or development set	<ul style="list-style-type: none">Model gives predictionsUnseen data


Once the model has been chosen, it is trained on the entire dataset and tested on the unseen test set. These are represented in the figure below:






▣ **Cross-validation** — Cross-validation, also noted CV, is a method that is used to select a model that does not rely too much on the initial training set. The different types are summed up in the table below:

k-fold	Leave-p-out
<ul style="list-style-type: none">Training on $k-1$ folds and assessment on the remaining oneGenerally $k=5$ or 10	<ul style="list-style-type: none">Training on $n-p$ observations and assessment on the p remaining onesCase $p=1$ is called leave-one-out

The most commonly used method is called k -fold cross-validation and splits the training data into k folds to validate the model on one fold while training the model on the $k-1$ other folds, all of this k times. The error is then averaged over the k folds and is named cross-validation error.



▣ **Regularization** — The regularization procedure aims at avoiding the model to overfit the data and thus deals with high variance issues. The following table sums up the different types of commonly used regularization techniques:










LASSO	Ridge	Elastic Net
<ul style="list-style-type: none">Shrinks coefficients to 0Good for variable selection	Makes coefficients smaller	Tradeoff between variable selection and small coefficients
		
$\dots + \lambda \theta _1$ $\lambda \in \mathbb{R}$	$\dots + \lambda \theta _2^2$ $\lambda \in \mathbb{R}$	$\dots + \lambda \left[(1-\alpha) \theta _1 + \alpha \theta _2^2 \right]$ $\lambda \in \mathbb{R}, \alpha \in [0, 1]$

Diagnostics

▣ **Bias** — The bias of a model is the difference between the expected prediction and the correct model that we try to predict for given data points.

▣ **Variance** — The variance of a model is the variability of the model prediction for given data points.

▣ **Bias/variance tradeoff** — The simpler the model, the higher the bias, and the more complex the model, the higher the variance.

	Underfitting	Just right	Overfitting
Symptoms	<ul style="list-style-type: none">High training errorTraining error close to test errorHigh bias	<ul style="list-style-type: none">Training error slightly lower than test error	<ul style="list-style-type: none">Very low training errorTraining error much lower than test errorHigh variance
Regression illustration			
Classification illustration			
Deep learning illustration			
Possible remedies	<ul style="list-style-type: none">Complexify modelAdd more featuresTrain longer		<ul style="list-style-type: none">Perform regularizationGet more data

▣ **Error analysis** — Error analysis is analyzing the root cause of the difference in performance between the current and the perfect models.

▣ **Ablative analysis** — Ablative analysis is analyzing the root cause of the difference in performance between the current and the baseline models.