

Open-Source Software Practice

2. Git Basics

Instructor: Jaemin Jo (조재민, jmjo@skku.edu)


Interactive Data Computing Lab (*IDCLab*),
College of Computing and Informatics,
Sungkyunkwan University

Version Control System (VCS)

- **A version control system** is a system that records changes to a file or set of files over time.
 - i.e., code versioning
 - revert selected files back to a previous state
 - revert the entire project
 - compare changes over time
 - see who last modified something that might be causing a problem
 - who introduced an issue and when


Local Version Control

- Local version control has limitations.
- No back-ups
- No collaboration
- Hard to maintain multiple files.




Centralized Version Control

- Centralized version control systems are better but have drawbacks.
- Single point of failure
- If the shared server is down, you cannot save versioned changes to anything.
- Require connection to the server
- Examples: CVS, Subversion, Perforce




Distributed Version Control

- Distributed version control systems fully mirror the remote repository to a local machine, including its full history.
- Even the server dies, any of the client repos can be copied back up to the server.
- Examples: ***Git***, Mercurial, Bazaar, Darcs





Distributed Version Control

- For most of time with Git, you will save code changes to your local repos.
 - `git commit`
- Sometimes, you will upload the changes in the local repo to the remote.
 - `git push`
- Or, download the changes from the remote to reflect changes made by others.
 - `git fetch`



Snapshots, Not Differences

- Git uses snapshot-based version control
 - c.f. delta-based version control which is used in many other VCSs
- Git stores the snapshots of every file modified in each version.
 - Faster lookups, but uses more disk space



Nearly Every Operation is Local











- Most operations in Git need only local files and resources to operate.
- This is very convenient especially when the network is unavailable.
- Local operations are done faster than remote ones.

Git Generally Only Adds Data

- When you do actions in Git, nearly all of them only add data to the Git database.
- It is hard to make the system to erase data in any way if you regularly push your local repo to the remote.


.git Directory

- If you initialize a Git repo (or cloning a Git repo), a hidden directory named “.git” is created.
- This is the local database of the Git repo, and you must not delete or modify this directory.

Name	Date modified	Type	Size
 hooks	1/18/2021 3:45 PM	File folder	
 info	1/18/2021 3:45 PM	File folder	
 logs	1/18/2021 3:46 PM	File folder	
 objects	1/18/2021 3:51 PM	File folder	
 refs	1/18/2021 3:45 PM	File folder	
 COMMIT_EDITMSG	1/18/2021 3:50 PM	File	1 KB
 config	1/18/2021 3:45 PM	File	1 KB
 description	1/18/2021 3:45 PM	File	1 KB
 HEAD	1/18/2021 3:45 PM	File	1 KB
 index	1/18/2021 3:51 PM	File	1 KB

Four States of Files

- Your files in a Git repo will be in any of the following 4 states:
- **Untracked:** The file is not under version control. Ignored by Git.
- **Unmodified:** The file is under VC, but not modified. You don't have to record changes for this file.
- **Modified:** The file is under VC and modified. You should record the changes.
- **Staged:** The file is under VC, modified, and the changes to the file are ready to commit.
- **Committed:** The changes were committed. This is the same as the “unmodified” state.




Why Modified and Staged?

- Why is an extra state “staged”?
- Suppose you modified 10 files.
- Sometimes, you want to record the changes only made to specific files.
 - e.g., commit the changes made to “interface.h” not “server.h”
- You can commit files selectively by staging them only.
 - *git add interface.h* vs. *git add .*
 - 10 modified, 5 staged for commit

Three Main Sections

- **Working directory** (or working tree) is a single checkout of one version of the project.
 - Initially, all files are in an unmodified state.
 - Modify some files (using a text editor).
 - Selectively stage files that you want to be part of your next commit (`git add`).
 - **Staging area** (or index) has files that are staged for the next commit.
 - Check out the staged files (`git status`), and do a commit (`git commit`)
 - **Local Git repo** (`.git`) stores commits.
- Note that we don't consider a remote repo for now.

Three Main Sections



On your computer

Basic Git Workflow (Addition)

- Suppose you want to add a new file “new.txt” to an existing Git repo.
 1. Create “new.txt” using your favorite editor (*untracked* for now).
 2. Add “new.txt” to the staging area by “`git add new.txt`” (*staged*).
 3. Commit the file by “`git commit`” (*committed and unmodified*).
- untracked → staged → committed (= unmodified)

Basic Git Workflow (Modification)


- Suppose you want to modify the file “new.txt”.
 1. new.txt is in an *unmodified* state.
 2. Modify new.txt (*modified*).
 3. Stage new.txt by “`git add new.txt`” (*staged*).
 4. Commit the file by “`git commit`” (*committed and unmodified*).
- unmodified → modified → staged → committed (= unmodified)

Basic Git Workflow (Deletion)

- Suppose you want to delete the file “new.txt”.
 1. new.txt is in an *unmodified* state.
 2. Delete new.txt (*modified*).
 3. Stage new.txt by “`git add new.txt`” (*staged*).
 4. Commit the file by “`git commit`” (*untracked*).
- unmodified → modified → untracked
- The file is removed from both the working directory and the local repository.

Git Commands

- git init
- git clone
- git add
 - .gitignore
- git commit
- git reset
- git rm
- git status





Prerequisites

- Install Visual Studio Code
- Install Git
 - Windows: <https://git-scm.com/>
 - If you already have Git, update it to the latest version.
 - `git update-git-for-windows`
 - Mac
 - Type `git --version` on your terminal. It will prompt you to install it.
- Check out the version by `git --version`
- My Git version is `git version 2.37.2.windows`

Prerequisites


- Open Git command line
 - Windows
 - Go to your Git repo (or an empty directory that you want to initialize as Git repo).
 - Right-click in the Explorer.
 - Click on “Git Bash Here” in the context menu.
 - Mac
 - Open the Terminal app
 - Go to your Git repo (or an empty directory that you want to initialize as Git repo) using `cd`.
 - Type commands on the terminal.



Getting a Git Repository

- There are two ways to get a Git Repository:
- Initialize one from scratch:
 - Go to an empty directory on your terminal (perhaps, you are already in it).
 - `cd path-to-directory`
 - `git init`
- You can clone an existing repository.
 - `git clone <url to an existing git repo>`

Cloning a Git Repository



Search or jump to... Pull requests Issues Marketplace Explore

d3 / d3 Watch 4k Unstar 95.3k Fork 22.4k

<> Code 6 Issues Pull requests 2 Actions Wiki Security Insights

master 25 branches 269 tags

mbostock 6.3.1

img	Add pack images.
test	Update dependencies.
.gitignore	Prepare for major release.
API.md	Update d3-array.
CHANGES.md	Update CHANGES.
ISSUE_TEMPLATE.md	Update ISSUE_TEMPLATE.md
LICENSE	Update year.
README.md	link to v6
d3.sublime-project	Update dependencies.
index.js	two
package.json	6.3.1
rollup.config.js	Squelch Rollup warnings.
yarn.lock	Update d3-array.

Go to file Add file Code

Clone

HTTPS SSH GitHub CLI

https://github.com/d3/d3.git

Use Git or checkout with SVN using the web URL.

Open with GitHub Desktop

Download ZIP

About

Bring data to life with SVG, Canvas and HTML.

d3js.org

visualization

Readme

BSD-3-Clause License

Releases 269

v6.3.1 Latest on 9 Dec 2020

+ 268 releases


Packages

No packages published

Used by 188k


Add a New File

- Let's add README.txt to the repo.
1. Create README.txt with your favorite text editor.
 2. Write "Hello, World" in README.txt
 3. `git add README.txt`



Check the States

- Check the state of README.txt by typing `git status`.



```
MINGW64:/d/pratice

jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$ git add README.txt

jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$ git status
On branch master
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
    new file:   README.txt

jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$
```



Unstage a File

- `git restore --staged README.txt` will unstage the file.
- You don't have to remember this command. There is a hint.

```
MINGW64:/d/pratice
jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$ git add README.txt

jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$ git status
On branch master
changes to be committed:
  (use "git restore --staged <file>..." to unstage)
    new file:   README.txt

jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$
```



Add the File Again

- Let's add README.txt again, but this time type `git add .`
- This command adds **all untracked or modified** files to the staging area.
 - Useful when there are too many files to stage.
- However, with this command, files that should be excluded from VC can be staged mistakenly.
 - Very big files or datasets
 - Images
 - Executable or binary files created by compilers/interpreters
 - Private files (passwords/certificate)

.gitignore

- You'll have a class of files that you don't want Git to automatically add or even show you as being untracked.
- Add the names of those files to a special text file ".gitignore".

```
.gitignore • unmodified.txt •
D: > pratice > .gitignore
1  # ignore all .a files
2  *.a
3
4  # but do track lib.a, even though you're ignoring .a files above
5  !lib.a
6
7  # only ignore the TODO file in the current directory, not subdir/TOD0
8  /TOD0
9
10 # ignore all files in any directory named build
11 build/
12
13 # ignore doc/notes.txt, but not doc/server/arch.txt
14 doc/*.txt
15
16 # ignore all .pdf files in the doc/ directory and any of its subdirectories
17 doc/**/*.pdf
```

.gitignore

- Different development environments generate different temporary files that should be ignored.
- The gitignore repository has a lot of template .gitignore files for different environments.
 - <https://github.com/github/gitignore>
- It is always a good practice to copy and paste an appropriate .gitignore file to your repo just after you initialize it.

.gitignore

github / gitignore

Watch 3.2k Star 113k Fork 61.2k

<> Code Pull requests 257 Actions Projects Security Insights

master 6 branches 0 tags

Go to file Add file Code

diegoherranz KiCad: add *.kicad_sch-bak and *.kicad_prl (#3427) 2 218a941 on 13 Jul 2020 3,253 commits

.github	Trim trailing whitespace	3 years ago
Global	Update stale heading anchor (#3445)	7 months ago
community	Ignore AWS Serverless Application Model build folder (#3357)	10 months ago
.travis.yml	.travis.yml: Trim trailing whitespace and indent (#3118)	2 years ago
Actionscript.gitignore	Fix comments on same line causing ignore to break	4 years ago
Ada.gitignore	ensure single trailing newline	7 years ago
Agda.gitignore	Add MAlonzo directory. (#2978)	2 years ago
Android.gitignore	ignore HPROF files (#3456)	7 months ago
AppEngine.gitignore	Added template for Google App Engine	6 years ago
AppceleratorTitanium.gitignore	Added Appcelerator Titanium .gitignore file.	9 years ago
ArchLinuxPackages.gitignore	Add .jar, .exe and .msi	6 years ago
Autotools.gitignore	Update Autotools.gitignore. (#3337)	10 months ago
C++.gitignore	added prerequisites for C and C++	5 years ago
C.gitignore	Update C.gitignore	4 years ago

About

A collection of useful .gitignore templates

gitignore git

Readme

CC0-1.0 License


Releases

No releases published

Packages

No packages published


Contributors 1,244




+ 1,233 contributors

.gitignore

master [gitignore](#) / C.gitignore [Go to file](#) [...](#)

 chaosdefinition Update C.gitignore [...](#) Latest commit f76d089 on 1 Nov 2016 [History](#)

[9 contributors](#) 

52 lines (44 sloc) | 430 Bytes [Raw](#) [Blame](#) [View](#) [Edit](#) [Delete](#)


```
1 # Prerequisites
2 *.d
3
4 # Object files
5 *.o
6 *.ko
7 *.obj
8 *.elf
9
10 # Linker output
11 *.ilk
12 *.map
13 *.exp
14
15 # Precompiled Headers
16 *.gch
17 *.pch
18
19 # Libraries
20 *.lib
21 *.a
22 *.la
23 *.lo
24
25 # Shared objects (inc. Windows DLLs)
26 *.dll
27 *.so
28 *.so.*
29 *.dylib
```

Usage of .gitignore and `git restore`

- You create a repo.
- You download one hundred CSV files as datasets.
- You write some source codes.
- `git add .`
- Oops, all CSV files are going to be uploaded with the source files!
- Add `*.csv` to the end of `.gitignore` (still CSV files are *staged*).
- `git restore --staged .` (both CSV files and source codes become *untracked*).
- `git add .` (only source codes are *staged*)

Commit Changes

- Let's commit the staged files by typing `git commit`
- If you have installed VS Code, VS Code will be launched for a commit message.



```
.gitignore  COMMIT_EDITMSG  unmodified.txt
D: > pratice > .git > COMMIT_EDITMSG
1 |
2 # Please enter the commit message for your changes. Lines starting
3 # with '#' will be ignored, and an empty message aborts the commit.
4 #
5 # On branch master
6 # Changes to be committed:
7 #   new file:   README.txt
8 #
9 # Untracked files:
10 #   .gitignore
11 #
12
```


Commit Changes

- Enter a commit message such as “Add README.txt”, **SAVE**, and close the tab.
- If VS Code is not launched, try the command on the first line (replace the path to Code.exe)




```
MINGW64:/d/pratice
jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$ git config core.editor "'C:\Program Files\Microsoft VS Code\Code.exe' -w"

jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$ git commit
hint: Waiting for your editor to close the file...
[master 2377587] Add README.txt
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 README.txt

jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$
```

Commit Changes


- We just committed the changes made to README.txt to our local Git repo.
- The state of README.txt changed to *committed* from *staged*.
- You created a new version, and from its point of view, README.txt is *unmodified*.
 - *unmodified* == *committed*



Modify a File

- Now, README.txt is in an *unmodified* state.

1. Modify README.txt.
2. `git status`
3. `git add README.txt`
4. `git status`
5. `git commit`
6. `git status`



Modify a File

```
MINGW64:/d/pratice
jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$ git status
On branch master
nothing to commit, working tree clean
jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$
```

modify



```
MINGW64:/d/pratice
jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$ git status
On branch master
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   README.txt
no changes added to commit (use "git add" and/or "git commit -a")
jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$ |
```

git commit



```
MINGW64:/d/pratice
jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$ git status
On branch master
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        modified:   README.txt
jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$ |
```

git add .




Modify a Modified File

- `git add` adds the snapshot of files to the index.
- You must add a file again to reflect the changes made after adding the file to the index.
- Edit a.txt (first)
- Add a.txt
- Edit a.txt (second)
- Add a.txt (again!)

Add + Commit at Once

- To commit, you must add a file.
- If you want to commit all the modified files, use `git commit -a`
 - It skips staging.
 - `git commit -a == git add . and git commit`
- For untracked files, you must add them first.



Remove a File

- Removing a file from a repo can mean two things:
- Remove the file from the disk (and from the repo).
 - The file will be gone completely.
 1. Just remove the file (e.g., with the Del key), `git add <file>`, and `git commit`.
 2. `git rm <file>` and `git commit`
- Remove the file from the repo but keep it locally.
 - The file will be *untracked*.
 - The changes made to the file will be kept.
 - `git rm --cached <file>` and `git commit`

Remove a File

- `git rm` vs `git rm --cached`
- `git rm <path> == rm <path> && git add <path>`

```
MINGW64:/d/pratice

jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$ git status
On branch master
nothing to commit, working tree clean

jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$ git rm README.txt
rm 'README.txt'

jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$ git status
On branch master
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        deleted:    README.txt

jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$
```

```
MINGW64:/d/pratice

jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$ git status
On branch master
nothing to commit, working tree clean

jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$ git rm --cached README.txt
rm 'README.txt'


jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$ git status
On branch master
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        deleted:    README.txt

Untracked files:
  (use "git add <file>..." to include in what will be committed)
        README.txt

jmjo@DESKTOP-BAAE9VV MINGW64 /d/pratice (master)
$ |
```



Remove a File

- Note that `git rm` does not remove a file from the index immediately.
 - You need to commit after executing `git rm`.
- It writes a commit like “this file will be removed.”
- Some students may be confused.
 - Why does `git rm --cached` change the state from *modified* to *staged*, not from *modified* to *untracked*?
- Untracked when committed



Remove a File

- `git rm` removes a file and stages it for removal.
- You can approve the staged changes by `git commit`.
- When addition/modification is approved, the state becomes *unmodified*.
- When removal is approved, the state becomes *untracked*.



Undoing Things


- Today, we will learn three scenarios of undoing:
 - Editing a commit
 - Unstaging a staged file
 - Unmodifying a modified file
- Note that these should be done before you commit.
 - We will learn how to undo committed things later.

Editing a Commit

- Scenario:
 - You staged files and committed them.
 - After committing, you found you forgot to add some files.
- `git add <forgotten files>`
- `git commit --amend`
- The commit-message editor will pop up with the previous commit message.
- This will end up with a single commit.
- This is only possible for the last commit you made.


Unstaging a Staged File

- Scenario:
 - You staged files to commit using `git add`.
 - You found some files that should not be included in the commit.
- We already know the solution.
- `git restore --staged <file>`
- Also possible through `git reset HEAD <file>` although not recommended.



Unmodifying a Modified File

- Scenario:
 - You modified a file, but the program doesn't work anymore. Something went wrong.
 - You want to reset the file to its **last committed** state.
- `git restore <file>`
- **Changes will be discarded.**
- Also possible through `git checkout --<file>` although not recommended.



Quiz

- `git restore --staged <file>`
- `git rm --cached <file>`

Summary: Git Basics

- Today, we learned basic commands of Git.
 - add, status, rm, commit, restore
 - .gitignore
- Note that these commands are done locally.
 - Changes are visible only to your local machine.
 - We did not even use a remote Git service like GitHub.

In case of fire



1. git commit



2. git push



3. leave building

Summary: Git Basics

- Reordered for readability

