

# Homework1

September 10, 2020

```
[26]: ##### Problem 1

##### part (a)
def divides(a,b):
    #We use that  $b\%a == 0$  if and only if  $a$  divides  $b$ 
    return b%a==0

##### part (b)
def getDivisors(a):

    #first give an empty list of divisors
    listOfDivisors = []

    #Check each integer and if it is a divisor add it to the list
    for i in range(1,a+1):
        if divides(i,a):
            listOfDivisors.append(i)
    return listOfDivisors

#I mentioned you could do this in square root of  $a$  steps, here's how (either
→one counts for credit).
def getDivisorsFaster(a):
    listOfDivisors = []
    for i in range(1,int(math.sqrt(a)+1)):
        if divides(i,a):
            listOfDivisors.append(i)
            listOfDivisors.append(a/i)
    return listOfDivisors

##### part (c)
def getCommonDivisors(a,b):
    #you could call getDivisors and compare lists, but it's a bit more
→efficient I think to just populate a new list at once.
    listOfCommonDivisors = []
    for i in range(1,min(a,b)+1):
        if divides(i,a) and divides(i,b):
            listOfCommonDivisors.append(i)
```

```

    return listOfCommonDivisors

##### part (d)

#because getCommonDivisors returns a sorted list, we just need the top (or
↳-1st) element of the list. If it were not sorted, you would have to sort
↳the list or at least go through it looking for the top element.
def findGCDSlow(a,b):
    return getCommonDivisors(a,b)[-1]

#a few tests
print("Divisors of 24:",getDivisors(24))
print("Divisors of 24:",getDivisorsFaster(24)) #notice this isn't sorted at the
↳moment
print("Common Divisors of 16 and 24:",getCommonDivisors(16,24))
print("gcd(2024,748) =",findGCDSlow(2024,748))

```

Divisors of 24: [1, 2, 3, 4, 6, 8, 12, 24]  
 Divisors of 24: [1, 24, 2, 12, 3, 8, 4, 6]  
 Common Divisors of 16 and 24: [1, 2, 4, 8]  
 gcd(2024,748) = 44

[39]: ##### Problem 2

```

##### part (a)
def divisionWithRemainder(a,b):
    #The trick here is to find the remainder first. Then it becomes a simple
    ↳division problem.
    r = a%b
    #then solve a = bq+r for r
    q = (a-r)/b
    return [q,r]

##### part(b)
def findGCDFast(a,b):
    while(b>0): #If the remainder hasn't yet become 0
        qr = divisionWithRemainder(a,b)
        #replace (a,b) with (b,r)
        a = b
        b = qr[1]
    #once we break out our remainder b=0, so the one before it is in position a.
    return a

#Notice we never really used q above. This suggests the next recursive
↳algorithm.
def findGCDRecursive(a,b):
    #first find the remainder

```

```

r = a%b
if r==0:
    return b
else:
    return findGCDRecursive(b,r)

#a few tests
print("divide 25 by 3: [q,r]=",divisionWithRemainder(25,3))
print("gcd(2024,748) =",findGCDFast(2024,748))
print("recursively gcd(2024,748) =",findGCDRecursive(2024,748))

```

divide 25 by 3: [q,r]= [8, 1]  
 gcd(2024,748) = 44  
 recursively gcd(2024,748) = 44

[49]: ##### Problem 3

#here we will need to remember q

```

def extendedGCD(a,b):
    #Each remainder can be computed in terms of a and b. These placeholders
    ↳ save the coefficients in the previous 2 remainders
    u0 = 1
    v0 = 0
    u1 = 0
    v1 = 1
    while(b>0): #If the remainder hasn't yet become 0
        #then do division with remainder
        qr = divisionWithRemainder(a,b)
        #replace (a,b) with (b,r)
        a = b
        b = qr[1]
        #compute the new coefficients
        u = u0 - qr[0]*u1
        v = v0 - qr[0]*v1
        #and shift them coefficients:
        u0 = u1
        u1 = u
        v0 = v1
        v1 = v
        #once we break out our remainder b=0, so the one before it is in position a.
        ↳ Therefore we want the coefficients associated to a as well, which are u0
        ↳ and v0
    return [a,u0,v0]

#The algorithm outlined in the book does essentially this, except it doesn't
↳ remember ssthe v's noting that you can find them at the end.

#a quick test

```

```
print(extendedGCD(2024,748))
```

[44, -7, 19]

[53]: ##### Problem 4

```
##### part(a)
print("gcd(527,1258)")
print(findGCDSlow(527,1258))
print(findGCDFast(527,1258))
print(extendedGCD(527,1258))

##### part(b)
print("gcd(1056,228)")
print(findGCDSlow(1056,228))
print(findGCDFast(1056,228))
print(extendedGCD(1056,228))

##### part(c)
print("gcd(163961,167181)")
print(findGCDSlow(163961,167181))
print(findGCDFast(163961,167181))
print(extendedGCD(163961,167181))

##### part(d)
print("gcd(3892394,239847)")
print(findGCDSlow(3892394,239847))
print(findGCDFast(3892394,239847))
print(extendedGCD(3892394,239847))

##### part(e)
print("gcd(32715482947251,649917361940562)")
#print(findGCDSlow(32715482947251,649917361940562)) #Doesn't run in time
print(findGCDFast(32715482947251,649917361940562))
print(extendedGCD(32715482947251,649917361940562))
##### part(a)
print("gcd(57993692894873334328961928359215776,375993729939672871359928438912)")
#print(findGCDSlow(57993692894873334328961928359215776,375993729939672871359928438912))
↳ Doesn't run in time
print(findGCDFast(57993692894873334328961928359215776,375993729939672871359928438912))
print(extendedGCD(57993692894873334328961928359215776,375993729939672871359928438912))
```

gcd(527,1258)

17

17

[17, -31, 13]

gcd(1056,228)

```
12
12
[12, 8, -37]
gcd(163961,167181)
7
7
[7, 4517, -4430]
gcd(3892394,239847)
1
1
[1, 59789, -970295]
gcd(32715482947251,649917361940562)
3
[3, 53354937663485, -2685776154786]
gcd(57993692894873334328961928359215776,375993729939672871359928438912)
32
[32, -1774150622414444425938744743, 273646973746237751512454653606925]
```

[0]: