

GOOOL LLC OFFICIAL CREST

MASTER ARTWORK AND BRAND CONTROL SHEET



Approved artwork

Use only the crest shown on this sheet. The lettering, shield, divider, ball, motion elements and spacing are locked.

Artwork ratio

201:256 (width:height). Scale proportionally only.

Approved colors

Element	Digital value	Production note
Black	#000000	Pantone Black C starting point
Red	#C61322	Pantone 186 C approximate starting point
White / negative space	#FFFFFF	Garment, base material or white ink/thread

Physical ink and thread samples control final color. Do not rely on monitor appearance alone.

MASTER FILES AND NON-NEGOTIABLE RULES

- Primary POD file: transparent PNG, sRGB, 300 PPI at final size, 4500 pixels high.
- Preferred production file: SVG, AI, EPS or vector PDF with all shapes expanded and lettering converted to outlines.
- Do not retype or replace the GOOOL lettering. Do not redraw the ball, swooshes, shield or red divider.
- Do not stretch, compress, skew, rotate, crop, add effects, add outlines, add shadows or change color values.
- Do not print the white square background. Use the supplied transparent artwork variant.

Garment / substrate	Required artwork variant
White and light garments	GOOOL_Crest_LightGarment_Transparent.png
Black and dark garments	GOOOL_Crest_DarkGarment_Transparent.png
One-color black applications	GOOOL_Crest_OneColor_Black.png
One-color white applications	GOOOL_Crest_OneColor_White.png

PRINT-ON-DEMAND PRINT SPECIFICATION

DTF, DTG AND SCREEN PRINT PRODUCTION

APPROVED PRINT METHODS

Method	Approval	Production requirement
DTF	Preferred for broad POD catalogs	Transparent 300 PPI PNG. Use light or dark garment artwork variant. Matte transfer finish preferred.
DTG	Approved	Use transparent 300 PPI PNG. White underbase required on dark garments. Preserve red as #C61322.
Screen print	Preferred for volume orders	Two spot colors: black and red. White is garment or underbase. Provide separated channels and physical strike-off.
Sublimation	Conditionally approved	Only on white or very light polyester. Confirm black density and red match before launch.
Vinyl / low-detail transfer	Not preferred	Use only when a vendor can reproduce all internal ball and lettering details without thickening.

STANDARD SHIRT PLACEMENTS AND ART SIZES

Placement	Approved width	Proportional height	Position tolerance
Left chest small	3.25 in	4.14 in	Center 3.5 to 4.0 in from shirt center; top 7.0 to 8.0 in below shoulder seam
Center chest medium	7.50 in	9.55 in	Top of art 2.75 to 3.25 in below collar seam
Center front large	9.00 in	11.46 in	Top of art 2.75 to 3.25 in below collar seam
Full back	10.50 in	13.37 in	Top of art 3.0 to 4.0 in below back collar seam
Youth center front	6.50 in	8.28 in	Scale down only when all ball and letter details remain open

POD upload and color settings

- Color space: sRGB IEC61966-2.1 for PNG upload files.
- Resolution: 300 PPI at final printed dimensions. Never upscale inside the vendor portal.
- Transparency: true alpha transparency. No white canvas and no semi-transparent drop shadow.
- Black: use solid process black #000000 for DTF and DTG. Screen printer may use Pantone Black C or approved equivalent.
- Red: use #C61322. Pantone 186 C is an approximate starting point only; approve a physical sample.
- Registration tolerance for two-color screen print: maximum 1.0 mm visible misregistration.
- Final print-size tolerance: plus or minus 2 percent. Placement tolerance: plus or minus 0.25 in.

REQUIRED BEFORE PRODUCT LISTING

- Order one physical sample in each print method and garment color family before enabling automatic fulfillment.
- Confirm shape, lettering, red divider, ball seams, black density, edge sharpness and placement against the approved artwork.

PRINT-ON-DEMAND EMBROIDERY SPECIFICATION

DIRECT EMBROIDERY AND CREST-SHAPED PATCH PRODUCTION

APPROVED EMBROIDERY APPLICATIONS

Application	Approval	Required construction
Crest-shaped patch	Preferred	White twill base, black and red embroidery, black merrow or satin border. Best match to approved artwork.
Direct embroidery on white / light garment	Approved	Garment supplies white negative space. Stitch black elements and red divider. Use cutaway backing.
Direct embroidery on dark garment	Conditional	Use the approved dark-garment reverse artwork or an applied patch. Do not stitch a large white fill field on lightweight tees.
Caps and very small placements	Not approved from this master	Requires a separate simplified horizontal mark. Do not auto-shrink this crest.

SIZE, DIGITIZING AND STITCH REQUIREMENTS

Item	Required specification
Preferred left-chest patch	3.50 in W x 4.46 in H
Minimum approved patch	3.00 in W x 3.82 in H, subject to physical sew-out approval
Preferred direct embroidery	3.50 in W x 4.46 in H on polo, sweatshirt, jacket or structured tee
Minimum direct embroidery	3.25 in W x 4.14 in H. Do not reduce further without a new simplified art file.
Thread	40 wt polyester. 60 wt permitted for small ball seams and narrow internal openings.
Needle	75/11 embroidery needle, adjusted to substrate and thread.
Outer border	2.5 to 3.0 mm satin stitch or black merrow edge for patches.
Minimum satin column	1.2 mm finished width.
Minimum open negative space	1.5 mm after pull compensation.
Minimum gap between objects	1.0 mm after pull compensation.
Red divider	1.5 to 2.0 mm satin column, centered and straight.

Digitizing map

- Lettering: satin stitch, preserving each O as an exact duplicate of the approved original O shape. Do not substitute a font.
- Shield borders: satin stitch with edge-run and zigzag underlay. Keep the double outline visually separated.
- Ball panels and motion shapes: satin stitch for bold shapes; use 60 wt running stitch only where a seam would otherwise close.
- Large black fields on a patch: use black twill whenever possible instead of dense fill. If fill is required, use tatami with controlled density.
- Recommended color sequence for white twill patch: black interior elements, red divider, outer black border last.
- Expected stitch count is vendor-dependent. The physical sew-out, not the estimated count, is the approval standard.

EMBROIDERY QUALITY CONTROL AND APPROVAL

BACKING, PATCH CONSTRUCTION, SEW-OUT AND ACCEPTANCE

BACKING AND STABILIZATION

Substrate	Required stabilization
Lightweight knit tee	Medium cutaway backing, approximately 2.0 to 2.5 oz. Patch application preferred over dense direct embroidery.
Polo / pique	Cutaway backing plus water-soluble topping to prevent stitch sink.
Sweatshirt / fleece	Cutaway backing plus water-soluble topping. Confirm fabric does not show through open areas.
Jacket / structured garment	Cutaway or appropriate structured backing selected by digitizer. Test for needle deflection and distortion.
Patch	White twill base with heat-seal, sew-on or hook-and-loop backing as ordered.

PATCH CONSTRUCTION

- Die-cut or laser-cut to the approved shield shape. Do not convert the crest to a circle, square or generic shield.
- Preferred edge: black merrow border, 2.5 to 3.0 mm finished width. Satin border is acceptable when merrow is unavailable.
- Use white twill as the negative-space field. Stitch the black artwork and red divider on top of the twill.
- Keep the double shield outline visibly separated at actual size.
- Patch backing must be selected and labeled as heat-seal, sew-on or hook-and-loop. Do not substitute without approval.

PHYSICAL SEW-OUT ACCEPTANCE CRITERIA

Inspection point	Pass condition
Lettering	GOOOL reads clearly. All three O shapes match one another and remain open.
Shield	Outer and inner border remain smooth, centered and separated. No corners collapse.
Divider	Red line is straight, centered, clean and does not bleed into black elements.
Ball	Panels remain recognizable. Internal openings do not close.
Motion elements	Swooshes remain separated and do not merge with the ball or shield.
Fabric condition	No puckering, tunneling, hoop burn, needle cuts or excessive stiffness.
Thread finish	No visible jumps, exposed bobbin, loose ends or inconsistent tension.
Placement	Within plus or minus 0.25 in of the approved position.

A PHOTOGRAPHED SEW-OUT AT ACTUAL SIZE AND ONE PHYSICAL SAMPLE ARE REQUIRED BEFORE AUTOMATIC FULFILLMENT.

POD FULFILLMENT AND QUALITY CONTROL

ONLINE ORDER ROUTING, SKU CONTROL AND VENDOR APPROVAL

PRODUCT SETUP RULES

Catalog decision	Required rule
White and light shirts	Use LightGarment transparent file. Black/red artwork.
Black and dark shirts	Use DarkGarment transparent file or approved patch. White/red artwork.
Performance polyester	DTF preferred unless a sublimation sample is approved.
Lightweight tees	Print preferred. Use patch rather than dense direct embroidery.
Polos, hoodies and jackets	Direct embroidery or patch approved after sew-out.
Automatic fulfillment	Enable only after the exact garment, placement, method and artwork variant pass a physical sample review.

Recommended SKU and file naming

Field	Example
Artwork version	GOOOL-CREST-V1
Print SKU	GOOOL-CREST-V1-DTF-LIGHT-CF-9
Embroidery SKU	GOOOL-CREST-V1-EMB-PATCH-LC-3.5
Master PNG	GOOOL_Crest_LightGarment_Transparent.png
Reverse PNG	GOOOL_Crest_DarkGarment_Transparent.png
Vendor proof file	GOOOL-CREST-V1_[VENDOR]_[GARMENT]_[METHOD]_PROOF.pdf

FINAL PRE-FLIGHT CHECKLIST

Check	Pass condition
Artwork	Approved GOOOL crest only; three O characters after G and before L.
Proportion	201:256 ratio is locked and not distorted.
Color	Black #000000, red #C61322, white / negative space as specified.
Transparency	No white square background in POD upload asset.
Placement	Correct product placement and size selected.
Detail	All O openings, ball panels, swooshes and double shield outline remain open and clean.
Proof	Digital proof approved; physical sample approved before automatic fulfillment.
Recordkeeping	Vendor, garment blank, method, asset version and approval date stored with SKU.

NO VENDOR MAY ALTER OR RECREATE THE MARK WITHOUT WRITTEN APPROVAL FROM GOOOL LLC.