Reliable APIs and Idempotency

LEFT Idempotency keeps retries safe.

LEFT Use one request ID per operation.

LEFT A database transaction stores results.

LEFT Line 4 in this column of the paper.

LEFT Line 5 in this column of the paper.

LEFT Line 6 in this column of the paper.

LEFT Line 7 in this column of the paper.

LEFT Line 8 in this column of the paper.

LEFT Line 9 in this column of the paper.

LEFT Line 10 in this column of the paper.

LEFT Line 11 in this column of the paper.

LEFT Line 12 in this column of the paper.

LEFT Line 13 in this column of the paper.

LEFT Line 14 in this column of the paper.

RIGHT Idempotency keeps retries safe.

RIGHT Use one request ID per operation.

RIGHT A database transaction stores results.

RIGHT Line 4 in this column of the paper.

RIGHT Line 5 in this column of the paper.

RIGHT Line 6 in this column of the paper.

RIGHT Line 7 in this column of the paper.

RIGHT Line 8 in this column of the paper.

RIGHT Line 9 in this column of the paper.

RIGHT Line 10 in this column of the paper.

RIGHT Line 11 in this column of the paper.

RIGHT Line 12 in this column of the paper.

RIGHT Line 13 in this column of the paper.

RIGHT Line 14 in this column of the paper.

Footnote: retries can arrive after a timeout.

Page three: independent coordinates.