

LOCALIZATION OF AN UAV FOR CRACK DETECTION IN RAILWAY TRACKS

Gabriel D. Silva

gd.silva@unesp.br

São Paulo State University
Mechanical Engineering Departament

31 de março de 2023

- ➊ Introduction
- ➋ MCL Algorithm
- ➌ 2D Localization of UAV
- ➍ Simulation Results
- ➎ Conclusion and Future Work

- UAV applications: sports, partys, get in places where human intervation might be difficult.
- E.g.: detecting cracks in a railway track using concepts of image processing.

- Study's based in India.
- There's a vast railway network.
- It's been increasing in a rapid pace, however its infrastructure's not been able to follow it.
- It causes severe loss of valuable human life and property.

Techniques used for damage detection:

- graphical inspection;
- non-destructive testing technologies (acoustic emission, ultra-sonic techniques, etc); and
- shuddering based global methods.

Techniques used for damage detection:

- graphical inspection;
- non-destructive testing technologies (acoustic emission, ultra-sonic techniques, etc); and
- shuddering based global methods.

Techniques used for damage detection:

- graphical inspection;
- non-destructive testing technologies (acoustic emission, ultra-sonic techniques, etc); and
- shuddering based global methods.

Two-fold objective

- Reduce risk of rail accidents; and
- reduce manned labor required to identify cracks along railway tracks.


GOAL: localizing the position of the UAV.

How does it work?

- Estimates its position and orientation;
- first interaction: uniform distribution;
- the later ones gets more precise.

MCL ALGORITHM (STATE REPRESENTATION)

- three element vector;
- initial input;
- mean of the highest weighed cluster of particles.



MCL ALGORITHM (INITIALIZATION OF PARTICLES)

Global Localization

- initial position is unknown;
- particles uniformly distributed;
- less performance.

Initial pose



- initial location is given;
- more particles accumulated at the initial pose;
- more performance.

MCL ALGORITHM (RESAMPLING PARTICLES)

- *UpdateThreshold*: minimum amount of necessary change in the three element vector.
- *ResamplingInterval*: defines the number of necessary updates for particle resampling.



2D LOCALIZATION OF UAV

MATLAB usage:



2D LOCALIZATION OF UAV

MATLAB usage:





UAV Characteristics

- 8 MP Digital camera;
- average speed: 33 mph;
- 20 frames/sec;¹
- UAV must be equipped with flash lights;

¹1200 frames per minute

SIMULATION RESULTS


- *improfile*: find the intensity profile of an image along a line segment.²





²Works with grayscale and RGB.

SIMULATION RESULTS



For crack detection in a railway track:



SIMULATION RESULTS



SIMULATION RESULTS



CONCLUSION AND FUTURE WORK

- Simple solution to detect cracks along railway lines using localization and image processing.
- Possible effects that the UAV is subjected to by the presence of electric wires above the tracks.
- Smartphone application can also be developed for monitoring the motion and position of the UAV.