

# 索引

## SYMBOLS AND NUMERICS

- > (angle bracket), defined, 9
- \$ (dollar sign) prefix, 8
- ./, (dot slash) adding to
  - require parameters, 43
- \r\n delimiter, 85
- [] (square brackets) for uploading multiple files, 134
- 404 (Not Found) status code, 117

## A

- absolute modules, defined, 41
- accepts extension for
  - Request, 156
- accessors in v8, 25–26
- acknowledgment, Socket.IO, 190–191
- acknowledgments, TCP, 71
- addEventListener API, 45–46
- addMessage function, 187, 190
- AJAX, 164–166, 180, 245
- Amazon Linux, 9
- angle bracket (>), defined, 9
- ANSI escape codes (website), 66
- Apache/PHP compared to Node, 28–29
- app. users function, 212
- app.configure function, 153
- app.enable function, 153
- app.error function, 155
- apply method, 18
- app.set function, 147, 148
- app.use function, 159, 161
- argv API, 63–64, 108
- arity of a function, 19, 296

- array JavaScript type, 16, 17
- arrays, 23, 239–240, 242–243
- assert module, 284, 290–291, 293
- AssertionError, 290
- asynchronous code
  - advantage for Node, 32
  - serial execution, 58, 59
  - synchronous code, compared to, 30, 53–55
  - testing, 295–297
- authentication, MongoDB access, 217–218

## B

- base64, defined, 48
- basicAuth middleware, 141–143
- BDD (behavior-driven development), 297
- belongsTo relationship type, 250
- binary data, representing in JavaScript, 47–48
- bind method, 24
- block body declaration, 238
- blocking code, 29–31, 32, 33, 46, 54
- bodyParser middleware, 131–134, 208, 214, 251
- boolean JavaScript type, 16
- broadcast function, 171, 173–174, 186, 187
- broadcasting issue, WebSocket, 177, 185–190
- browser. *See also* code sharing
  - Chrome, 1, 22
  - Mocha, compiling for, 299–300
  - Node's connection features, 94

- shimming browser APIs, 284
- WebSocket issues, 166, 177, 180
- browserbuild project, 279, 285–288
- Buffer object, 48
- buffers, 47–48
- bundling up client-side JavaScript, 128
- byte orientation in TCP, 70–71

## C

- call method, 18
- call stacks in v8, 32
- case sensitive routes in Express, 153
- casting in Mongoose, 225–226
- Chrome, Google, 1, 22
- chunked value for transfer encoding, 92–93
- classes, 20, 46, 220, 254
- CLI (command line interface), exploring APIs for, 63–66
- client. *See also* browser
  - bundling up JavaScript, 128
  - createClient in MySQL, 234
  - http.ClientRequest object, 105, 106
  - IRC, 83–85
  - mongo client, 207
  - Socket.IO, 183–185
  - telnet client, 71–73
  - WebSocket, 169
- client.end function, 236
- client.query function, 236
- close event, 77, 177, 180
- closures, JavaScript, 19



- cloud deployments, non-blocking IO advantages for, 33
- code sharing (browser/server)
  - browser APIs, shimming, 284
  - browserbuild project, 285–288
  - cross-browser inheritance, 284–285
  - ECMA APIs, shimming, 282–283
  - introduction, 279–280
  - modules, exposing, 280–282
  - Node APIs, shimming, 283–284
  - summary, 288
- `Collection.insert` function, 214
- collections of documents in MongoDB, 205, 213–216
- command line interface (CLI), exploring APIs for, 63–66
- complex JavaScript types, 16
- concurrency. *See* shared-state concurrency
- `configure` function, 153
- congestion control in TCP, 71
- Connect API. *See also* middleware
  - Connect-based website, creating, 119–120
  - HTTP-based website, creating, 116–119
  - introduction, 115–116
  - summary, 144
- `connect` event, 84, 180, 185–186
- `connect` function, 84, 184, 220
- `connection` event, 168, 181
- Connection HTTP header, 92, 94
- connections
  - client/server communications as, 70
  - HTTP, 93–94
  - MongoDB access, 212–214
  - node-mysql, 234
  - redis, 267–268
  - sequelize, 248–249
  - tracking in TCP, 79–81
  - WebSocket, 177
- console object, 40
- Content-Type HTTP header, 89, 99–100
- contracts, event, defined, 47

- controllers, separating HTML code from in Express, 146
- convenience methods, Express, 155–157, 253
- Cookie header, 134
- `createClient` API, 234
- `createServer` function
  - Connect style, 120
  - Express style, 147
  - HTTP server, 112, 117
  - TCP, 75
  - WebSocket, 168
- Crockford, Douglas (author)
  - JavaScript: The Good Parts*, 15
- cross-browser inheritance, 284–285
- crypto libraries, code sharing, 280
- current working directory, 64–65

## D

- Dahl, Ryan (developer), 1
- data deletion route, sequelize, 254–255
- data event, 60–61, 77–79
- data stream, client/server communication as, 70
- data types, 207, 262–266
- database access, non-blocking IO advantage for, 33. *See also* MongoDB; MySQL; Redis
- datagram, defined, 70
- `:date` dynamic token, 130
- date manipulation toolkits, code sharing, 280
- `db.getLastError` function, 220
- `db.query` function, 241
- default logging format, 129
- `delete` class, 254
- DELETE request, 99
- deletion route, data, sequelize, 254–255
- `destroy` command, 255
- dev logging format, 129
- `_dirname`, 64
- `disconnect` event, 180
- disconnecting and `close` event in WebSocket, 177
- `dispatchEvent` API, 45–46

- documents, MongoDB data as, 205, 206, 213–217, 222
- dollar sign (\$) prefix, 8
- DOM API, code sharing (website), 282, 284
- dot notation for nested keys in MongoDB, 222
- dot slash (./), adding to
  - `require` parameters, 43
- driver APIs, defined, 208. *See also*
  - node-mongodb-native driver;
  - node-mysql driver;
  - node-redis driver

## E

- ECMA APIs, shimming, 282–283
- ECMAScript, 15
- ejs template engine, 146–147, 154
- `elect` function, 192
- embedded documents, defining in Mongoose, 222
- encoded string as parameter of event, 57
- end event, 77
- end method, 107
- `ensureIndex` function, 216
- environmental variables, 65
- error event, 34, 47, 77
- error handling
  - `AssertionError` in testing, 290
  - `db.getLastError` function, 220
  - Express API, 150, 151, 155
  - MySQL, 236
  - Node, 34–35
  - shared-state concurrency, 33–35
  - stack traces, 35–37
- es5-shim project (website), 282
- event loop
  - introduction, 1
  - IO, relationship to, 32
  - keeping it running with `Stream`, 56
  - non-blocking code, relationship to, 30–31
  - single thread of execution, 31
- `EventEmitter` API, 45–46, 78, 284



## events

- close, 77, 177, 180
- connect, 84, 180, 185–186
- connection, 168, 181
- data, 60–61, 77–79
- disconnect, 180
- encoded string as parameter, 57
- end, 77
- error, 34, 47, 77
- join, 186
- Node JavaScript additions, 45–47
- open, 180
- Socket.IO, 180–181, 185
- exception, capturing, 21–22
- executing a file, 10
- exit API, 65
- expect function, 292–293
- expect.js project (website), 292–294
- exports global object, 41, 44
- exports style in Mocha, 298–299
- exposing APIs, Node JavaScript additions, 44–45
- Express API, 157–158. *See also*
  - routes and route handlers
  - convenience methods, 155–157
  - error handling, 150, 151, 155
  - HTML, 146–147
  - introduction, 145
  - middleware, 159–160
  - module, creating, 146
  - MongoDB, 208–212, 213
  - node-mysql, 232–233
  - organization strategies, 160–162
  - search module, 150–151, 152
  - sequelize, 245–248
  - settings, 153–154
  - setup, 147–148
  - summary, 162
  - template engines, 146, 147, 154, 209
- in WebSocket API, 167

## F

- file descriptors, 31, 56
- filesystem, 92. *See also* fs module
- filter method, 23
- find method in sequelize, 253–254
- findById query operation, 224
- findOne command, 216

- flag, defined, 186
- flow control, 71, 121, 158
- FLUSHALL command, 274
- forEach method, 23
- formidable module, 131
- 404 (Not Found) status code, 103, 117
- framing, defined, 166
- fs module
  - interacting with, 61–63
  - overview, 41
  - Stream, 66–68
  - sync compared to async style, 54
  - watch, 67–68
- fs.createReadStream function, 67
- fs.stat function, 58, 117
- fs.watch function, 68
- fs.WriteStream function, 67
- function JavaScript type, 16
- function name compared to variable name, 18
- functions, overview, 18–19. *See also specific functions and methods*

## G

- g flag, 13
- GET command, 262
- Get request, 99, 108, 109–110
- GitHub, 3
- global object, 40–41
- Google Chrome, 1, 22
- Grooveshark API (website), 192–196

## H

- handshake, defined, 166
- hash data type in Redis, 263–264
- hasMany association, 250
- HDEL command, 264
- header extension for Request, 155
- header extension for Response, 156
- headers, HTTP, 89–93, 99–100
- HEXLISTS command, 262, 264
- HGETALL command, 264, 273, 274

- hgetall function, 269
- hidden option in static middleware, 127
- hmset function, 269
- homebrew package manager, 261
- HSET command, 263
- HTML. *See* browser
- HTML5 WebSocket, 166–167
- HTTP (Hypertext Transfer Protocol)
  - Connect API, compared to, 116–119
  - connections, 93–94
  - headers, 89–93, 99–100
  - introduction, 87
  - reloading with up, 111–112
  - request+response model inefficiencies, 164–166
  - structure, 88–89
  - summary, 112
  - superagent module, 110–111
  - TCP, relationship to, 69, 88, 93
  - Twitter web client exercise, 104–110
  - web server, creating, 93–104
  - WebSocket, relationship to, 167
- http.ClientRequest
  - object, 105, 106
- http.request object, 105, 106, 108, 109
- http.Server object, 69, 182, 183
- http.ServerRequest
  - constructor, 88
- http.ServerResponse
  - constructor, 88
- :http-version dynamic token, 130

## I

- if node block in browserbuild, 288
- index method, 223
- index setup for Mongoose, 215–216, 222–223
- info object, 241
- inheritance, 20–21, 25, 284–285
- in-memory store, Redis, 260
- input and output, basics in Node, 57–59



- insert command, 214–215
- instanceof operator, 17, 21
- interpolation feature in jade, 240
- io.connect function, 184
- IP (Internet Protocol), 70
- IRC (Internet Relay Chat) client program, 83–85
- is extension for Request, 156
- isArray method, 23
- items array, database data, 239–240, 242–243

**J**

- jade template engine, 154, 209–210, 238–240
- JavaScript. *See also* Node, JavaScript additions
  - bundling up client-side, 128
  - classes, 20
  - defined, 15
  - functions, 18–19
  - inheritance, 20–21
  - JSON, compared to, 235
  - Redis, compared to, 266
  - summary, 26
  - try/catch, 21–22
  - types, 16–17
  - v8, 22–26
- JavaScript: The Good Parts* (Crockford), 15
- join event, 186
- jQuery listener for sequelize data, 250–251
- JSON
  - in Connect, 135
  - creating package.json, 12–13
  - data format, 104
  - encoding specification
    - from v8, 24
  - JavaScript, compared to, 235
  - MongoDB design, relationship to, 206
  - in sequelize, 252–253
  - Socket.IO's coordination of events, 181
  - in WebSocket, 173, 177
- json extension for
  - Response, 156
- jsonp function, 154

**K**

- keep-alive value for
  - Connection header, 94
- KEYS command, 261, 262
- keys method, 22–23
- key-value basis for Redis, 260, 263
- Kvalheim, Christian Amor (developer), 208

**L**

- lastIndexOf method, 24
- length property, 19
- Linux systems, installing
  - Node.js on, 8–9
- list data type in Redis, 265
- listen method, 76, 112
- locals object, 150
- logger middleware, 129–131
- login route, MongoDB, 215
- login system, creating with Connect, 134–140
- long polling, defined, 180
- LPUSH command, 265
- LRANGE command, 265

**M**

- Mac OS X, installing Node.js on, 8
- make test command, 9
- map method, 23
- math libraries, code sharing, 280
- maxAge option in static middleware, 127
- :method dynamic token, 130
- methodOverride
  - middleware, 141
- middleware
  - Connect API
    - basicAuth, 141–143
    - bodyParser, 131–134
    - Cookie header, 134
    - defined, 115
    - introduction, 121–122
    - logger, 129–131
    - methodOverride, 141
    - query, 128
    - RedisStore, 140
    - session, 134–140
    - static, 120, 127–128
    - writing reusable, 122–127

- Express API, 159–160

- MongoDB, 208, 214, 217–218

- Mongoose, 223

- next function, relationship to, 124, 158

- sequelize, 251

- mocha command, 295

- Mocha framework, 294–300

- Model.count function, 225

- models, database

- Mongoose, 219, 220–221, 223–224, 227–229

- Redis, 268

- sequelize, 249–250

- module global object, 41, 44, 280–281

- module system

- assert, 284, 290–291, 293

- code sharing, 280–282

- creating the module, 12–13, 53

- Express API, 146, 150–151

- formidable, 131

- fs, 41, 54, 61–63, 66–68

- HTTP, 95, 104–110

- input and output, 57–59

- Node JavaScript additions, 41–43

- querystring, 101–102, 106, 108

- refactoring, 59–61

- streams, 55–57

- superagent, 110–111, 146, 151, 291–292

- synchronous compared to asynchronous code, 53–55

- TCP (chat program), 74

- mongo client, 207

- mongod server, 207

- MongoDB

- compared to other database programs, 205–207, 260, 263

- defined, 205

- installing, 207

- Mongoose, 220–229

- node-mongodb-native driver

- application setup, 208

- atomicity, 219

- connecting to, 212–214

- creating documents, 214–215



- Express app, creating, 208–212, 213
  - finding documents, 215–217
  - middleware, 208, 214, 217–218
  - safe mode, 219–220
  - validation, 218–219
  - summary, 229
  - `mongodb.Server`, 212–213
  - Mongoose
    - atomicity, 219
    - automatic key populating, 225
    - casting, 225–226
    - defining the model, 220–221
    - embedded documents, defining, 222
    - example program, 226–229
    - index setup, 215–216, 222–223
    - inspecting the model state, 223–224
    - limiting, 225
    - middleware, 223
    - nested keys, defining, 222
    - querying, 224–225
    - selecting, 224
    - skipping, 225
    - sorting, 224
  - monkey-patch (overriding functions), 123
  - mounting with `static` middleware, 127
  - MSI installer in Windows, 8
  - `multi` function, 269
  - multiplexing, defined, 182
  - MySQL
    - introduction, 231
    - MongoDB, compared to, 205, 206
    - `node-mysql` driver
      - connecting to, 234
      - creating data, 238–242
      - Express app, 232–233
      - fetching data, 242–244
      - initializing the script, 234–238
      - setup, 232
    - `node-sequelize` ORM
      - connecting to, 248–249
      - creating data, 250–253
      - defining models, 249–250
      - Express app, 245–248
  - introduction, 244–245
  - other functionality, 256–257
  - removing data, 254–256
  - retrieving data, 253–254
  - setup, 245
  - synchronizing to the database, 250
  - summary, 257
- ## N
- `name` method, 24
  - namespaces in Socket.IO, 181–182
  - nested keys, defining in Mongoose, 222
  - `net.connect` function, 84
  - `net.createServer`, 75
  - `net.Server` API, 74–76
  - `net.Stream` API, 75, 84
  - `next` function and middleware, 124, 158
  - `nextTick` function, 40
  - `node` command, 2, 9–10
  - Node Package Manager (NPM), 2, 10–14, 53
  - `node-canvas` (canvas 2D context) (website), 284
  - `NODE_ENV`, 65, 153
  - Node.JS. *See also specific APIs and database programs*
  - code sharing, 279–288
  - data in memory disadvantage, 266–267
  - installing, 7–14
  - introduction, 1–3
  - JavaScript additions
    - buffers, 47–48
    - events, 45–47
    - exposing APIs, 44–45
    - global object, 40–41
    - introduction, 39
    - module system, 41–43
    - summary, 48
  - shared-state concurrency
    - blocking compared to non-blocking code, 29–31
    - error handling, 33–35
    - introduction, 27–29
    - single thread of execution, 31–33
    - stack traces, 35–37
  - state, 79
  - summary, 37
  - support resources, 3
  - testing
    - `expect.js` project, 292–294
    - introduction, 289
    - Mocha framework, 294–300
    - program, 291–292
    - strategy, 290–291
    - subject for, 290
    - summary, 300
  - `node_modules` directory, 41
  - `node-mongodb-native` driver
    - application setup, 208
    - atomicity, 219
    - connecting to, 212–214
    - creating documents, 214–215
    - Express app, creating, 208–212, 213
    - finding documents, 215–217
    - middleware, 208, 214, 217–218
    - safe mode, 219–220
    - validation, 218–219
  - `node-mysql` driver
    - connecting to, 234
    - creating data, 238–242
    - Express app, 232–233
    - fetching data, 242–244
    - initializing the script, 234–238
    - sequelize, relationship to, 245
    - setup, 232
  - `node-redis` driver
    - connecting to `redis`, 267–268
    - defining the model, 268
    - graph methods, 269–270
    - intersections, computing, 270
    - testing, 270–276
    - users, creating and modifying, 268–269
  - `node-sequelize` ORM
    - connecting to, 248–249
    - creating data, 250–253
    - defining models, 249–250
    - Express app, 245–248
    - introduction, 244–245
    - other functionality, 256–257
    - removing data, 254–256
    - retrieving data, 253–254
    - setup, 245
    - summary, 257



- non-blocking code, 29–31, 32, 33, 46, 54
  - nonprinting characters, 66
  - NoSQL, 206, 231
  - NPM (Node Package Manager), 2, 10–14, 53
  - `npm install` command, 12
  - `npm publish` command, 12, 13
  - `null` JavaScript type, 16
- O**
- object JavaScript type, 16
  - `ObjectID` Schema type, 221, 225, 226
  - `Object.keys` API, code sharing issue, 283
  - Object-Relational Mappers (ORMs), 207. *See also* `node-sequelize` ORM
  - octets, 48
  - ODM (Object Document Mapper), 207
  - `once` method, 142
  - onload handler, 174
  - OOP frameworks, code sharing, 280
  - open event, 180
  - option function, 63
  - ORMs (Object-Relational Mappers), 207. *See also* `node-sequelize` ORM
- P**
- `package.json` file, 12–13
  - `parse` method, 24
  - PATCH request, 99
  - paused state, 56
  - persistence, Redis data, 260
  - PHP compared to Node, 28–31
  - pipng streams, 93
  - PKG file in Mac OS X, 8
  - `port` method, 112
  - ports package manager, 261
  - positions object, 172–173
  - POST request, 46–47, 99, 131
  - PostgreSQL, 205
  - primitive JavaScript types, 16
  - private variable, defined, 19
  - process object, 40
  - `process.argv` API, 63–64, 108
  - `process.cwd` object, 64–65
  - `process.env` object, 65
  - `process.exit` object, 65
  - `process.on` handler, 297
  - programming requirements, setting, 52
  - progressive API, defined, 111
  - `_proto_`, 25, 284
  - prototype extension in code sharing, 282–283
  - prototypical inheritance, defined, 20
  - PUT request, 99
- Q**
- quality of service (QoS) for TCP, 71
  - query middleware, 128
  - query string in URLs, 101
  - querying database, 215–216, 224–225, 261–262
  - `query.limit` extension, 225
  - `query.select` extension for MongoDB, 224
  - `query.skip` extension for MongoDB, 225
  - `query.sort` extension for MongoDB, 224
  - `querystring` module, 101–102, 106, 108
  - `querystringparse` module, 102
  - query language, 261–262
  - summary, 276
  - `redis-cli` command line execution, 261
  - `RedisStore` middleware, 140
  - `reduce` method, 24
  - refactoring, 59–61, 226–227
  - `:referrer` dynamic token, 130
  - `RegExp` object, 157–158
  - relative modules, 42
  - `:remote-addr` dynamic token, 130
  - `removeEventListener` API, 45–46
  - `render` extension for `Response`, 156
  - `render` method, 149, 150
  - REPL (Read-Eval-Print Loop), 2, 9–10
  - `:req` dynamic token, 130
  - `req.params` object, 157
  - `Request` object
    - Express extensions, 155–156
    - HTTP, 88, 93, 104–106, 108, 109–110, 164–166
    - Node/JavaScript code sharing, 280, 284
  - `require` global object
    - `browserbuild` considerations, 286–287
    - exposing APIs, 44–45
    - Express, 160
    - JSON file loading, 235
    - keyword, 14
    - module system role, 41
    - relative modules, 42–43
  - `:res` dynamic token, 130
  - `Response` object
    - Express extensions, 156–157
    - HTTP, 88, 93, 105, 164–166
  - `:response-time` dynamic token, 130
  - REST principles, 245
  - resume state, 56
  - review command, 14
  - routes and route handlers
    - case-sensitive, 153
    - data deletion route in `sequelize`, 254–255
    - defining in Express, 148–150
    - error handling, 155–157
- R**
- RAW TCP mode, 72
  - Read-Eval-Print Loop (REPL), 2, 9–10
  - `ReadStream` filesystem APIs, 92
  - reception acknowledgment in `Socket.IO`, 190–191
  - reconnection issue in `WebSocket`, 177
  - `redirect` extension for `Response`, 157
  - Redis
    - data types, 262–266
    - installing, 261
    - introduction, 259–260
    - middleware, 140
    - `node-redis` driver, 266–276



- middleware, 159–160
- MongoDB, 210–211
- organization strategy role (route maps), 160–162
- strict, 154
- terms defined, 145, 146
- web application capabilities, 157–158

RPUSH command, 265

## S

SADD command, 266

safe option, MongoDB driver, 219–220

Schema class, 220

schema-less database, MongoDB as, 205–206

scope definition in JavaScript, 19

<script> tag, 183–184

search command, 14

search module for Express Twitter app, 150–151, 152

Select command, 242–243

self-invoked function, defined, 19

semver versioning spec, 53

send extension for Response, 156

send object, 110–111, 166

sendfile extension for Response, 157

sequelize. *See* node-sequelize ORM

Sequelize constructor, 248–249

sequelize.define, 249

sequelize.sync, 250

serial execution, 58, 59

serve function, 118

serve(1) utility, 300

server. *See also* createServer function; HTTP communications with client, 70 creating with Node.js, 1–2, 10 MongoDB, 207, 212–213 net global object, 74–76 Server API, 69, 95–104, 182, 183 session data, 140, 266–267 session middleware, 134–140, 208 SET command, 262 set data type in Redis, 265–266

set object, 110–111

setEncoding method, 105

setImmediate API, 40

setTimeout function, 40

shared-state concurrency blocking compared to non-blocking code, 29–31 error handling, 33–35 introduction, 27–29 single thread of execution, 31–33 stack traces, 35–37 state, 79 summary, 37

shimming of APIs, 280, 282–284

short logging format, 129

SIGKILL signal, 65

signals, 65–66

single thread of execution, 31–33

sio.listen function, 183

slash-r, slash-n (\r\n) delimiter, 85

SMEMBERS command, 262, 266

socket, TCP, 73

Socket.IO chat program exercise broadcasting, 185–190 client setup, 183–185 events, 185 reception acknowledgment, 190–191 server setup, 182–183 DJ-by-turns application exercise extending chat, 191–192 Grooveshark API integration, 192–196 playing function, 196–201 introduction, 179 summary, 201 transports, 180–182

socket.io, program setup, 182

sorted sets in Redis, 266

sorting in database, 224

square brackets ([]) for uploading multiple files, 134

SREM command, 266

Stack Overflow (website), 3

stack trace, 24–25, 35–37

Stat object, 58

state variables and TCP, 79–81

static middleware, 120, 127–128

:status dynamic token, 130

stderr stream object, 56, 57

stdin stream object, 56, 59–60

stdio process, 51

stdout stream object, 51, 56, 57, 59–60

store for login sessions, setting up with Connect, 140

Stream objects in first program module, 55–57 fs module, 66–68 net.createServer, 75–76 net.Stream API, 75, 84 types of, 51, 56–57, 59–60

strict routing in Express, 154

string data type in Redis, 263

string JavaScript type, 16

string methods in v8, 24

stringify method, 24, 106

String.prototype, 42

suite in TDD, 298

superagent module, 110–111, 146, 151, 291–292

synchronizing to database in sequelize, 250

synchronous code, 30, 53–55

## T

tablescan lookup, defined, 216

TCP (Transmission Control Protocol) characteristics of, 69–71 chat program exercise creating the module, 74 data event, 77–79 disconnecting, 81–83 net.Server API, 74–76 receiving connections, 76–77 state variables, 79–81 HTTP, relationship to, 69, 88, 93 introduction, 69 IRC client program, 83–85 summary, 85 Telnet, 71–73

TDD (test-driven development), 298

telnet client, 71–73

template engines code sharing, 280 ejs, 146–147, 154 jade, 154, 209–210, 238–240



tenants in cloud environment, 33

testing

- arrays, 23
- asynchronous code, 295–297
- expect.js project, 292–294
- introduction, 289
- Mocha framework, 294–300
- node-redis driver, 270–276
- program, 291–292
- strategy, 290–291
- subject for, 290
- summary, 300

test.js (Mocha), 295–300

text editor, 2

third-party modules, 41

time complexity, Redis, 262

timeouts

- setTimeout function, 40
- Socket.IO, 180
- TCP, 71

tiny logging format, 129

TinySong API, 193–196

Transfer-Encoding HTTP

- header, 92

Transmission Control Protocol.

- See* TCP (Transmission Control Protocol)

transports, Socket.IO, 180–182

try/catch in JavaScript, 21–22

type options in Mongoose, 221

typeof operator, 17, 281

## U

Ubuntu, 9

uncaughtException

- handler, 34

undefined JavaScript type, 16

Unix Standard Streams, 56

up executable, 111–112

updateAttributes

- method, 255

uploads, file, with bodyParser,

- 131–134

:url dynamic token, 130

url property, 97

/url property, 98

use function for static

- middleware, 120

:user-agent dynamic

- token, 130

utf8 string, 105

## V

v8 JavaScript interpreter, 1, 17, 22–26, 32, 33

validate option in sequelize, 256

validation, MongoDB, 218–219

versioning spec for NPM, 53

view options parameter in

- Express, 147, 209, 232

vim text editor (website), 2

virtualized operating systems in

- cloud environment, 33

## W

W3C, 166

watch function, 67–68, 112

Web 2.0, 164

web applications, rise of, 164

web browser. *See* browser

web server. *See* server

WebSocket. *See also* Socket.IO

- API compared to Protocol, 166
- background for, 163–167
- broadcasting issue, 177, 185–190
- client setups, 169
- close event and

  - disconnecting, 177

- defined, 166
- echo example, 167–171
- JSON packet encoding/

  - decoding, 173, 177

- mouse cursor example, 171–176
- Node/JavaScript code sharing, 280, 284
- reconnection issue, 177
- running the server, 170, 176
- server setups, 168, 172
- summary, 178

websocket.io, 167–168, 172

White, Nathan (developer), 207

window object, 40

Windows systems, installing

- Node.js on, 8

working directory, CLI, 64–65

writeHead API, 90, 92

## X

XCode, 8

XMLHttpRequest API, 280, 284




# JS精品图书



## 《基于MVC的 JavaScript Web 富应用开发》

Alex MacCaw 著  
李晶 张散集 译  
2012年05月出版  
ISBN:  
978-7-121-10956-0  
定 价: 59.00元



## 《JavaScript语言 精髓与编程实践》

周爱民 著  
2012年03月出版  
ISBN:  
978-7-121-15640-3  
定 价: 79.00元

## 《JavaScript语言 精粹 (修订版)》


Douglas Crockford 著  
赵泽欣 鄢学鹄 译  
2012年09月出版  
ISBN:  
978-7-121-17740-8  
定 价: 49.00元



O'REILLY

## 《用AngularJS开发 下一代Web应用》

Green,B. Seshadri,S. 著  
大漠穷秋 译  
2013年10月出版  
ISBN:  
978-7-121-21574-2  
定 价: 55.00元



O'REILLY



**Node.js**是一个由JavaScript书写而成的强大的Web开发框架，它让开发强壮的、伸缩性良好的服务器端Web应用变得更加简单、容易。本书向你展示了什么是Node以及如何让你在项目中使用它。本书包含大量实际应用中的示例程序，证明了为什么Node.js会快速成为Web开发首选工具，通过本书，你能够快速熟悉和掌握达到如下目标所需的Node知识和技能：

- 了解Node基于事件轮询的架构、无阻塞I/O以及事件驱动的编程方式
- 精通Node.js的API
- 轻松实现开发实时应用相关的技术，如Socket.IO和HTML5 WebSocket
- 编写能够支持跨多台服务器的高并发应用
- 通过Node来支持多种数据库以及数据存储工具
- 编写在单台服务器情况下能够处理万级并发量的程序
- 能够在包含更多Node知识和注解示例（含源代码）的网站上和其他开发者进行实时的沟通交流

本书包含大量全彩插图和实用的源代码，绝对是一本革命性Web开发工具——Node的实用指南。

Guillermo Rauch（旧金山，加利福尼亚州）是一家位于旧金山，为当地教育提供相关服务的创业公司LearnBoost的CTO和联合创始人。Rauch还是几个知名Node.js项目的发明者，曾在JSConf和一些Node.js workshop做过演讲。

**WILEY**



策划编辑：张春雨  
责任编辑：贾 莉  
封面设计：侯士卿



上架建议：Web开发/JavaScript

ISBN 978-7-121-21769-2



9 787121 217692 >

定价：79.00元