


2.  
*Do It, Do It Again, and  
Again, and Again...*



---

True or false: ( <i>lat?</i> <i>l</i> ) where <i>l</i> is (Jack Sprat could eat no chicken fat)	True, because each S-expression in <i>l</i> is an atom.
---	--

---

True or false: ( <i>lat?</i> <i>l</i> ) where <i>l</i> is ((Jack) Sprat could eat no chicken fat)	False, since ( <i>car l</i> ) is a list.
---	---

---

True or false: ( <i>lat?</i> <i>l</i> ) where <i>l</i> is (Jack (Spat could) eat no chicken fat)	False, since one of the S-expressions in <i>l</i> is a list.
--	---

---

True or false: ( <i>lat?</i> <i>l</i> ) where <i>l</i> is ()	True, because it does not contain a list.
---	--

---

True or false: a lat is a list of atoms.	True! Every lat is a list of atoms!
--	--

---

Write the function <i>lat?</i> using some, but not necessarily all, of the following functions: <i>car cdr cons null? atom? and eq?</i>	You were not expected to be able to do this yet, because you are still missing some ingredients. Go on to the next question. Good luck.
--	---

---

Are you rested?

---

```
(define lat?1
  (lambda (l)
    (cond
      ((null? l) #t)
      ((atom? (car l)) (lat? (cdr l)))
      (else #f))))
```

#t.  
The application (lat? l)  
where  
l is (bacon and eggs)  
has the value #t—true—because l is a lat.

What is the value of (lat? l)  
where  
l is the argument (bacon and eggs)

---

<sup>1</sup> L: (defun lat? (l)  
 (cond  
 ((null l) t)  
 ((atom? (car l)) (lat? (cdr l)))  
 (t nil)))

---

How do we determine the answer #t for the  
application  
(lat? l)

You were not expected to know this one  
either. The answer is determined by  
answering the questions asked by lat?  
Hint: Write down the definition of the  
function lat? and refer to it for the next  
group of questions.

---

What is the first question asked by (lat? l)

(null? l)  
Note:  
(cond ...) asks questions;  
(lambda ...) creates a function; and  
(define ...) gives it a name.

---

What is the meaning of the cond-line  
((null? l) #t)  
where  
l is (bacon and eggs)

(null? l) asks if the argument l is the null  
list. If it is, the value of the application is  
true. If it is not, we ask the next question.  
In this case, l is not the null list, so we ask  
the next question.

---

What is the next question?

(atom? (car l)).

---

---

What is the meaning of the line  
((atom? (car l)) (lat? (cdr l)))  
where  
l is (bacon and eggs)

(atom? (car l)) asks if the first S-expression of the list *l* is an atom. If (car l) is an atom, we want to know if the rest of *l* is also composed only of atoms. If (car l) is not an atom, we ask the next question. In this case, (car l) is an atom, so the value of the function is the value of (lat? (cdr l)).

---

What is the meaning of  
(lat? (cdr l))

(lat? (cdr l)) finds out if the rest of the list *l* is composed only of atoms, by referring to the function with a new argument.

---

Now what is the argument *l* for lat?

Now the argument *l* is (cdr l), which is (and eggs).

---

What is the next question?

(null? l).

---

What is the meaning of the line  
((null? l) #t)  
where  
l is now (and eggs)

(null? l) asks if the argument *l* is the null list. If it is, the value of the application is #t. If it is not, we ask the next question. In this case, *l* is not the null list, so we ask the next question.

---

What is the next question?

(atom? (car l)).

---

What is the meaning of the line  
((atom? (car l)) (lat? (cdr l)))  
where  
l is (and eggs)

(atom? (car l)) asks if (car l) is an atom. If it is an atom, the value of the application is (lat? (cdr l)). If not, we ask the next question. In this case, (car l) is an atom, so we want to find out if the rest of the list *l* is composed only of atoms.

---

What is the meaning of  
(lat? (cdr l))

(lat? (cdr l)) finds out if the rest of *l* is composed only of atoms, by referring again to the function lat?, but this time, with the argument (cdr l), which is (eggs).

---

What is the next question?	<i>(null? l)</i> .
What is the meaning of the line <i>((null? l) #t)</i> where <i>l</i> is now (eggs)	<i>(null? l)</i> asks if the argument <i>l</i> is the null list. If it is, the value of the application is <i>#t</i> —true. If it is not, move to the next question. In this case, <i>l</i> is not null, so we ask the next question.
What is the next question?	<i>(atom? (car l))</i> .
What is the meaning of the line <i>((atom? (car l)) (lat? (cdr l)))</i> where <i>l</i> is now (eggs)	<i>(atom? (car l))</i> asks if <i>(car l)</i> is an atom. If it is, the value of the application is <i>(lat? (cdr l))</i> . If <i>(car l)</i> is not an atom, ask the next question. In this case, <i>(car l)</i> is an atom, so once again we look at <i>(lat? (cdr l))</i> .
What is the meaning of <i>(lat? (cdr l))</i>	<i>(lat? (cdr l))</i> finds out if the rest of the list <i>l</i> is composed only of atoms, by referring to the function <i>lat?</i> , with <i>l</i> becoming the value of <i>(cdr l)</i> .
Now, what is the argument for <i>lat?</i>	<i>()</i> .
What is the meaning of the line <i>((null? l) #t)</i> where <i>l</i> is now <i>()</i>	<i>(null? l)</i> asks if the argument <i>l</i> is the null list. If it is, the value of the application is the value of <i>#t</i> . If not, we ask the next question. In this case, <i>()</i> is the null list. So, the value of the application <i>(lat? l)</i> where <i>l</i> is (bacon and eggs), is <i>#t</i> —true.
Do you remember the question about <i>(lat? l)</i>	Probably not. The application <i>(lat? l)</i> has the value <i>#t</i> if the list <i>l</i> is a list of atoms where <i>l</i> is (bacon and eggs).

---

Can you describe what the function *lat?* does in your own words?

Here are our words:

“*lat?* looks at each S-expression in a list, in turn, and asks if each S-expression is an atom, until it runs out of S-expressions. If it runs out without encountering a list, the value is *#t*. If it finds a list, the value is *#f*—false.”

To see how we could arrive at a value of “false,” consider the next few questions.

---

This is the function *lat?* again:

```
(define lat?  
  (lambda (l)  
    (cond  
      ((null? l) #t)  
      ((atom? (car l)) (lat? (cdr l)))  
      (else #f))))
```

*#f*,  
since the list *l* contains an S-expression that is a list.

What is the value of (*lat?* *l*)

where

*l* is now (bacon (and eggs))

---

What is the first question?

(*null?* *l*).

---

What is the meaning of the line

((*null?* *l*) *#t*)

where

*l* is (bacon (and eggs))

(*null?* *l*) asks if *l* is the null list. If it is, the value is *#t*. If *l* is not null, move to the next question. In this case, it is not null, so we ask the next question.

---

What is the next question?

(*atom?* (*car l*)).

---

What is the meaning of the line

((*atom?* (*car l*)) (*lat?* (*cdr l*)))

where

*l* is (bacon (and eggs))

(*atom?* (*car l*)) asks if (*car l*) is an atom. If it is, the value is (*lat?* (*cdr l*)). If it is not, we ask the next question. In this case, (*car l*) is an atom, so we want to check if the rest of the list *l* is composed only of atoms.

---

What is the meaning of ( <i>lat?</i> ( <i>cdr l</i> ))	( <i>lat?</i> ( <i>cdr l</i> )) checks to see if the rest of the list <i>l</i> is composed only of atoms, by referring to <i>lat?</i> with <i>l</i> replaced by ( <i>cdr l</i> ).
What is the meaning of the line (( <i>null?</i> <i>l</i> ) #t) where <i>l</i> is now ((and eggs))	( <i>null?</i> <i>l</i> ) asks if <i>l</i> is the null list. If it is null, the value is #t. If it is not null, we ask the next question. In this case, <i>l</i> is not null, so move to the next question.
What is the next question?	( <i>atom?</i> ( <i>car l</i> )).
What is the meaning of the line (( <i>atom?</i> ( <i>car l</i> )) ( <i>lat?</i> ( <i>cdr l</i> ))) where <i>l</i> is now ((and eggs))	( <i>atom?</i> ( <i>car l</i> )) asks if ( <i>car l</i> ) is an atom. If it is, the value is ( <i>lat?</i> ( <i>cdr l</i> )). If it is not, we move to the next question. In this case, ( <i>car l</i> ) is not an atom, so we ask the next question.
What is the next question?	<b>else.</b>
What is the meaning of the question <b>else</b>	<b>else</b> asks if <b>else</b> is true.
Is <b>else</b> true?	Yes, because the question <b>else</b> is always true!
<b>else</b>	Of course.
Why is <b>else</b> the last question?	Because we do not need to ask any more questions.
Why do we not need to ask any more questions?	Because a list can be empty, can have an atom in the first position, or can have a list in the first position.
What is the meaning of the line ( <b>else</b> #f)	<b>else</b> asks if <b>else</b> is true. If <b>else</b> is true—as it always is—then the answer is #f—false.

What is ))	These are the closing or matching parentheses of ( <b>cond</b> ..., ( <b>lambda</b> ..., and ( <b>define</b> ..., which appear at the beginning of a function definition.
Can you describe how we determined the value #f for (lat? l) where l is (bacon (and eggs))	Here is one way to say it: “(lat? l) looks at each item in its argument to see if it is an atom. If it runs out of items before it finds a list, the value of (lat? l) is #t. If it finds a list, as it did in the example (bacon (and eggs)), the value of (lat? l) is #f.”
Is (or (null? l1) (atom? l2)) true or false where l1 is () and l2 is (d e f g)	True, because (null? l1) is true where l1 is ().
Is (or (null? l1) (null? l2)) true or false where l1 is (a b c) and l2 is ()	True, because (null? l2) is true where l2 is ().
Is (or (null? l1) (null? l2)) true or false where l1 is (a b c) and l2 is (atom)	False, because neither (null? l1) nor (null? l2) is true where l1 is (a b c) and l2 is (atom).
What does (or ...) do?	(or ...) asks two questions, one at a time. If the first one is true it stops and answers true. Otherwise it asks the second question and answers with whatever the second question answers.



---

Is it true or false that *a* is a member of *lat*  
where *a* is tea  
and  
*lat* is (coffee tea or milk)

True,  
because one of the atoms of the *lat*,  
(coffee tea or milk)  
is the same as the atom *a*—tea.

---

Is (*member? a lat*) true or false  
where *a* is poached  
and  
*lat* is (fried eggs and scrambled eggs)

False,  
since *a* is not one of the atoms of the *lat*.

---

This is the function *member?*

```
(define member?  
  (lambda (a lat)  
    (cond  
      ((null? lat) #f)  
      (else (or (eq? (car lat) a)  
                 (member? a (cdr lat)))))))
```

#t,  
because the atom *meat* is one of the atoms  
of *lat*,  
(mashed potatoes and meat gravy).

What is the value of (*member? a lat*)  
where *a* is meat  
and  
*lat* is (mashed potatoes and meat gravy)

---

How do we determine the value #t for the  
above application?

The value is determined by asking the  
questions about (*member? a lat*).

Hint: Write down the definition of the  
function *member?* and refer to it while you  
work on the next group of questions.

---

What is the first question asked by  
(*member? a lat*)

(*null? lat*).  
This is also the first question asked by *lat?*.

---

# The First Commandment

(*preliminary*)

**Always ask *null?* as the first question in expressing any function.**

---

What is the meaning of the line

`((null? lat) #f)`

where

`lat` is (mashed potatoes and meat gravy)

`(null? lat)` asks if `lat` is the null list. If it is, the value is `#f`, since the atom meat was not found in `lat`. If not, we ask the next question. In this case, it is not null, so we ask the next question.

---

What is the next question?

**else.**

---

Why is **else** the next question?

Because we do not need to ask any more questions.

---

Is **else** really a question?

Yes, **else** is a question whose value is always true.

---

What is the meaning of the line

`(else (or (eq? (car lat) a)  
(member? a (cdr lat))))`

Now that we know that `lat` is not `null?`, we have to find out whether the `car` of `lat` is the same atom as `a`, or whether `a` is somewhere in the rest of `lat`. The answer

`(or (eq? (car lat) a)  
(member? a (cdr lat))))`

does this.

---

True or false:

`(or (eq? (car lat) a)  
(member? a (cdr lat))))`

where `a` is meat

and

`lat` is (mashed potatoes and meat gravy)

We will find out by looking at each question in turn.

---

Is (*eq?* (*car lat*) *a*) true or false  
where *a* is meat  
and  
    *lat* is (mashed potatoes and meat gravy)

False,  
    because meat is not *eq?* to mashed,  
    the *car* of  
        (mashed potatoes and meat gravy).

---

What is the second question of (**or** ...)

(*member?* *a* (*cdr lat*)).  
    This refers to the function with the  
    argument *lat* replaced by (*cdr lat*).

---

Now what are the arguments of *member?*

*a* is meat  
and  
    *lat* is now (*cdr lat*), specifically  
    (potatoes and meat gravy).

---

What is the next question?

(*null?* *lat*).  
    Remember The First Commandment.

---

Is (*null?* *lat*) true or false  
where  
    *lat* is (potatoes and meat gravy)

#f—false.

---

What do we do now?

Ask the next question.

---

What is the next question?

**else.**

---

What is the meaning of  
    (**or** (*eq?* (*car lat*) *a*)  
        (*member?* *a* (*cdr lat*)))

(**or** (*eq?* (*car lat*) *a*)  
    (*member?* *a* (*cdr lat*)))  
finds out if *a* is *eq?* to the *car* of *lat* or if *a* is  
a member of the *cdr* of *lat* by referring to the  
function.

---

Is *a eq?* to the *car* of *lat*

No, because *a* is meat and the *car* of *lat* is  
potatoes.

---

So what do we do next?	We ask ( <i>member?</i> <i>a</i> ( <i>cdr lat</i> )).
Now, what are the arguments of <i>member?</i>	<i>a</i> is meat, and <i>lat</i> is (and meat gravy).
What is the next question?	( <i>null?</i> <i>lat</i> ).
What do we do now?	Ask the next question, since ( <i>null?</i> <i>lat</i> ) is false.
What is the next question?	<b>else.</b>
What is the value of (or ( <i>eq?</i> ( <i>car lat</i> ) <i>a</i> ) ( <i>member?</i> <i>a</i> ( <i>cdr lat</i> )))	The value of ( <i>member?</i> <i>a</i> ( <i>cdr lat</i> )).
Why?	Because ( <i>eq?</i> ( <i>car lat</i> ) <i>a</i> ) is false.
What do we do now?	Recur—refer to the function with new arguments.
What are the new arguments?	<i>a</i> is meat, and <i>lat</i> is (meat gravy).
What is the next question?	( <i>null?</i> <i>lat</i> ).
What do we do now?	Since ( <i>null?</i> <i>lat</i> ) is false, ask the next question.
What is the next question?	<b>else.</b>

---

What is the value of  
(or (eq? (car lat) a)  
(member? a (cdr lat)))

#t,  
because (car lat), which is meat, and a,  
which is meat, are the same atom.  
Therefore, (or ...) answers with #t.

---

What is the value of the application  
(member? a lat)  
where a is meat  
and  
lat is (meat gravy)

#t,  
because we have found that meat is a  
member of  
(meat gravy).

---

What is the value of the application  
(member? a lat)  
where a is meat  
and  
lat is (and meat gravy)

#t,  
because meat is also a member of the lat  
(and meat gravy).

---

What is the value of the application  
(member? a lat)  
where a is meat  
and  
lat is (potatoes and meat gravy)

#t,  
because meat is also a member of the lat  
(potatoes and meat gravy).

---

What is the value of the application  
(member? a lat)  
where a is meat  
and  
lat is (mashed potatoes and meat gravy)

#t,  
because meat is also a member of the lat  
(mashed potatoes and meat gravy).  
Of course, this is our original lat.

---

Just to make sure you have it right, let's  
quickly run through it again. What is the  
value of (member? a lat)  
where  
a is meat  
and  
lat is (mashed potatoes and meat gravy)

#t.  
Hint: Write down the definition of the  
function member? and its arguments and  
refer to them as you go through the next  
group of questions.

---

(null? lat)

No. Move to the next line.

---

---

**else**

Yes.

---

(**or** (*eq?* (*car lat*) *a*)  
(*member?* *a* (*cdr lat*)))

---

Perhaps.

---

(*eq?* (*car lat*) *a*)

---

No. Ask the next question.

---

What next?

Recur with *a* and (*cdr lat*)  
where *a* is meat  
and  
(*cdr lat*) is (potatoes and meat gravy).

---

(*null?* *lat*)

---

No. Move to the next line.

---

**else**

Yes, but (*eq?* (*car lat*) *a*) is false.  
Recur with *a* and (*cdr lat*)  
where *a* is meat  
and  
(*cdr lat*) is (and meat gravy).

---

(*null?* *lat*)

---

No. Move to the next line.

---

**else**

Yes, but (*eq?* (*car lat*) *a*) is false.  
Recur with *a* and (*cdr lat*)  
where *a* is meat  
and  
(*cdr lat*) is (meat gravy).

---

(*null?* *lat*)

---

No. Move to the next line.

---

(*eq?* (*car lat*) *a*)

---

Yes, the value is #t.

---

---

(or (eq? (car lat) a) #t.  
 (member? a (cdr lat)))

---

What is the value of (member? a lat) #t.  
where a is meat  
and  
lat is (meat gravy)

---

What is the value of (member? a lat) #t.  
where a is meat  
and  
lat is (and meat gravy)

---

What is the value of (member? a lat) #t.  
where a is meat  
and  
lat is (potatoes and meat gravy)

---

What is the value of (member? a lat) #t.  
where a is meat  
and  
lat is (mashed potatoes and meat gravy)

---

What is the value of (member? a lat) #f.  
where a is liver  
and  
lat is (bagels and lox)

---

Let's work out why it is #f. What's the first (null? lat).  
question member? asks?

---

(null? lat) No. Move to the next line.

---

---

else

Yes, but (*eq?* (*car lat*) *a*) is false.  
Recur with *a* and (*cdr lat*)  
where *a* is liver  
and  
(*cdr lat*) is (and lox).

---

(*null? lat*)

No. Move to the next line.

---

else

Yes, but (*eq?* (*car lat*) *a*) is false.  
Recur with *a* and (*cdr lat*)  
where *a* is liver  
and  
(*cdr lat*) is (lox).

---

(*null? lat*)

No. Move to the next line.

---

else

Yes, but (*eq?* (*car lat*) *a*) is still false.  
Recur with *a* and (*cdr lat*)  
where *a* is liver  
and  
(*cdr lat*) is ().

---

(*null? lat*)

Yes.

---

What is the value of (*member? a lat*)  
where *a* is liver  
and  
*lat* is ()

---

#f.

What is the value of  
(or (*eq?* (*car lat*) *a*)  
(*member? a (cdr lat)*))  
where  
*a* is liver  
and  
*lat* is (lox)

---

#f.



---

What is the value of (*member?* *a lat*)                      #f.  
where *a* is liver  
and  
    *lat* is (lox)

---

What is the value of    #f.  
    (**or** (*eq?* (*car lat*) *a*)  
        (*member?* *a (cdr lat)*)))  
where  
    *a* is liver  
and  
    *lat* is (and lox)

---

What is the value of (*member?* *a lat*)                      #f.  
where *a* is liver  
and  
    *lat* is (and lox)

---

What is the value of    #f.  
    (**or** (*eq?* (*car lat*) *a*)  
        (*member?* *a (cdr lat)*)))  
where  
    *a* is liver  
and  
    *lat* is (bagels and lox)

---

What is the value of (*member?* *a lat*)                      #f.  
where *a* is liver  
and  
    *lat* is (bagels and lox)

---