whereexpr

A fast, expressive rule-based filtering engine for Rust

Evaluate boolean expressions over any data structure

Gavrilut Dragos

v 0.2.0

What is whereexpr?

▶ Stream Filtering

Drop or keep events on a live stream based on boolean rules

Detection Rules

Write custom detections that trigger when conditions match

🛡 Exclusions

Suppress known-good events from an existing detection

🔍 Data Querying

Filter rows from a database like a WHERE clause

Core Concepts

Attribute

A read-only data specific to an object (data-member or method)

Implementation

struct **Student**

- Fields
  - *Name*
  - *MathGrade*
  - *EnglishGrade*
  - *Age*
- Methods
  - *AverageGrade*
  - *FamilyName*



Attributes associated with Student

Name	*String*
MathGrade	*Integer*
EnglishGrade	*Integer*
Age	*Integer*
AverageGrade	*Integer*
Family Name	*String*

Supported Data Types

- **Numeric** (u8, u16, u32, u64, i8, i16, i32, i64, f32, f64)
- **Boolean** (bool)
- **Strings** (&str)
- **Path** (&str)
- **Ip addresses**
- **Hash-es** (128 bits, 160 bits, 256 bits) – e.g. MD5, SHA1, SHA256
- **DateTime** (seconds from 1970)

Core Concepts

Attribute

A read-only data specific to an object (data-member or method)

Predicate

A compiled operation over a constant value(s)

Supported operations

- **Comparisons** (> , < , different, equals, etc)
- **String/Buffer based** (starts with, contains, etc)
- **List** (is-one-of, etc)
- **Regular expressions** (matches …)
- **Ranges** (between X and Y)

* ***Each operation also supports the NOT operator***

Constant Value

- **Scalar**
- **Array**

* *A constant value supports the same type as an attribute*

Examples

> 10	*comparison*
starts-with "xyz"	*string based*
is-one-of ["John", "Alex", "Gabriel", "Martin"]	*list based*
in-range [192.168.0.1 , 192.168.0.255]	*range operation*
glob-match ["*.exe", "*.dll", "*.p??"]	*match*

Core Concepts

Attribute

A read-only data specific to an object (data-member or method)

Predicate

A compiled operation over a constant value(s)

Operation Aliases

- **Equal** (is, equals, eq, ==)
- **Different** (is-not, not-equals, neq, !=)
- **GreaterThan** (gt, >, greater-than)
- …

** Underline (_) and hyphen (-) are ignored when parsing an operation name. This means that* ***is-not*** , ***is_not*** , ***isnot*** *are the same.*

Operation Classes

- **Equality** (is, is-not)
- **Comparison** (> , < , >= , <=)
- **BufferFind** (starts-with, contains, ends-with)
- **Range**
- **Lists** (is-one-of, is-not-one-of)
- **AutomatFind** (starts-with-one-of, contains-one-of, ends-with-one-of)
- **RegExp** (re-match, glob-match)
- **AutomatRegExp** (glob-match with a list)

Core Concepts

Attribute

A read-only data specific to an object (data-member or method)

Predicate

A compiled operation over a constant value(s)

Data Type / Operation class associations

	EQ	CMP	BUF	R	LST	AF	RE	ARE
Numeric	√	√		√	√			
Bool	√							
String	√		√		√	√	√	
Path	√		√		√	√	√	√
IP	√			√	√			
Hashes	√				√			
DateTime	√	√		√				

Legend

EQ – equality, **CMP** – comparisons, **BUF** – buffer find, **R** – range,
LST – list, **AF** – automat find, **RE** – regular expression, **ARE** – automat re

Core Concepts

Attribute

A read-only data specific to an object (data-member or method)


Predicate

A compiled operation over a constant value(s)

Condition


A tuple formed out of an attribute and a predicate

Architecture



- **Modifier** – optional component that changes how the predicate is evaluated (e.g. if ***ignore-case*** should be used or not)

Examples



Core Concepts

Attribute

A read-only data specific to an object (data-member or method)

Predicate

A compiled operation over a constant value(s)


Condition

A tuple formed out of an attribute and a predicate

Expression

A compiled logical evaluation over a set of conditions

Architecture (set of conditions)



* *Each name is unique (they act as a* ***key*** *in a dictionary/map)*

Architecture (logical evaluation)

A logical expression using condition names and operator AND, OR, NOT as well as parentheses (…) e.g. $Cond_1$ AND $Cond_2$ AND ($Cond_3$ OR $Cond_4$)

Example (Student filtering)

Object / Structure

`struct` **Student**

- **Fields**
  - *Name*
  - *MathGrade*
  - *EnglishGrade*
  - *Age*
  - *Enroll*
  - *Birthday*
- **Methods**
  - *AverageGrade*
  - *FamilyName*

Attributes

Name	*String*
Grade.Math	*Integer*
Grade.English	*Integer*
Age	*Integer*
Grade.Average	*Integer*
Name.Family	*String*
Enroll.Year	*Integer*
Birthday.Month	*Integer*

Condition Set

Age-Is-Prime	*Age* ***is-one-of*** *[19,23,29,31]*
Common	*Name.Family* ***ends-with*** *"escu"* ignore-case
Old-Enroll	*Enroll.Year* ***in-range*** *[2010,2020]*
Passes-Courses	*Grade.Average* ***>=*** *5*
Born-in-dec	*BirthDay.Month* ***is*** *12*
Vowel-Name	*Name* ***starts-with-one-of*** *[A,E,I,O,U]*
Good-at-math	*Grade.Math* ***>=*** *8*

Expression

```
Age-Is-Prime OR Common OR (Old-Enroll AND Good-at-math)
OR NOT (Passes-Courses AND NOT (Born-in-dec OR Vowel-Name))
```

Example (Rust implementation)

1 **Structure Definition**

Code

```
struct Student {
    name: String,
    math_grade: u32,
    english_grade: u32,
    age: u32,
    enrolled: NaiveDate,
    birthday: NaiveDate,
}
```

Example (Rust implementation)

1. Structure Definition
2. Student implementation

Code

```
struct Student {…}
impl Student {
    const NAME: AttributeIndex           = AttributeIndex::new(0);
    const GRADE_MATH: AttributeIndex     = AttributeIndex::new(1);
    const GRADE_ENGLISH: AttributeIndex  = AttributeIndex::new(2);
    const GRADE_AVG: AttributeIndex      = AttributeIndex::new(3);
    const AGE: AttributeIndex            = AttributeIndex::new(4);
    const FAMILY_NAME: AttributeIndex    = AttributeIndex::new(5);
    const ENROLL_YEAR: AttributeIndex    = AttributeIndex::new(6);
    const BIRTHDAY_MONTH: AttributeIndex = AttributeIndex::new(7);

    fn family_name(&self) -> &str {
        self.name.split(' ').next().unwrap()
    }
    fn average_grade(&self) -> u32 {
        (self.math_grade + self.english_grade) / 2
    }
```

Example (Rust implementation)

1. Structure Definition
2. Student implementation
3. Attributes (type safety)

Code

```rust
impl Attributes for Student {
    const TYPE_ID: u64 = 0x12345678; // unique ID for Student type
    const TYPE_NAME: &'static str = "Student";
```

Example (Rust implementation)

1. Structure Definition
2. Student implementation
3. Attributes (type safety)
4. **Attributes (get values)**

Code

```rust
impl Attributes for Student {
    const TYPE_ID: u64 = 0x12345678; // unique ID for Student type
    const TYPE_NAME: &'static str = "Student";

    fn get(&self, idx: AttributeIndex) -> Option<Value<'_>> {
        match idx {
            Self::NAME => Some(Value::String(self.name.as_str())),
            Self::GRADE_MATH => Some(Value::U32(self.math_grade)),
            Self::GRADE_ENGLISH => Some(Value::U32(self.english_grade)),
            Self::GRADE_AVG => Some(Value::U32(self.average_grade())),
            Self::AGE => Some(Value::U32(self.age)),
            Self::FAMILY_NAME => Some(Value::String(self.family_name())),
            Self::ENROLL_YEAR => Some(Value::I32(self.enrolled.year())),
            Self::BIRTHDAY_MONTH => Some(Value::U32(self.birthday.month())),
            _ => None,
        }
    }
```

Example (Rust implementation)

1. Structure Definition
2. Student implementation
3. Attributes (type safety)
4. Attributes (get values)
5. **Attributes (type kind)**

Code

```
impl Attributes for Student {
    fn get(&self, idx: AttributeIndex) -> Option<Value<'_>> {…}

    fn kind(idx: AttributeIndex) -> Option<ValueKind> {
        match idx {
            Self::NAME => Some(ValueKind::String),
            Self::GRADE_MATH => Some(ValueKind::U32),
            Self::GRADE_ENGLISH => Some(ValueKind::U32),
            Self::GRADE_AVG => Some(ValueKind::U32),
            Self::AGE => Some(ValueKind::U32),
            Self::FAMILY_NAME => Some(ValueKind::String),
            Self::ENROLL_YEAR => Some(ValueKind::I32),
            Self::BIRTHDAY_MONTH => Some(ValueKind::U32),
            _ => None,
        }
    }
```

Example (Rust implementation)

1. Structure Definition
2. Student implementation
3. Attributes (type safety)
4. Attributes (get values)
5. Attributes (type kind)
6. **Attributes (indexes)**

Code

```rust
impl Attributes for Student {
    fn get(&self, idx: AttributeIndex) -> Option<Value<'_>> {…}
    fn kind(idx: AttributeIndex) -> Option<ValueKind> {…}
    // for compile time only
    fn index(name: &str) -> Option<AttributeIndex> {
        match name.to_ascii_lowercase().as_str() {
            "name" => Some(Self::NAME),
            "grade.math" => Some(Self::GRADE_MATH),
            "grade.english" => Some(Self::GRADE_ENGLISH),
            "grade.average" => Some(Self::GRADE_AVG),
            "age" => Some(Self::AGE),
            "name.family" => Some(Self::FAMILY_NAME),
            "enroll.year" => Some(Self::ENROLL_YEAR),
            "birthday.month" => Some(Self::BIRTHDAY_MONTH),
            _ => None,
        }
    }
```

Example (Rust implementation)

1. Structure Definition
2. Student implementation
3. Attributes (type safety)
4. Attributes (get values)
5. Attributes (type kind)
6. Attributes (indexes)
7. **Compile a whereexpr**

Code

```
let expr = ExpressionBuilder::<Student>::new()
    .add("age-is-prime", Condition::from_str("age is-one-of [19,23,29,31]"))
    .add("common", Condition::from_str(
                                    "name.family ends-with 'escu' {ignore-case}"))
    .add("old-enroll", Condition::from_str("enroll.year in-range [2010, 2020]"))
    .add("passes-courses", Condition::from_str("grade.average >= 5"))
    .add("born-in-dec", Condition::from_str("birthday.month is 12"))
    .add("vowel-name", Condition::from_str(
                        "name starts-with-one-of [A, E, I, O, U] {ignore-case}"))
    .add("good-at-math", Condition::from_str("grade.math >= 8"))
    .build("Age-Is-Prime OR Common OR (Old-Enroll AND Good-at-math) OR NOT
            (Passes-Courses AND NOT (Born-in-dec OR Vowel-Name))")
    .unwrap();
```

Example (Rust implementation)

1. Structure Definition
2. Student implementation
3. Attributes (type safety)
4. Attributes (get values)
5. Attributes (type kind)
6. Attributes (indexes)
7. Compile a whereexpr
8. **Create a Student Object**

Code

```
let expr = ExpressionBuilder::<Student>::new().add(…)…build(…).unwrap();

let student = Student {
    name: "Popescu Ion".to_string(),
    math_grade: 8,
    english_grade: 9,
    age: 20,
    enrolled: NaiveDate::from_ymd_opt(2020, 1, 1).unwrap(),
    birthday: NaiveDate::from_ymd_opt(1990, 12, 1).unwrap(),
};
```

Example (Rust implementation)

1. Structure Definition
2. Student implementation
3. Attributes (type safety)
4. Attributes (get values)
5. Attributes (type kind)
6. Attributes (indexes)
7. Compile a whereexpr
8. Create a Student Object
9. **Evaluate**

Code

```
let expr = ExpressionBuilder::<Student>::new().add(…)…build(…).unwrap();

let student = Student {…};

println!("matches: {}", expr.matches(&student) );

// three-valued result: Some(true), Some(false) or None (unknown)
match expr.evaluate(&student) {
    Some(true)  => println!("matches"),
    Some(false) => println!("does not match"),
    None        => println!("unknown (missing attribute)"),
}
```

Core Concepts

Condition

A tuple formed out of an attribute and a predicate

Expression

A compiled logical evaluation over a set of conditions

Unknown

A condition whose attribute is missing (get → None)

Kleene logic

How AND, OR and NOT combine true, false and unknown

Three-valued logic (truth tables)

AND	T	F	U
T	T	F	U
F	F	F	F
U	U	F	U

OR	T	F	U
T	T	T	T
F	T	F	U
U	T	U	U

a	NOT a
T	F
F	T
U	U

Rows: a · Columns: b · **T** = true **F** = false **U** = unknown

Rules

AND any false → false; else any unknown → unknown; else true
OR any true → true; else any unknown → unknown; else false
NOT swaps true and false; unknown stays unknown

Kleene logic (examples)

Examples (a, b, c, d are conditions)

Expression	a	b	c	d	Result	Why
`a AND b AND c AND d`	F	F	U	F	false	a false operand decides the AND
`a AND b AND c AND d`	F	F	U	T	false	a false operand decides the AND
`a AND b AND c AND d`	T	T	U	T	unknown	only c could still change the result
`a AND b AND c AND d`	T	T	T	T	true	all operands are true
`a OR b OR c OR d`	F	F	U	F	unknown	only c could still change the result
`a OR b OR c OR d`	F	F	U	T	true	a true operand decides the OR
`a AND b`	U	F			false	order does not matter ...
`a AND b`	F	U			false	... same result either way
`(a OR b) AND c`	U	T	T		true	a OR b is already true
`NOT (a AND b)`	U	T			unknown	NOT unknown is still unknown

Evaluation still short-circuits: AND stops at the first false and OR at the first true. An unknown operand does not stop it, because a later operand may still decide the result.

Kleene logic (matches vs evaluate)

Two ways to evaluate

Result	matches	evaluate
true	`true`	`Some(true)`
false	`false`	`Some(false)`
unknown	**`false`**	**`None`**

`matches` treats unknown as no match, the way a SQL WHERE clause drops rows whose condition is NULL.

`evaluate` returns the full result, so you can tell "does not match" from "cannot tell".

Both panic if the object is not the type the expression was built for (with the `enable_type_check` feature).

Code

```
// Person { name: String, age: Option<u32> }
// get(): Self::AGE => self.age.map(Value::U32)

let expr = ExpressionBuilder::<Person>::new()
    .add("is-ion", Condition::from_str("name is Ion"))
    .add("adult",  Condition::from_str("age >= 18"))
    .build("is-ion AND adult").unwrap();

let ana = Person { name: "Ana".into(), age: None };
expr.matches(&ana);   // false
expr.evaluate(&ana);  // Some(false): the name decides

let ion = Person { name: "Ion".into(), age: None };
expr.matches(&ion);   // false
expr.evaluate(&ion);  // None: the missing age decides
```

Performance considerations

Performance checks

Operation	Data set	Time/1M queries (ms)	Memory	Algorithm
Is-one-of	1000	85 ms	31K	BinSearch
Starts-with-one-of	1000	160 ms	10K	TRIE
Ends-with-one-of	1000	166 ms	10K	REV-TRIE
Contains-one-of	1000	330 ms	55K	DFA/NFA
Glob-Match	1000	1156 ms	4.4M	DFA+REGEXP

- **Data set** = the amount of string that were used to check against (**e.g. name contains […1000 strings…]**)
- **Time/1M queries** = how much time is required to run 1 millions of queries (conditions) of a specific kind (e.g. 1 million queries with different word that check if every word is contains any word from a specific list)

Each test was executed 10 times, and the median was used for time considerations

whereexpr

Write WHERE expressions. Filter anything.

crates.io
crates.io/crates/whereexpr

GitHub
github.com/gdt050579/whereexpr

docs.rs docs.rs/whereexpr

MIT License · Rust 2021 Edition