



Session 2. GSP: Apriori- Based Sequential Pattern Mining

GSP: Apriori-Based Sequential Pattern Mining

- Initial candidates: All singleton sequences
 - <a>, , <c>, <d>, <e>, <f>, <g>, <h>
- Scan DB once, count support for each candidate
- Generate length-2 candidate sequences

$min_sup = 2$

Cand.	sup
<a>	3
	5
<c>	4
<d>	3
<e>	3
<f>	2
<g>	1
<h>	1

	<a>		<c>	<d>	<e>	<f>
<a>	<aa>	<ab>	<ac>	<ad>	<ae>	<af>
	<ba>	<bb>	<bc>	<bd>	<be>	<bf>
<c>	<ca>	<cb>	<cc>	<cd>	<ce>	<cf>
<d>	<da>	<db>	<dc>	<dd>	<de>	<df>
<e>	<ea>	<eb>	<ec>	<ed>	<ee>	<ef>
<f>	<fa>	<fb>	<fc>	<fd>	<fe>	<ff>

	<a>		<c>	<d>	<e>	<f>
<a>		<(ab)>	<(ac)>	<(ad)>	<(ae)>	<(af)>
			<(bc)>	<(bd)>	<(be)>	<(bf)>
<c>				<(cd)>	<(ce)>	<(cf)>
<d>					<(de)>	<(df)>
<e>						<(ef)>
<f>						

SID	Sequence
10	<(bd)cb(ac)>
20	<(bf)(ce)b(fg)>
30	<(ah)(bf)abf>
40	<(be)(ce)d>
50	<a(bd)bcb(ade)>

- Length-2 candidates:
 $36 + 15 = 51$
- Without Apriori pruning:
 $8 * 8 + 8 * 7 / 2 = 92$ candidates

GSP (Generalized Sequential Patterns): Srikant & Agrawal @ EDBT'96)

GSP Mining and Pruning


5th scan: 1 cand. 1 length-5 seq. pat.

4th scan: 8 cand. 6 length-4 seq. pat.

3rd scan: 46 cand. 19 length-3 seq. pat. 20 cand. not in DB at all

2nd scan: 51 cand. 19 length-2 seq. pat. 10 cand. not in DB at all

1st scan: 8 cand. 6 length-1 seq. pat.



□ Repeat (for each level (i.e., length-k))

□ Scan DB to find length-k frequent sequences

□ Generate length-(k+1) candidate sequences from length-k frequent sequences using Apriori

□ set $k = k+1$

□ Until no frequent sequence or no candidate can be found

min_sup = 2	
SID	Sequence
10	<(bd)cb(ac)>
20	<(bf)(ce)b(fg)>
30	<(ah)(bf)abf>
40	<(be)(ce)d>
50	<a(bd)bcb(ade)>