

CBA: Classification Based on Associations

- □ CBA [Liu, Hsu and Ma, KDD'98]
- Method
 - Mine high-confidence, high-support class association rules
 - LHS: conjunctions of attribute-value pairs); RHS: class labels $p_1 \wedge p_2 \dots \wedge p_l \rightarrow \text{"}A_{class-label} = C"$ (confidence, support)
 - Rank rules in descending order of confidence and support
 - Classification: Apply the first rule that matches a test case; o.w. apply the default rule
 - Effectiveness: Often found more accurate than some traditional classification methods, such as C4.5
 - Why? Exploring high confident associations among multiple attributes may overcome some constraints introduced by some classifiers that consider only one attribute at a time

CMAR: Classification Based on Multiple Association Rules

- □ Rule pruning whenever a rule is inserted into the tree
 - Given two rules, R_1 and R_2 , if the antecedent of R_1 is more general than that of R_2 and conf(R_1) \geq conf(R_2), then prune R_2
 - Prunes rules for which the rule antecedent and class label are not positively correlated, based on the χ^2 test of statistical significance
- Classification based on generated/pruned rules
 - If only one rule satisfies tuple X, assign the class label of the rule
 - If a rule set S satisfies X
 - Divide S into groups according to class labels
 - Use a weighted χ^2 measure to find the strongest group of rules, based on the statistical correlation of rules within a group
 - Assign X the class label of the strongest group
- CMAR improves model construction efficiency and classification accuracy