

Android Services & Security:

Overview of Android Services

Douglas C. Schmidt

d.schmidt@vanderbilt.edu

www.dre.vanderbilt.edu/~schmidt



Professor of Computer Science



Institute for Software
Integrated Systems

Vanderbilt University
Nashville, Tennessee, USA




Learning Objectives in this Part of the Module

- Understand what a Service is, the two types of Services Android supports, & the steps involved in implementing & configuring a Service




Overview of a Service

- A Service can perform long-duration operations in the background




Overview of a Service

- A Service can perform long-duration operations in the background , e.g.
 - Perform e-commerce transactions




Overview of a Service

- A Service can perform long-duration operations in the background , e.g.
 - Perform e-commerce transactions
 - Play music or videos on the device




Overview of a Service

- A Service can perform long-duration operations in the background , e.g.
 - Perform e-commerce transactions
 - Play music or videos on the device
- Synchronize contents of SQLite database with the cloud




Overview of a Service

- A Service can perform long-duration operations in the background , e.g.
 - Perform e-commerce transactions
 - Play music or videos on the device
 - Synchronize contents of SQLite database with the cloud
- Download a file




Overview of a Service

- A Service can perform long-duration operations in the background , e.g.
 - Perform e-commerce transactions
 - Play music or videos on the device
 - Synchronize contents of SQLite database with the cloud
- Download a file




Overview of a Service

- A Service can perform long-duration operations in the background
- Other Android components can start a Service



Overview of a Service


- A Service can perform long-duration operations in the background
- Other Android components can start a Service



Overview of a Service


- A Service can perform long-duration operations in the background
- Other Android components can start a Service

A Service can continue to run in the background even if the user switches to another activity




Overview of a Service

- A Service can perform long-duration operations in the background
- Other Android components can start a Service





Overview of a Service

- A Service can perform long-duration operations in the background
- Other Android components can start a Service





Overview of a Service

- A Service can perform long-duration operations in the background
- Other Android components can start a Service



Overview of a Service



- A Service can perform long-duration operations in the background
- Other Android components can start a Service



A Service may or may not actually run in a background Thread


Overview of a Service

- A Service can perform long-duration operations in the background
- Other Android components can start a Service
- Android supports two Service types




Overview of a Service

- A Service can perform long-duration operations in the background
- Other Android components can start a Service
- Android supports two Service types
 - *Started Service*
 - Launched via `startService()`




Overview of a Service

- A Service can perform long-duration operations in the background
- Other Android components can start a Service
- Android supports two Service types
 - *Started Service*
 - Launched via `startService()`
 - Performs a single operation




Overview of a Service

- A Service can perform long-duration operations in the background
- Other Android components can start a Service
- Android supports two Service types
 - *Started Service*
 - Launched via `startService()`
 - Performs a single operation
 - Often doesn't return a result to the client directly




Overview of a Service

- A Service can perform long-duration operations in the background
- Other Android components can start a Service
- Android supports two Service types
 - *Started Service*
 - Launched via `startService()`
 - Performs a single operation
 - Often doesn't return a result to the client directly
 - Should shut itself down when it's done




Overview of a Service

- A Service can perform long-duration operations in the background
- Other Android components can start a Service
- Android supports two Service types
 - *Started Service*
 - *Bound Service*
 - Launched via `bindService()`




Overview of a Service

- A Service can perform long-duration operations in the background
- Other Android components can start a Service
- Android supports two Service types
 - *Started Service*
 - *Bound Service*
 - Launched via `bindService()`
 - Offers a client-service interface that allows extended two-way conversations between client(s) & the Service




Overview of a Service

- A Service can perform long-duration operations in the background
- Other Android components can start a Service
- Android supports two Service types
 - *Started Service*
 - *Bound Service*
 - Launched via `bindService()`
 - Offers a client-service interface that allows extended two-way conversations between client(s) & the Service
 - Is automatically destroyed when all clients unbind




Overview of a Service

- A Service can perform long-duration operations in the background
- Other Android components can start a Service
- Android supports two Service types
- Started & Bound Services can run in the same or different processes as their clients




Overview of a Service

- A Service can perform long-duration operations in the background
- Other Android components can start a Service
- Android supports two Service types
- Started & Bound Services can run in the same or different processes as their clients
 - This choice is determined via a configuration setting in AndroidManifest.xml






Overview of a Service

- A Service can perform long-duration operations in the background
- Other Android components can start a Service
- Android supports two Service types
- Started & Bound Services can run in the same or different processes as their clients
 - This choice is determined via a configuration setting in `AndroidManifest.xml`
- IPC mechanisms are needed to communicate with Services running in different processes




Overview of a Service

- A Service can perform long-duration operations in the background
- Other Android components can start a Service
- Android supports two Service types
- Started & Bound Services can run in the same or different processes as their clients
- Many POSA & GoF patterns are applied to implement Services & guide IPC between Activities & Services



Steps for Implementing a Service

Steps for Implementing a Service



Steps for Implementing a Service

- Implementing a Service is similar to implementing an Activity

```
public class DownloadService
    extends Service {
    public void onCreate() { ... }
    public int onStartCommand
        (Intent intent,
         int flags, int startId) {
        ...
    }
    public abstract IBinder
        onBind(Intent intent) { ... }
    public boolean
        onUnbind(Intent intent) { ... }
    protected void onDestroy() {
        ...
    }
    ...
}
```

Steps for Implementing a Service

- Implementing a Service is similar to implementing an Activity



Services & Activities are both programmed via canonical framework techniques

```
public class DownloadService
    extends Service {
    public void onCreate() { ... }
    public int onStartCommand
        (Intent intent,
         int flags, int startId) {
        ...
    }
    public abstract IBinder
        onBind(Intent intent) { ... }
    public boolean
        onUnbind(Intent intent) { ... }
    protected void onDestroy() {
        ...
    }
    ...
}
```


Steps for Implementing a Service

- Implementing a Service is similar to implementing an Activity, e.g.
 - Extend the Android Service class

```
public class DownloadService
    extends Service {
    public void onCreate() { ... }
    public int onStartCommand
        (Intent intent,
         int flags, int startId) {
        ...
    }
    public abstract IBinder
        onBind(Intent intent) { ... }
    public boolean
        onUnbind(Intent intent) { ... }
    protected void onDestroy() {
        ...
    }
    ...
}
```


Steps for Implementing a Service

- Implementing a Service is similar to implementing an Activity, e.g.
- Extend the Android Service class
 - Defines Service-specific lifecycle hook methods




Android's Service framework dispatches these hook methods via "inversion of control"

```
public class DownloadService
    extends Service {
    public void onCreate() { ... }
    public int onStartCommand
        (Intent intent,
         int flags, int startId) {
        ...
    }
    public abstract IBinder
        onBind(Intent intent) { ... }
    public boolean
        onUnbind(Intent intent) { ... }
    protected void onDestroy() {
        ...
    }
    ...
}
```

Steps for Implementing a Service

- Implementing a Service is similar to implementing an Activity, e.g.
- Extend the Android Service class
 - Defines Service-specific lifecycle hook methods
 - Selectively override lifecycle hook methods




Android's Service framework defines reusable structure & functionality that's specific to different type of Services

```
public class DownloadService
    extends Service {
    public void onCreate() { ... }
    public int onStartCommand
        (Intent intent,
         int flags, int startId) {
        ...
    }
    public abstract IBinder
        onBind(Intent intent) { ... }
    public boolean
        onUnbind(Intent intent) { ... }
    protected void onDestroy() {
        ...
    }
    ...
}
```

Steps for Implementing a Service

- Implementing a Service is similar to implementing an Activity
- Android communicates state changes to a Service by calling its lifecycle hook methods
- onCreate()** – called when Service is first launched, by any means


This method is typically used to initialize the Service



Steps for Implementing a Service

- Implementing a Service is similar to implementing an Activity
- Android communicates state changes to a Service by calling its lifecycle hook methods
- **onCreate()** – called when Service is first launched, by any means
- **onStartCommand()** – called each time a Started Service is sent an Intent via `startService()`


This method receives the Intent passed by the client's call to `startService()`



Steps for Implementing a Service


- Implementing a Service is similar to implementing an Activity
- Android communicates state changes to a Service by calling its lifecycle hook methods
- **onCreate()** – called when Service is first launched, by any means
- **onStartCommand()** – called each time a Started Service is sent an Intent via `startService()`

May be used in conjunction with the concurrency model the Service applies to perform its processing



Steps for Implementing a Service


- Implementing a Service is similar to implementing an Activity
- Android communicates state changes to a Service by calling its lifecycle hook methods
- **onCreate()** – called when Service is first launched, by any means
- **onStartCommand()** – called each time a Started Service is sent an Intent via `startService()`
- **onBind()/onUnbind** – called when client binds/unbinds to Bound Service via `bindService()/unBindService()`



This method receives the Intent passed by the client's call to `bindService()`

Steps for Implementing a Service


- Implementing a Service is similar to implementing an Activity
- Android communicates state changes to a Service by calling its lifecycle hook methods
- **onCreate()** – called when Service is first launched, by any means
- **onStartCommand()** – called each time a Started Service is sent an Intent via `startService()`
- **onBind()/onUnbind** – called when client binds/unbinds to Bound Service via `bindService()/unBindService()`



It is a factory method that returns an IPC channel to the client

Steps for Implementing a Service


- Implementing a Service is similar to implementing an Activity
- Android communicates state changes to a Service by calling its lifecycle hook methods
- **onCreate()** – called when Service is first launched, by any means
- **onStartCommand()** – called each time a Started Service is sent an Intent via `startService()`
- **onBind()/onUnbind** – called when client binds/unbinds to Bound Service via `bindService()/unBindService()`



onUnbind() is a disposal method called when all clients have disconnected

Steps for Implementing a Service

- Implementing a Service is similar to implementing an Activity
- Android communicates state changes to a Service by calling its lifecycle hook methods
- **onCreate()** – called when Service is first launched, by any means
- **onStartCommand()** – called each time a Started Service is sent an Intent via `startService()`
- **onBind()/onUnbind** – called when client binds/unbinds to Bound Service via `bindService()/unBindService()`
- **onDestroy()** – called as Service is being shut down




This method cleans up any resources held by the Service

Integrating a Service into an Application

Integrating a Service into an Application

- The Android Service framework provides a semi-complete portion of an Application

Android



The manifest file tells Android how the Activity & Service components "plug-in" to the framework


Integrating a Service into an Application

- The Android Service framework provides a semi-complete portion of an Application
- Include the Service in the AndroidManifest.xml file

```
<service
    android:enabled=
        ["true" | "false"]
    android:exported=
        ["true" | "false"]
    android:icon=
        "drawable resource"
    android:isolatedProcess=
        ["true" | "false"]
    android:label=
        "string resource"
    android:name="string"
    android:permission="string"
    android:process="string" >
    ...
</service>
```

Integrating a Service into an Application

- The Android Service framework provides a semi-complete portion of an Application
- Include the Service in the AndroidManifest.xml file
 - Add <service> element as a child of <application> element




AndroidManifest.xml

```
...  
<service android:name=  
    "DownloadService"  
    android:exported=  
        "false"/>  
...
```

Integrating a Service into an Application

- The Android Service framework provides a semi-complete portion of an Application
- Include the Service in the AndroidManifest.xml file
 - Add `<service>` element as a child of `<application>` element
 - Provide the `android:name` to reference the Service class




AndroidManifest.xml

```
...  
<service android:name=  
    "DownloadService"  
    android:exported=  
        "false"/>  
...
```

Services do not automatically run in their own processes or threads

Integrating a Service into an Application

- The Android Service framework provides a semi-complete portion of an Application
- Include the Service in the AndroidManifest.xml file
 - Add `<service>` element as a child of `<application>` element
 - Provide the `android:name` to reference the Service class
 - Use `android:process=` `":myProcess"` to run a Service in a separate process



AndroidManifest.xml


```
...  
<service android:name=  
    "DownloadService"  
    android:exported=  
        "false"  
    android:process=  
        ":myProcess" />  
...
```

Summary




Summary

- Apps can use Services to implement long-duration operations in background




Summary

- Apps can use Services to implement long-duration operations in background





Summary

- Apps can use Services to implement long-duration operations in background




Summary

- Apps can use Services to implement long-duration operations in background
- By default, a Service runs in the same process as the application it is part of




Summary

- Apps can use Services to implement long-duration operations in background
- By default, a Service runs in the same process as the application it is part of
- It can also be configured to run in a separate process





AndroidManifest.xml

```
...  
<service android:name=  
    "DownloadService"  
    android:exported=  
    "false"  
    android:process=  
    ":myProcess" />  
...
```



Summary

- Apps can use Services to implement long-duration operations in background
 - By default, a Service runs in the same process as the application it is part of
 - It can also be configured to run in a separate process
- It keeps running until it stops itself, is stopped by a user, or killed by the system if it needs memory



Summary



- Apps can use Services to implement long-duration operations in background
- You can configure many properties of Services via an AndroidManifest.xml file

```
<service
```

```
    android:enabled=["true" | "false"]  
    android:exported=["true" | "false"]  
    android:icon="drawable resource"  
    android:isolatedProcess=["true" | "false"]  
    android:label="string resource"  
    android:name="string"  
    android:permission="string"  
    android:process="string" >
```

```
    ...
```


```
</service>
```



Summary


- Apps can use Services to implement long-duration operations in background
- You can configure many properties of Services via an AndroidManifest.xml file
- Android implements Services via a framework that dispatches hook methods to manage Service lifecycle

Note inversion of control from the Android Service framework to the hook methods




Summary

- Apps can use Services to implement long-duration operations in background
- You can configure many properties of Services via an AndroidManifest.xml file
- Android implements Services via a framework that dispatches hook methods to manage Service lifecycle
- Its framework design is based on software product line techniques




Summary

- Apps can use Services to implement long-duration operations in background
- You can configure many properties of Services via an AndroidManifest.xml file
- Android implements Services via a framework that dispatches hook methods to manage Service lifecycle
- Its framework design is based on software product line methods
- **Commonality**
 - Provides a uniform interface for performing long-duration operations that don't interact directly with the user interface



Summary

- Apps can use Services to implement long-duration operations in background
- You can configure many properties of Services via an AndroidManifest.xml file
- Android implements Services via a framework that dispatches hook methods to manage Service lifecycle
- Its framework design is based on software product line methods
 - **Commonality**
 - **Variability**
 - Subclasses can override lifecycle hook methods to perform the desired initialization for *Started* & *Bound* Services



Summary

- Apps can use Services to implement long-duration operations in background
- You can configure many properties of Services via an `AndroidManifest.xml` file
- Android implements Services via a framework that dispatches hook methods to manage Service lifecycle
- Its framework design is based on software product line methods
- Android's packaged applications contain many Services

Service Type	Example	Behavior
Started	<i>SMS & MMS</i>	Manage message operations, such as sending data, text, & PDU messages
	Alert	Handle calendar event reminders
Bound	Bluetooth Headset	Provides Headset & Handsfree for Phone App
	<i>Media Playback</i>	Provides audio playback in the background
	<i>Exchange Email</i>	Send email messages

Summary

- Apps can use Services to implement long-duration operations in background
- You can configure many properties of Services via an AndroidManifest.xml file
- Android implements Services via a framework that dispatches hook methods to manage Service lifecycle
- Its framework design is based on software product line methods
- Android's packaged applications contain many Services

Service Type	Example	Behavior
Started	<i>SMS & MMS</i>	Manage message operations, such as sending data, text, & PDU messages
	Alert	Handle calendar event reminders
Bound	Bluetooth Headset	Provides Headset & Handsfree for Phone App
	<i>Media Playback</i>	Provides audio playback in the background
	<i>Exchange Email</i>	Send email messages

Summary

- Apps can use Services to implement long-duration operations in background
- You can configure many properties of Services via an `AndroidManifest.xml` file
- Android implements Services via a framework that dispatches hook methods to manage Service lifecycle
- Its framework design is based on software product line methods
- Android's packaged applications contain many Services

Service Type	Example	Behavior
Started	<i>SMS & MMS</i>	Manage message operations, such as sending data, text, & PDU messages
	Alert	Handle calendar event reminders
Bound	Bluetooth Headset	Provides Headset & Handsfree for Phone App
	<i>Media Playback</i>	Provides audio playback in the background
	<i>Exchange Email</i>	Send email messages

Summary

- Apps can use Services to implement long-duration operations in background
- You can configure many properties of Services via an `AndroidManifest.xml` file
- Android implements Services via a framework that dispatches hook methods to manage Service lifecycle
- Its framework design is based on software product line methods
- Android's packaged applications contain many Services

Service Type	Example	Behavior
Started	<i>SMS & MMS</i>	Manage message operations, such as sending data, text, & PDU messages
	Alert	Handle calendar event reminders
Bound	Bluetooth Headset	Provides Headset & Handsfree for Phone App
	<i>Media Playback</i>	Provides audio playback in the background
	<i>Exchange Email</i>	Send email messages

Summary

- Apps can use Services to implement long-duration operations in background
- You can configure many properties of Services via an AndroidManifest.xml file
- Android implements Services via a framework that dispatches hook methods to manage Service lifecycle
- Its framework design is based on software product line methods
- Android's packaged applications contain many Services

Service Type	Example	Behavior
Started	<i>SMS & MMS</i>	Manage message operations, such as sending data, text, & PDU messages
	Alert	Handle calendar event reminders
Bound	Bluetooth Headset	Provides Headset & Handsfree for Phone App
	<i>Media Playback</i>	<i>Provides audio playback in the background</i>
	<i>Exchange Email</i>	Send email messages

Summary

- Apps can use Services to implement long-duration operations in background
- You can configure many properties of Services via an AndroidManifest.xml file
- Android implements Services via a framework that dispatches hook methods to manage Service lifecycle
- Its framework design is based on software product line methods
- Android's packaged applications contain many Services

Service Type	Example	Behavior
Started	<i>SMS & MMS</i>	Manage message operations, such as sending data, text, & PDU messages
	Alert	Handle calendar event reminders
Bound	Bluetooth Headset	Provides Headset & Handsfree for Phone App
	<i>Media Playback</i>	Provides audio playback in the background
	<i>Exchange Email</i>	Send email messages

Summary

- Apps can use Services to implement long-duration operations in background
- You can configure many properties of Services via an AndroidManifest.xml file
- Android implements Services via a framework that dispatches hook methods to manage Service lifecycle
- Its framework design is based on software product line methods
- Android's packaged applications contain many Services

Service Type	Example	Behavior
Started	<i>SMS & MMS</i>	Manage message operations, such as sending data, text, & PDU messages
	Alert	Handle calendar event reminders
Bound	Bluetooth Headset	Provides Headset & Handsfree for Phone App
	<i>Media Playback</i>	Provides audio playback in the background
	<i>Exchange Email</i>	Send email messages