

Java Concurrency:

Overview of Java Threads



Douglas C. Schmidt

d.schmidt@vanderbilt.edu


www.dre.vanderbilt.edu/~schmidt

Institute for Software
Integrated Systems
Vanderbilt University
Nashville, Tennessee, USA



Learning Objectives in this Part of the Module


- Recognize the Java threading mechanisms available to program concurrent software



Alternative Ways of Giving Code to Java Threads


Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run



Alternative Ways of Giving Code to Java Threads


- Java Threads must be given code to run, e.g.
 - Extend the Thread class



See docs.oracle.com/javase/7/docs/api/java/lang/Thread.html


Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run, e.g.
 - Extend the Thread class



Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run, e.g.
 - Extend the Thread class




```
public class MyThread
    extends Thread {
    public void run() {
        // code to run goes here
    }
}
```

Create & start a Thread using
a named subclass of Thread

Alternative Ways of Giving Code to Java Threads


- Java Threads must be given code to run, e.g.
 - Extend the Thread class



```
public class MyThread
    extends Thread {
    public void run() {
        // code to run goes here
    }
}
```


Alternative Ways of Giving Code to Java Threads


- Java Threads must be given code to run, e.g.
 - Extend the Thread class



```
public class MyThread
    extends Thread {
    public void run() {
        // code to run goes here
    }
}
```

Alternative Ways of Giving Code to Java Threads


- Java Threads must be given code to run, e.g.
 - Extend the Thread class



```
public class MyThread
    extends Thread {
    public void run() {
        // code to run goes here
    }
}
```

Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run, e.g.
 - Extend the Thread class




```
public class MyThread
    extends Thread {
    public void run() {
        // code to run goes here
    }
}
```

```
final MyThread myThread =
    new MyThread();
```

Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run, e.g.
 - Extend the Thread class




```
public class MyThread
    extends Thread {
    public void run() {
        // code to run goes here
    }
}
```

```
final MyThread myThread =
    new MyThread();
myThread.start();
```

You can also write a one-liner:
`new MyThread().start()`

Alternative Ways of Giving Code to Java Threads


- Java Threads must be given code to run, e.g.
 - Extend the Thread class
 - Implement the Runnable interface



See docs.oracle.com/javase/tutorial/essential/concurrency/runThread.html


Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run, e.g.
 - Extend the Thread class
 - Implement the Runnable interface




Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run, e.g.
 - Extend the Thread class
 - Implement the Runnable interface



Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run, e.g.
 - Extend the Thread class
 - Implement the Runnable interface




```
public class MyRunnable
    implements Runnable {
    public void run() {
        // code to run goes here
    }
}
```

Create & start a Thread using
a named class as the Runnable

Alternative Ways of Giving Code to Java Threads


- Java Threads must be given code to run, e.g.
 - Extend the Thread class
 - Implement the Runnable interface



```
public class MyRunnable
    implements Runnable {
    public void run() {
        // code to run goes here
    }
}
```

Alternative Ways of Giving Code to Java Threads


- Java Threads must be given code to run, e.g.
 - Extend the Thread class
 - Implement the Runnable interface



```
public class MyRunnable
    implements Runnable {
    public void run() {
        // code to run goes here
    }
}
```

Alternative Ways of Giving Code to Java Threads


- Java Threads must be given code to run, e.g.
 - Extend the Thread class
 - Implement the Runnable interface



```
public class MyRunnable
    implements Runnable {
    public void run() {
        // code to run goes here
    }
}
```

Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run, e.g.
 - Extend the Thread class
 - Implement the Runnable interface




```
public class MyRunnable
    implements Runnable {
    public void run() {
        // code to run goes here
    }
}
```

```
final Runnable myRunnable =
    new MyRunnable();
```

Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run, e.g.
 - Extend the Thread class
 - Implement the Runnable interface




```
public class MyRunnable
    implements Runnable {
    public void run() {
        // code to run goes here
    }
}

final Runnable myRunnable =
    new MyRunnable();
new Thread(myRunnable).start();
```

Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run, e.g.
 - Extend the Thread class
 - Implement the Runnable interface




```
public class MyRunnable
    implements Runnable {
    public void run() {
        // code to run goes here
    }
}

final Runnable myRunnable =
    new MyRunnable();
new Thread(myRunnable).start();
```

Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run, e.g.
 - Extend the Thread class
 - Implement the Runnable interface




```
public class MyRunnable
    implements Runnable {
    public void run() {
        // code to run goes here
    }
}

final Runnable myRunnable =
    new MyRunnable();
new Thread(myRunnable).start();
```

Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run, e.g.
 - Extend the Thread class
 - Implement the Runnable interface




```
public interface Runnable {
    public void run();
}

new Thread(new Runnable() {
    public void run(){
        // code to run goes here
    }
}).start();
```

Create & start a Thread using an anonymous inner class as the Runnable

Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run, e.g.
 - Extend the Thread class
 - Implement the Runnable interface




```
public interface Runnable {
    public void run();
}

new Thread(new Runnable() {
    public void run(){
        // code to run goes here
    }
}).start();
```

Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run, e.g.
 - Extend the Thread class
 - Implement the Runnable interface




```
public interface Runnable {
    public void run();
}

new Thread(new Runnable() {
    public void run(){
        // code to run goes here
    }
}).start();
```

Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run, e.g.
 - Extend the Thread class
 - Implement the Runnable interface




```
public interface Runnable {
    public void run();
}

new Thread(new Runnable() {
    public void run(){
        // code to run goes here
    }
}).start();
```

Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run, e.g.
 - Extend the Thread class
 - Implement the Runnable interface




```
public interface Runnable {
    public void run();
}

new Thread(new Runnable() {
    public void run(){
        // code to run goes here
    }
}).start();
```

Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run, e.g.
 - Extend the Thread class
 - Implement the Runnable interface




```
public interface Runnable {
    public void run();
}

new Thread(new Runnable() {
    public void run(){
        // code to run goes here
    }
}).start();
```

This anonymous inner class idiom
is used extensively in Java code

Alternative Ways of Giving Code to Java Threads

- Java Threads must be given code to run, e.g.
 - Extend the Thread class
 - Implement the Runnable interface
 - Use Java 8 lambda expressions



```
public interface Runnable {
    public void run();
}



new Thread(() -> {
    // code to run goes here
}).start();
```

Java 8 lambda expressions are not officially supported in Android (yet)

Passing Parameters to a Started Thread


Passing Parameters to a Started Java Thread

- The run() methods defined in Java Thread & Runnable take no parameters



Passing Parameters to a Started Java Thread

- The run() methods defined in Java Thread & Runnable take no parameters
- Parameters passed to run() can be supplied via one of two other means



Passing Parameters to a Started Java Thread

- The `run()` methods defined in Java Thread & Runnable take no parameters
- Parameters passed to `run()` can be supplied via one of two other means, e.g.
 - As parameters to a class constructor

```
public class GCDRunnable extends Random implements Runnable {
    final private String mThreadType;

    public GCDRunnable(String threadType) {
        mThreadType = threadType;
    }

    public void run() {
        final String threadString =
            " with " + mThreadType + " thread id " +
            Thread.currentThread();
        ...
    }
}
```

Passing Parameters to a Started Java Thread

- The `run()` methods defined in Java Thread & Runnable take no parameters
- Parameters passed to `run()` can be supplied via one of two other means, e.g.
 - As parameters to a class constructor

```
public class GCDRunnable extends Random implements Runnable {
    final private String mThreadType;

    public GCDRunnable(String threadType) {
        mThreadType = threadType;
    }

    public void run() {
        final String threadString =
            " with " + mThreadType + " thread id " +
            Thread.currentThread();
        ...
    }
}
```

Passing Parameters to a Started Java Thread

- The run() methods defined in Java Thread & Runnable take no parameters
- Parameters passed to run() can be supplied via one of two other means, e.g.
 - As parameters to a class constructor
 - As parameters to “setter” methods

```
public class GCDRunnable extends Thread implements Runnable {  
    final private String mThreadType;  
  
    public void setThreadType(String threadType) {  
        mThreadType = threadType;  
    }  
  
    public void run() {  
        final String threadString =  
            " with " + mThreadType + " thread id " +  
            Thread.currentThread().getId();  
        ...  
    }  
}
```

Passing Parameters to a Started Java Thread


- The run() methods defined in Java Thread & Runnable take no parameters
- Parameters passed to run() can be supplied via one of two other means, e.g.
 - As parameters to a class constructor
 - As parameters to “setter” methods

```
public class GCDRunnable extends Thread implements Runnable {  
    final private String mThreadType;  
  
    public void setThreadType(String threadType) {  
        mThreadType = threadType;  
    }  
  
    public void run() {  
        final String threadString =  
            " with " + mThreadType + " thread id " +  
            Thread.currentThread().getId();  
        ...  
    }  
}
```

Running Java Threads


Running Java Threads

- After start() creates the Thread's resources, the JVM calls its run() hook method




Running Java Threads

- After start() creates the Thread's resources, the JVM calls its run() hook method




Running Java Threads

- After `start()` creates the Thread's resources, the JVM calls its `run()` hook method




Running Java Threads

- After start() creates the Thread's resources, the JVM calls its run() hook method




Running Java Threads

- After start() creates the Thread's resources, the JVM calls its run() hook method




Running Java Threads

- After start() creates the Thread's resources, the JVM calls its run() hook method
- Generally any code can run in a Thread



Running Java Threads


- After start() creates the Thread's resources, the JVM calls its run() hook method
 - Generally any code can run in a Thread
- Windowing toolkits often restrict which thread can access GUI components



See developer.android.com/training/multiple-threads/communicate-ui.html


Running Java Threads

- After start() creates the Thread's resources, the JVM calls its run() hook method
- A Thread can live as long as its run() method hasn't returned




Running Java Threads

- After start() creates the Thread's resources, the JVM calls its run() hook method
- A Thread can live as long as its run() method hasn't returned
 - i.e., either normally or via an exception




Running Java Threads

- After start() creates the Thread's resources, the JVM calls its run() hook method
- A Thread can live as long as its run() method hasn't returned
- The scheduler can suspend & resume a Thread many times




Running Java Threads

- After start() creates the Thread's resources, the JVM calls its run() hook method
- A Thread can live as long as its run() method hasn't returned
- The scheduler can suspend & resume a Thread many times
- For a Thread to execute "forever," its run() method needs an infinite loop




Running Java Threads

- After start() creates the Thread's resources, the JVM calls its run() hook method
- A Thread can live as long as its run() method hasn't returned
- The scheduler can suspend & resume a Thread many times
- For a Thread to execute "forever," its run() method needs an infinite loop
- After run() returns the Thread is no longer alive




Running Java Threads

- After start() creates the Thread's resources, the JVM calls its run() hook method
- A Thread can live as long as its run() method hasn't returned
- The scheduler can suspend & resume a Thread many times
- For a Thread to execute "forever," its run() method needs an infinite loop
- After run() returns the Thread is no longer alive
 - The join() method allows one Thread to wait for the completion of another



Running Java Threads


- After start() creates the Thread's resources, the JVM calls its run() hook method
- A Thread can live as long as its run() method hasn't returned
- The scheduler can suspend & resume a Thread many times
- For a Thread to execute "forever," its run() method needs an infinite loop
- After run() returns the Thread is no longer alive
 - The join() method allows one Thread to wait for the completion of another



See upcoming parts on "Java Barrier Synchronizers"


Running Java Threads

- After start() creates the Thread's resources, the JVM calls its run() hook method
- A Thread can live as long as its run() method hasn't returned
- The scheduler can suspend & resume a Thread many times
- For a Thread to execute "forever," its run() method needs an infinite loop
- After run() returns the Thread is no longer alive
 - The join() method allows one Thread to wait for the completion of another
 - Or the Thread can simple evaporate!



Running Java Threads






















- After start() creates the Thread's resources, the JVM calls its run() hook method
- A Thread can live as long as its run() method hasn't returned
- The scheduler can suspend & resume a Thread many times
- For a Thread to execute "forever," its run() method needs an infinite loop
- After run() returns the Thread is no longer alive
 - The join() method allows one Thread to wait for the completion of another
 - Or the Thread can simple evaporate!
 - The Java virtual machine recycles the resources associated with the Thread



Some Common Java Thread Methods

Some Common Java Thread Methods

- There are a number of commonly used methods in the Java Thread class

<<Java Class>>	
Thread	
	yield():void
	currentThread():Thread
	sleep(long):void
	sleep(long,int):void
	Thread()
	Thread(Runnable)
	Thread(String)
	start():void
	run():void
	exit():void
	interrupt():void
	interrupted():boolean
	isInterrupted():boolean
	isAlive():boolean
	setPriority(int):void
	getPriority():int
	join(long):void
	join(long,int):void
	join():void
	setDaemon(boolean):void
	isDaemon():boolean

See docs.oracle.com/javase/7/docs/api/java/lang/Thread.html






















Some Common Java Thread Methods

- There are a number of commonly used methods in the Java Thread class, e.g.,
 - **void setDaemon()**
 - Marks Thread as a Daemon

<<Java Class>>	
🌀 Thread	
🌀 ^S	yield():void
🌀 ^S	currentThread():Thread
🌀 ^S	sleep(long):void
🌀 ^S	sleep(long,int):void
🌀 ^C	Thread()
🌀 ^C	Thread(Runnable)
🌀 ^C	Thread(String)
🌀	start():void
🌀	run():void
🛑	exit():void
🌀	interrupt():void
🌀 ^S	interrupted():boolean
🌀	isInterrupted():boolean
🌀 ^F	isAlive():boolean
🌀 ^F	setPriority(int):void
🌀 ^F	getPriority():int
🌀 ^F	join(long):void
🌀 ^F	join(long,int):void
🌀 ^F	join():void
🌀 ^F	setDaemon(boolean):void
🌀 ^F	isDaemon():boolean

Some Common Java Thread Methods

- There are a number of commonly used methods in the Java Thread class, e.g.,
 - `void setDaemon()`
 - `void start()`
 - Initiates Thread execution

<<Java Class>>	
Thread	
	<code>yield():void</code>
	<code>currentThread():Thread</code>
	<code>sleep(long):void</code>
	<code>sleep(long,int):void</code>
	<code>Thread()</code>
	<code>Thread(Runnable)</code>
	<code>Thread(String)</code>
	<code>start():void</code>
	<code>run():void</code>
	<code>exit():void</code>
	<code>interrupt():void</code>
	<code>interrupted():boolean</code>
	<code>isInterrupted():boolean</code>
	<code>isAlive():boolean</code>
	<code>setPriority(int):void</code>
	<code>getPriority():int</code>
	<code>join(long):void</code>
	<code>join(long,int):void</code>
	<code>join():void</code>
	<code>setDaemon(boolean):void</code>
	<code>isDaemon():boolean</code>

Some Common Java Thread Methods

- There are a number of commonly used methods in the Java Thread class, e.g.,
 - `void setDaemon()`
 - `void start()`
 - **`abstract void run()`**
 - Hook method for user code

<<Java Class>>	
🌀 Thread	
🌀 ^S	<code>yield():void</code>
🌀 ^S	<code>currentThread():Thread</code>
🌀 ^S	<code>sleep(long):void</code>
🌀 ^S	<code>sleep(long,int):void</code>
🌀 ^C	<code>Thread()</code>
🌀 ^C	<code>Thread(Runnable)</code>
🌀 ^C	<code>Thread(String)</code>
🌀	<code>start():void</code>
🌀	<code>run():void</code>
■	<code>exit():void</code>
🌀	<code>interrupt():void</code>
🌀 ^S	<code>interrupted():boolean</code>
🌀	<code>isInterrupted():boolean</code>
🌀 ^F	<code>isAlive():boolean</code>
🌀 ^F	<code>setPriority(int):void</code>
🌀 ^F	<code>getPriority():int</code>
🌀 ^F	<code>join(long):void</code>
🌀 ^F	<code>join(long,int):void</code>
🌀 ^F	<code>join():void</code>
🌀 ^F	<code>setDaemon(boolean):void</code>
🌀 ^F	<code>isDaemon():boolean</code>






















Some Common Java Thread Methods

- There are a number of commonly used methods in the Java Thread class, e.g.,
 - `void setDaemon()`
 - `void start()`
 - `abstract void run()`
 - `void join()`
 - Waits for a Thread to finish

<<Java Class>>	
🌀 Thread	
🌀 ^S	<code>yield():void</code>
🌀 ^S	<code>currentThread():Thread</code>
🌀 ^S	<code>sleep(long):void</code>
🌀 ^S	<code>sleep(long,int):void</code>
🌀 ^C	<code>Thread()</code>
🌀 ^C	<code>Thread(Runnable)</code>
🌀 ^C	<code>Thread(String)</code>
🌀	<code>start():void</code>
🌀	<code>run():void</code>
■	<code>exit():void</code>
🌀	<code>interrupt():void</code>
🌀 ^S	<code>interrupted():boolean</code>
🌀	<code>isInterrupted():boolean</code>
🌀 ^F	<code>isAlive():boolean</code>
🌀 ^F	<code>setPriority(int):void</code>
🌀 ^F	<code>getPriority():int</code>
🌀 ^F	<code>join(long):void</code>
🌀 ^F	<code>join(long,int):void</code>
🌀 ^F	<code>join():void</code>
🌀 ^F	<code>setDaemon(boolean):void</code>
🌀 ^F	<code>isDaemon():boolean</code>

Some Common Java Thread Methods

- There are a number of commonly used methods in the Java Thread class, e.g.,
 - `void setDaemon()`
 - `void start()`
 - `abstract void run()`
 - `void join()`
 - `void sleep(long time)`
 - Sleeps for given time in ms

<<Java Class>>	
Thread	
	<code>yield():void</code>
	<code>currentThread():Thread</code>
	<code>sleep(long):void</code>
	<code>sleep(long,int):void</code>
	<code>Thread()</code>
	<code>Thread(Runnable)</code>
	<code>Thread(String)</code>
	<code>start():void</code>
	<code>run():void</code>
	<code>exit():void</code>
	<code>interrupt():void</code>
	<code>interrupted():boolean</code>
	<code>isInterrupted():boolean</code>
	<code>isAlive():boolean</code>
	<code>setPriority(int):void</code>
	<code>getPriority():int</code>
	<code>join(long):void</code>
	<code>join(long,int):void</code>
	<code>join():void</code>
	<code>setDaemon(boolean):void</code>
	<code>isDaemon():boolean</code>

Some Common Java Thread Methods

- There are a number of commonly used methods in the Java Thread class, e.g.,
 - `void setDaemon()`
 - `void start()`
 - `abstract void run()`
 - `void join()`
 - `void sleep(long time)`
 - **`Thread currentThread()`**
 - Object for current Thread

<<Java Class>>	
🌀 Thread	
🌀 ^S	<code>yield():void</code>
🌀 ^S	<code>currentThread():Thread</code>
🌀 ^S	<code>sleep(long):void</code>
🌀 ^S	<code>sleep(long,int):void</code>
🌀 ^C	<code>Thread()</code>
🌀 ^C	<code>Thread(Runnable)</code>
🌀 ^C	<code>Thread(String)</code>
🌀	<code>start():void</code>
🌀	<code>run():void</code>
■	<code>exit():void</code>
🌀	<code>interrupt():void</code>
🌀 ^S	<code>interrupted():boolean</code>
🌀	<code>isInterrupted():boolean</code>
🌀 ^F	<code>isAlive():boolean</code>
🌀 ^F	<code>setPriority(int):void</code>
🌀 ^F	<code>getPriority():int</code>
🌀 ^F	<code>join(long):void</code>
🌀 ^F	<code>join(long,int):void</code>
🌀 ^F	<code>join():void</code>
🌀 ^F	<code>setDaemon(boolean):void</code>
🌀 ^F	<code>isDaemon():boolean</code>

Some Common Java Thread Methods






















- There are a number of commonly used methods in the Java Thread class, e.g.,
 - `void setDaemon()`
 - `void start()`
 - `abstract void run()`
 - `void join()`
 - `void sleep(long time)`
 - `Thread currentThread()`
 - **`void interrupt()`**
 - Post an interrupt request to a Thread

<<Java Class>>	
🌀 Thread	
🌀 ^S	<code>yield():void</code>
🌀 ^S	<code>currentThread():Thread</code>
🌀 ^S	<code>sleep(long):void</code>
🌀 ^S	<code>sleep(long,int):void</code>
🌀 ^C	<code>Thread()</code>
🌀 ^C	<code>Thread(Runnable)</code>
🌀 ^C	<code>Thread(String)</code>
🌀	<code>start():void</code>
🌀	<code>run():void</code>
🛑	<code>exit():void</code>
🌀	<code>interrupt():void</code>
🌀 ^S	<code>interrupted():boolean</code>
🌀	<code>isInterrupted():boolean</code>
🌀 ^F	<code>isAlive():boolean</code>
🌀 ^F	<code>setPriority(int):void</code>
🌀 ^F	<code>getPriority():int</code>
🌀 ^F	<code>join(long):void</code>
🌀 ^F	<code>join(long,int):void</code>
🌀 ^F	<code>join():void</code>
🌀 ^F	<code>setDaemon(boolean):void</code>
🌀 ^F	<code>isDaemon():boolean</code>

See upcoming part on "Managing the Java Thread Lifecycle"

Some Common Java Thread Methods

- There are a number of commonly used methods in the Java Thread class, e.g.,
 - `void setDaemon()`
 - `void start()`
 - `abstract void run()`
 - `void join()`
 - `void sleep(long time)`
 - `Thread currentThread()`
 - `void interrupt()`
 - **`boolean isInterrupted()`**
 - Tests whether a thread has been interrupted

<<Java Class>>	
Thread	
	<code>yield():void</code>
	<code>currentThread():Thread</code>
	<code>sleep(long):void</code>
	<code>sleep(long,int):void</code>
	<code>Thread()</code>
	<code>Thread(Runnable)</code>
	<code>Thread(String)</code>
	<code>start():void</code>
	<code>run():void</code>
	<code>exit():void</code>
	<code>interrupt():void</code>
	<code>interrupted():boolean</code>
	<code>isInterrupted():boolean</code>
	<code>isAlive():boolean</code>
	<code>setPriority(int):void</code>
	<code>getPriority():int</code>
	<code>join(long):void</code>
	<code>join(long,int):void</code>
	<code>join():void</code>
	<code>setDaemon(boolean):void</code>
	<code>isDaemon():boolean</code>

`isInterrupted()` can be called multiple times
w/out affecting the *interrupted status*

Some Common Java Thread Methods






















- There are a number of commonly used methods in the Java Thread class, e.g.,
 - `void setDaemon()`
 - `void start()`
 - `abstract void run()`
 - `void join()`
 - `void sleep(long time)`
 - `Thread currentThread()`
 - `void interrupt()`
 - `boolean isInterrupted()`
 - **`boolean interrupted()`**
 - Tests whether current thread has been interrupted

<<Java Class>>	
G Thread	
S	<code>yield():void</code>
S	<code>currentThread():Thread</code>
S	<code>sleep(long):void</code>
S	<code>sleep(long,int):void</code>
C	<code>Thread()</code>
C	<code>Thread(Runnable)</code>
C	<code>Thread(String)</code>
	<code>start():void</code>
	<code>run():void</code>
■	<code>exit():void</code>
	<code>interrupt():void</code>
S	<code>interrupted():boolean</code>
	<code>isInterrupted():boolean</code>
F	<code>isAlive():boolean</code>
F	<code>setPriority(int):void</code>
F	<code>getPriority():int</code>
F	<code>join(long):void</code>
F	<code>join(long,int):void</code>
F	<code>join():void</code>
F	<code>setDaemon(boolean):void</code>
F	<code>isDaemon():boolean</code>

`interrupted()` clears the *interrupted status* the first time it's called

Some Common Java Thread Methods

- There are a number of commonly used methods in the Java Thread class, e.g.,
 - `void setDaemon()`
 - `void start()`
 - `abstract void run()`
 - `void join()`
 - `void sleep(long time)`
 - `Thread currentThread()`
 - `void interrupt()`
 - `boolean isInterrupted()`
 - `boolean interrupted()`
 - **`void setPriority(int newPriority)`
& **`int getPriority()`**
 - Set & get the priority of a Thread**

<<Java Class>>	
Thread	
	<code>yield():void</code>
	<code>currentThread():Thread</code>
	<code>sleep(long):void</code>
	<code>sleep(long,int):void</code>
	<code>Thread()</code>
	<code>Thread(Runnable)</code>
	<code>Thread(String)</code>
	<code>start():void</code>
	<code>run():void</code>
	<code>exit():void</code>
	<code>interrupt():void</code>
	<code>interrupted():boolean</code>
	<code>isInterrupted():boolean</code>
	<code>isAlive():boolean</code>
	<code>setPriority(int):void</code>
	<code>getPriority():int</code>
	<code>join(long):void</code>
	<code>join(long,int):void</code>
	<code>join():void</code>
	<code>setDaemon(boolean):void</code>
	<code>isDaemon():boolean</code>

Some Common Java Thread Methods

- There are a number of commonly used methods in the Java Thread class
- These methods establish various "Happens-Before" orderings

<<Java Class>>	
G Thread	
S	yield():void
S	currentThread():Thread
S	sleep(long):void
S	sleep(long,int):void
C	Thread()
C	Thread(Runnable)
C	Thread(String)
	start():void
	run():void
■	exit():void
	interrupt():void
S	interrupted():boolean
	isInterrupted():boolean
F	isAlive():boolean
F	setPriority(int):void
F	getPriority():int
F	join(long):void
F	join(long,int):void
F	join():void
F	setDaemon(boolean):void
F	isDaemon():boolean

See [en.wikipedia.org/
wiki/Happened-before](https://en.wikipedia.org/wiki/Happened-before)

Some Common Java Thread Methods

- There are a number of commonly used methods in the Java Thread class
- These methods establish various "Happens-Before" orderings, e.g.,
- Starting a thread happens-before the run method of the thread

<<Java Class>>	
G Thread	
S	yield():void
S	currentThread():Thread
S	sleep(long):void
S	sleep(long,int):void
C	Thread()
C	Thread(Runnable)
C	Thread(String)
	start():void
	run():void
■	exit():void
	interrupt():void
S	interrupted():boolean
	isInterrupted():boolean
F	isAlive():boolean
F	setPriority(int):void
F	getPriority():int
F	join(long):void
F	join(long,int):void
F	join():void
F	setDaemon(boolean):void
F	isDaemon():boolean

Some Common Java Thread Methods

- There are a number of commonly used methods in the Java Thread class
- These methods establish various “Happens-Before” orderings, e.g.,
 - Starting a thread happens-before the run method of the thread
 - The termination of a thread happens-before a join with the terminated thread

<<Java Class>>	
G Thread	
S	yield():void
S	currentThread():Thread
S	sleep(long):void
S	sleep(long,int):void
C	Thread()
C	Thread(Runnable)
C	Thread(String)
	start():void
	run():void
■	exit():void
	interrupt():void
S	interrupted():boolean
	isInterrupted():boolean
F	isAlive():boolean
F	setPriority(int):void
F	getPriority():int
F	join(long):void
F	join(long,int):void
F	join():void
F	setDaemon(boolean):void
F	isDaemon():boolean

Some Common Java Thread Methods


- There are a number of commonly used methods in the Java Thread class
- These methods establish various “Happens-Before” orderings, e.g.,
 - Starting a thread happens-before the run method of the thread
 - The termination of a thread happens-before a join with the terminated thread
- Many java.util.concurrent methods also establish happen-before orderings
 - e.g., placing an object into a concurrent collection happens-before the access or removal of the element from the collection

<<Java Class>>	
G Thread	
S	yield():void
S	currentThread():Thread
S	sleep(long):void
S	sleep(long,int):void
C	Thread()
C	Thread(Runnable)
C	Thread(String)
	start():void
	run():void
■	exit():void
	interrupt():void
S	interrupted():boolean
	isInterrupted():boolean
F	isAlive():boolean
F	setPriority(int):void
F	getPriority():int
F	join(long):void
F	join(long,int):void
F	join():void
F	setDaemon(boolean):void
F	isDaemon():boolean

Example of Starting & Joining with Java Threads

Example of Starting & Joining with Java Threads


- Demonstrates the use of various Thread methods to implement an "embarrassingly parallel" application



See github.com/douglasraigschmidt/LiveLessons/tree/master/ThreadJoinTest


Example of Starting & Joining with Java Threads

- Demonstrates the use of various Thread methods to implement an "embarrassingly parallel" application
- Concurrently searches for words in a List of Strings




Example of Starting & Joining with Java Threads

- Demonstrates the use of various Thread methods to implement an "embarrassingly parallel" application
 - Concurrently searches for words in a List of Strings
- Calls `Thread.start()` to spawn a worker Thread for each element in the List of Strings




Example of Starting & Joining with Java Threads

- Demonstrates the use of various Thread methods to implement an "embarrassingly parallel" application
 - Concurrently searches for words in a List of Strings
- Calls `Thread.start()` to spawn a worker Thread for each element in the List of Strings
 - Each Thread concurrently searches for words in its associated String




Example of Starting & Joining with Java Threads

- Demonstrates the use of various Thread methods to implement an "embarrassingly parallel" application
 - Concurrently searches for words in a List of Strings
 - Calls `Thread.start()` to spawn a worker Thread for each element in the List of Strings
 - The main thread uses `Thread.join()` to wait for the worker Threads to finish




Example of Starting & Joining with Java Threads

- Demonstrates the use of various Thread methods to implement an "embarrassingly parallel" application
 - Concurrently searches for words in a List of Strings
 - Calls `Thread.start()` to spawn a worker Thread for each element in the List of Strings
- The main thread uses `Thread.join()` to wait for the worker Threads to finish
 - `Thread.join()` is a simple form of barrier synchronization



Example of Starting & Joining with Java Threads

- Demonstrates the use of various Thread methods to implement an "embarrassingly parallel" application
 - Concurrently searches for words in a List of Strings
 - Calls `Thread.start()` to spawn a worker Thread for each element in the List of Strings
- The main thread uses `Thread.join()` to wait for the worker Threads to finish
 - `Thread.join()` is a simple form of barrier synchronization
 - No other Java synchronization mechanisms are needed



Upcoming parts show other examples of Java synchronization mechanisms