




東京工業大学

Tokyo Institute of Technology

MURATA LAB




Mid-term Presentation

Motif-aware method for graph analysis

Hoang Nguyen (M2), Supervisor: Assoc. Prof. Tsuyoshi Murata

2017/02/03



Scales of network analysis:



- Macroscopic (global view)
- Microscopic (interactions)
- Mesoscopic (sub-structures)

Network motifs are ¹

patterns of statistically significant interconnections occurring in complex networks.



Applications

- Social networks ²
- Biological systems ^{1,3,4}




Motif conductance *(Benson, 2016)*

- Generalization of graph conductance.
- Motif-cooccurrence matrix.
- Good results for graph partitioning.



$$\phi_m(S) = \frac{\text{cut}_M(S, \bar{S})}{\min[\text{vol}_M(S), \text{vol}_M(\bar{S})]}$$



Datasets:

- Blogcatalog3
- Cora, Citeseer, Pubmed
- Facebook (EgoNet)
- Transcription networks

<i>Networks</i>	<i>#nodes</i>	<i>#edge</i>
Blogcatalog3	10312	333983
Cora*	2708	5429
Citeseer*	3327	4732


* Each node has a feature vector (tf-idf)

Deciding motif:

- Motif frequency
- Z-score
- Motif conductance



$$z_m = \frac{N_m(emp) - N_m(rnd)}{\sigma_m}$$

Significant graph - Directed size 3 motifs



Using motif as a guiding pattern


- DeepWalk := Skip-gram+RW
- LINE := DeepWalk+bi-fan
- node2vec := Skip-gram + bias-ed walk
- motifwalk := Skip-gram + motif walk



Generated context: ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●
 Motif context: ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●


Node multi-label classification

- Blogcatalog3 - f1 score
- 39 classes (imbalanced), nodes can have multiple labels



- Bottleneck at context generation.

Motif laplacian for graph convolutional networks



(Kipf, 2016) (Kipf, 2017)

Node label classification

- Citation networks: Cora, citeseer, pubmed. - f1 and acc.
- 3 to 6 classes, each node has exactly one label.

<i>Methods</i>	Cora	Citeseer	Pubmed
Spectral Clus.	59.5	42.7	65.3
DeepWalk	67.2	43.2	65.3
GCN	81.5	70.3	79.0
m-gcn (ours)	83.3	71.4	80.4

- Explaining why does it work.
- Motif search and co-occurrence matrix construction.

My interests:

- Network sampling (diversity oriented).
- Turn m-gcn into a generative model.

Agenda:

- Investigate graph spectral theory.
- Determinantal processes on graphs.
- Graph motif sampling model definition.
- (opt.) Generative Adversarial Networks and Auto-Encoders.

- (Mikolov, 2013) Distributed Representations of Words and Phrases and their Compositionality.*
- (Bengio, 2013) Deep Learning of Representations: Looking Forward.*
- (Ng, 2001) On Spectral Clustering: Analysis and an algorithm.*
- (Perozzi, 2014) DeepWalk: Online Learning of Social Representations.*
- (Tang, 2015) LINE: Large-scale Information Network Embedding.*
- (Cao, 2015) GraRep: Learning Graph Representations with Global Structural Information.*
- (Grover, 2016) node2vec: Scalable Feature Learning for Networks*
- (Yang, 2016) Semi-Supervised Classification with Graph Convolutional Networks*
- (Alon, 2007) Network motifs: theory and experimental approaches.*
- (Benson, 2016) Higher-order organization of complex networks.*
- (Kipf, 2016) Variational Graph Auto-encoder.*
- (Kipf, 2017) Semi-Supervised Classification with Graph Convolutional Networks*

$$x_2 + y_1 = 100$$

$$x_2 + y_1 = 100$$