# Benchmarking Entity Linking for Question Answering over Knowledge Graphs

### Guillermo Echegoyen Blanco

Álvaro Rodrigo Anselmo Peñas {gblanco, alvarory, anselmo} **at** lsi.uned.es

Universidad Nacional de Educación a Distancia



## Overview

- 1. Introduction
- 2. Outcomes
- 3. Experiments
- 4. Results
- 5. Discussion
- 6. References


# Introduction

#### Introduction

## **Entity Linking**

**Def:** Link parts of a Natural Language passage to it's corresponding node in a Knowledge Graph. Usually comprises:

- Recognize the entity mention in the text.
- Disambiguate the mention.



### Introduction

#### **Motivation**

- Asses the impact of Entity Linking on a Question Answering task over a KG.
- Actual collections for QA are easy for Entity Linking.

# **Outcomes**

#### **Outcomes**

#### Our main contributions are:

- QA Datasets characterization
- Semi-automatic method to generate EL dataset.
- Release large benchmark dataset and baseline for EL in QA.

# **Experiments**

## **Experiments**

#### **Datasets**

- QALD {1-4} Unger et al. 2014) ≤ 200 QA pairs each
- LC-QuAD (Trivedi et al. 2017) 5K QA pairs

## **Example**

Q: List all episodes of the first season of the HBO television series The Sopranos

dbr:The\_Sopranos

5

# **Experiments # Characterization**

# **Difficulty**

• Given the Question, how easy is the Entity Linking?

Cases	QALD-1	QALD-2	QALD-3	QALD-4
Total	15	84	89	202
Identical to DBP uri	73.33	85.71	84.27	79.21
Missing tokens		4.76	5.62	9.9
Additional tokens	20.0	1.19	1.12	0.5
Lexical variation	6.67	5.95	5.62	8.42
Other		2.38	3.37	1.98

# **Experiments # Automatic Generation**

**Objective:** Complex dataset for Entity Linking

## **Strategy**

- 1. Develop baseline to detect as much mentions as possible
- 2. Remove items from collection

#### **Baselines**

- Trigram based mention detection
- Distance based mention detection

# **Results**

### **Results # Dataset Release**

#### **Released Datasets**

- QALD-{1-4}-EL: QALD-X version for EL ≤ 45 samples each.
- LC-QuAD-EL: LC-QuAD version for EL  $\leq 1.3K$  samples.
- **C-EL4QA**: Compilation of EL versions  $\leq 1.5K$  samples.

Baseline removed 70% of the dataset in the worst case!

# **Discussion**

### **Discussion**

#### **Research Questions**

- If Entity Linking were more difficult, how QA system would perform?
- Datasets should be created more carefully.



# References

### References i

### References



Priyansh Trivedi et al. "Lc-quad: A corpus for complex question answering over knowledge graphs". In: *International Semantic Web Conference*. Springer. 2017, pp. 210–218.



Christina Unger et al. "Question Answering over Linked Data (QALD-4)". In: (2014). URL: https://hal.inria.fr/hal-01086472/.