Concept for a Safe Self-Replicating Space Drone System

Controllable, Chained, Radio-Based Shutdown Architecture

Satoshi Nakomoto

563

Abstract

This document describes a high-level architecture for a self-replicating space drone system with a primary focus on controllability and safe shutdown capability. The system is not based on nanotechnology but on macroscopic drones. The core design principle is that replication must never be fully autonomous. Every replication process depends on an external, authenticated, and continuous authorization signal.

The proposed solution centers on a first-generation communication relay network, an oscillating (pulsed) authorization signal, a hardware-level shutdown mechanism, and generational limits.

Contents

1 Introduction and Problem Statement **2**

2 System Concept **2**

3 Communication and Shutdown Architecture **2**

3.1 First-Generation Relay Network 2

3.2 Oscillating Authorization Signal 2

3.3 Chained Propagation 3

3.4 Hardware Shutdown Mechanism 3

4 Additional Safety Layers **3**

5 Risks and Mitigations **3**

6 Summary **3**

7 Next Steps **4**

1 Introduction and Problem Statement

The greatest risk of self-replicating systems is that once they start, they become difficult or impossible to stop. This is especially true in space, where distances are large, communication delays are significant, and resources are in principle available (asteroids, regolith, etc.).

The goal is to create an architecture that prevents loss of control at the first-principles level, while still allowing useful operation within the inner Solar System.

2 System Concept

The system has a hierarchical and generational structure:

- **Generation 0:** Earth-based or mothership control center
- **Generation 1:** Pre-deployed communication relays (dense, Starlink-like network)
- **Generation 2+:** Replicating worker and explorer drones

Replication is only permitted when the drone receives a valid, continuous authorization signal.

3 Communication and Shutdown Architecture

3.1 First-Generation Relay Network

The role of the first generation is to provide a stable communication backbone. Recommended operational ranges from the relays:

Distance	Feasibility	Notes
100 – 1 000 km	Very easy	Stable even with small antennas
1 000 – 10 000 km	Easy	Medium-sized antenna sufficient
10 000 – 100 000 km	Well achievable	Larger antenna and higher power required
100 000 – 500 000 km	Still manageable	Around lunar distance
1 000 000 km	Borderline	Stronger system or laser link needed

Recommended practical limit for a pure first-generation radio network: approximately 50 000 – 300 000 km.

3.2 Oscillating Authorization Signal

Instead of a single STOP command, a continuous, authenticated heartbeat (pulsed) signal is used.

- Drones may only perform replication if they regularly receive the signal.
- If the signal is interrupted, the replication module is shut down at the hardware level.
- The signal is cryptographically signed.

3.3 Chained Propagation

The signal propagates outward in a chain through the relays and drones. Every unit forwards the authenticated pulse to other units within its range.

3.4 Hardware Shutdown Mechanism

Stop or signal loss is not a software command but a physical interruption (hardware cut-off of power to the replication module). This cannot be re-enabled by software.

4 Additional Safety Layers

1. **Generational limit:** After a defined maximum number of replication generations, the ability to replicate is permanently disabled.
2. **Resource dependency:** Replication requires a material or component that is only available from controlled sources.
3. **Hierarchy:** Only certain master units are capable of producing full replicas.
4. **Default-off:** In the absence of an authorization signal, the system always returns to the safe (non-replicating) state.

5 Risks and Mitigations

Risk	Mitigation
Communication delay	Default-off + generational limit
Signal spoofing	Strong cryptographic authentication
Hardware bypass	Physical, non-rewritable shutdown mechanism
Remote runaway	Resource restriction + generational limit
Relay network failure	Chained forwarding + redundancy

6 Summary

The presented architecture does not attempt to make self-replication perfectly safe (which is theoretically impossible). Instead, it significantly reduces the risk of loss of control through multiple independent layers.

Key design principles:

- The system must never be fully self-sufficient.
- Continuous, authenticated authorization signal (oscillating heartbeat).
- Hardware-level, irreversible shutdown capability.
- Generational and resource limits.

This approach is well scalable and controllable within the inner Solar System, particularly within a range of approximately 500 000 km.

7 Next Steps

- More detailed frequency and power budget
- Outline of a concrete cryptographic protocol
- Generational limit and error-growth model
- Development of simulation scenarios

This document is conceptual in nature and requires further detailed design work.