Interplanetary Communication and Navigation Architecture

Modified Starlink Constellation with Multi-Body Gravity Assists for Omnidirectional Deep-Space Deployment

Satoshi Nakamoto

1110

Abstract

The primary technological bottleneck of deep-space exploration is maintaining continuous, high-bandwidth communication and expanding sensor networks across the solar system. This White Paper introduces an autonomous, open-source architecture derived from first principles. The system consists of a local network of 6 specialized microsatellites deployed directly around a central node (Starship) combined with a highly dynamic interplanetary relay network. Crucially, the architecture utilizes a multi-body gravity-assist framework. Satellites execute precise slingshot maneuvers using the Moon, Earth, Mars, Jupiter, or solar close-approaches to redirect modified Starlink nodes into stable heliocentric orbits or launch them into completely randomized omnidirectional vectors as independent deep-space exploration probes.

1 Introduction and First Principles

Traditional deep-space exploration relies on Earth-centric tracking and single-target trajectories. Breaking down core orbital mechanics and signal propagation constraints from first principles reveals that localized clusters and flexible routing networks are necessary:

- **Distance-Dependent Signal Decay:** Signal power decreases with the square of the distance ($P_{rx} \propto 1/d^2$). Distributed nodes shorten single-hop distances over massive interplanetary gaps.
- **Line-of-Sight and Solar Occlusion:** High-density solar plasma completely blocks direct paths between inner and outer planets during conjunction phases.
- **Delta-V Efficiency Limits:** Utilizing chemical or ion propulsion alone to cover diverse orbital planes is mass-prohibitive. Gravity assists must substitute raw kinetic propulsion.

2 System Architecture and Network Topology

2.1 Local Starship Constellation Topology (S-LMSN)

The core of this architecture is a tight, dynamically coordinated fleet of exactly **6 network nodes** distributed around the Starship during transit and orbital insertion phases. The minimum required nodes (N_{min}) to guarantee omnidirectional line-of-sight coverage over a specific solid angle (Ω) is given by:

$$N_{min} \geq \frac{4\pi}{\Omega} \tag{1}$$

By deploying a symmetric formation of 6 satellites around the Starship, the spaceship is guaranteed to maintain a high-bandwidth line-of-sight with at least one node at all times, regardless of the vessel's orientation.

2.2 Multi-Body Gravity Assist Framework

Instead of relying on single-planet redirection, the trailing nodes utilize a versatile slingshot matrix utilizing multiple celestial bodies to achieve diverse orbital profiles without fuel expenditure:

- **The Earth-Moon Gateway System:** Initial trajectory modifications are achieved via lunar gravity assists, bending the probe's path relative to Earth to optimize departure velocities.
- **Martian and Solar Redirection:** Approaching the leading edge of Mars or performing a close perihelion burn near the Sun drops the nodes' hyperbolic excess velocity relative to the solar system baricenter, trapping them in tight, stable heliocentric orbits to bridge the inner solar system.
- **The Jupiter Slingshot:** For deep outer-solar-system routing, nodes are directed toward Jupiter's massive gravitational well. The immense orbital energy transfer allows the system to change inclination drastically or accelerate probes beyond escape velocity.
- **Randomized Omnidirectional Vectors:** By varying the periapsis altitude and B-plane targeting during these planetary flybys, the network can systematically distribute nodes into randomized, unmapped deep-space trajectories. This creates an expanding sphere of sensor and relay nodes searching for anomalous data across deep space.

3 Hardware Platform: Deep-Space Starlink Variant

To maximize economic feasibility, the nodes utilize SpaceX's mass-production lines with specific deep-space modifications:

- **Mass and Power:** Augmented with high-power deep-space laser transceivers and expanded solar arrays, bringing the individual dry mass to $\sim$1,000 kg (1 metric ton) per node.
- **Laser Inter-Satellite Links (ISL):** Long-range optical (laser) terminals capable of maintaining cross-links over millions of kilometers in a vacuum at gigabit speeds.
- **Delay-Tolerant Networking (DTN):** Network protocols built explicitly to handle massive light-speed delays using store-and-forward bundle architectures.

4 Launch Deployment and Cost Estimation

Launch logistics utilize Falcon 9 vehicles to Low Earth Orbit (LEO). With a reuse-optimized LEO payload capacity of $\sim$17.5 metric tons, a single Falcon 9 flight can comfortably carry a full block of 15 modified 1-ton satellites. This allows a single launch to provide the 6 local nodes for the Starship, with 9 additional units designated for the deep-space relay train and multi-body gravity assist trajectories.

Due to extreme hardware reuse and vertical integration, SpaceX can establish and upgrade this entire interplanetary internet backbone as an internal project for a mere **$42.5 million USD** every 26 months.

Table 1: Cost Breakdown per Launch Window (15-Satellite Manifest)

Cost Component	**Commercial List Price (USD)**	**Internal SpaceX Cost (US**
Falcon 9 Launch Cost	$67,000,000	$20,000
Satellite Production ($1.5M × 15 units)	$22,500,000	$22,500
Total Budget	**$89,500,000**	**$42,500,**

5 Conclusion

The architecture proposed under the Satoshi Nakamoto protocol offers a decentralized, redundant, and financially viable path toward making humanity multiplanetary and exploring the deep solar system. Publishing this under an open-source GitHub repository guarantees that the protocol can be openly audited and integrated into future Starship mission manifests.