
University of Michigan–Ann Arbor

Department of Electrical Engineering and Computer Science

EECS 475 **Introduction to Cryptography**, Winter 2023

Lecture 22: CPA security continued, El Gamal cryptosystem

March 29, 2023

Lecturer: Mahdi Cheraghchi

Scribe: Yi-Wen Tseng

1 CPA Security

In continuation of the previous class, we want to show that one-query CPA secure implies many-query CPA secure.

Imagine a many-query attacker A that makes up to q queries where $q \in \text{poly}(n)$. Consider the following worlds:

Hybrid 0 (Left World) : all queries (m_0, m_1) to the LR oracle answered by $c \leftarrow \text{Enc}_{pk}(m_0)$.

Hybrid 1 : First query (m_0, m_1) to the LR oracle answered by $c \leftarrow \text{Enc}_{pk}(m_1)$, then $c \leftarrow \text{Enc}_{pk}(m_0)$ thereafter.

Hybrid 2 : First 2 queries (m_0, m_1) to the LR oracle answered by $c \leftarrow \text{Enc}_{pk}(m_1)$, then $c \leftarrow \text{Enc}_{pk}(m_0)$ thereafter.

\vdots

Hybrid q (Right World) : all queries (m_0, m_1) to the LR oracle answered by $c \leftarrow \text{Enc}_{pk}(m_1)$.

Note here, the only difference between $\text{Hybrid}(i - 1)$ and $\text{Hybrid}(i)$ is how the i^{th} query is answered.

Now, we build a "simulator" $S_i^{LR_{pk,b}(\cdot, \cdot)}(pk)$ that gets **one query** and simulates either $\text{Hybrid}(i - 1)$ or $\text{Hybrid}(i)$ depending on b .




Figure 1: Simulator Model

On j^{th} query of A (m_0^j, m_1^j):

- If $j < i$, S_i runs $c \leftarrow Enc_{pk}(m_1^j)$
- If $j > i$, S_i runs $c \leftarrow Enc_{pk}(m_0^j)$
- If $j = i$, S_i queries its LR oracle and gives the result to A

$$\begin{cases} S_i \text{ is in the left world } (b = 0), \text{ then we perfectly simulate } Hybrid(i - 1) \\ S_i \text{ is in the right world } (b = 1), \text{ then we perfectly simulate } Hybrid(i) \end{cases} \quad (1)$$

By triangle inequality,

$$\begin{aligned} Adv_{\pi}^{CPA}(A) &= |Pr(A = 1 \text{ in } Hybrid(0)) - Pr(A = 1 \text{ in } Hybrid(q))| \\ &= |Pr(A = 1 \text{ in } Hybrid(0)) - Pr(A = 1 \text{ in } Hybrid(1)) + Pr(A = 1 \text{ in } Hybrid(1)) \\ &\quad - Pr(A = 1 \text{ in } Hybrid(2)) + Pr(A = 1 \text{ in } Hybrid(2)) \cdots - Pr(A = 1 \text{ in } Hybrid(q))| \\ &\leq \sum_{i=1}^q \underbrace{Adv_{\pi}^{single-CPA}(S_i)}_{negl(n)} = \underbrace{q}_{poly(n)} \cdot negl(n) = negl(n) \end{aligned}$$

The theorem implies that we can encrypt long messages bit-by-bit (or block-by-block) or broken up in any other reasonable way. In other words, it is acceptable to convert one call to encryption on long message to many calls to encryption on short messages.




Figure 2: Block-by-block encryption

Theorem: Any public key encryption scheme with deterministic $Enc_{pk}(\cdot)$ cannot be CPA secure even for 1 query.

Proof: query $c \leftarrow LR_{pk,b}(m_0, m_1)$ for any $m_0 \neq m_1$. Then, run $c' = Enc_{pk}(m_0)$. If $c = c'$ outputs 0, else 1. Because the adversary knows the query (m_0, m_1) and the public key pk , the adversary has a perfect advantage in distinguishing c and c' .

2 El Gamal Cryptosystem

El Gamal is the public key encryption version of Diffie Hellmen. It works as follows:

$$\begin{array}{ccc} & A = g^a \in G & \\ Alice & \xleftrightarrow{\quad} & Bob \\ & B = g^b \in G & \end{array}$$

choose random $a \leftarrow Z_q$

choose random $b \leftarrow Z_q$

$$K = B^a = g^{ab \bmod q} \in G$$

$$K = A^b = g^{ba \bmod q} \in G$$

where G is a group of order q and g is a generator of G .

K is the secret key derived by two parties. We use the properties of cyclic group to get random number with multiplication.

We can look at El Gamal Cryptosystem in terms of (Gen, Enc, Dec) :

Idea: Basically, message is $M \in G$. The "one-time-pad effect" would involve multiplying M with something random: K .

- $Gen(1^n)$: choose random $a \leftarrow Z_q$ output $(pk = A = g^a \in G, sk = a) \Leftarrow$ what Alice computes
- $Enc(pk = A, M \in G)$: choose random $b \leftarrow Z_q$ output ciphertext $(B = g^b \in G, C = M \cdot A^b \in G) \Leftarrow$ what Bob computes
- $Dec(sk = a, (B, C))$: compute $K = B^a$, output $C \cdot K^{-1} \in G$

We need to check the correctness and the security requirement of the cryptosystem.

(1) Correctness: $\forall M \in G, (pk = g^a, sk = a)$

$$Enc(pk, A) = (B = g^b, C = M \cdot (g^a)^b)$$

$$Dec(B, C) = C \cdot (B^a)^{-1} = M \cdot g^{ab} \cdot (g^{(ab)})^{-1} = M$$

(2) CPA Security: Based on the DDH assumption over $G : (g, g^a, g^b, g^{ab}) \in G^4$, where $a, b \leftarrow \mathbb{Z}_q$, is indistinguishable from $(g, g^a, g^b, g^c) \in G^4$, where $a, b, c \leftarrow \mathbb{Z}_q$.

Theorem: If DDH holds for G , then El Gamal is CPA-secure.

Proof: Let A be any feasible p.p.t attacker against El Gamal. Use A to construct the distinguisher against DDH.




Figure 3: Use the attacker against El Gamal to construct the distinguisher against DDH

If (g, A, B, C) is a DH tuple ("real world"), D perfectly simulates the left CPA world because $C = g^{ab}$.

Ideal world: (g, A, B, C) is random then D perfectly simulates a "hybrid" CPA world where the ciphertext is two independent random-group elements (regardless of message).

Symmetrically, we can construct D' vs DDH that replies A with $(B, m_1 \cdot C)$

$$Adv^{CPA}(A) \leq Adv^{DDH}(D) + Adv^{DDH}(D') = negl(n) + negl(n) = negl(n)$$