

## Job overview

- Two-piece ISO B5 kit: one 28-page saddle-stitched mission booklet and one 30-sheet top-glued execution pad with separate front and reverse artwork.
- Trim size: 176 x 250 mm. Supplied production pages: 182 x 256 mm including 3 mm bleed on all sides. TrimBox is embedded in each press PDF.
- Artwork is vector-first and uses process CMYK colors. Manrope and Inter fonts are embedded/subset in the PDFs.
- Do not scale, auto-fit, reflow, impose or convert the supplied files without written approval from NexQ3.

## Production files

- NexQ3\_RE-HUSLE\_V1\_Mission\_Booklet\_Print.pdf
- NexQ3\_RE-HUSLE\_V1\_Execution\_Pad\_Fronts\_Print.pdf
- NexQ3\_RE-HUSLE\_V1\_Execution\_Pad\_Backs\_Print.pdf
- NexQ3\_RE-HUSLE\_V1\_Screen\_Proof.pdf - visual reference only; not for press

## Stock and finish

- Cover: 300 gsm board, matte lamination on outer faces. Confirm fold grain runs parallel to the spine.
- Interior: 100 gsm premium uncoated white or natural-white writing stock, high opacity, suitable for ballpoint, gel, rollerball and pencil.
- Binding: two-wire saddle stitch at the left spine. Final page count is 28, which is divisible by four.

## Booklet checks

- Verify reader order 1-28 before imposition. Page 1 is the front cover; page 28 is the back cover.
- Maintain the 10 mm safe area. No live text is intended inside the bleed. Check all compact labels remain sharp and readable.
- Produce one folded and stitched proof before the full run. Confirm page creep does not compromise the safe area.

## Stock and assembly

- Thirty 100 gsm uncoated writing sheets, printed front and back, collated in sequence from Week 1 Day 1 through the two flex sheets.
- Top glue binding with a clean tear-off edge. A 16 mm top-binding allowance is designed into every sheet.
- Backing board: 400 gsm or equivalent rigid greyboard/whiteback, trimmed flush. Confirm board caliper before packing.
- Duplex registration must keep the matching Sync ID on the front and reverse of each physical sheet. Use long-edge orientation appropriate to top binding; provide a duplex dummy for approval.

## Writing and QR proof

- Test ballpoint, gel, rollerball, fineliner and pencil. Reject stock with distracting show-through or slow ink drying.
- Scan every QR from the physical proof at normal desk distance. Each code must open its matching static route; no code contains personal data.
- The production master currently uses [go.nexq3.com](https://go.nexq3.com). Do not approve the full print run until this branded redirect domain and all routes are live and tested.

## Required proof sequence

1. Printer preflight report: page size, page count, TrimBox/BleedBox, embedded fonts and CMYK confirmation.
2. One booklet dummy plus one fully collated and glued pad proof.
3. NexQ3 checks writing comfort, show-through, tear-off behavior, QR scanning, alignment and final hand feel.
4. Only after written approval: run the agreed quantity, finish, pack and deliver.

## Expected timing after files are accepted

- Local digital-print proof: typically 1-2 working days. Physical corrections, if any, add another proof cycle.
- Short production run: typically 3-7 working days after proof approval. Plan about 5-10 working days total, plus shipping, for a safe first run.
- Before mass production, perform the planned controlled 10-20-user usability and safeguarding test.

## Packaging target

- Finished B5 footprint: 176 x 250 mm - about 6.93 x 9.84 inches. Estimated combined thickness: approximately 6-8 mm, subject to actual paper caliper and board.
- Estimated finished kit weight: approximately 220-250 g before sleeve or mailer. Ask the printer to confirm from the selected stock sample.