

Deep Learning

01 The Artificial Neuron (MP Neuron and Perceptron)

Dr. Konda Reddy Mopuri
Dept. of AI, IIT Hyderabad
Jan-May 2025

Previously

- Course organization
- Brief history - connectionist philosophy

The Neuron

- About 90 billion neurons in human brain




Figure credits: Wikipedia


The dilemma: To watch or not to watch?




భారతీయ టెక్నోలాజికల్ విజ్ఞాన సంస్థ హైదరాబాద్
Indian Institute of Technology Hyderabad



Let's use our brain




Let's use our brain




It's a network of many neurons



There is a division of responsibilities



Neurons in the brain have a hierarchy



Threshold Logic Unit


① First Mathematical Model for a neuron

Threshold Logic Unit

- ① First Mathematical Model for a neuron
- ② McCulloch and Pitts, 1943 \rightarrow MP neuron


Threshold Logic Unit

- ① First Mathematical Model for a neuron
- ② McCulloch and Pitts, 1943 \rightarrow MP neuron
- ③ Boolean inputs and output



Threshold Logic Unit

- 1 First Mathematical Model for a neuron
- 2 McCulloch and Pitts, 1943 \rightarrow MP neuron
- 3 Boolean inputs and output



4

$$f(x) = \mathbb{1}(\sum_i x_i \geq \theta)$$

Threshold Logic Unit

- ① Inputs can be of excitatory or inhibitory nature


Threshold Logic Unit

- ① Inputs can be of excitatory or inhibitory nature
- ② When an inhibitory input is set ($=1$) output $\rightarrow 0$

Threshold Logic Unit

- ① Inputs can be of excitatory or inhibitory nature
- ② When an inhibitory input is set ($=1$) output $\rightarrow 0$
- ③ Counts the number of 'ON' signals on the excitatory inputs versus the inhibitory

Threshold Logic Unit



Example Boolean functions


Threshold Logic Unit

- ① let's implement simple functions

Threshold Logic Unit

① let's implement simple functions


② xy'




Threshold Logic Unit

① let's implement simple functions

② xy'



③ NOR



Threshold Logic Unit

- ① What does one unit do? - Learn linear separation

Threshold Logic Unit

- ① What does one unit do? - Learn linear separation
 - line in 2D, plane in 3D, hyperplane in higher dimensions

Threshold Logic Unit

- ① What does one unit do? - Learn linear separation
 - line in 2D, plane in 3D, hyperplane in higher dimensions
- ② No learning; heuristic approach

- ① Frank Rosenblatt 1957 (American Psychologist)

Perceptron

- ① Frank Rosenblatt 1957 (American Psychologist)
- ② Very crude biological model

Perceptron

- ① Frank Rosenblatt 1957 (American Psychologist)
- ② Very crude biological model
- ③ Similar to MP neuron - Performs linear classification

Perceptron

- ① Frank Rosenblatt 1957 (American Psychologist)
- ② Very crude biological model
- ③ Similar to MP neuron - Performs linear classification
- ④ Inputs can be real, weights can be different for different i/p components

- ① Frank Rosenblatt 1957 (American Psychologist)
- ② Very crude biological model
- ③ Similar to MP neuron - Performs linear classification
- ④ Inputs can be real, weights can be different for different i/p components

⑤

$$f(x) = \begin{cases} 1 & \text{when } \sum_i w_i x_i + b \geq 0 \\ 0 & \text{else} \end{cases}$$

Perceptron

- ① For simplicity we consider +1 and -1 responses

$$\sigma(x) = \begin{cases} 1 & \text{when } x \geq 0 \\ -1 & \text{else} \end{cases}$$



$$f(\mathbf{x}) = \sigma(\mathbf{w}^T \cdot \mathbf{x} + \mathbf{b})$$

Perceptron

- ① For simplicity we consider +1 and -1 responses

$$\sigma(x) = \begin{cases} 1 & \text{when } x \geq 0 \\ -1 & \text{else} \end{cases}$$



$$f(\mathbf{x}) = \sigma(\mathbf{w}^T \cdot \mathbf{x} + \mathbf{b})$$

- ② In general, $\sigma(\cdot)$ that follows a linear operation is called an activation function

Perceptron

- ① For simplicity we consider +1 and -1 responses

$$\sigma(x) = \begin{cases} 1 & \text{when } x \geq 0 \\ -1 & \text{else} \end{cases}$$



$$f(\mathbf{x}) = \sigma(\mathbf{w}^T \cdot \mathbf{x} + \mathbf{b})$$

- ② In general, $\sigma(\cdot)$ that follows a linear operation is called an activation function
- ③ \mathbf{w} are referred to as weights and b as the bias

Perceptron vs. MP neuron

- ① Perceptron is more general computational model

Perceptron vs. MP neuron

- ① Perceptron is more general computational model
- ② Inputs can be real

Perceptron vs. MP neuron

- ① Perceptron is more general computational model
- ② Inputs can be real
- ③ Weights are different on the input components

Perceptron vs. MP neuron

- ① Perceptron is more general computational model
- ② Inputs can be real
- ③ Weights are different on the input components
- ④ Mechanism for **learning** the weights

Weights and Bias

① Why are the weights important?




Figure credits: DeepAI

Weights and Bias

- ① Why are the weights important?
- ② Why is it called 'bias'? What does it capture?




Figure credits: DeepAI

Perceptron




Figure credits: François Fleuret

Perceptron




Figure credits: François Fleuret

Perceptron Learning algorithm

① Training data $(x^i, y^i) \in \mathcal{R}^D \times \{-1, 1\}, i = 1, \dots, N$

Perceptron Learning algorithm

- ① Training data $(x^i, y^i) \in \mathcal{R}^D \times \{-1, 1\}, i = 1, \dots, N$
- ② Start with $k \leftarrow 1$ and $\mathbf{w}_k = \mathbf{0}$

Perceptron Learning algorithm

- ① Training data $(x^i, y^i) \in \mathcal{R}^D \times \{-1, 1\}, i = 1, \dots, N$
- ② Start with $k \leftarrow 1$ and $\mathbf{w}_k = \mathbf{0}$
- ③ While $\exists i \in \{1, 2 \dots N\}$ such that $y^i(\mathbf{w}_k^T \cdot \mathbf{x}^i) \leq 0$, update
 $\mathbf{w}_{k+1} = \mathbf{w}_k + \mathbf{y}^i \cdot \mathbf{x}^i$
 $k \leftarrow k + 1$

Perceptron Learning algorithm

- ① Training data $(x^i, y^i) \in \mathcal{R}^D \times \{-1, 1\}, i = 1, \dots, N$
- ② Start with $k \leftarrow 1$ and $\mathbf{w}_k = \mathbf{0}$
- ③ While $\exists i \in \{1, 2 \dots N\}$ such that $y^i(\mathbf{w}_k^T \cdot \mathbf{x}^i) \leq 0$, update
 $\mathbf{w}_{k+1} = \mathbf{w}_k + \mathbf{y}^i \cdot \mathbf{x}^i$
 $k \leftarrow k + 1$
- ④ Note that the bias b is absorbed as a component of \mathbf{w} and \mathbf{x} is appended with 1 suitably

Perceptron Learning Algorithm

► Colab Notebook: [Perceptron-learning](#)

Perceptron Learning Algorithm

- ① Convergence result: For linearly separable dataset, the algorithm converges after finite iterations (refer to suggested readings)

Perceptron Learning Algorithm

- ① Convergence result: For linearly separable dataset, the algorithm converges after finite iterations (refer to suggested readings)
- ② Stops as soon as it finds a separating boundary

Perceptron Learning Algorithm

- ① Convergence result: For linearly separable dataset, the algorithm converges after finite iterations (refer to suggested readings)
- ② Stops as soon as it finds a separating boundary
- ③ Other (some) algorithms maximize the margin from the boundary to the samples

So far...

- ① Generalized to non-binary (real) input

So far...

- ① Generalized to non-binary (real) input
- ② Considered unequal importance to the inputs

So far...

- ① Generalized to non-binary (real) input
- ② Considered unequal importance to the inputs
- ③ Avoided heuristics with 'learning' the Threshold

So far...

- ① Generalized to non-binary (real) input
- ② Considered unequal importance to the inputs
- ③ Avoided heuristics with 'learning' the Threshold
- ④ What if the data is not linearly separable?

Coming..

① Single layer Neural Networks - Regression & Classification