

OVERVIEW

PACKAGE

CLASS

TREE

DEPRECATED

INDEX

HELP

SRU2024-10.2.7

ALL CLASSES

SUMMARY: NESTED | FIELD | CONSTR | METHODDETAIL: FIELD | CONSTR | METHOD

SEARCH:

Package

com.prowidesoftware.swift.model.mx

Class MxPacs00800112

java.lang.Object  
com.prowidesoftware.swift.model.AbstractMessage  
com.prowidesoftware.swift.model.mx.AbstractMX  
com.prowidesoftware.swift.model.mx.MxPacs00800112

All Implemented Interfaces:  
com.prowidesoftware.JsonSerializable

public class MxPacs00800112  
extends AbstractMX

Class for pacs.008.001.12 ISO 20022 message.

Field Summary

Fields		
Modifier and Type	Field	Description
static java.lang.Class[]	_classes	
static java.lang.String	BUSINESS_PROCESS	
protected com.prowidesoftware.swift.model.mx.dic.FIToFICustomerCreditTransferV12	fiToFICstmrCdtTrf	
static int	FUNCTIONALITY	
static java.lang.String	NAMESPACE	
static int	VARIANT	
static int	VERSION	

Fields inherited from class com.prowidesoftware.swift.model.mx.AbstractMX

DEFAULT\_ROOT\_ELEMENT, DOCUMENT\_LOCALNAME

Constructor Summary

Constructors	
Constructor	Description
MxPacs00800112()	
MxPacs00800112(MxSwiftMessage mxSwiftMessage)	Creates the MX object parsing the raw content from the parameter MxSwiftMessage
MxPacs00800112(java.lang.String xml)	Creates the MX object parsing the parameter String with the XML content

Method Summary

All Methods	Static Methods	Instance Methods	Concrete Methods		
Modifier and Type			Method		Description
boolean			equals(java.lang.Object that)		
static MxPacs00800112			fromJson(java.lang.String json)		Creates an MxPacs00800112 messages from its JSON representation.
java.lang.String			getBusinessProcess()		get the Alphabetic code in four positions (fixed length) identifying the Business Process
java.lang.Class[]			getClasses()		Get the classes associated with this message
com.prowidesoftware.swift.model.mx.dic.FIToFICustomerCreditTransferV12			getFIToFICstmrCdtTrf()		Gets the value of the fiToFICstmrCdtTrf property.
int			getFunctionality()		Get the code identifying the Message Functionality
java.lang.String			getNamespace()		Get the XML namespace of the message
int			getVariant()		Get the Message variant
int			getVersion()		Get the message version
int			hashCode()		
static MxPacs00800112			parse(java.lang.String xml)		Creates the MX object parsing the raw content from the parameter

OVERVIEW PACKAGE CLASS TREE DEPRECATED INDEX HELP

SRU2024-10.2.7

ALL CLASSES

SUMMARY: NESTED | FIELD | CONSTR | METHODDETAIL: FIELD | CONSTR | METHOD

SEARCH:

static MxPacs00800112

parse(java.lang.String xml, MxRead parserImpl)

Creates the MX object parsing the raw content from the parameter XML with injected read implementation

static MxPacs00800112

parse(java.lang.String xml, MxReadConfiguration conf)

Creates the MX object parsing the raw content from the parameter XML, using the provided unmarshalling options

MxPacs00800112

setFIToFICstmrCdtTrf  
(com.prowidesoftware.swift.model.mx.dic.FIToFICustomerCreditTransferV12 value)

Sets the value of the fitoFICstmrCdtTrf property.

java.lang.String

toString()

Methods inherited from class com.prowidesoftware.swift.model.mx.AbstractMX

document, document, document, element, element, fromJson, fromJsonV9, fromJsonV9, getAppHdr, getMxId, header, header, message, message, parse, parse, parse, parse, setAppHdr, targetNamespace, toJson, toJsonV9, write, write, xmlSource

Methods inherited from class com.prowidesoftware.swift.model.AbstractMessage

getMessageStandardType, isMT, isMX

Methods inherited from class java.lang.Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Field Detail

fitoFICstmrCdtTrf

protected com.prowidesoftware.swift.model.mx.dic.FIToFICustomerCreditTransferV12 fitoFICstmrCdtTrf

BUSINESS\_PROCESS

public static final transient java.lang.String BUSINESS\_PROCESS

See Also:  
Constant Field Values

FUNCTIONALITY

public static final transient int FUNCTIONALITY

See Also:  
Constant Field Values

VARIANT

public static final transient int VARIANT

See Also:  
Constant Field Values

VERSION

public static final transient int VERSION

See Also:  
Constant Field Values

\_classes

public static final transient java.lang.Class[] \_classes

NAMESPACE

public static final transient java.lang.String NAMESPACE

See Also:  
Constant Field Values

**MxPacs00800112**

public MxPacs00800112()

**MxPacs00800112**

public MxPacs00800112(java.lang.String xml)

Creates the MX object parsing the parameter String with the XML content

**MxPacs00800112**

public MxPacs00800112(MxSwiftMessage mxSwiftMessage)

Creates the MX object parsing the raw content from the parameter MxSwiftMessage

getFIToFICstmrCdtTrf

public com.providesoftware.swift.model.mx.dic.FIToFICustomerCreditTransferV12 getFIToFICstmrCdtTrf()

Gets the value of the fitoFICstmrCdtTrf property.

Returns:

possible object is FIToFICustomerCreditTransferV12

setFIToFICstmrCdtTrf

public MxPacs00800112 setFIToFICstmrCdtTrf(com.providesoftware.swift.model.mx.dic.FIToFICustomerCreditTransferV12 value)

Sets the value of the fitoFICstmrCdtTrf property.

Parameters:

value - allowed object is FIToFICustomerCreditTransferV12

getBusinessProcess

public java.lang.String getBusinessProcess()

Description copied from class: AbstractMX

get the Alphabetic code in four positions (fixed length) identifying the Business Process

Specified by:

getBusinessProcess in class AbstractMX

Returns:

the business process of the implementing class

getFunctionality

public int getFunctionality()

Description copied from class: AbstractMX

Get the code identifying the Message Functionality

Specified by:

getFunctionality in class AbstractMX

Returns:

the set functionality or null if not set

getVariant

public int getVariant()

Description copied from class: AbstractMX

Get the Message variant

Specified by:

getVariant in class AbstractMX

Returns:

the set variant or null if not set

getVersion

public int getVersion()

Description copied from class: AbstractMX

Get the message version

Specified by:

getVersion in class AbstractMX

Returns:

the set vesion or null if not set

parse

public static MxPacs00800112 parse(java.lang.String xml)

Creates the MX object parsing the raw content from the parameter XML, using default unmarshalling options

parse

public static MxPacs00800112 parse(java.lang.String xml, MxReadConfiguration conf)

Creates the MX object parsing the raw content from the parameter XML, using the provided unmarshalling options

Since:

9.2.6

parse

public static MxPacs00800112 parse(java.lang.String xml, MxRead parserImpl)

Creates the MX object parsing the raw content from the parameter XML with injected read implementation

OVERVIEWPACKAGECLASSTREEDEPRECATEDINDEXHELP

ALL CLASSES

SUMMARY: NESTED | FIELD | CONSTR | METHODDETAIL: FIELD | CONSTR | METHOD

SRU2024-10.2.7

SEARCH:

getNamespace

public java.lang.String getNamespace()  
**Description copied from class: AbstractMX**  
Get the XML namespace of the message  
**Specified by:**  
getNamespace in class AbstractMX

getClasses

public java.lang.Class[] getClasses()  
**Description copied from class: AbstractMX**  
Get the classes associated with this message  
**Specified by:**  
getClasses in class AbstractMX

fromJson

public static final MxPacs00800112 fromJson(java.lang.String json)  
  
Creates an MxPacs00800112 messages from its JSON representation.  
  
For generic conversion of JSON into the corresponding MX instance see AbstractMX.fromJson(String)  
**Parameters:**  
json - a JSON representation of an MxPacs00800112 message  
**Returns:**  
a new instance of MxPacs00800112  
**Since:**  
7.10.2

toString

public java.lang.String toString()  
  
**Overrides:**  
toString in class java.lang.Object

equals

public boolean equals(java.lang.Object that)  
  
**Overrides:**  
equals in class java.lang.Object

hashCode

public int hashCode()  
  
**Overrides:**  
hashCode in class java.lang.Object