

# Security Idiots

[Home](#)[Categories](#)[Video Gallery](#)[The Idiots Team](#)[Contact Us](#)

## Tutorials Browser

### Web Pentest

#### Information-Gathering

[Part-0-Purpose-of-Information-Gathering.html](#)[Part-1-information-Gathering-with-websites.html](#)[Part-2-information-Gathering-with-Google.html](#)[Part-3-information-Gathering-with-nmap.html](#)[Part-4-DNS-information-Gathering-with-DIG.html](#)[Part-5-information-Gathering-with-Fierce.html](#)[Part-6-information-Gathering-with-FOCA.html](#)[Part-7-information-Gathering-with-Metagoofil.html](#)

#### Cloudflare-Bypass

[Part-1-Understanding-Cloudflare-Security.html](#)[Part-2-Cloudflare-Security-Bypass.html](#)[Part-3-Cloudflare-Security-Bypass.html](#)[Part-4-Cloudflare-Security-Bypass.html](#)

### LFI

[guide-to-lfi.html](#)

### SQL-Injection

#### SQL-Injection

[Part-1-Basic-of-SQL-for-SQLi.html](#)[Part-2-Basic-of-SQL-for-SQLi.html](#)[Part-3-Basic-of-SQL-for-SQLi.html](#)[Basic-Union-Based-SQL-Injection.html](#)[basic-injection-single-line-or-death.html](#)

## Basics of Javascript for XSS part 2

Welcome to the Part2 of Basics of JavaScript for XSS.

In our last Tutorial, Part1 of Basics of JavaScript for XSS we learnt about:

- DOM
- JavaScript Basic Syntax
- Declaring variables
- Different datatypes (number,String,boolean,Object,Array)
- Different Notations to access Object's properties value

Now we will continue our discussion on some other Important Properties of "window" and "d

[window.location.hash or location.hash](#) - This property returns the part of URI Fragment ie. V the URL after "#" (hash symbol) For example a URL <https://www.securityidiots.com/#blablabla> "location.hash;" would return "#blablabla" and [location.hash.slice\(1\)](#); would return blablabla; character from the string, which is #.

This part after hash in the URL is for client side usage and hence it couldn't be accessed by Server Side Languages which is why it is very helpful in bypassing Server Side WAF.

[window.location.search or location.search](#) - This property returns the query string or the example:

```
https://www.securityidiots.com/?xyz=1&abc=zen
"location.search;" would return "?xyz=1&abc=zen"
```

[document.domain](#) - This property is used to return the hostname of where javascript is running. This is mainly used to confirm that XSS is executing on the right domain.

[document.cookie](#) - This property is used to get all Cookies as a String, but if there is a "HttpOnly" cookies, then cookies couldn't be accessed via JavaScript.

[document.getElementById\('123'\)](#) - This is a Method (a Function) which is used to get all elements with the value of "id" attribute provided in the argument. We could then even modify/remove the element. Example:

```
<!doctype html>
<html>
<p id="someID">Select Me</p>
<script>
var selected=document.getElementById("someID");/*would store the <p id="someID">Select Me</p>
</script>
</html>
```

XPATH-Error-Based-Injection-  
Extractvalue.html

XPATH-Error-Based-Injection-  
UpdateXML.html

Error-Based-Injection-  
Subquery-Injection.html

sql-evil-twin-injection.html

Blind-SQL-Injection.html

bypass-login-using-sql-  
injection.html

dump-database-from-login-  
form-sqli.html

url-spoofed-phishing-with-  
sqli.html

ddos-website-with-sqli-  
siddos.html

delete-query-injection.html

update-query-injection.html

xss-injection-with-sqli-  
xssqli.html

time-based-blind-  
injection.html

insert-query-injection.html

group-by-and-order-by-sql-  
injection.html

Union-based-Oracle-  
Injection.html

Dump-in-One-Shot-part-1.html

Dump-in-One-Shot-part-2.html

DIOS-the-SQL-Injectors-  
Weapon-Upgraded.html

database-type-testing-sql-  
injection.html

routed\_sql\_injection.html

multi-query-injection.html

mssql-insert-query-  
injection.html

oracle-sql-injection-dios-  
query.html

mssql-out-of-band-  
exploitation.html

addslashes-bypass-sql-  
injection.html

MSSQL

mssql-dios.html

MSSQL-Union-Based-  
Injection.html

MSSQL-Error-Based-  
Injection.html

Tricks

Grab-IP-Address-Using-  
Image.html

WAF-Bypass

waf-bypass-guide-part-1.html

bypass-sucuri-webSite-  
firewall.html

XPATH-Injection

There are many other similar methods too to manipulate the DOM like:

```
document.getElementsByName('Name');
document.getElementsByTagName('TagName');
document.getElementsByClassName('ClassName');
```

However there could be Multiple Tags with the same value of Tag Names, name & class at an array of nodes is returned and could be accessed via array indices like selected[0], select

[document.innerHTML](#) - This method is used to write HTML content within a selected node. F

```
<!doctype html>
<html>
<p id="someID">Select Me</p>
<script>
var selected=document.getElementById("someID");/*would store the <p id="someID">Sele
selected.innerHTML="<p>Text blabla</p>";/*you would see the content inside <p id="somal
</script>
</html>
```

Any User Input to This is Very Dangerous Even if its filtering > , < , " , ' only by using back g),alphabets Malicious User could Execute Javascript.(Explained Later)

[document.write/document.writeln\("HTML Content"\)](#) - This is used to rewrite(remove existi structure of web page with its supplied Argument(HTML content). For Example:

```
<!doctype html>
<html>
<script>
document.write("Contents of The Page");
</script>
</html>
```

Any User Input to this is Very Dangerous Even if it's filtering > , < , " , ' only by using backsl alphabets Malicious User could Execute JavaScript which will be explained Later in out tutor

[document.createElement\('Element Name'\)](#) – createElement Method is used to create a new javascript. For example if we want to create an img src="http://securityidiots.com/post\_images/backxss.png"

```
var imgtag = document.createElement("img");//creates img element
imgtag.src="http://securityidiots.com/post_images/backxss.png";//adds attribute src to it
document.body.appendChild(imgtag);//appends the created element to the body tag of th
```

**Note:** There may be more properties that we would cover as we move further but for now th be enough to move ahead.

## JAVASCRIPT FUNCTIONS

Like other languages, there are functions in JavaScript too which used to statements/instructions to reduce repetition of our code.

### Defining Javascript Functions:

A JavaScript function is defined with "function" keyword, followed by the function's parenthesis () and inside it may include arguments/parameter names separated by cc JavaScript are called, similar to other languages:

functionname(larg1,arg2); // [] indicates that arguments/parameters are optional

### Ways of Defining and Calling Functions:

```
//Defining
var x=function myFunction(a, b) {
    return a * b;
};
```

Basics-of-XPATH-for-XPATH-  
Injection-part-1.html

Basics-of-XPATH-for-XPATH-  
Injection-part-2.html

Basics-XPATH-injection.html

xpath-injection-part-1.html

XSS

XXE

XXE-Cheat-Sheet-by-  
SecurityIdiots.html

```
//Calling
z=x(30,40);// would return 1200 in variable z
```

we could also call a function directly without storing it in a variable

```
//Defining
function myFunction(a, b) {
    return a * b;
};

//Calling
z=myFunction(30,40);
```

We could also define functions without names called as "Closures" or anonymous functions

```
//Defining
var x=function(arg){
    return arg*100;
};

//Calling
x(10);//would return 1000
```

And also, we can do define and call, both at the same time:

```
var x=function(arg){
    return arg*100;
}(10); // function would be called & would return 1000 in x variable
```

### Concatenation in Javascript:

Since Javascript is a loosely typed language, We can Concatenate Strings with Strings as we can concatenate numbers with numbers. We can concatenate Type like number (integer/floats)/boolean with "+" Operator

For example :

```
var x="aaaaaa"+"bbbb"; //console.log(x) would return aaaaaabbbb
var x="aaa"*1234;//console.log(x) would return aaa1234
```

## IMPORTANT JS FUNCTIONS RELATED TO XSS

**1. console.log:** ("logs this to browser's developer console "); - This writes the output to the browser's developer console. It is used for debugging purposes i.e. We could get/set/change/override the values of variables in the console itself. A very nice example would be:

```
<!doctype html>
<html>
<script>
console.log("Test!!");
</script>
</html>
```

Now open the Browser's Developer Console (by pressing F12/Ctrl+Shift+J depends on browser), you would see "Test!!" logged in the console.

Getting the values of variables in console:

```
<!doctype html>
<html>
<script>
var a=10,b=null,c="String",d=false,e={A:1,B:"String2",C:[1,2]},f=[1,2,3,"String3"],g;
console.log("Value of a:");
console.log(a);
```

```
console.log("Value of b:");
console.log(b);
console.log("Value of c:");
console.log(c);
console.log("Value of d:");
console.log(d);
console.log("Value of e:");
console.log(e);
console.log("Value of f:");
```

Open Browser's Developer Console and reload The above Page you would see the values of in Console.

## 2. `alert(1);prompt(1);confirm(1)` -

**alert("Argument Here"):** ( The very infamous :P `alert()` is used to popup an alert message bc String written in it, it doesn't return anything

**prompt("Argument Here"):** ( is used to popup a prompt to take user input with a message s String, it returns the value entered by the user

```
var x=prompt("Enter Value: "); // after User enters value it will be stored in x for further operat
```

**confirm("Message"):** is used to popup a confirm box to confirm(OK/Cancel) Something, Pre and Cancel returns false.

```
var conf=confirm("Are You Sure To blablabla?");
```

From XSS point of view, these are the functions which we use to confirm/identify th Executing on the target

## 3. `setTimeout()` - The `setTimeout()` method calls a function after a specified number of millise

```
setTimeout(function(){ alert("Hello"); }, 3000); // will call anonymous function after 3 second
```

## 4. `setInterval()` - The `setInterval()` method calls a function after specified intervals endlessly

```
setInterval(alert(1),3000); // will call alert(1) after every 3 seconds
```

Therefore these `setTimeout` and `setInterval` functions could be used to execute JavaScript C is in the first parameter.

**6.`var z=new Function('arg1','arg2','body')`** - creates a new Function object similar to `var z=function` The User input to the last parameter is dangerous and could be used to XSS if that function the page.

```
var z=new Function('arg1','arg2','alert(1)')
z(1,2);//would cause alert(1)
```

## 7.`eval("JavaScript here")` - used to evaluate string in its argument as JavaScript.

```
eg.eval('var x=1;alert(x)');
```

User input to this `eval()` is extremely dangerous.

That's enough for basics about Functions, for now, we would keep covering more about the in further topics. So in our next part of JavaScript Basics, we would cover Event (XMLHttpRequest).

Author : Rahul Maini

Date : 2017-04-29