# while loop

**INTERMEDIATE PYTHON** 



Hugo Bowne-Anderson
Data Scientist at DataCamp



#### if-elif-else

control.py

Goes through construct only once!

```
z = 6
if z % 2 == 0 : # True
    print("z is divisible by 2") # Executed
elif z % 3 == 0 :
    print("z is divisible by 3")
else :
    print("z is neither divisible by 2 nor by 3")
... # Moving on
```

• While loop = repeated if statement

```
while condition :
    expression
```

- Numerically calculating model
- "repeating action until condition is met"
- Example
  - Error starts at 50
  - Divide error by 4 on every run
  - Continue until error no longer > 1

```
while condition :
expression
```

```
error = 50.0
while error > 1:
    error = error / 4
    print(error)
```

- Error starts at 50
- Divide error by 4 on every run
- Continue until error no longer > 1

```
while condition :
   expression
```

while\_loop.py

```
error = 50.0
# 50
while error > 1:  # True
    error = error / 4
    print(error)
```

12.5

```
while condition :
   expression
```

```
12.5
3.125
```

```
while condition :
   expression
```

```
12.5
3.125
0.78125
```

```
while condition :
   expression
```

```
12.5
3.125
0.78125
```

```
while condition :
expression
```

while\_loop.py

```
error = 50.0
while error > 1 :  # always True
    # error = error / 4
    print(error)
```

```
50
50
50
50
50
50
50
```

 DataCamp: session disconnected

• Local system: Control + C

# Let's practice!

**INTERMEDIATE PYTHON** 



**INTERMEDIATE PYTHON** 



Hugo Bowne-Anderson
Data Scientist at DataCamp



```
for var in seq :
    expression
```

• "for each var in seq, execute expression"

### fam

family.py

```
fam = [1.73, 1.68, 1.71, 1.89]
print(fam)
```

[1.73, 1.68, 1.71, 1.89]

#### fam

family.py

```
fam = [1.73, 1.68, 1.71, 1.89]
print(fam[0])
print(fam[1])
print(fam[2])
print(fam[3])
```

```
1.731.681.711.89
```

```
for var in seq :
    expression

family.py
```

```
fam = [1.73, 1.68, 1.71, 1.89]
for height in fam :
    print(height)
```

```
for var in seq :
   expression
```

family.py

```
fam = [1.73, 1.68, 1.71, 1.89]
for height in fam :
    print(height)
    # first iteration
    # height = 1.73
```

1.73

```
for var in seq :
   expression
```

family.py

```
fam = [1.73, 1.68, 1.71, 1.89]
for height in fam :
    print(height)
    # second iteration
    # height = 1.68
```

1.73

1.68

```
for var in seq :
    expression
family.py
fam = [1.73, 1.68, 1.71, 1.89]
for height in fam :
    print(height)
1.73
1.68
1.71
1.89
```

No access to indexes

```
for var in seq :
    expression

family.py

fam = [1.73, 1.68, 1.71, 1.89]
```

• ???

```
index 0: 1.73
index 1: 1.68
index 2: 1.71
index 3: 1.89
```

#### enumerate

```
for var in seq :
    expression
family.py
fam = [1.73, 1.68, 1.71, 1.89]
for index, height in enumerate(fam) :
    print("index " + str(index) + ": " + str(height))
index 0: 1.73
index 1: 1.68
index 2: 1.71
index 3: 1.89
```

## Loop over string

```
for var in seq :
    expression
strloop.py
for c in "family" :
   print(c.capitalize())
```

# Let's practice!

**INTERMEDIATE PYTHON** 



# Loop Data Structures Part 1

**INTERMEDIATE PYTHON** 



Hugo Bowne-Anderson
Data Scientist at DataCamp



## Dictionary

```
for var in seq : expression
```

dictloop.py

```
ValueError: too many values to unpack (expected 2)
```



## **Dictionary**

```
for var in seq :
   expression
```

dictloop.py

```
algeria -- 39.21
afghanistan -- 30.55
albania -- 2.77
```

## Dictionary

```
for var in seq :
   expression
```

dictloop.py

```
algeria -- 39.21
afghanistan -- 30.55
albania -- 2.77
```

## **Numpy Arrays**

```
for var in seq :
expression
```

nploop.py

```
import numpy as np
np_height = np.array([1.73, 1.68, 1.71, 1.89, 1.79])
np_weight = np.array([65.4, 59.2, 63.6, 88.4, 68.7])
bmi = np_weight / np_height ** 2
for val in bmi :
    print(val)
```

```
21.852
20.975
21.750
24.747
21.441
```

## 2D Numpy Arrays

nploop.py

```
import numpy as np
np_height = np.array([1.73, 1.68, 1.71, 1.89, 1.79])
np_weight = np.array([65.4, 59.2, 63.6, 88.4, 68.7])
meas = np.array([np_height, np_weight])

for val in meas :
    print(val)
```

```
[ 1.73    1.68    1.71    1.89    1.79]
[ 65.4    59.2    63.6    88.4    68.7]
```

## 2D Numpy Arrays

nploop.py

```
import numpy as np
np_height = np.array([1.73, 1.68, 1.71, 1.89, 1.79])
np_weight = np.array([65.4, 59.2, 63.6, 88.4, 68.7])
meas = np.array([np_height, np_weight])
for val in np.nditer(meas) :
    print(val)
```

```
1.73
1.68
1.71
1.89
1.79
65.4
```

## Recap

Dictionary

```
o for key, val in my_dict.items() :
```

- Numpy array
  - o for val in np.nditer(my\_array) :

# Let's practice!

**INTERMEDIATE PYTHON** 



# Loop Data Structures Part 2

INTERMEDIATE PYTHON



Hugo Bowne-Anderson
Data Scientist at DataCamp



## brics

```
capital
                                   population
        country
                             area
         Brazil
                  Brasilia
                             8.516
                                       200.40
                    Moscow 17.100
                                     143.50
         Russia
                New Delhi
                                      1252.00
          India
                            3.286
          China
                   Beijing
                             9.597
                                      1357.00
SA South Africa
                  Pretoria
                            1.221
                                        52.98
```

```
import pandas as pd
brics = pd.read_csv("brics.csv", index_col = 0)
```

## for, first try

```
import pandas as pd
brics = pd.read_csv("brics.csv", index_col = 0)
for val in brics :
    print(val)
```

```
country
capital
area
population
```

### iterrows

```
import pandas as pd
brics = pd.read_csv("brics.csv", index_col = 0)
for lab, row in brics.iterrows():
    print(lab)
    print(row)
               Brazil
country
capital
             Brasilia
                8.516
area
                200.4
population
Name: BR, dtype: object
RU
             Russia
country
capital
             Moscow
               17.1
area
              143.5
population
Name: RU. dtvpe: object
```

## Selective print

```
import pandas as pd
brics = pd.read_csv("brics.csv", index_col = 0)
for lab, row in brics.iterrows():
    print(lab + ": " + row["capital"])
```

```
BR: Brasilia
RU: Moscow
IN: New Delhi
CH: Beijing
SA: Pretoria
```

#### Add column

```
import pandas as pd
brics = pd.read_csv("brics.csv", index_col = 0)

for lab, row in brics.iterrows() :
    # - Creating Series on every iteration
    brics.loc[lab, "name_length"] = len(row["country"])
print(brics)
```

```
capital
                                     population name_length
         country
                               area
                   Brasilia
BR
          Brazil
                              8.516
                                         200.40
                                                            6
                             17.100
RU
          Russia
                     Moscow
                                        143.50
                                                            6
IN
          India
                  New Delhi
                              3.286
                                        1252.00
                                                            5
                    Beijing
CH
           China
                              9.597
                                         1357.00
                                                            5
   South Africa
                   Pretoria
                              1.221
                                           52.98
                                                           12
```

## apply

```
import pandas as pd
brics = pd.read_csv("brics.csv", index_col = 0)
brics["name_length"] = brics["country"].apply(len)
print(brics)
```

```
population
                    capital
         country
                                area
BR
          Brazil
                    Brasilia
                               8.516
                                          200.40
RU
          Russia
                     Moscow
                                          143.50
                              17.100
IN
           India
                  New Delhi
                               3.286
                                         1252.00
CH
           China
                                         1357.00
                    Beijing
                               9.597
    South Africa
                    Pretoria
                               1.221
                                            52.98
```

# Let's practice!

**INTERMEDIATE PYTHON** 

