

# CS598 - Project 1

*Xiaoming Ji*

## Computer System

### Hardware

- Dell Precision Tower 5810
- CPU: Intel Xeon E5-1607 @ 3.10GHz
- Memory: 32GB

### Software

- OS: Windows 10 Professional 64bit
- R: 3.5.1
- R Packages:
  - randomForest\_4.6-14
  - glmnet\_2.0-16
  - xgboost\_0.71.2
  - psych\_1.8.4

## PART 1

In this part, I pre-processed the data and built 2 models (boosting and lasso) to make the training and evaluations.

### Preprocessing and Feature Engineering

Several approaches are taken to pre-process the data.

- Missing value: ‘Garage\_Yr\_Blt’ has some missing values, ‘Year\_Built’ is used to fill the value. Note: ‘Garage\_Yr\_Blt’ is removed due to low importance, I still leave this step for generalizing the processing pipeline.
- Handle categorical value mismatch between train and test dataset:
  - For categorical value only exists in test predictor, the value is replaced with the **most frequent** categorical value of the same training predictor.
  - For ordered value only exists in test predictor, the value is replaced with the **closest** value of the same training predictor.
- Fix the skewness of numeric predictors: take the log for all numeric predictors with an absolute skew greater than 0.8.
- Take log for response variable: Sale\_Price.
- Add more predictor to help prediction:
  - Total bath: combine all full and half bath rooms.
  - Age: how old the house was when sold.
  - IsNew: whether this is a new house when sold.
  - Remodeled: This is seen as some sort of penalty parameter that indicates that if the Age is based on a remodeling date, it is probably worth less than houses that were built from scratch in that same year.

- TotalSqFeet: combine space in living area and basement.
- TotalPorchSF: combine space of all porches.
- Remove predictors: remove some highly correlated and dominate categorical variables predictors.

Note: Winsorizing is not used because per my testing, it doesn't improve the accuracy.

## Models

For evaluation purpose, I build 4 models,

- RandomForest
- Boosting (Xgboost)
- Lasso
- MyLasso (self-implemented lasso)

## Evaluation

I tested all 10 test dataset against these models. The RMSEs are:

```
print(rmse)
```

```
##           Lasso
## [1,] 0.1275106
## [2,] 0.1288868
## [3,] 0.1376953
## [4,] 0.1226088
## [5,] 0.1058202
## [6,] 0.1227174
## [7,] 0.1124693
## [8,] 0.1126837
## [9,] 0.1189350
## [10,] 0.1078492
```

```
cat("\n Avg:", colMeans(rmse), "\n" )
```

```
##
## Avg: 0.1197176
```

Computing time: 17.647 seconds

## PART 2

In this part, I use my own lasso implementation to predict the test set. In order to find the best  $\lambda$ , A cross validation function: `cv.mylasso` is implemented. Here I used the pre-found  $\lambda=30$  to shorten the computation time.

Run against the test set, the results are:

- Test Accuracy: 0.1157969
- Computation Time: 9.471 seconds