
NAME : Geetha S

USN : 1RUA25BCA0033

LAB – 9

To create and execute MySQL stored procedures for displaying, inserting, updating and deleting employee records. • Create table and insert records



```
mysql> CREATE TABLE Employee (
    ->     emp_id INT PRIMARY KEY,
    ->     emp_name VARCHAR(50),
    ->     salary DECIMAL(10,2)
    -> );
Query OK, 0 rows affected (0.03 sec)

mysql>
mysql> INSERT INTO Employee VALUES
    -> (1, 'Asha', 30000),
    -> (2, 'Rahul', 35000),
    -> (3, 'Priya', 40000);
Query OK, 3 rows affected (0.00 sec)
Records: 3  Duplicates: 0  Warnings: 0

mysql>
mysql> SELECT * FROM Employee;
+--------+----------+----------+
| emp_id | emp_name | salary   |
+--------+----------+----------+
|      1 | Asha     | 30000.00 |
|      2 | Rahul    | 35000.00 |
|      3 | Priya    | 40000.00 |
+--------+----------+----------+
3 rows in set (0.01 sec)
```

- Basic procedure

```
mysql> DELIMITER //
mysql>
mysql> CREATE PROCEDURE GetEmployees()
    -> BEGIN
    ->     SELECT * FROM Employee;
    -> END //
Query OK, 0 rows affected (0.04 sec)

mysql>
mysql> DELIMITER ;
mysql> CALL GetEmployees();
+--------+----------+----------+
| emp_id | emp_name | salary   |
+--------+----------+----------+
|      1 | Asha     | 30000.00 |
|      2 | Rahul    | 35000.00 |
|      3 | Priya    | 40000.00 |
+--------+----------+----------+
3 rows in set (0.01 sec)

Query OK, 0 rows affected (0.02 sec)
```

- Procedure for INSERT

```
mysql> CREATE PROCEDURE InsertEmployee(
    ->     IN p_id INT,
    ->     IN p_name VARCHAR(50),
    ->     IN p_salary DECIMAL(10,2)
    -> )
    -> BEGIN
    ->     INSERT INTO Employee (emp_id, emp_name, salary)
    ->     VALUES (p_id, p_name, p_salary);
    -> END //
Query OK, 0 rows affected (0.02 sec)

mysql>
mysql> DELIMITER ;
mysql> CALL InsertEmployee(4, 'Kiran', 42000);
Query OK, 1 row affected (0.01 sec)

mysql>
mysql> SELECT * FROM Employee;
+--------+----------+----------+
| emp_id | emp_name | salary   |
+--------+----------+----------+
|      1 | Asha     | 30000.00 |
|      2 | Rahul    | 35000.00 |
|      3 | Priya    | 40000.00 |
|      4 | Kiran    | 42000.00 |
+--------+----------+----------+
4 rows in set (0.00 sec)
```

- Procedure for UPDATE

```
mysql> DELIMITER //
mysql>
mysql> CREATE PROCEDURE UpdateEmployee(
    ->     IN p_id INT,
    ->     IN p_salary DECIMAL(10,2)
    -> )
    -> BEGIN
    ->     UPDATE Employee
    ->     SET salary = p_salary
    ->     WHERE emp_id = p_id;
    -> END //
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> DELIMITER ;
mysql> CALL UpdateEmployee(1, 38000);
Query OK, 1 row affected (0.01 sec)

mysql>
mysql> SELECT * FROM Employee;
+--------+----------+----------+
| emp_id | emp_name | salary   |
+--------+----------+----------+
|      1 | Asha     | 38000.00 |
|      2 | Rahul    | 35000.00 |
|      3 | Priya    | 40000.00 |
|      4 | Kiran    | 42000.00 |
+--------+----------+----------+
4 rows in set (0.00 sec)
```

- Procedure for DELETE

```
mysql> DELIMITER //
mysql>
mysql> CREATE PROCEDURE DeleteEmployee(
    ->     IN p_id INT
    -> )
    -> BEGIN
    ->     DELETE FROM Employee
    ->     WHERE emp_id = p_id;
    -> END //
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> DELIMITER ;
mysql> CALL DeleteEmployee(2);
Query OK, 1 row affected (0.01 sec)

mysql>
mysql> SELECT * FROM Employee;
+--------+----------+----------+
| emp_id | emp_name | salary   |
+--------+----------+----------+
|      1 | Asha     | 38000.00 |
|      3 | Priya    | 40000.00 |
|      4 | Kiran    | 42000.00 |
+--------+----------+----------+
3 rows in set (0.00 sec)
```

- Verify the procedures

```
mysql> SHOW PROCEDURE STATUS
    -> WHERE Db = 'DBMS_Lab';
+---------+-----------------+-----------+---------------+---------------------+---------------------+---------------+---
----------+----------------------+----------------------+--------------------+
| Db      | Name            | Type      | Definer       | Modified            | Created             | Security_type | C
omment | character_set_client | collation_connection | Database Collation |
+---------+-----------------+-----------+---------------+---------------------+---------------------+---------------+---
----------+----------------------+----------------------+--------------------+
| dbms_lab | DeleteEmployee | PROCEDURE | root@localhost | 2026-10-09 19:07:09 | 2026-10-09 19:07:09 | DEFINER       |
         | cp850            | cp850_general_ci     | utf8mb4_0900_ai_ci |
| dbms_lab | GetEmployees   | PROCEDURE | root@localhost | 2026-10-09 19:03:41 | 2026-10-09 19:03:41 | DEFINER       |
         | cp850            | cp850_general_ci     | utf8mb4_0900_ai_ci |
| dbms_lab | InsertEmployee | PROCEDURE | root@localhost | 2026-10-09 19:04:48 | 2026-10-09 19:04:48 | DEFINER       |
         | cp850            | cp850_general_ci     | utf8mb4_0900_ai_ci |
| dbms_lab | UpdateEmployee | PROCEDURE | root@localhost | 2026-10-09 19:05:59 | 2026-10-09 19:05:59 | DEFINER       |
         | cp850            | cp850_general_ci     | utf8mb4_0900_ai_ci |
+---------+-----------------+-----------+---------------+---------------------+---------------------+---------------+---
----------+----------------------+----------------------+--------------------+
4 rows in set (0.04 sec)
```