
CNNP SKILL – 1


2520090108

Sai geethika

Select your network interface





Generate network traffic




Apply display filters


tcp


*Wi-Fi
File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help
tcp
No. Time Source Destination Protocol Length Info
9444 12.952598700 57.144.123.32 10.250.30.19 TCP 126 5222 → 60158 [PSH, ACK] Seq=1 Ack=71 Win=2036 Len=72
9445 12.966094000 10.250.30.19 149.154.170.100 TLSv1.2 210 Application Data
9446 12.974626600 10.250.14.255 10.250.30.19 MS-DO 63 Have Message (piece 2193)
9447 12.974903600 149.154.167.99 10.250.30.19 TLSv1.2 174 Application Data
9448 12.994868100 10.250.30.19 57.144.123.32 TCP 54 60158 → 5222 [ACK] Seq=71 Ack=73 Win=254 Len=0
9481 13.022334400 149.154.170.100 10.250.30.19 TCP 60 443 → 58745 [ACK] Seq=857 Ack=1335 Win=660 Len=0
9482 13.025537600 149.154.170.100 10.250.30.19 TLSv1.2 174 Application Data
9483 13.026620400 10.250.30.19 10.250.14.255 TCP 54 7680 → 54780 [ACK] Seq=649 Ack=722 Win=64768 Len=0
9484 13.026709600 10.250.30.19 149.154.167.99 TCP 54 60878 → 443 [ACK] Seq=1181 Ack=841 Win=254 Len=0
9485 13.073788100 10.250.30.19 149.154.170.100 TCP 54 58745 → 443 [ACK] Seq=1335 Ack=977 Win=254 Len=0
9549 13.215870200 10.250.30.19 10.247.0.33 TCP 66 [TCP Retransmission] 58589 → 7680 [SYN] Seq=0 Win=65535 Len=0 MSS=1460 WS=256 SACK_PERM
9572 13.297857900 10.250.14.255 10.250.30.19 MS-DO 63 Have Message (piece 2194)
9585 13.313703700 10.250.30.19 149.154.167.99 TLSv1.2 244 Application Data
9633 13.342770300 10.250.30.19 10.250.14.255 TCP 54 7680 → 54780 [ACK] Seq=649 Ack=731 Win=64768 Len=0
9659 13.405866700 10.250.30.19 10.250.19.241 TCP 66 [TCP Retransmission] 58590 → 7680 [SYN] Seq=0 Win=65535 Len=0 MSS=1460 WS=256 SACK_PERM
9660 13.406014500 10.250.30.19 57.144.123.32 TCP 55 55556 → 443 [ACK] Seq=1 Ack=1 Win=255 Len=1
9813 13.454383300 57.144.123.32 10.250.30.19 TCP 60 443 → 55556 [ACK] Seq=1 Ack=2 Win=2031 Len=0
9815 13.474022000 149.154.167.99 10.250.30.19 TLSv1.2 174 Application Data
9824 13.516509000 10.250.30.19 149.154.167.99 TCP 54 59460 → 443 [ACK] Seq=1345 Ack=841 Win=254 Len=0
Frame 9483: Packet, 54 bytes on wire (432 bits), 54 bytes captured (432 bits) on interface \Device\NPF_{
Ethernet II, Src: AzureWaveTec_ef:5b:ae (f8:3d:c6:ef:5b:ae), Dst: AzureWaveTec_cb:f1:de (a8:e2:91:cb:f1:
Internet Protocol Version 4, Src: 10.250.30.19, Dst: 10.250.14.255
Transmission Control Protocol, Src Port: 7680, Dst Port: 54780, Seq: 649, Ack: 722, Len: 0
0000 a8 e2 91 cb f1 de f8 3d c6 ef 5b ae 08 00 45 00
0010 00 28 9b 6c 40 00 80 06 1c 5e 0a fa 1e 13 0a fa
0020 0e ff 1e 00 d5 fc ed 40 f9 1d 2a b2 aa 2b 50 10
0030 00 fd bc 98 00 00
wireshark_Wi-FiDB10Y3.pcapng
Packets: 10085 · Displayed: 255 (2.5%) · Dropped: 0 (0.0%)
Profile: Default



CN_Skill1_Capture.pcapng
File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help
tcp
Frame 2487: Packet, 244 bytes on wire (1952 bits), 244 bytes captured (1952 bits) on interface \Device\NPF_{17C0C129-D07E-
Section number: 1
Interface id: 0 (\Device\NPF_{17C0C129-D07E-4FE6-ADAA-337E397DF08D})
Encapsulation type: Ethernet (1)
Arrival Time: Nov 12, 2026 12:04:39.075456600 India Standard Time
UTC Arrival Time: Nov 12, 2026 06:34:39.075456600 UTC
Epoch Arrival Time: 1794465279.075456600
[Time shift for this packet: 0.000000000 seconds]
[Time delta from previous captured frame: 75.950700 milliseconds]
[Time delta from previous displayed frame: 96.929400 milliseconds]
[Time since reference or first frame: 3.266192500 seconds]
Frame Number: 2487
Frame Length: 244 bytes (1952 bits)
Capture Length: 244 bytes (1952 bits)
[Frame is marked: False]
[Frame is ignored: False]
[Protocols in frame: eth:ethertype:ip:tcp:tls]
Character encoding: ASCII (0)
[Coloring Rule Name: TCP]
[Coloring Rule String: tcp]
Ethernet II, Src: AzureWaveTec_ef:5b:ae (f8:3d:c6:ef:5b:ae), Dst: HewlettPacka_52:c1:00 (4c:d5:87:52:c1:00)
Destination: HewlettPacka_52:c1:00 (4c:d5:87:52:c1:00)
Source: AzureWaveTec_ef:5b:ae (f8:3d:c6:ef:5b:ae)
Type: IPv4 (0x0800)
[Stream index: 191]
Internet Protocol Version 4, Src: 10.250.30.19, Dst: 149.154.167.99
0100 .... = Version: 4
.... 0101 = Header Length: 20 bytes (5)
Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
Total Length: 230
Identification: 0x3f91 (16273)
010. .... = Flags: 0x2, Don't fragment
...0 0000 0000 0000 = Fragment Offset: 0
Time to Live: 128
Protocol: TCP (6)
Header Checksum: 0x5476 [validation disabled]
[Header checksum status: Unverified]
Source Address: 10.250.30.19
Destination Address: 149.154.167.99
[Stream index: 83]
Transmission Control Protocol, Src Port: 59460, Dst Port: 443, Seq: 207, Ack: 121, Len: 190
Transport Layer Security
[Stream index: 3]
TLSv1.2 Record Layer: Application Data Protocol: Hypertext Transfer Protocol
0000 4c d5 87 52 c1 00 f8 3d c6 ef 5b ae 08 00 45 00
0010 00 e6 3f 91 40 00 80 06 54 76 0a fa 1e 13 95 9a
0020 a7 63 e8 44 01 bb 21 fe a1 14 80 60 57 72 50 18
0030 00 fb de b1 00 00 17 03 03 00 b9 00 00 00 00 00
0040 00 00 a3 68 7c 9e 0e 52 3c eb b0 c3 98 00 19 ae
0050 80 4c 72 d9 36 62 42 7a fb a3 4f c5 63 61 c8 11
0060 15 9b 63 bc 9c 8a ec 59 30 b6 cd c1 1c 73 6a d5
0070 d4 4a 1b f6 50 64 21 84 3a 6a 63 a1 73 73 8a 21
0080 ae e6 25 97 52 38 44 a5 47 26 b3 dc 33 11 02 3f
0090 0c f5 8a 24 86 ac 44 45 f3 3e 9c ea af 2f 80 aa
00a0 1a 55 f8 4c 65 e3 aa ec c7 38 a9 78 8e 11 9c c2
00b0 c3 97 03 d8 01 cf 3b 3b db b9 e1 cb f3 ef 62 d2
00c0 f1 3a 7f 2d 77 58 c6 5c b0 db 6e 80 47 9b 81 b1
00d0 86 8a e7 e0 95 96 e2 e5 6d f7 d0 a3 22 8d a9 43
00e0 73 da 41 e6 c1 0d 45 c5 42 50 95 62 61 8b f6 ec
00f0 72 74 de 4b
Total Length (ip.len), 2 bytes
Packets: 10085 · Displayed: 255 (2.5%)
Profile: Default

upd



*Wi-Fi
File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help
udp
No. Time Source Destination Protocol Length Info
9470 13.005948900 10.250.24.132 239.255.255.250 SSDP 179 M-SEARCH * HTTP/1.1
9471 13.006327000 10.250.9.231 224.0.0.251 MDNS 486 Standard query response 0x0000 PTR, cache flush Android_9OEW2RM3.local AAAA, cache flush fe80::9c67:b8ff:fea4:b786 PTR, cache fl
9472 13.006781100 fe80::9c67:b8ff:fea… ff02::fb MDNS 506 Standard query response 0x0000 PTR, cache flush Android_9OEW2RM3.local AAAA, cache flush fe80::9c67:b8ff:fea4:b786 PTR, cache fl
9474 13.007159500 10.250.21.148 224.77.77.77 UDP 155 56782 → 12177 Len=113
9475 13.007196200 10.250.8.245 224.0.0.251 MDNS 126 Standard query 0x0000 ANY Android-79.local, "QM" question ANY Android-79.local, "QM" question A 10.250.8.245 AAAA fe80::64af:e7a2
9476 13.007416600 fe80::64af:e7a2:a51… ff02::fb MDNS 146 Standard query 0x0000 ANY Android-79.local, "QM" question ANY Android-79.local, "QM" question A 10.250.8.245 AAAA fe80::64af:e7a2
9478 13.007738700 10.250.27.161 224.0.0.251 MDNS 163 Standard query 0x0000 TXT Hima's MacBook Air._companion-link._tcp.local, "QU" question TXT Mothe's MacBook Air._companion-link._
9479 13.007877300 fe80::1c4f:72cd:97a… ff02::fb MDNS 183 Standard query 0x0000 TXT Hima's MacBook Air._companion-link._tcp.local, "QU" question TXT Mothe's MacBook Air._companion-link._
9490 13.105070600 10.250.24.187 224.0.0.251 MDNS 214 Standard query response 0x0000 PTR Apple's MacBook Pro._companion-link._tcp.local TXT
9491 13.105760300 fe80::8be:b193:46df… ff02::fb MDNS 234 Standard query response 0x0000 PTR Apple's MacBook Pro._companion-link._tcp.local TXT
9493 13.105762200 10.250.3.250 239.255.255.250 SSDP 212 M-SEARCH * HTTP/1.1
9502 13.106691100 10.250.11.109 224.0.0.251 MDNS 184 Standard query 0x0014 PTR _googlecast._tcp.local, "QM" question PTR _%9E5E7C8F47989526C9BCD95D24084F6F0B27C5ED._sub._googlecast._
9503 13.106691700 fe80::78d7:82ff:fea… ff02::fb MDNS 204 Standard query 0x0014 PTR _googlecast._tcp.local, "QM" question PTR _%9E5E7C8F47989526C9BCD95D24084F6F0B27C5ED._sub._googlecast._
9504 13.106692900 10.250.6.93 224.0.0.251 MDNS 103 Standard query 0x001b PTR _googlecast._tcp.local, "QM" question PTR _CC32E753._sub._googlecast._tcp.local, "QM" question
9505 13.107678300 fe80::5007:f8ff:fe0… ff02::fb MDNS 123 Standard query 0x001b PTR _googlecast._tcp.local, "QM" question PTR _CC32E753._sub._googlecast._tcp.local, "QM" question
9508 13.107682100 10.250.17.45 224.0.0.251 MDNS 204 Standard query response 0x0000 PTR Hrushika's MacBook Air._companion-link._tcp.local TXT
9509 13.107682800 fe80::3:e523:2c11:3… ff02::fb MDNS 224 Standard query response 0x0000 PTR Hrushika's MacBook Air._companion-link._tcp.local TXT
9514 13.108683600 10.250.11.233 224.0.0.251 MDNS 198 Standard query response 0x0000 PTR Divya's MacBook Neo._companion-link._tcp.local TXT
9515 13.108684400 fe80::82:f079:528d:… ff02::fb MDNS 218 Standard query response 0x0000 PTR Divya's MacBook Neo._companion-link._tcp.local TXT
Frame 9491: Packet, 234 bytes on wire (1872 bits), 234 bytes captured (1872 bits) on interface \Device\
Ethernet II, Src: e2:e0:d7:08:7f:2e (e2:e0:d7:08:7f:2e), Dst: IPv6mcast_fb (33:33:00:00:00:fb)
Internet Protocol Version 6, Src: fe80::8be:b193:46df:a57f, Dst: ff02::fb
User Datagram Protocol, Src Port: 5353, Dst Port: 5353
Multicast Domain Name System (response)
wireshark_Wi-FiDB10Y3.pcapng
Packets: 10085 · Displayed: 6518 (64.6%) · Dropped: 0 (0.0%)
Profile: Default



CN_Skill1_Capture.pcapng
File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help
udp
Frame 2503: Packet, 530 bytes on wire (4240 bits), 530 bytes captured (4240 bits) on interface \Device\NPF_{17C0C129-D07E-
Section number: 1
Interface id: 0 (\Device\NPF_{17C0C129-D07E-4FE6-ADAA-337E397DF08D})
Encapsulation type: Ethernet (1)
Arrival Time: Nov 12, 2026 12:04:39.091080100 India Standard Time
UTC Arrival Time: Nov 12, 2026 06:34:39.091080100 UTC
Epoch Arrival Time: 1794465279.091080100
[Time shift for this packet: 0.000000000 seconds]
[Time delta from previous captured frame: 540.400 microseconds]
[Time delta from previous displayed frame: 540.400 microseconds]
[Time since reference or first frame: 3.281816000 seconds]
Frame Number: 2503
Frame Length: 530 bytes (4240 bits)
Capture Length: 530 bytes (4240 bits)
[Frame is marked: False]
[Frame is ignored: False]
[Protocols in frame: eth:ethertype:ipv6:udp:mdns]
Character encoding: ASCII (0)
[Coloring Rule Name: UDP]
[Coloring Rule String: udp]
Ethernet II, Src: 42:ee:d7:43:95:ff (42:ee:d7:43:95:ff), Dst: IPv6mcast_fb (33:33:00:00:00:fb)
Destination: IPv6mcast_fb (33:33:00:00:00:fb)
Source: 42:ee:d7:43:95:ff (42:ee:d7:43:95:ff)
Type: IPv6 (0x86dd)
[Stream index: 89]
Internet Protocol Version 6, Src: fe80::1451:1274:cf7f:ffc7, Dst: ff02::fb
User Datagram Protocol, Src Port: 5353, Dst Port: 5353
Multicast Domain Name System (query)
User Datagram Protocol: Protocol
Packets: 10085 · Displayed: 6518 (64.6%)
Profile: Default

icmp


*Wi-Fi
File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help
icmp
No. Time Source Destination Protocol Length Info
wireshark_Wi-FiD810Y3.pcapng
Packets: 10085 · Displayed: 0 (0.0%) · Dropped: 0 (0.0%)
Profile: Default
CN_Skill1_Capture.pcapng
File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help
icmp
No. Time Source Destination Protocol Length Info
CN_Skill1_Capture.pcapng
Packets: 10085 · Displayed: 0 (0.0%)
Profile: Default

tcp.len > 0


*Wi-Fi
File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help
tcp.len > 0
No. Time Source Destination Protocol Length Info
350 0.512460400 10.250.30.19 149.154.167.99 TLSv1.2 260 Application Data
599 0.675733500 149.154.167.99 10.250.30.19 TLSv1.2 174 Application Data
706 0.749389800 10.250.30.19 149.154.167.99 TLSv1.2 260 Application Data
895 0.940736600 10.250.30.19 149.154.170.100 TLSv1.2 260 Application Data
923 0.971451400 149.154.167.99 10.250.30.19 TLSv1.2 174 Application Data
999 1.039332000 149.154.170.100 10.250.30.19 TLSv1.2 174 Application Data
1106 1.258151400 10.250.30.19 149.154.167.99 TLSv1.2 260 Application Data
1142 1.363691700 192.178.211.139 10.250.30.19 TLSv1.2 202 Application Data
1143 1.363956000 10.250.30.19 192.178.211.139 TLSv1.2 89 Application Data
1144 1.363997100 10.250.30.19 192.178.211.139 TLSv1.2 89 Application Data
1147 1.415309800 149.154.167.99 10.250.30.19 TLSv1.2 174 Application Data
1814 2.154370600 10.250.30.19 149.154.167.99 TCP 55 63467 → 443 [ACK] Seq=1 Ack=1 Win=255 Len=1
2139 2.521330100 10.250.30.19 149.154.167.99 TLSv1.2 244 Application Data
2194 2.625719400 10.254.4.30 10.250.30.19 MS-DO 60 KeepAlive Message
2213 2.759333300 10.250.30.19 149.154.167.99 TLSv1.2 210 Application Data
2247 2.777100800 149.154.167.99 10.250.30.19 TLSv1.2 174 Application Data
2276 2.949385300 10.250.30.19 149.154.170.100 TLSv1.2 244 Application Data
2337 2.999722200 149.154.167.99 10.250.30.19 TLSv1.2 174 Application Data
2338 3.039750600 149.154.170.100 10.250.30.19 TLSv1.2 174 Application Data
Frame 2139: Packet, 244 bytes on wire (1952 bits), 244 bytes captured (1952 bits) on interface \Device\
Ethernet II, Src: AzureWaveTec_ef:5b:ae (f8:3d:c6:ef:5b:ae), Dst: HewlettPacka_52:c1:00 (4c:d5:87:52:c1:
Internet Protocol Version 4, Src: 10.250.30.19, Dst: 149.154.167.99
Transmission Control Protocol, Src Port: 52119, Dst Port: 443, Seq: 207, Ack: 121, Len: 190
Transport Layer Security
0000 4c d5 87 52 c1 00 f8 3d c6 ef 5b ae 08 00 45 00
0010 00 e6 3f 8d 40 00 80 06 54 7a 0a fa 1e 13 95 9a
0020 a7 63 cb 97 01 bb b7 91 e8 de 9e 40 0a 07 50 18
0030 00 fb 47 e5 00 00 17 03 03 00 b9 00 00 00 00 00
0040 00 00 a3 97 06 82 dd 82 22 e5 75 58 46 87 99 a6
0050 f6 c6 ea a5 8f fe 43 0a a9 08 29 2e 0d 97 36 b4
0060 6a a1 e3 41 6c 18 28 00 ce 29 7d c8 34 1f 35 46
0070 c5 e3 36 53 c1 8e de 1b c3 9e f8 b5 09 4f d9 9f
0080 fa 09 c3 2e 16 54 94 ee be e7 97 2b 39 24 c1 6b
0090 6e ae 23 72 2d 72 3b b7 96 6c a9 0a bd a6 60 9c
00a0 e2 8b e9 9e 49 d0 2e ce bf 0c dc 85 c8 d9 6b c3
00b0 62 fc 0b 46 91 dc fe f5 69 71 65 c1 73 1b 1e 61
00c0 71 08 e8 57 b1 c8 37 a8 14 65 20 02 3f da b3 88
00d0 f4 24 80 a3 60 a7 0f 27 5a 71 3b 0c 7b 26 87 41
00e0 85 a4 5b a6 4f bf 09 66 27 7c 12 79 3a dc 1c cd
00f0 d2 fa 6c 9a
wireshark Wi-FiDB10Y3.pcapng
Packets: 10085 · Displayed: 126 (1.2%) · Dropped: 0 (0.0%)
Profile: Default


CN_Skill1_Capture.pcapng
File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help
tcp.len > 0
Frame 2487: Packet, 244 bytes on wire (1952 bits), 244 bytes captured (1952 bits) on interface \Device\NPF_{17C0C129-D07E-
Section number: 1
Interface id: 0 (\Device\NPF_{17C0C129-D07E-4FE6-ADAA-337E397DF08D})
Encapsulation type: Ethernet (1)
Arrival Time: Nov 12, 2026 12:04:39.075456600 India Standard Time
UTC Arrival Time: Nov 12, 2026 06:34:39.075456600 UTC
Epoch Arrival Time: 1794465279.075456600
[Time shift for this packet: 0.000000000 seconds]
[Time delta from previous captured frame: 75.950700 milliseconds]
[Time delta from previous displayed frame: 226.441900 milliseconds]
[Time since reference or first frame: 3.266192500 seconds]
Frame Number: 2487
Frame Length: 244 bytes (1952 bits)
Capture Length: 244 bytes (1952 bits)
[Frame is marked: False]
[Frame is ignored: False]
[Protocols in frame: eth:ethertype:ip:tcp:tls]
Character encoding: ASCII (0)
[Coloring Rule Name: TCP]
[Coloring Rule String: tcp]
Ethernet II, Src: AzureWaveTec_ef:5b:ae (f8:3d:c6:ef:5b:ae), Dst: HewlettPacka_52:c1:00 (4c:d5:87:52:c1:00)
Destination: HewlettPacka_52:c1:00 (4c:d5:87:52:c1:00)
Source: AzureWaveTec_ef:5b:ae (f8:3d:c6:ef:5b:ae)
Type: IPv4 (0x0800)
[Stream index: 191]
Internet Protocol Version 4, Src: 10.250.30.19, Dst: 149.154.167.99
0100 .... = Version: 4
.... 0101 = Header Length: 20 bytes (5)
Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
Total Length: 230
Identification: 0x3f91 (16273)
010. .... = Flags: 0x2, Don't fragment
...0 0000 0000 0000 = Fragment Offset: 0
Time to Live: 128
Protocol: TCP (6)
Header Checksum: 0x5476 [validation disabled]
[Header checksum status: Unverified]
Source Address: 10.250.30.19
Destination Address: 149.154.167.99
[Stream index: 83]
Transmission Control Protocol, Src Port: 59460, Dst Port: 443, Seq: 207, Ack: 121, Len: 190
Transport Layer Security
[Stream index: 3]
TLSv1.2 Record Layer: Application Data Protocol: Hypertext Transfer Protocol
0000 4c d5 87 52 c1 00 f8 3d c6 ef 5b ae 08 00 45 00
0010 00 e6 3f 91 40 00 80 06 54 76 0a fa 1e 13 95 9a
0020 a7 63 e8 44 01 bb 21 fe a1 14 80 60 57 72 50 18
0030 00 fb de b1 00 00 17 03 03 00 b9 00 00 00 00 00
0040 00 00 a3 68 7c 9e 0e 52 3c eb b0 c3 98 00 19 ae
0050 80 4c 72 d9 36 62 42 7a fb a3 4f c5 63 61 c8 11
0060 15 9b 63 bc 9c 8a ec 59 30 b6 cd c1 1c 73 6a d5
0070 d4 4a 1b f6 50 64 21 84 3a 6a 63 a1 73 73 8a 21
0080 ae e6 25 97 52 38 44 a5 47 26 b3 dc 33 11 02 3f
0090 0c f5 8a 24 86 ac 44 45 f3 3e 9c ea af 2f 80 aa
00a0 1a 55 f8 4c 65 e3 aa ec c7 38 a0 78 8e 11 9c c2
00b0 c3 97 03 d8 81 cf 3b 3b db b9 e1 cb f3 ef 62 d2
00c0 f1 3a 7f 2d 77 58 c6 5c b0 db 6e 80 47 9b 81 b1
00d0 86 8a e7 e0 95 96 e2 e5 6d f7 d0 a3 22 8d a9 43
00e0 73 da 41 e6 c1 0d 45 c5 42 50 95 62 61 8b f6 ec
00f0 72 74 de 4b
CN_Skill1_Capture.pcapng
Packets: 10085 · Displayed: 126 (1.2%)
Profile: Default