1.inserting into table mysql

BEFORE:

	emp_id	first_name	last_name	department_id
▶	1	Anirudh	Ravichandar	10
	2	Geeth	Sai	20
	3	george	clint	30
	4	SS	Thaman	10
*	NULL	NULL	NULL	NULL

AFTER:

	emp_id	first_name	last_name	department_id
▶	1	Anirudh	Ravichandar	10
	2	Geeth	Sai	20
	3	george	clint	30
	4	SS	Thaman	10
	5	niksha	singh	40
*	NULL	NULL	NULL	NULL

2.read from table:

FROM:

	emp_id	first_name	last_name	department_id
▶	1	Anirudh	Ravichandar	10
	2	Geeth	Sai	20
	3	george	clint	30
	4	SS	Thaman	10
	5	niksha	singh	40
*	NULL	NULL	NULL	NULL

TO:

/Geeth/Day-8/from db/

Name	Size	Changed	Rights	Owner
⬆ ..				
{} hi.json	1 KB	29-05-2024 20:22:54	rw-r--r--	u83451...

3.update

Before:

```
mysql> select *from student;
+-------+---------+
| id    | name    |
+-------+---------+
|     1 | geeth   |
|     2 | abhi    |
|     3 | jyothi  |
+-------+---------+
```

After:

```
mysql> select *from student;
+-------+----------+
| id    | name     |
+-------+----------+
|     1 | geeth    |
|     2 | abhi     |
|     7 | koushik  |
+-------+----------+
```

4.delete

Before:

```
mysql> select *from student;
+-------+----------+
| id    | name     |
+-------+----------+
|     1 | geeth    |
|     2 | abhi     |
|     7 | koushik  |
+-------+----------+
3 rows in set (0.00 sec)
```

After:

```
mysql> select *from student;
+--------+---------+
| id     | name    |
+--------+---------+
|      1 | geeth   |
|      2 | abhi    |
+--------+---------+
```

MANGODB

1.insert into mongodb

From:

Name	Size	Changed	Rights	Owner
..				
from mongodb		31-05-2024 17:35:04	rwxr-xr-x	u83451...
student.json	1 KB	31-05-2024 17:30:29	rw-r--r--	u83451...

TO:


```
_id: ObjectId('6659be4f1413c6e48d9493c8')
name : "drake"
age : "20"
hobby : "music"
```

2.getting data from DB

FROM:


```
_id: ObjectId('6659bf701413c6e48d9493cc')
name : "drake"
age : "20"
hobby : "music"
```

TO:

Name	Size	Changed	Rights	Owner
/Geeth/Day-8/to mongodb/from mongodb/				
🗁				
📄 mongodb.json	1 KB	31-05-2024 17:52:45	rw-r--r--	u83451...

3.Update:

Before:

```
_id: ObjectId('6659bf701413c6e48d9493cc')
name : "drake"
age : "20"
hobby : "music"
```

After:

```
_id: ObjectId('6659bf701413c6e48d9493cc')
name : "ABHI"
age : "21"
hobby : "CRICKET"
```

4.Delete

Before:

```
_id: ObjectId('6659bf701413c6e48d9493cc')
name : "ABHI"
age : "21"
hobby : "CRICKET"
```

After:

This collection has no data

It only takes a few seconds to import data from a JSON or CSV file.