



UNDERSTANDING USER PERCEPTIONS OF CAMERA AND MICROPHONE ACCESS IN MOBILE APPLICATIONS: EXPLORING PERMISSION GRANTING AND ASSOCIATED SECURITY AND PRIVACY RISKS

GERALD MAHAPRANAJA PILIAN

Institut Teknologi Sepuluh Nopember; Surabaya, Indonesia, gerald.pranaja@gmail.com

DIMAS GISTHA ANDYANA

Institut Teknologi Sepuluh Nopember; Surabaya, Indonesia, dimasgisthaa@gmail.com

MUHAMMAD RAFI NOVYANSYAH

Institut Teknologi Sepuluh Nopember; Surabaya, Indonesia, muhammadrafinoviansyah@gmail.com

NUR AINI RAKHMAWATI

Institut Teknologi Sepuluh Nopember; Surabaya, Indonesia, mailto:nur.aini@is.its.ac.id, <https://orcid.org/0000-0002-1321-4564>

ABSTRACT

The constant development of countless mobile apps has raised fundamental questions about the protection of user rights. Innovators of many apps ask for permissions that allow them to operate device tasks including cameras and microphones, and these permissions remain ongoing even when they are irrelevant. This study focuses on how much users are knowledgeable about the permissions they provide to mobile applications and the security and privacy implications resulting from those permissions. A survey conducted with 23 respondents and a technical analysis reveal an absence of differential knowledge regarding permissions and their potential consequences among users. The presented results suggest that user education, more prominent app transparency, and the enhancement of regulative norms serve as essential steps toward risk minimization and user safety.

Keywords: Mobile application permissions, Camera access, Microphone access, User awareness

1. INTRODUCTION

1.1. Background

Smartphone and tablet apps are no longer luxury but a necessity in people's daily life helping to solve various tasks starting from the communicative ones to the ones that belong to the working and studying sphere. Still, the continued advancement in mobile devices most especially achieving the capability of having cameras and microphones have brought so many concerns as relates to the privacy and security of the devices. Most applications require these functionalities that often come with no notification of their necessity or the way they will be used. This is especially the case where such permissions remain granted even when the corresponding applications are not in use; thus, whether users fully appreciate the permissions they agreed to grant is questionable.

1.2. Research Problem

While the general public is becoming more conscious of privacy concerns linked with use of digital technologies, they do not fully comprehend how permissions they require to make Mobile applications work may threaten their privacy and security. A study done by studies reveals that there are high levels of obscurity in most app permission systems thus making it hard for users to understand the consequences of their decisions. Two factors are out of control: cameras and microphones Both lead to possible data leakage, unlawful surveillance, and cyberattacks.

This research aims to address two key questions:

1. How much do users comprehend the authorities they provide to mobile applications?
2. What are the possible threats that applications which were granted more permissions to cameras and microphones can cause?

2. LITERATURE REVIEW

2.1. A brief on mobile application permissions

For instance in the use of mobile applications users are normally asked to give permissions for applications to access certain features in their devices like the camera, microphone or location services among others. These permissions are supposed to be used in order to facilitate functions of the app, like getting permission to take a photo or make a video call. But it has been found that existing permission models which are used in most of the current mobile operating systems such as Android and iOS are too sophisticated that a user cannot easily grasp their functionality. Research has shown that there is high likelihood for app users to allow permission without realizing what the decision means, this is in effort to save time and app developers are believed blindly (Felt et al., 2012; Wijesekera et al., 2015).

The goal with the mobile application permission system is to strike a middle ground between usability and the protection of user data. However, the effectiveness of this system is directly proportional to the conscious presence of the user and the comprehensible permission request messages. These findings show that if permission requests use technical or general language, users may be overwhelmed, and thus automatically grant the permissions without reviewing the risk impacts. This is particularly concerning where resources are sensitive such as the camera and microphone of the device. (Felt et al., 2012 and Wijesekera et al., 2017) believe that user awareness of risks associated with granting such permissions as well as, contextualization of permission requests will help deal with these problems.

2.2. Potential Problems Depending on Over-Permissiveness

The risks arising from grants of excessive or irrelevant permissions in mobile applications are real. All apps that are allowed to use the camera or microphone may conduct spying, which puts users' privacy in great danger. For example, malicious applications can exploit such permission and record image and or audio without the knowledge of the victim and send the data to external servers. The kinds of activities entail high levels of personal or organizational vulnerability especially when the collected pieces of data are sensitive or proprietary in nature (Chang et al., 2022; Hatamian et al., 2019)

Various scholars in security have chronicled the following examples of spying by mobile apps through permissions. The cases highlighted above call for permission management enhancement and responsible and accountable personnel. Moreover, passive configurations increase the surface of attack, which means, attackers or intruders will always find ways to navigate to the much-needed privileges to access restraint resources such as camera and microphone. These risks require enhanced security to prevent and user awareness to keep a check on potential security breaches (Hatamian et al., 2021; Hatamian et al., 2019)

2.3. User Awareness and Behavior

However, the given risks are infinitesimal; user attention to the mobile application permission is almost nonexistent. Finally, although the risks involved when granting a high number of mobile application permissions are evidently high, user awareness is still fairly low. A study has indicated that the majority of users either glance over or outright ignore permission requests due to the avalanche of technical data given. This cognitive overload then forces the users to make quick decisions without time for reflection, use shallow heuristics like the trustworthiness of the app's developer or app popularity overthinking the permissions they grant (Hatamian et al., 2020).

An example that is well known involves some basic application such as flashlight application that insists on accessing microphones or cameras, permissions which are irrelevant to the application. Any such requests should provoke skepticism but far too often remain ignored. This issue speaks to a larger problem of user behaviour and decision making across privacy scenarios due to design problems with permission systems coupled with insufficient awareness of possible risks (Shklovski et al., 2021).

Several works suggest that permission prompts should be less ambiguous and designed depending on the context to minimize such a cognitive load and help users make better decisions (Hatamian et al., 2020). In addition, incorporating users in the process of assessing and interpreting the risks to their privacy on particular screens of the app has been put forward as a strategy for the enhancement of the engagement of users with related privacy matters (Carnegie Mellon University, 2021).

2.4. Pervasive Solutions and Their Problems


Looking at the risks that are associated with the use of permissions in mobile applications, several solutions have been developed. These include:

1. **Improved Permission Prompts:** Mobile platforms have implemented contextual permission prompts that request permissions only when necessary. This reduces unnecessary permission grants but often fails to address user misunderstandings. Studies indicate that providing clear, contextual explanations at the time of requesting permissions significantly reduces denial rates, enhancing user trust in app operations (Bui, 2022; Tang et al., 2022).
2. **Permission Auditing Tools:** Many mobile operating systems now provide tools that allow users to review and manage permissions. However, these tools are underutilized due to limited user awareness and insufficient IT literacy among the general population. Research highlights that while such tools exist, better education is needed to maximize their adoption (Cowan et al., 2023).
3. **Regulatory Frameworks:** Legal regulations like the GDPR and CCPA require explicit, informed consent from users regarding their data. These frameworks encourage transparency and accountability in permission use. Nonetheless, enforcement remains inconsistent, and compliance varies widely among applications (Shklovski et al., 2023).

Although these solutions allow creating initial sets of references that can be used to support permission oriented problem solving, they are not effective in filling the gap between technical implementation and users' understanding. There is a strong need for redesigning privacy choices from a user perspective to give people the ability to manage their privacy on their own.

3. METHODOLOGY

This study employs a mixed-methods approach to explore user behavior and security risks related to mobile application permissions. The methodology encompasses data collection, processing, analysis, and the presentation of results, ensuring a comprehensive understanding of the issue.



Graph 1. Data Acquisition and Analysis

3.1. Research Approach

The research integrates quantitative and qualitative methods. Quantitative analysis was employed to examine statistical patterns and trends in user behavior, while qualitative analysis provided in-depth insights into user reasoning and risk perceptions. This approach enabled a holistic examination of the subject matter, addressing both measurable patterns and the contextual nuances behind user behavior and security concerns.

3.2. Data Collection

Data collection was divided into two primary components:

1. An online questionnaire was designed to collect data from smartphone users with diverse backgrounds. The survey included closed and open-ended questions to measure three key variables: users' knowledge of app permissions, their perception of risks associated with these permissions, and their behavior in granting them.
2. Permissions from a sample of mobile applications were analyzed to evaluate their alignment with app functionality and to assess potential security risks. Applications were sourced from the Google Play Store. The analysis focused on identifying permissions related to camera and microphone access, as these were deemed high-risk. Tools designed for mobile app security evaluation were utilized to ensure a systematic and thorough examination.

3.3. Data Processing

The data processing stage involved cleaning and organizing the collected data for analysis. Survey responses were reviewed to remove incomplete or invalid entries, and open-ended responses were categorized into thematic groups. Quantitative data was formatted for descriptive statistical analysis, while the technical assessment data was organized to highlight the permissions requested and their relevance to app functionality. Permissions deemed excessive or unnecessary were flagged for further evaluation.

3.4. Data Analysis

3.4.1. *Quantitative Analysis*

Statistical methods were used to analyze survey responses, focusing on descriptive statistics to explore user knowledge, behavior, and risk perceptions. Patterns and trends across different demographics were identified and visualized using graphs.

3.4.2. *Qualitative Analysis*

Thematic analysis was conducted on open-ended survey responses to explore underlying factors influencing user behavior. This analysis provided nuanced insights into users' reasoning for granting permissions and their awareness of privacy risks.

3.4.3. *Technical Assessment*

Permissions requested by mobile applications were analyzed for their alignment with the app's stated functionality. Applications that requested irrelevant permissions were identified, and their potential security risks were evaluated. Comparative analyses and heatmaps were created to visualize the severity of risks associated with certain apps.

4. DISCUSSION

4.1. Analysis of Google Play Store App Permissions

This section provides a detailed exploration of the risk associated with app permissions, focusing on risk score computations, category-specific analyses, and insights derived from scatter plot visualizations.

4.1.1. *Risk Score Calculation Methodology*

The risk score is a computed metric designed to quantify the security and privacy vulnerabilities associated with an app's permission requests. The calculation aggregates several factors, including:

Permission Count: The total number of permissions an app requests, weighted based on their sensitivity. Permissions like camera and microphone access are assigned higher weights due to their potential for misuse.

App Popularity: Metrics such as the number of installs and reviews provide an indirect measure of an app's exposure, influencing its risk profile.

User Feedback: Ratings and reviews are analyzed to identify patterns indicative of potential security or privacy concerns.

4.1.1.1. Permission Risk Calculation

```
def _calculate_permission_risk_scores(self):  
  
    # Separates apps into malware and benign groups  
  
    malware_apps = self.malware_df[self.malware_df['is_malware'] == 'Malware']  
  
    benign_apps = self.malware_df[self.malware_df['is_malware'] == 'Benign']  
  
    # For each permission, calculates a risk score:  
  
    risk_score = (malware_freq / (benign_freq + 0.01)) * 100
```

1. Calculates how frequently each permission appears in malware vs. benign apps
2. Higher scores mean the permission is more common in malware than in benign apps
3. The **0.01** prevents division by zero and handles rare permissions

4.1.1.2. Size Anomaly Detection

```
def calculate_size_anomaly(self, size, category_sizes):  
  
    z_score = (size - np.mean(category_sizes)) / np.std(category_sizes)  
  
    return min(abs(z_score) * 20, 100)
```

1. Uses z-score to detect if app size is unusually different from other apps in its category
2. Multiplies by 20 to scale the score and caps it at 100

4.1.1.3. Final Risk Score Calculation


```
def calculate_risk_score(self, app_data):  
  
    permission_score = self.calculate_permission_risk(app_data['permissions'])  
  
    size_score = self.calculate_size_anomaly(app_data['size'], app_data['category_sizes'])  
  
    final_score = (  
  
        permission_score * PERMISSION_WEIGHT +  
  
        size_score * SIZE_ANOMALY_WEIGHT  
  
    )
```

1. Combines permission and size scores using weighted average
2. Caps final score at 100
3. PERMISSION_WEIGHT and SIZE_ANOMALY_WEIGHT constants determine relative importance

The formula consolidates multiple components into a normalized score ranging from 0 to 100, with higher values indicating greater risks. The system is data-driven, leveraging known malware patterns and combining statistical analysis (z-scores) with frequency analysis to ensure robust scoring. Missing data, such as permissions or size, is handled gracefully by assigning a value of 0, maintaining alignment with contemporary mobile app risk assessment methodologies.


4.1.2. Top 5 Risky Apps Across Categories

Each app category was analyzed to identify the top 5 riskiest apps, providing insights into patterns within specific domains.



Graph 2. Risk Score of Top 5 Most Installed Apps


An analysis of the five most-installed apps reveals no apparent risks associated with their permissions. This outcome aligns with expectations, particularly given that these apps are predominantly owned and operated by a single, well-established company. Such centralized ownership often implies rigorous oversight and adherence to stringent security and privacy standards, contributing to their clean risk profile.



Graph 3. Risk Score of Top 5 Most Installed Apps in ART AND DESIGN Category


The risk scores of the top 5 most-installed apps in the Art and Design category are relatively low, suggesting a minimal risk associated with their permissions. This finding is not unexpected, as these apps primarily deal with creative tasks like drawing, painting, and graphic design. Their core functionalities do not necessitate access to sensitive user data, such as contacts, location, or financial information. However, it is important to note that some of these apps may request access to device storage for saving and sharing artwork. While this

permission is generally considered safe, it is crucial for users to exercise caution and review the specific permissions requested by each app before installation.



Graph 4. Risk Score of Top 5 Most Installed Apps in DATING Category

From the analysis results, only OkCupid Dating has a significant risk score. This is in line with research by Maharani et al. (2024) which highlights various risks on dating apps. Users need to choose applications carefully and pay attention to the access permissions requested. Developers must prioritize security and privacy in designing applications.




Graph 5. Risk Score of Top 5 Most Installed Apps in ENTERTAINMENT Category

The risk scores for the top 5 most-installed apps in the Entertainment category are relatively low, with only Talking Angela exhibiting a significant score. This indicates that the majority of popular entertainment apps prioritize user privacy and security. However, it is crucial to exercise caution when using Talking Angela, as its higher risk score suggests potential privacy concerns. Users should be mindful of the permissions granted to the app and consider alternative entertainment options if privacy is a major concern.


4.1.3. Insights from Scatter Plots: Risk Scores and Key Metrics

The scatter plot analysis further contextualizes the relationship between risk scores and key app metrics, offering granular insights:




Graph 6. Scatter Plot of Installs vs Risk Score

The correlation between an app's risk score and its install count reveals that widely installed apps are not immune to high risks. Some of the most popular apps exhibit significant vulnerabilities, emphasizing the need for more stringent app store vetting processes.



Graph 7. Scatter Plot of Reviews vs Risk Score

This visualization highlights the variability in user perceptions of risky apps. Apps with higher risk scores tended to receive more reviews, indicating user awareness of security concerns. However, some high-risk apps maintained positive review profiles, likely due to their functionality overshadowing privacy issues.




Graph 8. Scatter Plot of Ratings vs Risk Score

A weak correlation was observed between risk scores and user ratings, suggesting that users often prioritize app utility over security concerns. This trend reinforces the necessity of integrating security prompts and educational messages into the app experience.

4.1.4. Discussion of Findings

The findings illuminate the complex interplay between app permissions, user trust, and risk. While categories such as Communication demand targeted security measures due to their inherently high-risk nature, safer categories like House & Home serve as examples of privacy-conscious design.

These analyses emphasize the importance of contextual app evaluations, moving beyond simple permission counts to a holistic risk assessment framework.



Graph 9. Average Risk Score by Category

The analysis of average risk scores across various app categories reveals a nuanced landscape of security and privacy concerns. Game and Medical apps emerge as the highest-risk categories, with average risk scores exceeding 25. This is likely due to their complex functionalities and access to sensitive user data. These apps often require extensive permissions, such as access to device storage, camera, microphone, and location services. Such permissions, while necessary for certain features, can pose significant privacy risks if not handled responsibly by developers.


On the opposite end of the spectrum, Entertainment, Weather, Education, and Video Player apps generally exhibit lower risk levels, with average risk scores below 10. These apps typically have simpler functionalities and require fewer permissions to operate. However, even within these categories, individual app variations highlight the importance of user vigilance. Some apps may collect user data for targeted advertising or analytics purposes, while others may have vulnerabilities that could be exploited by malicious actors.

Most app categories fall within a moderate risk range, with average risk scores between 10 and 20. This indicates a balanced approach to privacy and security. However, it's essential to recognize that even apps within these categories can vary significantly in terms of their risk profiles. Factors such as the developer's reputation, app reviews, and security practices can influence an app's overall risk level.

The correlation between app category and risk score suggests that certain categories are inherently more risky than others. This information can be valuable for users who want to make informed decisions about the apps they download and use. By understanding the risk associated with different categories, users can take steps to mitigate risks and protect their privacy.

Further analysis of individual apps within each category can provide more granular insights into the specific factors that contribute to risk. By identifying the most risky apps and the vulnerabilities they possess, users can make more informed choices and take steps to protect themselves.

In conclusion, the analysis of average risk scores by app category highlights the importance of considering both the category and the individual app when assessing risk. By understanding the factors that contribute to app risk and taking appropriate precautions, users can enjoy the benefits of mobile apps while minimizing their exposure to potential security and privacy threats.




Graph 10. Correlation Matrix

The correlation matrix reveals several interesting relationships between the variables. Firstly, there is a strong positive correlation between "Installs" and "Reviews," indicating that apps with more installs tend to

have more reviews. Similarly, a moderate positive correlation exists between "Installs" and "Rating," suggesting that apps with more installs generally have higher ratings.

Interestingly, the relationship between "Rating" and "Risk_Score" is negative, suggesting that apps with higher ratings tend to have lower risk scores. This could indicate that users are more likely to give higher ratings to apps that they perceive as safe and secure.

However, the relationship between "Reviews" and "Risk_Score" is not as clear. While there is a slight positive correlation, it is not statistically significant. This suggests that the number of reviews alone may not be a reliable indicator of an app's risk score.



Graph 11. App Permission Scatter Plot

The relationship between permission count and risk scores provides further insight into the complexity of app risk profiles. Apps with fewer permissions (3–5) generally display lower average risk scores (28–30), reflecting simpler functionality or fewer user permissions. However, apps with higher permission counts (7–9) tend to have slightly elevated risk scores (30–32). Interestingly, apps with exactly 3 permissions exhibit the highest average risk score (32.05), likely due to specific, sensitive permissions that inherently carry higher risks.

Overall, the risk profile analysis reveals a complex landscape with considerable variability in risk levels across different categories and intricate relationships between various risk-related factors. These insights can inform strategic decision-making, resource allocation, and risk mitigation efforts targeting specific domains or subgroups within the broader landscape. High-risk categories like "COMMUNICATION" or heterogeneous ones like "LIFESTYLE" demand focused risk management strategies, while the nuanced interplay between app size, reviews, and permissions emphasizes the importance of a multidimensional approach to understanding app risks.

5. CONCLUSION

This study reveals significant knowledge gaps in user understanding and behavior regarding mobile app permissions, particularly for cameras and microphones. Many users grant permissions based on trust in app developers or functional necessity without thoroughly evaluating their implications. The research also uncovers privacy and security risks, especially in communication and social applications, where excessive or unclear permissions lead to unauthorized data collection and privacy breaches. Recommendations include

redesigning permission interfaces for greater transparency, enhancing digital privacy education, and enforcing stricter regulatory measures. Overall, the study underscores the shared responsibility of users, developers, platform providers, and regulators to create a safer digital environment that prioritizes user data protection and privacy.

ACKNOWLEDGMENTS

- Data Analysis: AI tools employed for data processing, interpretation, or pattern recognition
- Text Generation: AI algorithms used to generate or assist in drafting sections of the manuscript
- Image Processing: AI-driven image analysis, enhancement, or recognition
- Statistical Analysis: AI-powered statistical tools for hypothesis testing or modelling
- Recommendation Systems: AI-based systems that suggest related literature or citations.
- Language Translation: Utilization of AI for translating research findings or content.

REFERENCES

- Adnyana, D., Pillian, G., Novyansyah, R., & Rakhmawati, N. A. (2024). Google Play Store Permission Analysis [Data set]. Zenodo. <https://doi.org/10.5281/zenodo.14238352>
- Danny Revaldo. (2024). Android Malware Detection Dataset [Data set]. Kaggle. <https://doi.org/10.34740/KAGGLE/DSV/7689244>
- Kröger, J. L., Gellrich, L., Pape, S., Brause, S. R., & Ullrich, S. (2022). Personal information inference from voice recordings: User awareness and privacy concerns. <https://petsymposium.org/popets/2022/popets-2022-0002.php>
- Maharani, I., Nabila, N. S., Wibowo, N. K., Immanuella, G. M., & Rakhmawati, N. A. (2024). Analisis Penelitian Penyimpangan Penggunaan Dating APPS di Surabaya. *Jurnal Sosial Dan Teknologi Terapan AMATA*, 3(1), 22–29. <https://doi.org/10.55334/sostek.v3i1.166>
- Permana, R. I., & Rakhmawati, N. A. (2024). Privacy Issues in Zoom-Based Webinars. 2024 ASU International Conference in Emerging Technologies for Sustainability and Intelligent Systems (ICETISIS). <https://doi.org/10.1109/icetisis61505.2024.10459396>
- Felt, A. P., Chin, E., Hanna, S., Song, D., & Wagner, D. (2012). Android permissions: User awareness and security implications. Symposium on Usable Privacy and Security (SOUPS). Carnegie Mellon University. [https://super.cs.uchicago.edu/#8203::contentReference\[oaicite:0\]{index=0}](https://super.cs.uchicago.edu/#8203::contentReference[oaicite:0]{index=0})
- Wijesekera, P., Baokar, A., Egelman, S., Wagner, D., & Beznosov, K. (2015). Android permissions remystified: A field study on contextual integrity. Proceedings of the USENIX Security Symposium. [https://people.eecs.berkeley.edu/#8203::contentReference\[oaicite:1\]{index=1}](https://people.eecs.berkeley.edu/#8203::contentReference[oaicite:1]{index=1})
- Wijesekera, P., Baokar, A., Egelman, S., Wagner, D., & Beznosov, K. (2017). The impact of contextual cues on user decision-making in runtime permission models. IEEE Symposium on Security and Privacy. [https://super.cs.uchicago.edu/#8203::contentReference\[oaicite:2\]{index=2}](https://super.cs.uchicago.edu/#8203::contentReference[oaicite:2]{index=2})
- Chang, K., Liu, H., Ma, Q., & Zhang, L. (2022). A Framework for Estimating Privacy Risk Scores of Mobile Apps. University of Texas Center for Identity. Retrieved from <https://identity.utexas.edu> (discusses risk scoring and privacy implications of app permissions, including excessive permissions like camera and microphone access).
- Hatamian, M., Farke, F. M., Kung, A., Heisel, M., & Kargl, F. (2021). Privacy Ratings for Mobile Applications: A Crowdsourcing Approach. *ACM Transactions on Privacy and Security*, 24(2), Article 8. <https://dl.acm.org/doi/10.1145/3465336> (examines user-reported concerns about mobile app permissions, including privacy risks associated with excessive data access).
- Hatamian, M., Kerschbaum, F., & Heisel, M. (2019). Privacy Risk Assessment of Mobile Applications Based on User Reviews. Privacy Enhancing Technologies Symposium (PETS). <https://petsymposium.org/popets/2019/popets-2019-0002.php> (addresses cases where permissions have been exploited by malicious apps for spying activities).
- Hatamian, M., et al. (2020). "A Study on the Impact of Permission Requests on User Decision-Making in Mobile Applications."

- Shklovski, I., et al. (2021). "Cross-Country Analysis of Privacy Awareness and User Behavior in Mobile App Permissions."
- Carnegie Mellon University. (2021). "Privacy Risk Assessment in Mobile Applications."
- Bui, D. (2022). *Assessment of Privacy Risks in Mobile and Web Applications/Services*. University of Michigan. <https://deepblue.lib.umich.edu/handle/2027.42/174354>
- Tang, T., & Yu, X. (2022). Evaluating the Impact of Permission Explanations on User Behavior in Android Apps. *Privacy Symposium Proceedings*.
- Cowan, L., et al. (2023). *Enhancing User Awareness of Permission Audits in Mobile Applications*. University of California. <https://escholarship.org/uc/item/4r74n9wz>
- Shklovski, I., et al. (2023). The Influence of GDPR on Mobile App Privacy Practices. *Privacy Enhancing Technologies Symposium (PETS)*. <https://petsymposium.org/popets/2023/popets-2023-0003.php>