

Topological Quantum Computing

Gergely Lendvay

September 2, 2026

Contents

0.1	Course Info	3
0.1.1	Teachers	3
0.1.2	Exercise Classes	3
0.1.3	Exam	3
0.1.4	Books	3
1	First Lecture	4
1.1	Topological Quantum Computing	4
1.2	What is Topological Quantum Computing?	4
1.3	Non-abelian anyons	4
1.4	Plan	4
2	Second Lecture	6
2.1		6

Introduction

0.1 Course Info

0.1.1 Teachers

Konstantin Wernli – kwernli@imada.sdu.dk

William Mistegard – wem@imada.sdu.dk

0.1.2 Exercise Classes

Once a week with at least 3 solutions handed in.

0.1.3 Exam

1. Assessment is based on four graded exercise sheets, and
2. Final oral exam consisting of:
 - 10–12 minutes presentation,
 - 13–15 minutes discussion and questions,
 - 4–5 possible topics, with 30 minutes of preparation time.
3. Tentative exam date: January 18, 2027

0.1.4 Books

N/A

1 First Lecture

1.1 Topological Quantum Computing

Different fields:

- Condensed matter physics: topological phases of matter
- Topological Quantum Field Theory
- TQFT's in math
- Anyon models/UMTC in math

1.2 What is Topological Quantum Computing?

Digital vs analog quantum computing.

Problem They are prone to errors and noise, such as spam error during state preparation, gate fidelities as well as decoherence.

The idea of TQC is to use very special physical systems where information is encoded in discrete global properties. These are topological phases of matter.

Certain phases in $2+1$ dimensions, with 2 spatial dimensions and 1 time, admit anyons. Anyons are a special class of (quasi) particles with statistics different from bosons and fermions.

In more than $2+1$ dimensions $T^2 = 1 \rightarrow T = \pm 1$ $+1 = e^{i2\pi i}$ bosons $-1 = e^{i\pi i}$ fermions

In $2+1$ dimension $T_2 \neq 1$, meaning it can get any phase $T = e^{i\Theta}$

If $T = e^{i\Theta} \rightarrow$ abelian anyons, but there are non-abelian anyons where T can be a unitary acting on $\mathcal{H}$. These are the unitary we want to use in TQC.

1.3 Non-abelian anyons

Described by $|\psi\rangle \in \mathcal{H}$ when exchanging anyons

$$|\psi\rangle \rightarrow U |\psi\rangle,$$

for some unitary U .

Braids form a group.

Companies trying to develop non-abelian anyons: Microsoft and Nokia Simulate anyons on quantum computer (topological codes): Google and Quantinuum

1.4 Plan

Math foundations:

- Groups (braid),
- Representation,
- Category theory,
- Topology.

TQC:

- Anyon models,
- Examples,
- Equivalence to digital quantum computing,
- Relation to TQFT's, etc.

TQC in practice:

- Topological phases of matter,
- Experimental realizations.

Topological codes:

- Surface codes,
- Other classes of topological codes.

2 Second Lecture

2.1