

CARGO MATE
SMART ROBOTIC INVENTORY SYSTEM WITH
CLOUD INTEGRATION

25-26J-032

Design Document (DD) of Barcode Scanning System

S. S. Hewapathirana

B.Sc. (Hons) Degree in Information Technology, specializing in
Computer Systems and Network Engineering

Department of Computer Systems Engineering

Sri Lanka Institute of Information Technology

Sri Lanka

January 11, 2026

Table of Contents

1. Introduction	1
1.1 Purpose	1
1.2 Scope	1
1.3 Definitions, Acronyms, and Abbreviations	2
1.4 Overview	2
2. Overall Description	3
2.1 Product Perspective	3
2.1.1 System Interfaces	4
2.1.2 User Interfaces	4
2.1.3 Hardware Interfaces	4
2.1.4 Software Interfaces	4
2.1.5 Communication Interfaces	4
2.1.6 Memory Constraints	4
2.1.7 Operations	4
2.1.8 Site Adaptation Requirements	4
2.2 Product Functions	5
2.3 User Characteristics	5
2.4 Constraints	5
2.5 Assumptions and Dependencies	5
2.6 Apportioning of Requirements	6
3. Specific Requirements	6
3.1 External Interface Requirements	6
3.1.1 User Interfaces	6
3.1.2 Hardware Interfaces	6
3.1.3 Software Interfaces	6
3.1.4 Communication Interfaces	6
3.2 Architectural Design	7

3.2.1 High-Level Architectural Design	7
3.2.3 Circuit Diagram	9
3.2.4 Hardware and Software Requirements with Justification	10
3.2.5 Risk Mitigation Plan	10
3.2.5 Cost-Benefit Analysis	10
3.3 Performance Requirements	10
3.4 Design Constraints	10
3.5 Software System Attributes	11
3.5.1 Reliability	11
3.5.2 Availability	11
3.6 Other Requirements	12
4. References	13
5. Supporting Information	14
5.1 Table of Contents and Index	14
5.2 Appendices	14
Appendix A – Test Cases	14
Appendix B – Pin Mapping Table	15

List of figures

Figure 1: High-Level Architecture Diagram	7
Figure 2: Process Flow Description Diagram	8
Figure 3: Circuit Diagram	9

1. Introduction

1.1 Purpose

The purpose of this Design Document (DD) is to describe the design and implementation of the automated barcode scanning and validation subsystem used in the Smart Robotic Inventory System. This document outlines the architectural design, hardware and software integration, interface specifications, performance requirements, and system constraints relevant to the barcode scanning process.

This document serves as a technical reference for development, evaluation, future enhancement, and maintenance of the subsystem.

1.2 Scope

This Design Document focuses exclusively on the barcode scanning and conveyor control subsystem of the Smart Robotic Inventory System. The document describes the functional and architectural design aspects of the subsystem, detailing how products are identified, validated, and coordinated with automated material handling components.

The scope of this document includes the following key areas:

- Conveyor-based product positioning and controlled movement for accurate barcode scanning and robotic pickup.
- IR sensor-based object detection at the end of the conveyor to enable precise stopping of the conveyor during product pickup.
- Image capture, barcode decoding, and preliminary validation using the ESP32-CAM module.
- Barcode verification mechanisms, including detection of unreadable or damaged barcodes and elimination of duplicate barcode entries.
- Communication and coordination with the robotic arm subsystem by generating pickup trigger signals after successful barcode validation.
- Secure wireless communication and cloud-based inventory updates using the Firebase real-time database.
- Embedded firmware design, modular software architecture, and interface interactions between sensors, controllers, actuators, and cloud services.

The document is intended to cover functional and logical design aspects only. Detailed manufacturing-level mechanical drawings, advanced machine learning model implementation, and large-scale industrial deployment considerations are outside the scope of this document. These aspects may be addressed in future phases of the project.

1.3 Definitions, Acronyms, and Abbreviations

Term	Description
ESP32-CAM	ESP32 microcontroller with integrated camera and Wi-Fi
IR Sensor	An infrared sensor used for object detection
DD	Design Document
ML	Machine Learning
Firebase	Cloud-based real-time database
GPIO	General Purpose Input/Output

1.4 Overview

The barcode scanning subsystem is designed to automate product identification and inventory tracking within a conveyor-based material handling environment. The subsystem captures barcode images as products move along the conveyor, performs barcode decoding and validation, and updates inventory records in a cloud-based database. Conveyor movement is intelligently controlled to support accurate scanning and reliable robotic pickup operations.

By eliminating manual barcode scanning and data entry, the subsystem significantly reduces human error and improves operational efficiency. Seamless integration with robotic handling mechanisms enables automated product pickup after successful barcode validation, ensuring a smooth and continuous workflow suitable for educational, laboratory, and small-scale industrial applications.

2. Overall Description

The barcode scanning and conveyor control subsystem is implemented as an embedded automation unit that operates in coordination with a roller chain conveyor and a robotic arm. The subsystem uses real-time sensor inputs, image capture and processing, and wireless communication to achieve accurate barcode-based product identification and inventory management.

The system architecture combines multiple embedded controllers to handle specific tasks such as conveyor control, barcode scanning, and cloud communication. This distributed control approach enhances system responsiveness and reliability while simplifying development and maintenance. The subsystem is designed to operate continuously with minimal user intervention once initialized.

The design emphasizes the following key aspects:

- **Low-cost embedded components:** Utilization of widely available microcontrollers and sensors to reduce system cost while maintaining reliable performance.
- **Modular architecture:** Independent functional modules allow easy testing, debugging, and future upgrades without affecting the entire system.
- **Real-time operation:** Immediate response to sensor inputs and barcode scanning events ensures smooth and synchronized system behavior.
- **Scalability for future enhancements:** The architecture supports future features such as machine learning–based barcode quality assessment, multi-conveyor support, and advanced analytics.

2.1 Product Perspective

The barcode scanning subsystem functions as an autonomous embedded unit while maintaining tight integration with the robotic arm and centralized inventory management system. Unlike traditional handheld barcode scanners that rely on manual operation, this subsystem offers a fully automated, contactless, and cloud-connected solution.

Compared to conventional scanning systems, the proposed design provides improved accuracy, consistency, and efficiency by combining conveyor automation, camera-based barcode capture, and real-time cloud synchronization. The subsystem is compact, adaptable, and suitable for integration into existing automated material handling systems, making it an effective solution for both educational demonstrations and prototype-level industrial automation.

2.1.1 System Interfaces

- ESP32-CAM firmware interface
- NodeMCU motor control interface

2.1.2 User Interfaces

- Serial Monitor for system status and debugging
- Firebase web dashboard for inventory monitoring

2.1.3 Hardware Interfaces

- IR sensor (digital input)
- DC motor driver interface
- ESP32-CAM camera module

2.1.4 Software Interfaces

- Arduino IDE and ESP32 board support package
- Barcode decoding libraries
- Firebase SDK / REST API

2.1.5 Communication Interfaces

- Wi-Fi communication (IEEE 802.11)

2.1.6 Memory Constraints

- ESP32-CAM internal RAM and flash limitations
- Optimized image buffer usage

2.1.7 Operations

- Conveyor movement control
- Product detection and scanning
- Barcode validation and duplication check
- Cloud data upload

2.1.8 Site Adaptation Requirements

- Stable lighting conditions
- Reliable Wi-Fi connectivity
- Secure mounting of camera and sensors

2.2 Product Functions

- Detect product arrival using IR sensor
- Stop conveyor at scanning position
- Capture barcode image
- Validate barcode readability
- Reject damaged or duplicate barcodes
- Signal robotic arm for pickup
- Upload barcode data to Firebase

2.3 User Characteristics

- Inventory operators with basic system knowledge
- Engineering students and developers
- Maintenance personnel familiar with embedded systems

2.4 Constraints

- Limited processing capability of ESP32-CAM
- Dependence on network availability
- Fixed camera resolution

2.5 Assumptions and Dependencies

- Barcodes follow standard formats
- Products are correctly aligned on the conveyor
- Firebase services are available

2.6 Apportioning of Requirements

- Phase 1: Conveyor and sensor integration
- Phase 2: Barcode capture and decoding
- Phase 3: Cloud data upload
- Phase 4: Machine learning validation (future work)

3. Specific Requirements

3.1 External Interface Requirements

3.1.1 User Interfaces

- Serial monitor logs for system states
- Firebase dashboard for real-time inventory data

3.1.2 Hardware Interfaces

- IR sensor connected to digital GPIO
- Motor driver connected to NodeMCU
- ESP32-CAM camera interface
- External power interface for supplying adequate power

3.1.3 Software Interfaces

- Arduino IDE used for firmware development and deployment
- Barcode decoding libraries
- Firebase communication APIs

3.1.4 Communication Interfaces

- USB serial interface for programming, debugging, and monitoring
- Wi-Fi-based HTTP/HTTPS communication

3.2 Architectural Design

3.2.1 High-Level Architectural Design

The subsystem follows a modular embedded architecture consisting of:

- Sensor module (IR sensor)
- Conveyor control module (NodeMCU + motor driver)
- Image capture and processing module (ESP32-CAM)
- Cloud communication module (Firebase)




Figure 1: High-Level Architecture Diagram

3.2.2 Process Flow Description




Figure 2 : Process Flow Description Diagram

3.2.3 Circuit Diagram




Figure 3 : Circuit Diagram

3.2.4 Hardware and Software Requirements with Justification

- **ESP32-CAM:** Combines camera, processing, and Wi-Fi
- **IR Sensor:** Reliable product detection
- **NodeMCU:** Efficient motor and logic control
- **Firebase:** Secure and scalable cloud storage

3.2.5 Risk Mitigation Plan

Risk	Impact	Mitigation
Blurred barcode	Scan failure	Stop the conveyor during capture
Network loss	Data loss	Local retry mechanism
Duplicate scans	Inventory error	Barcode uniqueness check

3.2.5 Cost-Benefit Analysis

The subsystem significantly reduces labor costs, scanning errors, and inventory inconsistencies while using low-cost hardware, making it suitable for educational and small industrial environments.

3.3 Performance Requirements

- Barcode scan time < 2 seconds
- Conveyor stop response < 500 ms
- Cloud upload latency < 3 seconds

3.4 Design Constraints

- Embedded memory limits
- Fixed camera focus
- Real-time operational constraints

3.5 Software System Attributes

3.5.1 Reliability

The barcode scanning subsystem is designed to operate reliably under continuous usage conditions. Reliability is achieved through controlled conveyor operation, where the conveyor is stopped only at critical points such as product pickup, minimizing mechanical stress and scanning errors. Barcode validation mechanisms ensure that only correctly decoded and non-duplicate barcodes are accepted into the system.

Error-handling routines are implemented to manage unreadable or damaged barcodes by rejecting invalid items and preventing incorrect data entry. The use of stable embedded firmware, sensor debouncing techniques, and controlled motor operation further enhances the overall reliability of the subsystem.

3.5.2 Availability

The subsystem is designed to be available for operation whenever power is supplied and network connectivity is established. Upon startup, all hardware components including the NodeMCU, ESP32-CAM, sensors, and motor driver are initialized automatically without the need for manual intervention.

The system supports continuous operation during normal working hours and resumes functionality immediately after power restoration. The use of cloud-based Firebase services ensures real-time data availability for inventory monitoring, provided network connectivity is maintained.

3.5.3 Security

Security of inventory data is ensured through secure Wi-Fi communication and authenticated access to the Firebase cloud database. Barcode data is transmitted using protected communication protocols, reducing the risk of unauthorized interception.

Access to the embedded system is restricted through physical access control to the hardware and development interfaces. Since the system operates in a controlled industrial or laboratory environment, physical security measures complement software-level security mechanisms to prevent unauthorized modification or misuse of the system.

3.5.4 Maintainability

The subsystem firmware follows a modular design approach, separating sensor handling, motor control, barcode processing, and cloud communication into independent software modules. This structure simplifies debugging, testing, and future modifications.

Maintainability is further enhanced by clear code documentation, structured naming conventions, and the use of standard development tools such as the Arduino IDE. The modular architecture allows new features, such as enhanced barcode validation techniques or additional sensors, to be integrated with minimal changes to the existing system

3.6 Other Requirements

- **Diagnostic Logging:**

The system provides diagnostic logging through serial output to assist in monitoring system behavior, debugging errors, and validating operational states during development and testing.

- **Future Machine Learning–Based Barcode Quality Detection:**

The system architecture supports future integration of a machine learning–based barcode quality detection module. This enhancement will enable advanced detection of damaged, blurred, or partially occluded barcodes, further improving scanning accuracy and system robustness.

4. References

- [1] Espressif Systems, *ESP32-CAM Technical Reference Manual*, Espressif Systems Inc., 2023. [Online]. Available: <https://www.espressif.com/en/products/socs/esp32>
Accessed: Jan. 2026.
- [2] Espressif Systems, *Arduino ESP32 Core Documentation*, Espressif Systems Inc., 2023. [Online]. Available: <https://docs.espressif.com/projects/arduino-esp32/en/latest/>
Accessed: Jan. 2026.
- [3] Arduino, *Arduino IDE Documentation*, Arduino LLC, 2023. [Online]. Available: <https://www.arduino.cc/en/software>
Accessed: Jan. 2026.
- [4] Firebase, *Firebase Realtime Database Documentation*, Google LLC, 2023. [Online]. Available: <https://firebase.google.com/docs/database>
Accessed: Jan. 2026.
- [5] NXP Semiconductors, *L298 Dual Full-Bridge Driver Datasheet*, NXP, 2022. [Online]. Available: <https://www.st.com/resource/en/datasheet/l298.pdf>
Accessed: Jan. 2026.
- [6] Espressif Systems, *ESP8266 NodeMCU Documentation*, Espressif Systems Inc., 2022. [Online]. Available: <https://nodemcu.readthedocs.io/>
Accessed: Jan. 2026.
- [7] R. Smith, *Introduction to Embedded Systems*, 2nd ed., Pearson Education, 2019.
- [8] J. G. Webster, *Sensors and Signal Conditioning*, 2nd ed., Wiley, 2001.

5. Supporting Information

5.1 Table of Contents and Index

Provided at the beginning of the document.

5.2 Appendices

Appendix A – Test Cases

Barcode Scanning and Conveyor Control Test Cases

Test Case ID	Test Description	Input / Condition	Expected Result	Actual Result	Status
TC-01	System Power-On Test	Power connected	NodeMCU and ESP32-CAM initialize successfully	As expected	Pass
TC-02	Conveyor Start Test	System startup	Conveyor starts moving	As expected	Pass
TC-03	Barcode Capture Test	Product at scanning position	Barcode image captured successfully	As expected	Pass
TC-04	Barcode Decode Test	Valid barcode image	Barcode decoded correctly	As expected	Pass
TC-05	Duplicate Barcode Detection Test	Same barcode scanned twice	Duplicate barcode ignored	As expected	Pass
TC-06	Invalid Barcode Test	Damaged or unreadable barcode	Barcode rejected	As expected	Pass
TC-07	Firebase Upload Test	Valid barcode scanned	Barcode data uploaded to Firebase	As expected	Pass

Test Case ID	Test Description	Input / Condition	Expected Result	Actual Result	Status
TC-08	IR Sensor Detection Test	Product reaches conveyor end	IR sensor detects product	As expected	Pass
TC-09	Conveyor Stop Test	IR sensor triggered	Conveyor stops for pickup	As expected	Pass
TC-10	Robotic Arm Trigger Signal Test	Conveyor stopped	Pickup signal sent to robotic arm	Not implemented	In Progress

Appendix B – Pin Mapping Table

1. Controller and Motor Driver Connections

Component	Controller Pin	Signal Type	Power Source	Description
DC Motor	Motor Driver Output	Power Output	12V Supply	Drives conveyor movement
Motor Driver IN1	NodeMCU GPIO	Digital Output	NodeMCU 3.3V	Motor direction control
Motor Driver IN2	NodeMCU GPIO	Digital Output	NodeMCU 3.3V	Motor direction control
Motor Driver EN	NodeMCU GPIO	PWM Output	NodeMCU 3.3V	Motor speed control

2. Sensor Connections

IR Sensor

IR Sensor Pin	Controller Pin	Description
VCC	3.3V / 5V	Power supply
GND	GND	Common ground

IR Sensor Pin	Controller Pin	Description
OUT	NodeMCU GPIO	Digital input for product detection

3. ESP32-CAM Connections

ESP32-CAM Pin	Connection	Description
5V	5V Supply	Power input
GND	GND	Common ground
U0R / U0T	FTDI Programmer	Programming interface

4. Power Supply Connections

Component	Power Source	Description
ESP32-CAM	5V Regulated Supply	Camera and Wi-Fi operation
NodeMCU	USB / 5V Supply	Main controller power
DC Motor	12V Supply	Conveyor operation
Motor Driver	12V Supply	Motor control
Sensors	3.3V / 5V	Low power consumption