

Outer Dictionary Network: An Efficient Network For Named Entity Recognition

Junxiang Ge, Qi Zhang, Haizhou Zhao

AI Research Department, Sogou Inc.
Beijing, China

Abstract

With the risen use of AI application, we need to understand some specific type of message from user's query. Named Entity Recognition (NER) is a basic task for that use. Dictionary information is very useful when doing NER, however, most of the current method use it in word embedding format, which will bring out the situation that we need to retrain model when the list of words in dictionary is greatly changed. In this paper, we propose a new conception, called Outer Dictionary Model (ODM), which means to use the outer type info of gazette for each word, without using the specific word or word embedding vector. In other word, we try to combine information of knowledge graph into Neural Networks (NN). To implement the ODM, we propose a new structure, called Tag Embedding LSTM (TE-LSTM). Experiment results shows that our model achieve a great improvement on tasks within which gazette is heavily depended on, with comparison with current state-of-the-art methods.

Introduction

Named Entity Recognition (NER) is a base task when doing many Natural Language Processing (NLP) tasks. Usually, we need to extract mainly information from users' sentences to help us understand their meanings, and then use the extracted information to do further process. For example, in weather domain, we may need to extract **date and position** to help us understand when and where the user is asked towards the weather; in music type service, we may need to track **singer, song, style** entities to suit user's command; for many common use, we need **person, location, organization** message to understand a sentence.

To accomplish this task, many method has been explored. Convolution Neural Network (CNN) is used in Image Classification (Krizhevsky, Sutskever and Geoffrey 2012), and then proved also powerful in Text Classification (Kim 2014). CNN is also useful in NER tasks, whether to capture character-level features (Chiu and Nichols 2016; Ma and Hovy 2016; Peters et al. 2017), or to do word-level sequence labelling (Santos, Xiang, and Zhou 2015; Strubell et al. 2017). To learn the correlation between words in sentence, Recurrent Neural Network (RNN) (Sutskever, Vinyals

and Le 2014) and Long Short-Term Memory (LSTM) (Sak, Senior and Beaufays 2014) are proposed, and they achieve great success on machine translation area and so on. They are then used in NER tasks and achieve significant improvement (Chiu and Nichols 2016; Ma and Hovy 2016; Peters et al. 2017). These structures can be use in different situations (Yang, Liang, and Zhang 2018). As the depth of Neural Network (NN) usually improve the final performance, more and more complicated method has been proposed in recent years. Transformer structure (Vaswani et al. 2017) and its derivative methods, like OpenAI GPT (Radford et al. 2018), BERT (Devlin et al. 2018), XLNet (Yang et al. 2019), make innovative attempt to NN structures.

Among these years, many method focus on base layer of NN structure, usually the embedding input layer, and then directly use it to do NLP tasks (Peters et al. 2018; Radford et al. 2018; Devlin et al. 2018; Yang et al. 2019). Though will it make improvement, it usually pays a long time to train the model. But in these way, it tell us that embedding input can directly infect the result of NLP tasks.

There exists a little difference between English NER tasks and Chinese NER tasks. In Chinese or other hieroglyphics language, character means a single word; and word is a character phrase which has length longer than one. In English or other letter base language, character means a single letter, and word is a composition of letters. English word is composed by characters, for which character level CNN can help improve NER tasks (Huang et al. 2015; Chiu and Nichols 2016; Ma and Hovy 2016; Peters et al. 2017; Yang, Liang, and Zhang 2018); but that can not be use in Chinese NER tasks, which is hieroglyphics. For this reason, Chinese NER tasks is usually done by word baseline or character baseline structure. Word baseline structure refer to using word segmentor to split sentence into word tokens and then use their word vector (Peng and Dredez 2015; Peng and Dredez 2016); while character structure simply treat each sentence into combination of single Chinese character, and then using character embedding to do NLP tasks (Zhang and Yang 2018; Gui et al. 2019). In these methods, it seems useful when using word embedding within character baseline structure, or the opposite.

Most of state-of-the-art NER methods uses Conditional

Chat: You/O raise/O me/O up/O
 Song: You/B-SONG raise/I-SONG me/I-SONG up/E-SONG

Chat: 韩/O 红/O 的/O 家/O 乡/O
 Song: 韩/O 红/O 的/O 家/B-SONG 乡/E-SONG

Figure 1: In certain NER situation, dictionary info is necessary, as cases showed in figure. With knowing the certain name is a song, we tend to denote the word as a song rather a common sentence.

Random Fields (CRF) (Lafferty, McCallum, and Pereira 2011) to decode the sequence labelling result. CRF can work even without any NN cells. Hand-writing trait can sometimes already achieve high performance (Finkel, Grenager, and Manning 2005; Okazaki 2007).

In some situations, word background knowledge, namely dictionary (the same meaning as lexicon and gazette), is necessary to do NER jobs. For example, in music service case, "You Raise Me Up" would be treated more likely as a chat information rather than a song, unless the model is given that knowledge (see in Figure 1). Most of the state-of-the-art methods using word embedding to complete these task. But it then gives two problems:

- Out Of Vocabulary (OOV) problem. As for **song** entity in music service, word embedding size will be too large; and sometimes will the length of song be too long to make word vector.
- Retrain problem. When the content of dictionary changes abundantly, the trained model would have poor performance doing the same jobs. Still use the **song** entity as an example, the dictionary would be changed monthly or even daily, thus we need to retrain our model synchronously.

Faced with this problem, we proposed a new conception, called Outer Dictionary Model (ODM), which means using the dictionary's outer trait, without using its specific content. For example, we use the word type "song", rather than a specific song name, to help model understand the outer information. In these way, word embedding is no longer needed for Chinese NER task. Experiment result show that in gazette depended-on task, ODM gives the best result among state-of-the-art method. And when the content of dictionary changed, the model can synchronously update its result without retraining.

Contributions

In summary, we make these contributions:

- We proposed a new conception: Outer Dictionary Model (ODM), which is used to update the content of dictionary without retraining the model.
- In order to realize ODM, we explored Tag Embedding LSTM (TE-LSTM), using the word type, rather the word itself, to improve the performance of NER tasks.

- Experiment result shows our model gives significant improvements on gazette depended-on tasks among state-of-the-art models.
- We release the music service dataset, which we use in our paper, for further scientific research.

Related Work

Success of BERT (Devlin et al. 2018) and XLNet (Yang et al. 2019) show that word embedding is important and useful for many upper NLP tasks. More useful information is there in the input vector, more efficiently the model would work. To a great degree, embedding layer decides the performance. Same conclusion can be made from a lot of NER models, as for character level message, word level message, position message, handwriting message and so on. Especially in some specific NER task, like music service, gazette is heavily depended on to make better performance.

Most of the recent models use gazette as word embedding input, or its string format, to give the model related message. Lattice LSTM (Zhang and Yang 2018) use the embedding as additional input to character baseline LSTM, which can give the model more sentence information. Lexivon Rethinking CNN (Gui et al. 2019), corparate the word embedding vector to correlated CNN layer, and the conflict word segment could be learned by rethinking. Stanford NER (Finkel, Grenager, and Manning 2005) can use the gazette information, as string format, in CRF model.

However, in some practical use, the content of the gazette will change greatly and constantly. In this way, most of the recent model need to be retrained after every abundantly change of gazette. To solve this problem, we need to construct a model which can still be used after such change. We then came out with the ODM, and use TE-LSTM to realize these model. As a result, with no more word embedding is needed, and model needed only to be trained once. What we need is the word tag information to help the model better understand user's intention.

Outer Dictionary LSTM

In this chapter, we illustrate the specific method we use to realize the ODM. Our framework is based on Tensorflow (Abadi et al. 2015). We use the character baseline model for Chinese NER task, inspired by the results of Lattice LSTM (Zhang and Yang 2018) and Lexicon Rethinking CNN (Gui et al. 2019). In order to better understand the model, we make a appointment that: In Chinese or other hieroglyphics language, character means a single word; and word is a character phrase which has length longer than one. In English or other letter base language, character means a single letter, and a word is a composition of letters; then a phrase is composited of a set of words. For Chinese NER jobs, only character embedding will we use, and no more word embedding is needed, for we hold the following opinions towards these jobs:

- Common characters in hieroglyphics language, can be exhaustive, especially for Chinese, because there are no more than 100,000 characters in simplified Chinese.




Figure 2: Illustration for tag embedding scheme. For dictionary ‘song’, there are two possible songs, the longer one is put in the first place (column 1). For dictionary ‘language’, only one possible result will be matched, however in this case, since we set the tag blank number to 2, we should add one more padding blank to fill the position, which is showed as column 4.

- Words in hieroglyphics language, will be uncountable, because there are still many new words or phrases are still created every day. Thus, OOV error can not be avoided in these case.

Thus, in Chinese NER jobs, we denote a sentence as a composition of many characters: $s = (c_1, c_2, \dots, c_n)$ as the base input to model.

Character-Base LSTM

We use character embedding lookup table to turn character id to vector:

$$a_i = e_c(c_i) \quad (1)$$

Usually a dropout layer is connected with the embedding output, which is proved useful in NER jobs (Ma and Hovy 2016). After that, bi-directional LSTM (Bi-LSTM), the most common structure used in NER tasks, is applied to learn the character connection within the sentence. We use the hidden vector for LSTM output, that is, for input: $x = (a_1, a_2, \dots, a_n)$, we get output: $h = (h_1, h_2, \dots, h_n)$, where h_i is the concatenation of forward (\vec{h}_i) and backward (\overleftarrow{h}_i) LSTM hidden vector:

$$h_i = [\vec{h}_i; \overleftarrow{h}_i] \quad (2)$$

Tag Embedding Model

As case show in Figure 1, we need to use dictionary for certain NER tasks. However, the constant variation of dictionary may cause constant retrain problem. Therefore, we may not use the specific word in each dictionary, instead, only the outer information will be used, which is the main idea in ODM. Here, we implement our ODM through Tag Embedding (TE), which uses the tag embedding of the dictionary. Cause we use LSTM structure to utilize tag embedding info, we called our network TE-LSTM.

Specifically, we do this by two step:

- a) Match sentence with the word in dictionary using certain outer model method.

- b) Turn match result into embedding information, used as the input of LSTM.

Match Policy. In this part, we need to match all the word in given dictionary occurred in current sentence. We impletement this by using Aho-Corasick Automation Algorithm (Aho and Corasick 1975). In summary, we complete a KMP (Knuth, Morris, and Pratt 1977) + Trie Tree (Briandais 1959) algorithm to accomplish this task. In methematical, given sentence $s = (c_1, c_2, \dots, c_n)$, and a dictionary d_i , which is composed of word set $D_i = \{w_1, w_2, \dots, w_V\}$. We denote the result of match policy as:

$$r_{d_i, j} = [(f_1, b_1), (f_2, b_2), \dots, (f_k, b_k)] \quad (3)$$

Here, f_i and b_i denote the front and back position of each match word. Let W_{f_i, b_i} represent the substring of sentence s with the rank $[f_i, b_i]$, then each (f_i, b_i) tuple forms a word matched in d_i , which is uncertain. Cause there will be conflict intervals after AC algorithm is performed, we need to select the meaningful intervals, the footnote j thus means that there will be many valid interval arrays. To format the input, we make the following policy to select our valid interval arrays:

- We choose certain number of valid interval arrays, which is called **tag blank number**, denoted as w . If there is not enough candidate interval arrays, the padding interval arrays will be use, as showed in Figure 2.
- We choose the interval arrays which cover the most characters in sentence (words for English), and have no conflict intervals inside itself. And the more characters the interval array has, the prior it will be in embedding position.

Tag Embedding Scheme. After match policy is fulfilled, we need to turn that result into vector so that it can be understood by model. Cause the result of match policy is denoted as position, we can simply use it to get a new sequence form from original sentence. With dictionary d_i and a matched word position rank range $[f_i, b_i]$, we then apply tag scheme for these sequence: turn the match word to correspond tag as shown in Figure 2, the unmatched part is turn to tag **O**.

Here, we choose **IOBES** scheme for it is proved better than IOB1 and IOB2 tag scheme in result by previous works (Chiu and Nichols 2016; Ma and Hovy 2016). Yet we need to emphasis that: the tag of dictionary here need not to be the same with the result tag species. As an illustration, to extract **name** entity, we can use dictionary **first name** and dictionary **last name** to match the sentence.

As related before, we choose **tag blank number**, w , of valid interval arrays and perform the tag scheme. We do the tag scheme in this way cause we think the position is important for model to understand, to fix the certain tag result in certain position and to fix the better result on the certain position. Of course, w could be variable for different dictionary, but that needs a bit more efforts and seems low performance increase.

With the tag embedding sequence produced, denoting each tag sequence as: $s_t = (t_1, t_2, \dots, t_n)$, we turn the result to vector using:

Table 1: Statistics of Sogou MusicNER dataset.

Count	Sentences	Tokens	Entities
Train	7,177	55,613	8,585
Dev	897	6,858	1,057
Test	897	6,775	1,047

$$g_i = e_t(t_i) \quad (4)$$

where e_t is the tag embedding lookup table. We use random generated number to produce this lookup table. Then the char embedding output a_i and tag embedding output g_i is concatenated together:

$$x_i = (a_i; g_i) \quad (5)$$

The concat input is then fed into the Bi-LSTM layer.

Loss and Training

CRF layer is applied on the top, same with many previous works and proved to be useful (Collobert et al. 2011; Chiu and Nichols 2016; Ma and Hovy 2016; Yang, Liang, and Zhang 2018; Zhang and Yang 2018; Gui et al. 2019). Denote y_j as a possible label sequence for sentence s_i and Y as the total set of all possible y_j , then the probability of y_j is:

$$p(y_j|s_i) = softmax(\sum_i W_{c_i} * h_i + B_{c_i})_j \quad (6)$$

W_{c_i}, B_{c_i} is respectively the emission matrix and transformation matrix correlate to h_i , and j is the rank for y_j in all possible label sequence set Y . While training, we take the L_2 regularization for all parameters into account together with CRF loss. With batch number N and corresponding gold set (s_i, y_i) , the final loss can be computed as:

$$L = \sum_{i=1}^N \log(p(y_i|s_i)) + \frac{\lambda}{2} \|\theta\|^2 \quad (7)$$

λ is the L_2 hyper parameter, and θ stands for all the training parameters. At decoding step, we use the Viterbi algorithm (Viterbi 1967) to decode result, finding the label sequence with the highest score:

$$y^* = \arg \max_{y_i \in Y} p(y_i|s_i) \quad (8)$$

Experiments

Settings

Here displays the experiment settings within our work.

Dataset. For Chinese NER task, We explore **MSRA** (Levow, 2006), **Weibo NER** (Peng and Dredze, 2015) and **ResumeNER** (Zhang and Yang, 2018). On music domain, We use the music domain dataset obtained on China Conference on Knowledge Graph and Semantic Computing (CCKS) 2018 music dataset. Cause we can only get the training dataset, we split that file into three part with portion 8:1:1 as train set, dev set and test set. Call this dataset as

Table 2: Hyperparameters

Layer	Hyper-parameters	Value
Char-layer	embeddding size	50
Tag-layer	embeddding size tag blank number	10 [1, 3]
LSTM	state size number of layers	200 1
Dropout	dropout rate	[0.0, 0.5]
	batch size	[1, 10]
	initial learning rate	[0.01, 0.03]
	decay rate	0.05
	momentum	0.9
	gradient clipping	5.0
	L2 λ	1e-8

CCKS dataset. Another music domain dataset is annotated by ourselves, and the tags defined is richer than CCKS. The statistics information of this dataset is listed in Table 1. We call it **Sogou MusicNER** dataset. For English NER task, we report the result on **CoNLL** 2003 shared English NER (Sang and Meulder, 2003).

Data Preprocessing. In our paper, all input file is turned to a certain jsonalized format, which we call standard NER format. For example, **Peter/B-PER Blackburn/E-PER** is turned to jsonalized string as **{text: Peter Blackburn, slot: [0, 15, PER]}**. The numbers stand for the start position and end position in the original sentence. We do it this way since we can get the original input sentence without splitting words, and turn it into all other tag scheme (mainly IOB1, IOB2, IOBES) easily. Furthermore, we can easily statistics the sentence number and entity numbers in this format. On training, we turn the standard NER format into the tag scheme we appointed. In this way, take the CoNLL 2003 dataset as example, it will first be transformed into standard format, and turn to IOBES tag scheme when training. In truth, this transformation doesn't change the content of dataset at all, but make it easier to process different format of input file, and allow us to get the original input sentence.

Character Embedding. In order to compare with Lattice LSTM (Zhang and Yang 2018) and Lexicon Rethinking CNN (Gui et al. 2019), we use the word vector provided in their papers (these two paper use the same character embedding and word embedding). There are character embedding and word embedding, we use the latter one as character embedding.

Tag Embedding. Given tag embedding length l_t as hyper parameter, we use uniform random policy to generate the tag embedding lookup table.

Word Embedding. For Lattice LSTM and Lexicon Rethinking CNN, they use the same word embedding file, which can not incorporate the word of dictionary directly. For Stanford NER (Finkel, Grenager, and Manning 2005) model and ODM, we use the dictionary file, which in true is a list of word name. For the same dataset, the dictionary they used keep the same. We make up the dictionary according to

Table 3: Main Results on MSRA.

Model	Precision	Recall	F1
La-LSTM	93.57%	92.79%	93.18%
LR-CNN	94.50%	92.93%	93.71%
C-LSTM	92.49%	89.87%	91.16%
ST-NER(*)	—	—	—
TE-LSTM(*)	—	—	—

Table 4: Main Results on Weibo NER.

Model	NE	NM	Overall
La-LSTM	53.04%	62.25%	58.79%
LR-CNN	57.14%	66.67%	59.92%
C-LSTM	51.03%	47.58%	49.25%
ST-NER	46.69%	57.32%	52.04%
TE-LSTM	48.78%	71.31%	60.10%

the follow principles:

- For exhaustive tag, we list all the items of that tag as a dictionary. For example, entity **Country** and **Project**.
- For tag which is limited but updated constantly, we list the current item of that tag as a dictionary. For example, entity **Singer** and **Song**.
- For tag that is unlimited but has common prefix or suffix, we list all the common prefix or suffix for it as a dictionary. For example, entity **Organization** usually has a common suffix, such as: inc., company, league.
- For unlimited and no rule tag, we don't use dictionary for it.
- We build the content of tag mainly through knowledge graph we collected, some of the dictionary are enriched with the dataset.

Handcrafted Features. Handcrafted features is only used in Stanford NER model. Main features include previous word, next words, NGrams and so on.

Compared Models

For compared purposed, we impletemment these models below:

Lattice LSTM. The author of Lattice LSTM (Zhang and Yang 2018) has generously provided his code on website. We directly use his code and settings, and run on experiment dataset. We denote it as La-LSTM.

Lexicon Rethinking CNN. Same with Lattice LSTM, we use the code provided by the author (Gui et al. 2019) and run on our dataset. We denote it as LR-CNN.

Character LSTM. We basically impletemment the character-level LSTM as the first model, no any other properties (like bichar, softword, position etc.) used. We use the word embedding in Lattice LSTM as character embedding here for it gives better performance. We abbreviate it as C-LSTM.

Table 5: Main Results on ResumeNER.

Model	Precision	Recall	F1
La-LSTM	94.81%	94.11%	94.46%
LR-CNN	95.37%	94.84%	95.11%
C-LSTM	94.31%	94.27%	94.29%
ST-NER(*)	—	—	—
TE-LSTM	95.31%	94.90%	95.11%

Table 6: Main Results on CCKS.

Model	Precision	Recall	F1
La-LSTM	87.34%	75.03%	80.72%
LR-CNN	88.17%	76.98%	82.2%
C-LSTM	75.66%	71.12%	73.32%
ST-NER	91.00%	76.15%	82.92%
TE-LSTM(*)	84.28%	84.51%	84.40%

Stanford NER model. Stanford NER tool (Finkel, Grenager, and Manning 2005) is used in our work to do comparison, for it is convenient to add handcrafted features into model, and use dictionary (called gazette in its term) directly, which can be compared to our ODM intuitively. For short, denote it as ST-NER.

Tag Embedding LSTM. This is the model which we proposed in this paper. The character embedding is the same with C-LSTM, and the dictionary used is the same with ST-NER model for comparison. We denote it as TE-LSTM.

Hyper-parameters and Strategies

Shown in Table 2, we choose the hyper-parameters referring to BLSTM-CNNs-CRF structure (Ma and Hovy 2016).

- **Fine-tuning.** We apply fine-tuning on all the embedding vector, which is proved useful by previous works (Collobert et al. 2011; Peng and Dredze 2015; Ma and Hovy 2016).
- **Dropout.** We choose the dropout rate between 0.0 and 0.5, for different dataset, the best result will occur at different rate.
- **SGD policy.** We use stochastic gradient descent (SGD) policy to train model, with momentum set as 0.9.

Main Results

Compared to previous work, we report the best result of our experiment here.

MSRA Dataset. There is no dev set on this dataset. We split the training file and report results on the test set. Table 3 shows the experiment results. On this dataset, dictionary for **Chinese Last Name**, **Location**, **Organization Suffix** is used in both ST-NER and TE-LSTM.

Weibo NER Dataset. As comparison to previous works, shown in Table 4, we report the F1-score for named entities (NE), nominal entities (NM) and overall entities. The dictionaries we use here are the set of **GPE_NAM**, **ORG_NOM**, **PER_NOM**, **LOC_NOM** and **Chinese Last Name**.

Table 7: Main Results on Sogou MusicNER.

Model	Precision	Recall	F1
La-LSTM	86.24%	84.43%	85.33%
LR-CNN	85.99%	85.00%	85.49%
C-LSTM	84.11%	82.50%	83.30%
ST-NER	88.00%	85.48%	86.72%
TE-LSTM	93.09%	92.82%	92.96%

Table 8: Main Results on CoNLL 2003.

Model	Precision	Recall	F1
Ma and Hovy, 2016	91.35%	91.06%	91.21%
Yang et al, 2018	—	—	91.35%
Devlin et al., 2018	—	—	92.80%
C-LSTM	87.32%	85.25%	86.27%
ST-NER(*)	—	—	—
TE-LSTM	96.63%	96.67%	96.65%

ResumeNER Dataset. We use the same train, dev and test file as La-LSTM and LR-CNN. Dictionary for **Title Suffix, Organization Suffix, Project, China Peoples** is used here on ST-NER and TE-LSTM. Results on this dataset also prove the efficiency of ODM.

CCKS / Sogou MusicNER Dataset. Table 6 and 7 shows the result of music domain dataset. The mainly dictionary used here is **Singer** and **Song**. Results show that our model report the best result on both dataset for F1 score. With dictionary information given, we can see that ST-NER shows better performance than La-LSTM and LR-CNN. That, to some extent, cause by the lack of music domain word information in La-LSTM and LR-CNN. Compared to ST-NER, our model gives **1.48%** percent promotion of F1 score on **CCKS** dataset, and **6.24%** percent promotion of F1 score on **MusicNER** dataset. This result proves that TE-LSTM is useful to utilize the information of dictionary, though without specially making word embedding vector for each word in lexicon.

CoNLL Dataset. On this dataset, we list some of the effective model results reported by previous works. And we use dictionary **English Last Name, Location, Organization, MISC** here. We make a suppose here that we can get all the name of location, organization and miscellaneous in English. With this prerequisite, we could see significant improvement on this dataset, shown in Table 8. Though the result is amazing, **we need to emphasis here that, it is hard and burdensome to collect all the entities in these dictionaries in reality.** For simplicity, we use the set of entities extracted from the dataset here. So the result is a powerful proof to suport ODM in dictionary message using, but not usually pratcal in fact.

Analysis

Conflict Solving. Though given dictionary information, there exists many conflict items, labeled with different tag, to challenge the model. For example, **French Open**, The word **French** will be given both the **S-MISC** tag and **B-ORG** tag

Before	After
播/O 放/O 三/O 加/O 四/O	播/O 放/O 三/B-SONG 加/I-SONG 四/E-SONG
播/O 放/O 一/O 杯/O	播/O 放/O 一/B-SONG 杯/E-SONG
开/O 心/O 就/O 好/O	开/B-SONG 心/I-SONG 就/I-SONG 好/E-SONG
忆/O 梦/O 琉/O 瑞/O	忆/B-SONG 梦/I-SONG 琉/I-SONG 瑞/E-SONG

Figure 3: After adding words into dictionary, the new entities can be recognized by the model.

Before	After
播/O 放/O 青/B-SONG 云/I-SONG 志/E-SONG	播/O 放/O 青/O 云/O 志/O
播/O 放/O 海/B-SONG 贼/I-SONG 王/E-SONG	播/O 放/O 海/O 贼/O 王/O
天/B-SONG 气/I-SONG 真/I-SONG 好/E-SONG	天/O 气/O 真/O 好/O
王/B-SONG 者/I-SONG 荣/I-SONG 耀/E-SONG	王/O 者/O 荣/O 耀/O

Figure 4: After delete existing words in dictionary, the corresponding entities can be ignored by the model.

here, according to the message in the dictionary. As results shown in Table 8, TE-LSTM can solve the conflict cases very well by using all the message in dictionary together with the character embedding knowledge.

Helpful to Improve Recall. All the experiment results on different dataset get the highest recall score, proving that ODM is a powerful tool to get higher recall, mainly because we better utilize the message in dictionary.

Without Retraining. We show it here that TE-LSTM need not to retrain the model when dictionary is greatly changed. The cost of retraining a model is changed to be the cost of maintaining the dictionaries, which is more convenient and can be better understood and modified by human.

Here, we use entity **Song**, in CCKS dataset, as example. Figure 3 shows the difference after adding corresponding words as song, the model can recognize this entities with the new given knowledge. Figure 4 shows the change after deleting redundant words in dictionary, the model will ignore these words. But there are also cases which will not change or partly change after deleting the words, shown in Figure 5, these cases exist because there exist certain sentence phrase to discriminate the word as a song, or part of the word is still in the dictionary.

Conclusion

We proposed a new model to better explored the information of dictionary without make embedding for each word, which helps us need not to retrain a model after the content of dictionary is greatly changed. And the result shows that our model reach higher performance on dictionary-depended task, which certificated that our model is a powerful structure to utilize the information of dictionary. And with ODM, the cost of training a new model is replaced by protecting the dictionaries, which is more understandable to human beings.

We have several dicrections to move ahead. For the structure itself, ODM can also be simply implemented using the Lattice LSTM structure, which also, is a powerful way to use lexicon message. Furthermore, the information of dictionary can be reached on website or knowledge graph, which can be more convinient and promising. On this way, the model need to understand and consult the needed information by

Before	After
播/O 放/O 西/B-SONG 游/I-SONG 记/E-SONG	播/O 放/O 西/B-SONG 游/I-SONG 记/E-SONG
播/O 放/O 红/B-SONG 楼/I-SONG 梦/E-SONG	播/O 放/O 红/B-SONG 楼/I-SONG 梦/E-SONG
播/O 放/O 王/B-SONG 者/I-SONG 荣/I-SONG 耀/E-SONG	播/O 放/O 王/B-SONG 者/I-SONG 荣/I-SONG 耀/E-SONG
播/O 放/O 速/B-SONG 度/I-SONG 与/I-SONG 激/I-SONG 情/E-SONG	播/O 放/O 速/O 度/O 与/O 激/B-SONG 情/E-SONG

Figure 5: After delete existing words in dictionary, some of the the result will not change.

itself. Our model is just the start of combining outer knowledge into neural network model.

Acknowledgments

Especially grateful to Can Cui (Chengdu, Operational Platform Department, Sogou Inc.) for cooperation on the Sogou MusicNER dataset, to Jindou Wu (Hangzhou, AI Research Department, Sogou Inc.) for advice on data processing of CCKS 2018 music dataset and handcrafted features on StanfordNER tools.

References

Krizhevsky, A.; Sutskever, I.; and Geoffrey E. H. 2012. ImageNet Classification with Deep Convolutional Neural Networks. In *Proceedings of Advances in Neural Information Processing Systems 25 (NIPS 2012)*.

Kim, Y. 2014. Convolutional Neural Networks for Sentence Classification. arXiv:1408.5882.

Sutskever, I.; Vinyals, O.; and Le, Q.V. 2014. Sequence to Sequence Learning with Neural Networks. In *Proceedings of Advances in Neural Information Processing Systems 27 (NIPS 2014)*.

Sak, H.; Senior, A.; and Beaufays, F. 2014. Long Short-Term Memory Based Recurrent Neural Network Architectures for Large Vocabulary Speech Recognition. arXiv:1402.1128.

Collobert, R.; Weston, J.; Bottou, L.; Karlen, M.; Kavukcuoglu, K.; and Kuksa, P. 2011. Natural Language Processing (Almost) from Scratch. *Journal of Machine Learning Research* 12 (2011) 2493-2537.

Santos, C. N.; Xiang, B.; and Zhou, B. 2015. Classifying Relations by Ranking with Convolutional Neural Networks. arXiv:1504.06580.

Strubell, E.; Verga, P.; Belanger, D.; and McCallum, A. 2017. Fast and Accurate Entity Recognition with Iterated Dilated Convolutions. arXiv:1702.02098.

Peters, M. E.; Ammar, W.; Bhagavatula, C.; and Power, R. 2017. Semi-supervised sequence tagging with bidirectional language models. arXiv:1705.00108.

Peters, M. E.; Neumann, M.; Iyyer, M.; Gardner, M.; Clark, C.; Lee, K.; and Zettlemoyer, L. 2018. Deep contextualized word representations. arXiv:1802.05365.

Ma, X.; and Hovy, E. 2016. End-to-end Sequence Labeling via Bi-directional LSTM-CNNs-CRF. arXiv:1603.01354.

Yang, J.; Liang, S.; and Zhang, Y. 2018. Design Challenges and Misconceptions in Neural Sequence Labeling. arXiv:1806.04470.

Vaswani, A.; Shazeer, N.; Parmar, N.; Uszkoreit, J.; Jones, L.; Gomez, A. N.; Kaiser, L.; and Polosukhin, I. 2017. Attention Is All You Need. arXiv:1706.03762.

Radford, A.; Narasimhan, K.; Salimans, T.; and Sutskever, I. 2018. Improving Language Understanding by Generative Pre-Training. Technical report, Open AI.

Devlin, J.; Chang, M.; Lee, K.; and Toutanova, K. 2018. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. arXiv:1810.04805.

Yang, Z.; Dai, Z.; Yang, Y.; Carbonell, J.; Salakhutdinov, R.; and Le, Q. V. 2019. XLNet: Generalized Autoregressive Pre-training for Language Understanding. arXiv:1906.08237.

Sang, E. F.; and Meulder, F. D. 2003. Introduction to the CoNLL-2003 Shared Task: Language-Independent Named Entity Recognition. arXiv:cs/0306050.

Chiu, J. P.C.; and Nichols, E. 2016. Named Entity Recognition with Bidirectional LSTM-CNNs. *Transactions of the Association for Computational Linguistics*, Volume 4, 2016, p.357-370.

Huang, Z.; Xu, W.; and Yu, K. 2015. Bidirectional LSTM-CRF Models for Sequence Tagging. arXiv:1508.01991.

Peng, N.; and Dredze, M. 2015. Named Entity Recognition for Chinese Social Media with Jointly Trained Embeddings. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.

Peng, N.; and Dredze, M. 2016. Improving Named Entity Recognition for Chinese Social Media with Word Segmentation Representation Learning. arXiv:1603.00786.

He, H.; and Sun, X. 2016. F-Score Driven Max Margin Neural Network for Named Entity Recognition in Chinese Social Media. arXiv:1611.04234.

Chen, Q.; Zhuo, Z.; and Wang, W. 2019. BERT for Joint Intent Classification and Slot Filling. arXiv:1902.10909.

Zhang, Y.; and Yang, J. 2018. Chinese NER Using Lattice LSTM. arXiv:1805.02023.

Gui, T.; Ma, R.; Zhang, Q.; Zhao, L.; Jiang, Y.; and Huang, Y. 2019. CNN-Based Chinese NER with Lexicon Rethinking. In *Proceedings of the International Joint Conference on Artificial Intelligence 2019 (IJCAI 2019)*.

Lafferty, J.; McCallum, A.; and Pereira, F. 2001. Conditional Random Fields: Probabilistic Models for Segmenting and Labeling Sequence Data. In *Proceedings of the 18th International Conference on Machine Learning 2001 (ICML 2001)*, pages 282-289.

Socher, R.; Manning, C. D.; and Andrew Y. Ng. 2010. Learning Continuous Phrase Representations and Syntactic Parsing with Recursive Neural Networks. In *Proceedings of the NIPS-2010 Deep Learning and Unsupervised Feature Learning Workshop*.

Finkel, J. R.; Grenager, T.; and Manning, C. 2005. Incorporating non-local information into information extraction systems by Gibbs sampling. In *Proceedings of the 43rd Annual Meeting of the Association for Computational Linguistics (ACL 2005)*, pp. 363-370.

- Okazaki, N. 2007. CRFsuite: a fast implementation of Conditional Random Fields (CRFs). URL <http://www.chokkan.org/software/crfsuite>.
- Mikolov, T.; Chen, K.; Corrado, G.; and Dean, J. 2013. Efficient Estimation of Word Representations in Vector Space. In Proceedings of Workshop at ICLR.
- Mikolov, T.; Sutskever, I.; Chen, K.; Corrado, G.; and Dean, J. 2013. Distributed Representations of Words and Phrases and their Compositionality. In Proceedings of NIPS.
- Mikolov, T.; Yih, W.; and Zweig, G. 2013. Linguistic Regularities in Continuous Space Word Representations. In Proceedings of NAACL HLT.
- Pennington, J.; Socher, R.; and Manning, C.D. 2014. GloVe: Global Vectors for Word Representation. In Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP), pages 1532-1543.
- Mikolov, T.; Grave, E.; Bojanowski, P.; Puhersch, C.; and Joulin, A. 2017. Advances in Pre-Training Distributed Word Representations. arXiv:1712.09405.
- Aho, A. V.; and Corasick, M. J. 1975. Efficient string matching: An aid to bibliographic search. Communications of the ACM. June 1975, 18 (6): 333-340.
- Knuth, D.; Morris, J. H.; and Pratt, V. 1977. Fast pattern matching in strings. SIAM Journal on Computing. 6 (2): 323-350.
- Briandais, D. L. R. 1959. File searching using variable length keys. Proc. Western J. Computer Conf. pp. 295-298.
- Viterbi AJ. 1967. Error bounds for convolutional codes and an asymptotically optimum decoding algorithm. IEEE Transactions on Information Theory. 13 (2): 260-269. doi:10.1109/TIT.1967.1054010.
- Liu, K.; Guo, S.; Liu, S.; Zhang, Y. 2018. China Conference on Knowledge Graph and Semantic Computing, 2018. https://biendata.com/competition/CCKS2018_2/data/.
- Martn Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S. Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow, Andrew Harp, Geoffrey Irving, Michael Isard, Rafal Jozefowicz, Yangqing Jia, Lukasz Kaiser, Manjunath Kudlur, Josh Levenberg, Dan Man, Mike Schuster, Rajat Monga, Sherry Moore, Derek Murray, Chris Olah, Jonathon Shlens, Benoit Steiner, Ilya Sutskever, Kunal Talwar, Paul Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda Vi-gas, Oriol Vinyals, Pete Warden, Martin Wattenberg, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. 2015. TensorFlow: Large-scale machine learning on heterogeneous systems. <https://www.tensorflow.org>.