

# Operating Systems and Concurrency

Concurrency 6 + Revision  
COMP2007

Dan Marsden  
(Geert De Maere)  
{ Geert.DeMaere,Dan.Marsden } @Nottingham.ac.uk

University Of Nottingham  
United Kingdom

2023

# Goals

Today

- Writers before readers.
- Beyond locks - alternative approaches to concurrency.

# The Readers – Writers Problem (Last Time)

## Solution 2: Readers First

- We implemented as solution to readers-writers that allowed concurrent reading when safe to do so.
- Recall the **room with a light switch analogy** - writers only enter a darkened room, readers happy to mix together.
- Unfortunately readers can overwhelm writers, and the **writers can starve**.
- Today - try to reverse the situation and **favour the writers**.

# The Readers – Writers Problem

## Solution 3: Writers First

Solution 3 gives priority to **writers** and uses:

- Integers `iReadCount` and `iWriteCount` to keep track of the number of readers/writers.
- Mutexes `sRead` and `sWrite` to synchronise the **reader's/writer's critical section**.
- Semaphore `sReadTry` to stop readers when there is a **writer waiting**.
- Semaphore `sResource` to **synchronise** the resource for **reading/writing**.

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
```

```
{  
    while(1)  
    {  
        sem_wait(&sReadTry);  
        sem_wait(&sRead);  
        iReadCount++;  
        if(iReadCount == 1)  
            sem_wait(&sResource);  
        sem_post(&sRead);  
        sem_post(&sReadTry);
```

```
        printf("reading\n");
```

```
        sem_wait(&sRead);  
        iReadCount--;  
        if(iReadCount == 0)  
            sem_post(&sResource);  
        sem_post(&sRead);
```

```
    }  
}
```

```
void * writer(void * arg)
```

```
{  
    while(1)  
    {  
        sem_wait(&sWrite);  
        iWriteCount++;  
        if(iWriteCount == 1)  
            sem_wait(&sReadTry);  
        sem_post(&sWrite);
```

```
        sem_wait(&sResource);  
        printf("writing\n");  
        sem_post(&sResource);
```

```
        sem_wait(&sWrite);  
        iWriteCount--;  
        if(iWriteCount == 0)  
            sem_post(&sReadTry);  
        sem_post(&sWrite);
```

```
    }  
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry); // 1=>0
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead); // 1=>0
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```



# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++; // 0=>1
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource); // 1=>0
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead); // 0=>1
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry); // 0=>1

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite); // 1=>0
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++; // 0=>1
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry); // 1=>0
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite); // 0=>1

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```



# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource); // 1=>0
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource); // 0=>-1 (sleep)
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead); // 1=>0
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--; // 1=>0
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource); // -1=>0
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource); // wakeup
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead); // 0=>1
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry); // 0=>-1
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry); // 1=>0
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource); // (woken up)
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```



# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource); // 0=>1

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite); // 1=>0
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--; // 1=>0
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry); // wakeup
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```

```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry); // -1=>0
        sem_post(&sWrite);
    }
}
```

# The Readers – Writers Problem

## Solution 3: Writers First

```
void * reader(void * arg)
{
    while(1)
    {
        sem_wait(&sReadTry);
        sem_wait(&sRead);
        iReadCount++;
        if(iReadCount == 1)
            sem_wait(&sResource);
        sem_post(&sRead);
        sem_post(&sReadTry);

        printf("reading\n");

        sem_wait(&sRead);
        iReadCount--;
        if(iReadCount == 0)
            sem_post(&sResource);
        sem_post(&sRead);
    }
}
```


```
void * writer(void * arg)
{
    while(1)
    {
        sem_wait(&sWrite);
        iWriteCount++;
        if(iWriteCount == 1)
            sem_wait(&sReadTry);
        sem_post(&sWrite);

        sem_wait(&sResource);
        printf("writing\n");
        sem_post(&sResource);

        sem_wait(&sWrite);
        iWriteCount--;
        if(iWriteCount == 0)
            sem_post(&sReadTry);
        sem_post(&sWrite); // 0=>1
    }
}
```


# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions



# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.



# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.



# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.



# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.



# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions




### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The Readers – Writers Problem

## Solution 3: Writers First - Intuitions



### Constraints:

- Everyone happy to go into a room with the light off.
- Readers and writers don't like each other.
- Readers happy to enter a room with a green light on, but not a yellow one.
- Writers happy to enter a room with a yellow light on, but not a green one.
- Only readers are allowed to use the bottom exit.

# The trouble with locks

Locking style coordination of threads, such as with mutexes and semaphores has multiple problems. For example:

- **Deadlocks.**
- **Starvation.**
- **Priority inversion.**

# The trouble with locks

Locking style coordination of threads, such as with mutexes and semaphores has multiple problems. For example:

- **Deadlocks.**
- **Starvation.**
- **Priority inversion.**
- Lack of **compositionality** - you cannot compose small correct concurrent programs to form large correct concurrent programs.

# The trouble with locks

Locking style coordination of threads, such as with mutexes and semaphores has multiple problems. For example:

- **Deadlocks.**
- **Starvation.**
- **Priority inversion.**
- Lack of **compositionality** - you cannot compose small correct concurrent programs to form large correct concurrent programs.
- We could try to grab locks and back-off if we cannot acquire them all - we risk another problem - **livelock**.

# The trouble with locks

Locking style coordination of threads, such as with mutexes and semaphores has multiple problems. For example:

- **Deadlocks.**
- **Starvation.**
- **Priority inversion.**
- Lack of **compositionality** - you cannot compose small correct concurrent programs to form large correct concurrent programs.
- We could try to grab locks and back-off if we cannot acquire them all - we risk another problem - **livelock**.
- **Access to shared state is implicit** - it can be hard to tell who's modifying what, and if suitable locks are held at the time.
- **Lock convoying** - threads end up queuing up behind a thread holding a lock - linearizes behaviour and can take a long time to clear.

# Alternative Concurrency Approaches

We should not just be satisfied with such a status-quo. Therefore, we shall look at two alternatives:



# Alternative Concurrency Approaches

We should not just be satisfied with such a status-quo. Therefore, we shall look at two alternatives:

- 1 Message passing - **synchronous** or **asynchronous**.

# Alternative Concurrency Approaches

We should not just be satisfied with such a status-quo. Therefore, we shall look at two alternatives:

- ① Message passing - **synchronous** or **asynchronous**.
- ② **Transactional memory**.

# Message Passing

## Synchronous Message Passing

- We avoid sharing memory, and instead have have channels  $c, d, \dots$
- There are two operations on channel  $c$ :
  - 1  $c(x)$  sends message  $x$  over the channel.
  - 2  $\bar{c}(x)$  receives a value over the channel into  $x$ .
- Communication is **synchronous** - a send must wait for a corresponding receive and vice-versa. **Think phone calls.**

# Message Passing

## Synchronous Message Passing

- We avoid sharing memory, and instead have have channels  $c, d, \dots$
- There are two operations on channel  $c$ :
  - 1  $c(x)$  sends message  $x$  over the channel.
  - 2  $\bar{c}(x)$  receives a value over the channel into  $x$ .
- Communication is **synchronous** - a send must wait for a corresponding receive and vice-versa. **Think phone calls.**

**Thread 1**

$c(data)$

**Thread 2**

$\dots$

# Message Passing

## Synchronous Message Passing

- We avoid sharing memory, and instead have have channels  $c, d, \dots$
- There are two operations on channel  $c$ :
  - 1  $c(x)$  sends message  $x$  over the channel.
  - 2  $\bar{c}(x)$  receives a value over the channel into  $x$ .
- Communication is **synchronous** - a send must wait for a corresponding receive and vice-versa. **Think phone calls.**

**Thread 1**

$c(data)$

**blocked**

**Thread 2**

$\dots$

$\dots$

# Message Passing

## Synchronous Message Passing

- We avoid sharing memory, and instead have have channels  $c, d, \dots$
- There are two operations on channel  $c$ :
  - 1  $c(x)$  sends message  $x$  over the channel.
  - 2  $\bar{c}(x)$  receives a value over the channel into  $x$ .
- Communication is **synchronous** - a send must wait for a corresponding receive and vice-versa. **Think phone calls.**

### Thread 1

$c(data)$

**blocked**

**blocked**

### Thread 2

$\dots$

$\dots$

$\bar{c}(x)$

# Message Passing

## Synchronous Message Passing

- We avoid sharing memory, and instead have have channels  $c, d, \dots$
- There are two operations on channel  $c$ :
  - 1  $c(x)$  sends message  $x$  over the channel.
  - 2  $\bar{c}(x)$  receives a value over the channel into  $x$ .
- Communication is **synchronous** - a send must wait for a corresponding receive and vice-versa. **Think phone calls.**

### Thread 1

$c(data)$

**blocked**

**blocked**

...

### Thread 2

...

...

$\bar{c}(x)$

... ( $x = data$ )

# Message Passing

## Synchronous Message Passing

Pros and cons of synchronous message passing:

- Flow of data is **explicit** - no exposure to race conditions and other difficult debugging.
- Synchronizing senders and receivers can slow performance.



# Message Passing

## Synchronous Message Passing

Pros and cons of synchronous message passing:

- Flow of data is **explicit** - no exposure to race conditions and other difficult debugging.
- Synchronizing senders and receivers can slow performance.
- Can implement mutexes and semaphores using synchronous message passing - **deadlocks, starvation etc. all still possible.**

# Message Passing

## Asynchronous Message Passing

In an attempt to mitigate the issues of synchronous message passing, **senders do not block** waiting for an available receiver. **Think sending an email.** Often use what is known as an **Actor** based model.

---

<sup>1</sup>Example adapted from notes of Ian Stark  
©University of Nottingham

# Message Passing

## Asynchronous Message Passing

In an attempt to mitigate the issues of synchronous message passing, **senders do not block** waiting for an available receiver. **Think sending an email.**

Often use what is known as an **Actor** based model.

For example, to specify a simple counter <sup>1</sup>:

```
class Counter extends Actor {  
  var counter = 0  
  
  def receive = {  
    case Zero => counter = 0  
    case Inc => counter = counter + 1  
  }  
}
```

---

<sup>1</sup>Example adapted from notes of Ian Stark

# Message Passing

## Asynchronous Message Passing

In an attempt to mitigate the issues of synchronous message passing, **senders do not block** waiting for an available receiver. **Think sending an email.**

Often use what is known as an **Actor** based model.

For example, to specify a simple counter <sup>1</sup>:

```
class Counter extends Actor {  
  var counter = 0  
  
  def receive = {  
    case Zero => counter = 0  
    case Inc => counter = counter + 1  
  }  
}
```

Then to increment a `Counter` object, you just send it a message:

```
mycounter ! Inc // Send Inc message - don't wait for receiver  
mycounter ! Inc // Send another - queued up until dealt with
```

---

<sup>1</sup>Example adapted from notes of Ian Stark

# Message Passing

## Asynchronous Message Passing

Pros and cons of synchronous message passing:

- As with the synchronous model, flow of data is **explicit** - less exposure to race conditions and other difficult debugging.
- Less **explicit** coupling between senders and receivers.
- *May* be less efficient than shared memory.

# Message Passing

## Asynchronous Message Passing

Pros and cons of synchronous message passing:

- As with the synchronous model, flow of data is **explicit** - less exposure to race conditions and other difficult debugging.
- Less **explicit** coupling between senders and receivers.
- *May* be less efficient than shared memory.
- Can simulate synchronous message passing.

# Message Passing

## Asynchronous Message Passing

Pros and cons of synchronous message passing:

- As with the synchronous model, flow of data is **explicit** - less exposure to race conditions and other difficult debugging.
- Less **explicit** coupling between senders and receivers.
- *May* be less efficient than shared memory.
- Can simulate synchronous message passing.
- Can implement mutexes using asynchronous message passing - **deadlocks, starvation etc. all still possible.**

# Transactional Memory

## A Database Analogy

Imagine I owe Geert £10.

- Inside the bank, our account balances might be stored in a database table:

Holder	Balance
Geert	10000000
Dan	15

- Transferring the money to Geert requires two steps:
  - 1 Deduct £10 from the Dan account.
  - 2 Add £10 to the Geert account.



# Transactional Memory

## A Database Analogy

### Requirements for the bank transfer

- We would like the transfer to be **atomic** - In particular it either completely succeeds or totally fails.
- If other (atomic) changes are being made to the database, we would like them to be **serializable** - as if they don't overlap in time.

# Transactional Memory

## Database Transactions

To satisfy our requirements, we wrap our changes in a **transaction**:

```
begin transaction;  
update accounts set balance = balance + 10 where holder = 'Geert';  
update accounts set balance = balance - 10 where holder = 'Dan';  
commit;
```

Either both updates take place, or neither.

# Transactional Memory

## Database Transactions

To satisfy our requirements, we wrap our changes in a **transaction**:

```
begin transaction;  
update accounts set balance = balance + 10 where holder = 'Geert';  
update accounts set balance = balance - 10 where holder = 'Dan';  
commit;
```

Either both updates take place, or neither.

### Rollback

Realistic transactions may be more complex, and can encounter reasons they cannot succeed. Instead of `commit` they explicitly call `rollback` to fail the whole transaction.

# Transactional Memory

## Transactions for thread coordination

The idea of transactional memory is to have the memory shared between threads behave transactionally, just like a database does.

```
do {  
    begin_transaction();  
    modify_shared_data();  
    commit();  
} while(!transaction_succeeds());
```

# Transactional Memory

## Transactions for thread coordination

The idea of transactional memory is to have the memory shared between threads behave transactionally, just like a database does.

```
do {  
    begin_transaction();  
    modify_shared_data();  
    commit();  
} while(!transaction_succeeds());
```

- No locks, and **no risk of deadlock**.

# Transactional Memory

## Transactions for thread coordination

The idea of transactional memory is to have the memory shared between threads behave transactionally, just like a database does.

```
do {  
    begin_transaction();  
    modify_shared_data();  
    commit();  
} while(!transaction_succeeds());
```

- No locks, and **no risk of deadlock**.
- A form of **livelock** still possible - as we back-off and try again after rollbacks.

# Transactional Memory

## Transactions for thread coordination

The idea of transactional memory is to have the memory shared between threads behave transactionally, just like a database does.

```
do {  
    begin_transaction();  
    modify_shared_data();  
    commit();  
} while(!transaction_succeeds());
```

- No locks, and **no risk of deadlock**.
- A form of **livelock** still possible - as we back-off and try again after rollbacks.
- **Starvation** still possible - smaller transactions may cause repeated rollbacks of longer ones.

# Thanks!

Change of lecturer back to Geert and a new topic on Wednesday!