

mlrFDA: an R toolbox for functional data analysis


Laura Beggel, Xudong Sun, Florian Pfisterer, Bernd Bischl

Ludwig-Maximilians-Universität München

Statistical Computing, 07/24/2017

mlr

- How does your code for experiments look like?



-> mlr: unified interface for machine learning algorithms



- Supported tasks: classification, clustering, regression, survival
- for performance evaluation, resampling,


preprocessing and

feature selection, hyperparameter tuning


Functional data

[1]

- Data is sampled over an ordered continuum
- Here: time



- Smoother representation allows for more data



[1]

3

CR/AEY2 | 07/24/2017


Psych.mcgill.ca/miso/fda/index

Psych.mcgill.ca/miso/fda/index, also regarding any disposal, exploitation, reproduction, editing, distribution, as well as in the event of applications for industrial property rights.

mlrFDA

Data handling

- mlr internally:
data frame with annotations



- NOW:
Functional features

mlrFDA


Data handling

```
df = data.frame(matrix(rnorm(100), nrow = 10),  
  "target" = as.factor(sample(1:2, 10, replace = TRUE)))  
str(df)
```


```
## 'data.frame':    10 obs. of  11 variables:  
## $ X1      : num  -0.5605 -0.2302 1.5587 0.0705 0.1293 ...  
## $ X2      : num  1.224 0.36 0.401 0.111 -0.556 ...  
## $ X3      : num  -1.068 -0.218 -1.026 -0.729 -0.625 ...  
## $ X4      : num  0.426 -0.295 0.895 0.878 0.822 ...  
## $ X5      : num  -0.695 -0.208 -1.265 2.169 1.208 ...  
## $ X6      : num  0.2533 -0.0285 -0.0429 1.3686 -0.2258 ...  
## $ X7      : num  0.38 -0.502 -0.333 -1.019 -1.072 ...  
## $ X8      : num  -0.491 -2.309 1.006 -0.709 -0.688 ...  
## $ X9      : num  0.00576 0.38528 -0.37066 0.64438 -0.22049 ...  
## $ X10     : num  0.994 0.548 0.239 -0.628 1.361 ...  
## $ target: Factor w/ 2 levels "1","2": 1 2 2 2 1 2 1 1 1 1
```

```
functionaldf = makeFunctionalData(df, fd.features = list("CO2" = 1:6, "NOX" = 8:10))  
str(functionaldf)
```

```
## 'data.frame':    10 obs. of  4 variables:  
## $ X7      : num  0.38 -0.502 -0.333 -1.019 -1.072 ...  
## $ target: Factor w/ 2 levels "1","2": 1 2 2 2 1 2 1 1 1 1  
## $ CO2     : num  [1:10, 1:6] -0.5605 -0.2302 1.5587 0.0705 0.1293 ...  
## ..- attr(*, "dimnames")=List of 2  
## .. ..$ : NULL  
## .. ..$ : chr  "X1" "X2" "X3" "X4" ...  
## $ NOX     : num  [1:10, 1:3] -0.491 -2.309 1.006 -0.709 -0.688 ...  
## ..- attr(*, "dimnames")=List of 2  
## .. ..$ : NULL  
## .. ..$ : chr  "X8" "X9" "X10"
```



Standard data frame



Functional data frame

mlrFDA

Task abstraction

- Supp

orted

```
tsk = makeClassifTask(data = functionaldf, target = "target")  
print(tsk)
```

```
## Supervised task: functionaldf  
## Type: classif  
## Target: target  
## Observations: 10  
## Features:  
##      numerics      factors      ordered functionals  
##           1           0           0           2  
## Missings: FALSE  
## Has weights: FALSE  
## Has blocking: FALSE  
## Classes: 2  
## 1 2  
## 6 4  
## Positive class: 1
```

mlrFDA

Fda learning algorithms

- Currently implemented learning algorithms consist of

```
lr <- makeLearner("classif.fdaknn")  
print(lr)
```

```
## Learner classif.fdaknn from package fda.usc  
## Type: classif  
## Name: fdaknn; Short name: fdaknn  
## Class: classif.fdaknn  
## Properties: twoclass,multiclass,weights,prob,single.functional  
## Predict-Type: response  
## Hyperparameters: draw=FALSE
```

parameter set
specific

mlrFDA

Fda learning algorithm: fdaknn

- Calcula

late

distance

$$\|f(t) - g(t)\|^p = \left(\frac{1}{\int_a^b w(t)dt} \int_a^b |f(t) - g(t)|^p w(t)dt \right)^{1/p}$$

between

a

pair

of

functional

data

data



mlrFDA

Fda learning algorithms

```
modelfit = train(lrn, subsetTask(tsk, features = "CO2"), subset = 1:5)
print(modelfit)
```

```
## Model for learner.id=classif.fdaknn; learner.class=classif.fdaknn
## Trained on: task.id = functionaldf; obs = 5; features = 1
## Hyperparameters: draw=FALSE
```

```
prediction = predict(modelfit, subsetTask(tsk, features = "CO2"), subset = 6:10)
print(prediction)
```

```
## Prediction: 5 observations
## predict.type: response
## threshold:
## time: 0.00
##      id truth response
## 6      6      2        2
## 7      7      1        2
## 8      8      1        2
## 9      9      1        2
## 10    10      1        2
```

mlrFDA

Fda feature extraction

- How can we apply
non-functional ML algorithms to
functional data?
functional
structure

- Extract

```
feat.methods = list("CO2" = extractFDAFourier(), "NOX" = extractFDAMean())  
newlrn = makeExtractFDAFeatsWrapper("classif.rpart", feat.methods = feat.methods)  
print(newlrn)
```

```
## Learner classif.rpart.extracted from package rpart  
## Type: classif  
## Name: ; Short name:  
## Class: extractFDAFeatsWrapper  
## Properties: twoclass,multiclass,missings,numerics,factors,ordered,prob,weights,featimp,functionals  
## Predict-Type: response  
## Hyperparameters: xval=0
```



```
newmodel = train(newlrn, tsk, subset = 1:5)  
print(newmodel)
```

```
## Model for learner.id=classif.rpart.extracted; learner.class=extractFDAFeatsWrapper  
## Trained on: task.id = functionalfd; obs = 5; features = 3  
## Hyperparameters: xval=0
```

Fda feature extraction: fourier transform

- Key idea: each signal (over time) can be filtered into combinations of circular paths, i.e.

$$X_k = \sum_{n=0}^{N-1} x_n e^{-i2\pi kn/N}$$



Benchmark experiments

[2]

- Compare to UCR Time Series Classification Repository Bakeoff
- 83 classification data sets (univariate time series)
- Fixed train-test split, LOOCV
- 36 (non) time series learners
 - ST
 - BOSS
 - COTE
 - ...
- tuning via random search (100iters) and MBO (100iters)

mlrFDA

4 functional learners

- fdanp - fdaknn
- fdaglm - fdakernel

default

6 standard ml learners

- ranger - rpart
- ksvm - cvglmnet

default

d +

tuned

t +

[2]

- Anthony Bagnall, et al.,
 - Anthony Bagnall, et al., The
 Time Series
 Classification
 Bake Off: a
 CRAVEY2-107/24/2017
 Benchmark Time
 Series Classification
 Evaluation

12

of Recent Algorithmic


Advances Data
 Series Classification

© 2016 Bosch GmbH. All rights reserved, also regarding any disposal, exploitation, reproduction, editing, distribution, as well as in the event of applications for industrial property rights.




Benchmark experiments

Overview ACC




Benchmark experiments

Ranking




In more than $0.5 * 83$ experiments we are under the 10 best performing learners




Benchmark experiments

Individual datasets



Summary

- How is functional data analysis integrated into mlr?



- Functional classification and regression
- What can you do with mlrFDA and how?
 - Feature extraction for standard ML methods
- Considering functional learners in time series applications is worth a try

Header of section fgam

- Functi

onal

gene

alize

additi

ve

model

s for

regre

ssion

of

functi

$$g(E(Y_i)) = \beta_0 + \int_{T_1} F(X_{i1}, t) dt + \int_{T_2} \beta(t) X_{i2} dt + f(z_{i1}) + f(z_{i2}, z_{i3}) + \dots$$

