

## STSCI4740HW4

Nick Gembs

10/30/2022

```
library(ISLR)
data=Default

#glimpse(data)

#1

mylogit <- glm(default ~ income + balance, data = data, family = "binomial")

summary(mylogit)

##
## Call:
## glm(formula = default ~ income + balance, family = "binomial",
##      data = data)
##
## Deviance Residuals:
##      Min       1Q   Median       3Q      Max
## -2.4725  -0.1444  -0.0574  -0.0211   3.7245
##
## Coefficients:
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept) -1.154e+01  4.348e-01 -26.545  < 2e-16 ***
## income      2.081e-05  4.985e-06   4.174  2.99e-05 ***
## balance     5.647e-03  2.274e-04  24.836  < 2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## (Dispersion parameter for binomial family taken to be 1)
##
##      Null deviance: 2920.6  on 9999  degrees of freedom
## Residual deviance: 1579.0  on 9997  degrees of freedom
## AIC: 1585
##
## Number of Fisher Scoring iterations: 8

#2

set.seed(1)

train = sample(length(data$default), length(data$default)/2)
```

```

training = data[train,]
testing = data[-train,]

mylogit <- glm(default ~ income + balance, data = training, family =
"binomial")

logit.pred=predict(mylogit, data=testing)
pred = (exp(logit.pred))/(1+exp(logit.pred))

for( i in 1:length(pred)){
  if (pred[i] > .5){
    pred[i] = "Yes"
  } else {
    pred[i] = "No"
  }
}

table(pred,testing$default)

##
## pred      No  Yes
##      No  4090  132
##      Yes   753   25

mean(pred==testing$default)

## [1] 0.823

cat("Testing Error Rate is:" , 1-mean(pred==testing$default))

## Testing Error Rate is: 0.177

#3

set.seed(2)

train = sample(length(data$default), length(data$default)/2)

training = data[train,]
testing = data[-train,]

mylogit <- glm(default ~ income + balance, data = training, family =
"binomial")

logit.pred=predict(mylogit, data=testing)
pred = (exp(logit.pred))/(1+exp(logit.pred))

for( i in 1:length(pred)){
  if (pred[i] > .5){
    pred[i] = "Yes"

```

```

} else {
  pred[i] = "No"
}
}

table(pred,testing$default)

##
## pred      No  Yes
##   No  4292  141
##   Yes   545   22

mean(pred==testing$default)

## [1] 0.8628

cat("Testing Error Rate is:" , 1-mean(pred==testing$default))

## Testing Error Rate is: 0.1372

set.seed(3)

train = sample(length(data$default), length(data$default)/2)

training = data[train,]
testing = data[-train,]

mylogit <- glm(default ~ income + balance, data = training, family =
"binomial")

logit.pred=predict(mylogit, data=testing)
pred = (exp(logit.pred))/(1+exp(logit.pred))

for( i in 1:length(pred)){
  if (pred[i] > .5){
    pred[i] = "Yes"
  } else {
    pred[i] = "No"
  }
}

table(pred,testing$default)

##
## pred      No  Yes
##   No  3948  121
##   Yes   897   34

mean(pred==testing$default)

## [1] 0.7964

```

```

cat("Testing Error Rate is:" , 1-mean(pred==testing$default))

## Testing Error Rate is: 0.2036

print("After running the logistic regression on 3 different samples, the max
validation error rate was .2036 and the minimum was .1372. It appears that
the model is significantly better than random guessing, but does have
noticeable variance among trials")

## [1] "After running the logistic regression on 3 different samples, the max
validation error rate was .2036 and the minimum was .1372. It appears that
the model is significantly better than random guessing, but does have
noticeable variance among trials"

#4

set.seed(1)
options(contrasts = c("contr.treatment", "contr.helmert")) # dummy

train = sample(length(data$default), length(data$default)/2)

training = data[train,]
testing = data[-train,]

mylogit <- glm(default ~ income + balance + student, data = training, family
= "binomial")

logit.pred=predict(mylogit, data=testing)
pred = (exp(logit.pred))/(1+exp(logit.pred))

for( i in 1:length(pred)){
  if (pred[i] > .5){
    pred[i] = "Yes"
  } else {
    pred[i] = "No"
  }
}

table(pred,testing$default)

##
## pred      No  Yes
##    No  4070  132
##    Yes   773   25

mean(pred==testing$default)

## [1] 0.819

cat("Testing Error Rate is:" , 1-mean(pred==testing$default))

```

```

## Testing Error Rate is: 0.181

options(contrasts = c("contr.treatment", "contr.helmert")) # dummy
set.seed(2)

train = sample(length(data$default), length(data$default)/2)

training = data[train,]
testing = data[-train,]

mylogit <- glm(default ~ income + balance + student, data = training, family
= "binomial")

logit.pred=predict(mylogit, data=testing)
pred = (exp(logit.pred))/(1+exp(logit.pred))

for( i in 1:length(pred)){
  if (pred[i] > .5){
    pred[i] = "Yes"
  } else {
    pred[i] = "No"
  }
}

table(pred,testing$default)

##
## pred      No  Yes
##    No  4239  141
##    Yes   598   22

mean(pred==testing$default)

## [1] 0.8522

cat("Testing Error Rate is:" , 1-mean(pred==testing$default))

## Testing Error Rate is: 0.1478

options(contrasts = c("contr.treatment", "contr.helmert")) # dummy
set.seed(3)

train = sample(length(data$default), length(data$default)/2)

training = data[train,]
testing = data[-train,]

mylogit <- glm(default ~ income + balance +student, data = training, family =
"binomial")

```

```

logit.pred=predict(mylogit, data=testing)
pred = (exp(logit.pred))/(1+exp(logit.pred))

for( i in 1:length(pred)){
  if (pred[i] > .5){
    pred[i] = "Yes"
  } else {
    pred[i] = "No"
  }
}

table(pred,testing$default)

##
## pred      No  Yes
##   No  3903  120
##   Yes   942   35

mean(pred==testing$default)

## [1] 0.7876

cat("Testing Error Rate is:" , 1-mean(pred==testing$default))

## Testing Error Rate is: 0.2124

print("After running the logistic regression on 3 different samples, the max
validation error rate was .2124 and the minimum was .1478. It appears that
the model is significantly better than random guessing, but does have
noticeable variance among trials. It does not appear that the student
variable was effective in predicting default. Including a dummy variable for
student does not lead to a reduction in the test error rate")

## [1] "After running the logistic regression on 3 different samples, the max
validation error rate was .2124 and the minimum was .1478. It appears that
the model is significantly better than random guessing, but does have
noticeable variance among trials. It does not appear that the student
variable was effective in predicting default. Including a dummy variable for
student does not lead to a reduction in the test error rate"

#5

library(caret)

## Loading required package: ggplot2

## Loading required package: lattice

library(tidyverse)

```

```

## — Attaching packages
## _____
## tidyverse 1.3.2 —

## ✓ tibble 3.1.8      ✓ dplyr 1.0.10
## ✓ tidyr 1.2.1       ✓ stringr 1.4.1
## ✓ readr 2.1.3       ✓ forcats 0.5.2
## ✓ purrr 0.3.5
## — Conflicts —
tidyverse_conflicts() —
## ✗ dplyr::filter() masks stats::filter()
## ✗ dplyr::lag() masks stats::lag()
## ✗ purrr::lift() masks caret::lift()

ctrl <- trainControl(method = "cv", number = 5)

options(contrasts = c("contr.treatment", "contr.helmert")) # dummy

mylogit <- train(default ~ income + balance, data = data, method = "glm",
family = "binomial", trControl = ctrl)

print(mylogit)

## Generalized Linear Model
##
## 10000 samples
## 2 predictor
## 2 classes: 'No', 'Yes'
##
## No pre-processing
## Resampling: Cross-Validated (5 fold)
## Summary of sample sizes: 8000, 8000, 8001, 8000, 7999
## Resampling results:
##
## Accuracy Kappa
## 0.9732997 0.4282539

logit.pred=predict(mylogit, data=testing)
table(pred,testing$default)

##
## pred No Yes
## No 3903 120
## Yes 942 35

mean(pred==testing$default)

## [1] 0.7876

cat("Testing Error Rate is:" , 1-mean(pred==testing$default) , "\n")

```

```

## Testing Error Rate is: 0.2124

mylogit <- train(default ~ income + balance + student, data = data, method =
"glm", family = "binomial", trControl = ctrl)

print(mylogit)

## Generalized Linear Model
##
## 10000 samples
##      3 predictor
##      2 classes: 'No', 'Yes'
##
## No pre-processing
## Resampling: Cross-Validated (5 fold)
## Summary of sample sizes: 8000, 8000, 8000, 8001, 7999
## Resampling results:
##
##   Accuracy   Kappa
##  0.9730001  0.4206439

logit.pred=predict(mylogit, data=testing)
table(pred,testing$default)

##
## pred      No  Yes
##   No  3903  120
##   Yes  942   35

mean(pred==testing$default)

## [1] 0.7876

cat("Testing Error Rate is:" , 1-mean(pred==testing$default))

## Testing Error Rate is: 0.2124

print("5-fold cross-validation yields the same results, adding dummy variable
student does not reduce test error in predicting default.")

## [1] "5-fold cross-validation yields the same results, adding dummy
variable student does not reduce test error in predicting default."

#LOOCV

ctrl <- trainControl(method = "LOOCV")

options(contrasts = c("contr.treatment", "contr.helmert")) # dummy

mylogit <- train(default ~ income + balance, data = data, method = "glm",
family = "binomial", trControl = ctrl)

```



```
print(mylogit)
logit.pred=predict(mylogit, data=testing)
table(pred,testing$default)
mean(pred==testing$default)

cat("Testing Error Rate is:" , 1-mean(pred==testing$default) , "\n")

mylogit <- train(default ~ income + balance + student, data = data, method =
"glm", family = "binomial", trControl = ctrl)

print(mylogit)
logit.pred=predict(mylogit, data=testing)
table(pred,testing$default)
mean(pred==testing$default)

cat("Testing Error Rate is:" , 1-mean(pred==testing$default))
```