

CEng 140


Dynamic Memory Management

Dynamic Memory Management

- C provides DMM functions that enable storage to be **allocated** as needed & **released** when no longer required!
- `sizeof()` **operator**
 - Unary
 - `sizeof(type_name)`
 - `sizeof(expression)`
 - Result of `sizeof()` is of type **size_t** which is an unsigned integral type

Dynamic Memory Management

- C p
to k
no |
- size
 - l
 - s
 - s
 - R
 - u



DMM: sizeof()

- `sizeof(type_name)`
 - When applied to a typename, `sizeof()` yields the **size in bytes** of an object of the type named
 - `sizeof(int) → 2` (assuming your system has 2 byte integers)
 - `sizeof(char) → 1`
 - `sizeof(float) → 4`

DMM: sizeof()

- sizeof(*expression*)
 - When applied to an expression, **analyzes** the expression at the **compile time** to determine its type, and yields the same result as if it had been applied to the type of the expression.

short s, *sp;

- sizeof(s) → sizeof(short)
- sizeof(sp) → sizeof(short *)
- sizeof(*sp) → sizeof(short)

DMM: sizeof()

- If the operand to sizeof is an n-element array of type T, the result is: **n x sizeof(T)**

int a[10]; \rightarrow sizeof(a) $\rightarrow 2 \times 10 = 20$ bytes

- Size of a string constant is number of chars + 1
– sizeof("computer") $\rightarrow 9$ bytes

DMM: sizeof()

- sizeof does not cause any of the usual type conversions in determining the type of the expression
 - E.g.: when applied to an array name, sizeof does **not** cause the array name to be converted to a pointer.

However, if the expression contains operators that do perform usual type conversions, these are taken into account while determining the expression's type (see example on the next slide)

Example

`char c;`

`sizeof(c) → same as sizeof(char)`

`sizeof(c+0) → same as sizeof(int)`

DMM: sizeof()

- When sizeof is applied to an expression, it is compiled to determine **its type**, but **not** compiled to the **executable code**!

```
int i, j;
```

```
i=1;
```

```
j= sizeof(--i);
```

What is the value of i afterwards?

Example

```
char arr[] = "hello";  
char *cp = arr;  
int main()  
{ printf("%lu \n", (unsigned long) sizeof(arr); }
```


What is the output?


→ 6

What if we print sizeof(*cp)

→ 1

DMM





- A program may ask for allocating memory (for its data objects) as it needs, and may release the memory when it does not need it anymore

```
int *p, *q;
```

```
double *w;
```

```
p = /* allocate mem to store 100 ints */
```

```
w= /* allocate mem to store 20 doubles */
```

```
q = /* allocate mem to store 30 ints */
```

```
/* release mem for doubles */
```

```
w= /* allocate mem to store 50 doubles */
```

```
/* increase prev memory for 100 int to 120*/
```

```
/* reduce prev memory for 30 ints to 5*/
```

```
/* increase prev memory for 120 int to 500*/
```

DMM Functions

- malloc, calloc, realloc, free (in <stdlib.h>)
- **malloc, calloc**: obtain storage for an object
- **realloc**: change the size of the storage allocated to an object
- All three functions allocate **contiguous** memory blocks
- **free**: releases the storage

DMM Functions

- Calling **malloc**, **calloc**, **realloc**:
 - yields a pointer to the beginning of the storage allocated to an object, and
 - it is suitably aligned, so that it may be assigned to a pointer of any type of object
 - Returns a generic pointer **void *** that can be safely converted to a pointer of any type.

```
void * malloc(size_t size);
```

- allocates storage for an object whose size is specified by size
- **if** there is available memory space (in HEAP)
 - returns a pointer to the allocated storage (which is NOT initialized in any way)
- **else** (not enough space)
 - returns NULL

Example


```
float *fp, fa[10];
```

```
/* allocate storage dynamically to store an array  
of 10 floats */
```

```
fp = (float *) malloc (sizeof(float)*10);
```

Or:

```
fp = (float *) malloc (sizeof(fa));
```



void * **coerced to** float *

Example


```
float *fp;  
fp = (float *) malloc (sizeof(float)*10);
```

The area allocated is size of 10 floats

– 10 x 4 bytes (if each float is 4 bytes)

and coerced to float *.

So, *fp is the float at address 800, *(fp+1) is the next float (at address 804) and so on...



REMARK: There is no other name of the allocated memory space, **we access only via the pointer!**

```
void * calloc(size_t nobj, size_t size);
```

- Allocates storage for an array of **nobj** objects, each of size **size**
- and, the allocated storage is **initialized to zeros!**

```
float *fp;
```

```
fp = (float *) calloc(10, sizeof(float));
```

Remark!

- A good practice is checking whether we get the memory or not after calling malloc or calloc!


```
int *ip;  
if ( (ip = (int *) malloc(5 * sizeof(int))) == NULL )  
    printf("Error, not enough memory \n");  
else /* you allocated, do whatever you want... */
```

```
void * realloc(void *p, size_t size);
```

- Changes the size of the object **pointed to by p** to *size*.
- If succesfull,
 returns a pointer to the new object,
else
 returns NULL, and *p remains unchanged

realloc


```
int *ip;  
ip = (int *) malloc (sizeof(int) * 5);  
ip[0]=10; ip[1]=25; ip[2]=31;  
ip[3]=24; ip[4]=2;  
  
ip = (int *) realloc (ip, sizeof(int) * 3);  
– If the new size is smaller, original  
  contents up to new size are  
  preserved.
```



realloc

```
int *ip;  
ip = (int *) malloc (sizeof(int) * 5);  
ip[0]=10; ip[1]=25; ip[2]=31;  
• ip = (int *) realloc (ip, sizeof(int) * 7);  
  – If the new size is larger, the original  
    contents are preserved and the  
    remaining space is uninitialized.  
  – In particular, if there is additional  
    space after the initially allocated  
    area, allocate it. Otherwise,  
    allocate a new block (of the new  
    size), copy data there, release old  
    block, return the pointer.
```

80



Pitfalls!

```
int *ip;
```

```
ip = (int *) malloc (sizeof(int) * 5);
```

```
ip = (int *) realloc (ip, sizeof(int) * 10);
```

- if allocated, fine; but what if realloc fails to allocate the required memory?
 - returns NULL, ip = NULL, and the pointer to access the original area (of 5 ints) is lost!!

```
int *tmp;
```

```
tmp = (int *) realloc (ip, sizeof(int) * 10);
```

```
if (tmp) ip =tmp;
```

Pitfalls!

- Similarly, if more than one pointer points to the original place, after realloc, some of them may point to a wrong place!
 - guarantee that all point to the newly allocated area!
- Another common mistake:
- `ip = (int *) realloc (ip, sizeof(ip) + sizeof(int) * 5);`
- `sizeof(ip) → sizeof(int *)!`


`void free(void *p);`

- Deallocates the storage pointed by p, where p is previously allocated by malloc/calloc/realloc
 - if p is NULL, does nothing
- Behaviour of free (and realloc) are **undefined**:
 - if p does not match to a pointer returned by a call to malloc/calloc/realloc
 - if the storage has already been deallocated by a call to realloc or free!

```

int main()
{
float *fp;
fp = (float *) malloc (sizeof(float)*10);
/* do whatever you want
   with fp */
free(fp); /* frees the storage for 10
           floats */
/* do not access *fp anymore */
}

```



Pitfall

- Memory leak:

```
int *p;
```

```
for (i = 0; i < 1000; i++)
```

```
    p = (int *) malloc (sizeof(int) * 10000);
```

Warning

BU VIDEO TÜMÜYLE AŞAĞIDA BELİRTİLMİŞ LİSANS ALTINDADIR.
THIS VIDEO, AS A WHOLE, IS UNDER THE LICENSE STATED BELOW.

Türkçe:

Creative Commons Atıf-GayriTicari-Türetilemez 4.0 Uluslararası Kamu Lisansı
<https://creativecommons.org/licenses/by-nc-nd/4.0/legalcode.tr>

English:

Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International Public License
<https://creativecommons.org/licenses/by-nc-nd/4.0/legalcode>

LİSANS SAHİBİ ODTÜ BİLGİSAYAR MÜHENDİSLİĞİ BÖLÜMÜDÜR.
METU DEPARTMENT OF COMPUTER ENGINEERING IS THE LICENCE OWNER.

LİSANSIN ÖZÜ

Alıntı verilerek indirilebilir ya da paylaşılabilir ancak değiştirilemez ve ticari amaçla kullanılamaz.

LICENSE SUMMARY

**Can be downloaded and shared with others, provided the licence owner is credited,
but cannot be changed in any way or used commercially.**

