
mkpkg

Release 7.5.0

Gene C

Jun 22, 2025

CONTENTS:

1	mkpkg	1
1.1	Overview	1
1.2	New / Interesting	1
2	mkpkg application	3
2.1	Overview of mkpkg	3
2.2	Triggering Rebuilds Summary	3
2.3	Background Motivation	4
3	Using mkpkg	7
3.1	Getting Started	7
3.2	Options	7
3.3	How mkpkg works	8
3.4	Triggering Rebuilds Details	8
3.5	Discussion and Next Steps	10
4	Appendix	11
4.1	mkpkg Source	11
4.2	Installation	11
4.3	Dependencies	11
4.4	Philosophy	12
4.5	License	12
4.6	Some history	12
5	Changelog	15
5.1	Tags	15
5.2	Commits	15
6	MIT License	25
7	How to help with this project	27
7.1	Important resources	27
7.2	Reporting Bugs or feature requests	27
7.3	Code Changes	27
8	Contributor Covenant Code of Conduct	29
8.1	Our Pledge	29
8.2	Our Standards	29
8.3	Our Responsibilities	29
8.4	Scope	30
8.5	Enforcement	30

8.6	Attribution	30
8.7	Interpretation	30
9	Indices and tables	31

1.1 Overview

Tool to rebuild Arch packages based on dependency triggers.

- All git tags will be signed by <arch@sapience.com>. Public key is available via WKD or download from website: <https://www.sapience.com/tech> After key is on keyring use the PKGBUILD source line ending with *?signed* or manually verify using *git tag -v <tag-name>*

1.2 New / Interesting

- Fixed issue where build subprocesses that generate very large amounts of data on stdout/stderr could occasionally lead to blocked IO when data exceeded python IO.DEFAULT_BUFFER_SIZE. Symptom is that the build hangs waiting for IO to get unblocked. Fixed by enhancing run_prog() to use non-blocking I/O.
- Improved code
 - PEP-8, PEP-257, PEP-484 and PEP-561 Refactor & clean ups.
- Improved handling of split packages. Now checks every packages for any being missing or out of date.
- soname logic updated.

Default is now 'keep' which only rebuilds of a soname is no longer available. This is in line with how sonames are typically used where soname only changes when ABI changes.

- Major update: soname handling has been re-written from scratch and improved substantially.

It now identifies every soname versioned library in elf executables along with their full path. It also properly handles executables built with *-rpath* loader options.

Previous versions relied on makepkg soname output which, unfortunately, only lists sonames if they are also listed as a PKGBUILD dependency. We need every soname versioned library to ensure we do the right thing and rebuild when needed. So it was a mistake to rely on this.

Can also specify how to handle version comparisons similar to the way package version comparisons are done (e.g. soname > major)

If you're interested, the soname info is saved into the file *.mkp_dep_soname*

N.B.

that the build must be run at least once with this new version to generate the soname info (mkpkg -f forces a fresh build)

- Old options now deprecated
 - (*-mpk-xxx*)

- (*–soname-build*) : use *–soname-comp* instead

MKPKG APPLICATION

2.1 Overview of mkpkg

Building an Arch package requires invoking *makepkg* with a *PKGBUILD* file. *PKGBUILD* file contains a *depends* variable which lists those packages that are needed to use tool provided by the package.

It also has a ‘*makedepends*’ variable which is a list of other packages that are needed to build the package. *makepkg* also assumes that any package listed in the *depends* variable must also be present to build the package.

However, once a package has been built, then the only thing which causes a rebuild is a change to the actual package version itself. This can be either because the version of the tool itself changed or because the packager manually changed the release version, thereby forcing a rebuild.

If you have ever needed to rebuild a package by manually bumping the release version, then something is not ideal. If something requires a rebuild, other than the package itself having an update, it would be far better if this is done automatically rather than by hand.

This is what *mkpkg* does. It automates rebuilds when they are needed for some reason other than the tool / package version itself being newer. As a simple example, if something depends on *openssl* and the last build was against 3.0.0, then it can be set to rebuild if *openssl* has been installed more recently version than when the last package build was done. It could also be set to rebuild if *openssl* has a minor version update like 3.1.x.

Triggers are discussed in detail below, *mkpkg-triggers*, but we’ll provide a short summary here.

2.2 Triggering Rebuilds Summary

To accomplish this *mkpkg* allows you to define a set of *triggers* that will cause a rebuild. These are packages, or files, that trigger a rebuild whenever they change in a specified way. Straightforward concept.

The packager is responsible for providing the list of appropriate triggers.

The way to provide the these triggers is by adding a *PKGBUILD* array variable to provide the list of conditions that should trigger a rebuild.

2.2.1 Package Trigger

_mkpkg_depends variable is this list of such triggers

There are 2 ways a package can trigger a rebuild.

1. **A package name**

Rebuilds if the install date is more recent than the last build time e.g.

```
_mkpkg_depends=('openssl' 'systemd')
```

2. A package name plus a version condition

It can be an explicit version or a key word such as *major* which would then only trigger a rebuild when the major version of that package was greater than that at the last build. More details and the different options are detailed below. e.g.

```
_mkpkg_depends=('openssl>3.0.6' 'systemd')
```

2.2.2 File Trigger

It can also use any file to trigger a build using `_mkpkg_depends_file`. When a file in this list is newer than the last build, it triggers a rebuild.

A typical use case for these file triggers are files provided by the packager, rather than the source, and include things such as systemd unit files or pacman hook files or other package related items. e.g.:

```
_mkpkg_depends_file=('xxx.service')
```

This is useful to ensure packages build and work when conditions are met by other packages being updated.

It is certainly helpful for packages which statically link in libraries, or when core build tools change and it's important to rebuild with the newer versions. Do we really need to rebuild a package when tool chain changes? Sometimes yes; for example, whenever the compiler toolchain is updated, I always rebuild my kernel packages and test.

The majority of compiled packages are built against shared libraries and this can be helpful in this case too; there are additional comments on this topic below.

As another example, I rebuild my python applications when python's major.minor is larger than what was used for previous build.

An additional little benefit, if packages are up to date then running mkpkg is significantly faster than makepkg; can be something like 10x faster or even more.

2.3 Background Motivation

mkpkg has one run-time dependency, python.

It uses makepkg to perform the actual package builds in the usual way. That said, makepkg is a part of pacman which is always installed and thus not a *dependency* as far as PKGBUILD is concerned.

When a tool chain used to build a package is updated, it's good practice, IMHO, to rebuild packages which use that tool chain. For example, when gcc, cargo, binutils et al are updated packages using those tools should also be updated. As mentioned above, whenever compiler/binutils tool chain changes, I always rebuild and test my kernel packages. This not only ensures that things compile and work properly with the new build tools but can also be key to reducing the attack surface. One recent (as of time of writing) little example, not to pick on cargo, is [CVE-2022-36113](#)

Of course this would require a case where cargo is actually downloading something which should never be permitted; still, it's a conceivable danger.

While static linked libraries surely don't demand a rebuild to function, obviously, because the older library is part of the binary itself, it's still a good idea to rebuild it. This will pick up bug fixes, including security related ones, as well as improvements. Of course, it's always sensible to confirm that an application properly builds and works with the newer tool or library as well.

Here's an example. The *refind* boot manager statically links against gnu-efi. So when gnu-efi is updated, refind should be rebuilt as well even though the previous one will continue to work just fine.

Recently, arch started switching many packages to be compiled with lto. The gnu-efi package was subsequently compiled with `* -flto -ffat-lto-object*`. The refind boot manager statically links gnu-efi. At this point, refind itself had not changed and so it's up to date as far standard approach is concerned.

However, I would like to know as early as possible that refind builds and runs with the the new gnu-efi library that was updated. In fact, unfortunately perhaps, this build failed and refind not longer builds with the updated gnu-efi library due to lto changes. Good to know.

You could of course have waited until refind itself gets an update and then discover - oh no it no longer builds. But, by doing this early and in this case knowing refind itself has not changed, I know with certainty that this problem stems from the gnu-efi rebuild and not from a refind change - without even looking at any refind source changes.

Given the large number of packages I build I doubt I'd remember what trigger packages are appropriate for every package anyway. Computers are good at automating repetitive tasks after all and are much quicker at identifying the trigger packages.

mkpkg was created to address this need. It automates this for you and rebuilds packages when needed. This allows for early detection of problems or confirmation that things are actually fine.

A small comment on shared libraries. While these are generally not a problem, there is an assumption that the library itself still functions the same for whatever part of it the tool is using.

The majority of providers are careful with *sonames* as well, so most of the time that's likely true, however, the cautious among us may want to run regression tests even in this case.

Certainly for mission critical tools. Bugs happen, and it's good to learn of any issues as soon as possible.

But there are indeed some shared library packages, some with dynamically loaded libraries (plugins) that may also be trigger packages. One symptom of that need are those packages that are manually rebuilt by forcing a release version bump typically with a comment such as *rebuilt with latest ...* - we certainly see plenty of that happening.

USING MKPKG

3.1 Getting Started

Edit the PKGBUILD and add a `_mkpkg_depends` variable with a list of triggers that should cause a rebuild when the condition is met. Triggers are discussed in detail (*mkpkg-triggers*) below, but a simple example is:

```
_mkpkg_depends=('python>major', 'python-foo')
```

This would trigger a package rebuild if a version of *python-foo* is installed more recently than the last package build or if *python* has a major version which is larger than that used when package was last built.

With the trigger conditions in the PKGBUILD, then simply call `mkpkg` instead of `makepkg`. Couldn't be simpler. Options for `mkpkg` are those before any double dash `--`. Any options following `--` are passed through to *makepkg*³.

3.2 Options

The options currently supported by `mkpkg` are:

- **(-v, -verb)**

Show (stdout) output of `makepkg`. Default is not to show it.

- **(-f, -force)**

Force a `makepkg` run even if not needed. Bump the package release and rebuild

- **(-r, -refresh)**

Attempts to update saved metadata files. Faster, if imperfect, alternative to rebuild. If there is no saved metadata, and build is up to date, will try refresh the build info. Files updated are `.mkp_dep_vers` and `.mkp_dep_soname`.

Note that *sonames* are found by examining any executables in the *pkg* directory. If the *pkg* directory is empty, the refresh will not find any sonames.

- **(-so-comp, -soname-comp)**

How to handle automatic soname changes. Default value is *keep* - only rebuilds if soname is no longer available.

- *newer* : if soname is newer then rebuild (time based)
- *keep* : if soname library is still available, then dont rebuild even if newer version(s) are available
- *vcomp* : rebuild if soname version is greater than the *vcomp* version. *vcomp* is one of *major*, *minor*, *patch*, *extra* or *last* - same as for regular dependencies.
- *neverever* : Developer option - will not rebuild even if the soname library is no longer available.

³ The older style options using `-mkp-` are now deprecated.

- (-)

All options following this are passed to makepkg

Config file

Configs are looked for in first in `/etc/mkpkg/config` and then in `~/.config/mkpkg/config`. Config files are in TOML format. e.g. to change the default soname rebuild compare option from default of *last*:

```
soname_comp = "newer"
```

3.3 How mkpkg works

Outline of what it does

- If PKGBUILD has a `pkgver()` function, check if the `pkgver` variable matches its output
- If the 2 `pkgver` match or if there is no `pkgver()` function then check if a matching package exists
- If package not up to date, then run `makepkg build`.
- If package seems otherwise up to date, then check if any of the conditions given by *mkpkg_depends* or *mkpkg_depends_files* triggers a build. If a build is called for, then bump the `pkgrel` and rebuild.
- If the package is out of date, as there is newer version then reset `pkgrel` back to “1” and build.

So, if a package builds and gets larger package release number, it was because of some trigger package dependency; absent manual modification. If package release is “1” - then you know its a fresh package version.

I use separate tool to run all my package builds so I prefer the output to be easily parseable and provide simple and clear information to feed the builder too.

mkpkg thus prints a line of the form:

```
*mkp-status: <status> <package-version>*
```

Where status is one of :

- **current** -> package is up to date
- **success** -> package was built successfully
- **error** -> problem occurred.

Obviously, package-version is what is sounds like.

It is possible for mkpkg itself to fail for some reason, in which case the *mkp-status:* line could be absent. This is also simple to detect programatically.

3.4 Triggering Rebuilds Details

3.4.1 _mkpkg_depends

There are 2 kinds of triggers. A trigger based on package and a trigger based on file changed. Each is set using the PKGBUILD variable with a an array of triggers. The variables used are:

- **_mkpkg_depends**

This variable provides a list of packages to trigger a rebuild. Each item in the list can be in one of 2 forms:

1. *name*

The item is the name of the package then this will trigger a rebuild if the install time of a listed package is newer than the time of the last build.

2. *package_name compare-op vers_trigger*

This provides semantic version triggers. Package versions are taken to be of the form 'major.minor.patch' or more generally 'elem1.elem2.elem3...' White space around the comparison operator is optional.

- *compare-op*

is one of : >, >= or <

- *vers_trigger*

Based on comparing the first [N] elems of the version or the entire version.

- First_[N] : rebuild if first [N] elems of package version greater than when last built
- major : alias for First_1 (rebuild if major > last_build)
- minor : alias for First_2 (rebuild if major.minor > last_build)
- patch : alias for First_3 (if major.minor.patch > last_build)
 - * micro : another name for patch
- extra : alias for First_4 (major.minor.patch.extra)
 - * releaselevel : alias for extra
- serial : alias for First_5 (major.minor.patch.extra.serial)
- last : rebuild if package version > last_build version.

last is very similar to a time based trigger but based on version instead of time.

For example if the expression is

```
'pkg_name>First_2'
```

or equivalently:

```
'pkg_name>minor'
```

and the current package version is 1.2.3, while the version when last built was 1.2.0 then the versions being compared would be

```
'1.2' > '1.2' which is false.
```

Whereas if the expression was:

```
'pkg_name>First_3'
```

then the comparison would be

```
'1.2.3' > '1.2.0'
```

which is true

N.B. The package must be built at least once using mkpkg so it can save the dependent package versions used. So if a version trigger is added, then this triggers a rebuild as it treats this as if the dependent package version is greater than

last used (which is not known at this point). On subsequent builds the last built version of each dependent package is then known.

Unlike the standard *makedepends* variable, this allows one to not include things that are required to build the package but don't have any affect on the tool function. For example 'git' - which while required to build will not generally change the tool.

Another example, if python was version 3.10 when the package was last built and we have::

```
_mkpkg_depends=('python>minor' 'python-dnspython')
```

Then a rebuild will be done if python is greater than or equal to 3.11.x or if python-dnspython was installed more recently than the last build. This will not trigger a rebuild if python is updated from 3.10.7 to 3.10.8, since this is a patch update not a minor or major update.

Why support '<' you may ask. The only sensible use for less than operator would be to provide a mechanism to trigger a rebuild when a package gets downgraded. This would be accomplished using

```
pkg_name < last
```

3.4.2 `_mkpkg_depends_files`

- `_mkpkg_depends_files`

This variable can be used to provide a list of files that should trigger a rebuild. The files are relative to the directory containing PKGBUILD.

This might be useful, for example, if the source for some daemon doesn't provide a systemd service file, and the packager adds the file. Adding the file to this list would now trigger rebuilds should there be changes to the service file. An alternative would be to put these files into a git repo and just using the git version. For a small number of files this may be more convenient/simpler.

These variables offer considerable control over what can be used to trigger rebuilds.

3.5 Discussion and Next Steps

3.5.1 Possible future enhancement

While mkpkg works for all the packages I build, I am more than happy to take enhancement requests - and, of course, to fix bugs!

As mentioned earlier, it's pretty useful to run regression tests after run-time dependencies change. For example shared libraries or other programs used by the tool. To handle this case we might consider adding a separate variable - such as *mkpkg_test_depends* which lists these kind of dependencies.

We note that *checkdepends* variable is quite different in intent, as it is used to identify those packages needed to do testing but NOT for things which could impact the outcome of running the tool.

4.1 mkpkg Source

The source is kept in the github repository [Github-mkpkg](#).

4.2 Installation

Available on

- [Github-mkpkg](#)
- [Archlinux AUR](#)

On Arch you can build using the provided PKGBUILD in the packaging directory or from the AUR. All git tags are signed with arch@sapience.com key which is available via WKD or download from <https://www.sapience.com/tech>. Add the key to your package builder gpg keyring. In PKGBUILD use source= line with *?signed* at the end. You can also manually verify the signature

To build manually, clone the repo and :

```
rm -f dist/*  
/usr/bin/python -m build --wheel --no-isolation  
root_dest="/"   
./scripts/do-install $root_dest
```

When running as non-root then set root_dest a user writable directory

4.3 Dependencies

- Run Time: - python (3.9 or later) - pyalpm
- Building Package : - git - build aka python-build - intaller aka python-installer - wheel aka python-wheel - poetry aka python-poetry - rsync
- Optional for building docs:
 - sphinx
 - texlive-latexextra (archlinux packaguing of texlive tools)

4.4 Philosophy

We follow the *live at head commit* philosophy. This means we recommend using the latest commit on git master branch. We also provide git tags.

This approach is also taken by Google¹².

4.5 License

Created by Gene C. and licensed under the terms of the MIT license.

- SPDX-License-Identifier: MIT
- Copyright (c) 2022-2023 Gene C

4.6 Some history

4.6.1 Version 6.0.0

- soname rewrite

New argument for how soname changes are treated : *-so-comp*, *-soname-comp*.

Can be *<compare>*, *newer*, *never* or key how to compare the soname versions. The comparison types are the same as for package dependencies described above. Default is *last* which means the entire soname version will be compared to whats available and rebuild will be triggered if a later version now available.

<compare> e.g. *>major* or *>minor* or *last* etc. If the last built soname was 5.1, and now available is 5.2 then *minor* and *last* will trigger rebuild while *major* would not. *newer* triggers if the last modify time of the library is newer.

Previous version used sonmaes produced by makepkg - however this only generates sonames if they are listed as dependencies. We want to get every soname - so we started over from scratch. By using our own soname generate we catch every soname and its absolute path - this enables us to correctly treat soname changes. This approach will also correctly deal with any *rpath* loader flags causing executable to use shared library from path(s) specified at compile time.

4.6.2 Version 4.1.0

- Arguments

Change in argument handling. Arguments to be passed to *makepkg* must now follow *-*. Arguments before the double dash are used by mkpkg itself. To keep backward compatibility the older *-mkp-* style arguments are honored, but the newer simpler ones are preferred. e.g. *-v*, *-verb* for verbose. Help available via *-h*.

- Config file now available.

Configs are looked for in */etc/mkpkg/config* then *~/.config/mkpkg/config*. It should be in TOML format. e.g. to change the default soname rebuild option:

```
soname_comp = "newer"
```

¹ <https://github.com/google/googletest>

² <https://abseil.io/about/philosophy#upgrade-support>

4.6.3 Version 4.0.0

- Soname drive rebuilds.

Adds support for detecting missing soname libraries, and triggering rebuild. If soname is found then no rebuild is done. Typically happens when older soname is deprecated.

- Adds new option *-mkp-refresh*.

Attempts to update saved metadata files. Faster, if imperfect, alternative to rebuild.

4.6.4 Older

Adds support for epoch.

Version 2.x.y brings fine grain control by allowing package dependences to trigger builds using semantic version. For example 'python>minor' will rebuild only if a new python package has it's major.minor greater than what it was when package was last built. See *_mkpkg_depends* below for more detail.

The source has been reorganized and packaged using poetry which simplifies installation. The installer script, callable from *package()* function in PKGBUILD has been updated accordingly. Ther *build()* function uses python build module to generate the wheel package, as outlined above.

Changed the PKGBUILD variables to have underscore prefix to follow Arch Package Guidelines. Variables are now: *_mkpkg_depends* and *_mkpkg_depends_files*. The code is backward compatible and supports the previous variable names without the leading "_" as well as the ones with the "_".

Now also available on aur.

CHANGELOG

5.1 Tags

1.0.0 (2022-09-03) -> 7.5.0 (2025-06-22)
174 commits.

5.2 Commits

- 2025-06-22 : 7.5.0

2025-06-19 Sync local copy of run_prog with latest from pyconcurrent
update Docs/Changelogs Docs/mkpkg.pdf for 7.4.0

- 2025-06-19 : 7.4.0

2025-06-16 Keep internal copy of run_prog in sync with pyconcurrent
For subprocess stdin add .flush() on the file object before closing
update Docs/Changelogs Docs/mkpkg.pdf for 7.2.0

- 2025-06-16 : 7.2.0

↪ should run_prog: Fix one more possible hang. Add more exception checks that
never happen.
2025-06-14 update Docs/Changelogs Docs/mkpkg.pdf for 7.1.0

- 2025-06-14 : 7.1.0

2025-05-22 Fixed issue where build subprocesses that generate very large amounts
of data on stdout/stderr could occasionally lead to blocked IO when data
exceeded python
IO.DEFAULT_BUFFER_SIZE.
Symptom is that the build hangs waiting for IO to get unblocked.
Fixed by enhancing run_prog() to use non-blocking I/O.
update Docs/Changelogs Docs/mkpkg.pdf for 7.0.0

- 2025-05-22 : 7.0.0

Improved code
PEP-8, PEP-257, PEP-484 and PEP-561

(continues on next page)

(continued from previous page)

Refactor & clean up
Improved handling of split packages.
Now checks every packages **for** **any** being missing **or** out of date.
2024-12-31 update Docs/Changelog.rst Docs/mkpkg.pdf **for** 6.2.4

- 2024-12-31 : 6.2.4

Add git signing key to Arch Package
update Docs/Changelog.rst Docs/mkpkg.pdf **for** 6.2.3

- 2024-12-31 : 6.2.3

fix typo **in** PKGBUILD
update Docs/Changelog.rst Docs/mkpkg.pdf **for** 6.2.2

- 2024-12-31 : 6.2.2

Git tags are now signed.
Update python dep to 3.13
Small clean ups **and** linting.
PKGBUILD has info on how to activate verifying git signature once key **is** **in** keyring
2024-12-19 update Docs/Changelog.rst Docs/mkpkg.pdf **for** 6.2.0

- 2024-12-19 : 6.2.0

drop tomli **for** tomllib (python now >= 3.11)
2024-03-09 update Docs/Changelog.rst Docs/mkpkg.pdf **for** 6.1.0

- 2024-03-09 : 6.1.0

soname logic updated.
Default **is** now keep which only rebuilds of a soname **is** no longer available.
This **is in** line **with** how sonames are typically used where soname only changes when ABI changes.
update Docs/Changelog.rst Docs/mkpkg.pdf **for** 6.0.4

- 2024-03-09 : 6.0.4

Add missing pydantic **from** PKGBUILD depends
update Docs/Changelog.rst Docs/mkpkg.pdf **for** 6.0.3

- 2024-03-09 : 6.0.3

Tidy up code comments. Ensure pylint **is** clean.
add comment to README - new build needed to get soname info
2024-03-08 update Docs/Changelog.rst Docs/mkpkg.pdf **for** 6.0.1

- 2024-03-08 : 6.0.1

Tidy comments **in** soname file(s)
 README - use 6.0.0 **for** version **in** history section
 2024-03-07 update Docs/Changelog.rst Docs/mkpkg.pdf **for** 6.0.0

- 2024-03-07 : 6.0.0

* soname handling has been re-written **from scratch and** improved substantially.
 It now identifies every soname versioned library **in** elf executables along **with** their full path. It also properly handles executables built **with** `*--rpath*` loader options.
 Previous versions relied on `makepkg soname` output which, unfortunately, only lists sonames **if** they are also listed **as** a PKGBUILD dependency.
 We need every soname versioned library to ensure we do the right thing **and** rebuild when needed. So it was a mistake to rely on this.
 Can also specify how to handle version comparisons similar to the **way** package version comparisons are done (e.g. `soname > major`)
 * Old options now deprecated
 * (`*--mpk-xxx*`)
 * (`*--soname-build*`) : use `*--soname-comp*` instead
 2023-12-20 update Docs/Changelog.rst Docs/mkpkg.pdf **for** 5.0.0

- 2023-12-20 : 5.0.0

Fix soname dep handling when there are multiple pkgnames **in** PKGBUILD
 verbose option **is** boolean - does **not** take argument
 2023-11-28 update Docs/Changelog.rst Docs/mkpkg.pdf **for** 4.9.0

- 2023-11-28 : 4.9.0

Switch python build backend to hatch (was poetry)
 Switch python build backend to hatch (was poetry)
 2023-11-17 update Docs/Changelog.rst Docs/mkpkg.pdf **for** 4.8.0

- 2023-11-17 : 4.8.0

Change to using `pyalpm` to compare package versions instead of `packaging`.
`ing.version()` barfs on `systemd` version 255rc2.1 **for** some reason
 2023-10-03 update Docs/Changelog.rst **for** 4.7.0

- 2023-10-03 : 4.7.0

Bug fix semantic version comparisons
 Stop treating Arch `pkgrel` **as** part of the last version element - its separate additional element
 2023-09-28 update Docs/Changelog.rst **for** 4.6.0

- 2023-09-28 : 4.6.0

- 2023-06-05 Reorganize the tree and documents.
Switch from markdown to restructured text.
Now easy to build html and pdf docs using sphinx
update CHANGELOG.md for 4.5.5

 - 2023-06-05 : 4.5.5
- 2023-05-18 Small tweak to README
update CHANGELOG.md for 4.5.4

 - 2023-05-18 : 4.5.4
- Change PKGBUILD makedepnds from pip to installer
update CHANGELOG.md for 4.5.3

 - 2023-05-18 : 4.5.3
- install: switch from pip to python installer package. This adds optimized
bytecode
update CHANGELOG.md for 4.5.2

 - 2023-05-18 : 4.5.2
- 2023-05-17 PKGBUILD: build wheel back to using python -m build instead of poetry
update CHANGELOG.md for 4.5.1

 - 2023-05-17 : 4.5.1
- 2023-02-19 Simplify Arch PKGBUILD and more closely follow arch guidelines
update CHANGELOG.md for 4.5.0

 - 2023-02-19 : 4.5.0
- 2023-02-18 Fix bug when soname dependency drives rebuild by ensuring pkgrel is bumped
update CHANGELOG.md for 4.4.0

 - 2023-02-18 : 4.4.0
- 2023-01-31 Bug fix extracting PKGBUILD info for certain cases
update CHANGELOG.md for 4.3.0

 - 2023-01-31 : 4.3.0
- 2023-01-06 Force now bumps the package release and rebuilds
update CHANGELOG.md for 4.2.1

 - 2023-01-06 : 4.2.1
- 2023-01-03 Add SPDX licensing lines
Lint and tidy
update CHANGELOG.md for 4.2.0

 - 2023-01-03 : 4.2.0

2022-12-16 Fix **for** potential color name match bug - **not with** current color sets
update CHANGELOG.md **for** 4.1.1

- 2022-12-16 : 4.1.1

Add toml dependency to PKGBUILD
update CHANGELOG.md **for** 4.1.0

- 2022-12-16 : 4.1.0

Add config file support.
Change option handling. Options to be passed to makepkg must now be placed after --
Improved soname treatment via option --soname-build (missing,
↪(default),
newer **or** never)
2022-12-15 update CHANGELOG.md

- 2022-12-15 : 4.0.0

Add --mkp-refresh
Attempts to update saved metadata files. Faster, **if** imperfect,
alternative to rebuild.
refactor some code
pull out pacman queries to more easily share
Add suport **for** missing soname library driving rebuild
suggestion thanks to Alberto Novella Archlinux subredit.
2022-11-29 update CHANGELOG.md

- 2022-11-29 : 3.5.4

Small change to README.
Change variable check **in** installer (no functional change)
2022-11-05 update CHANGELOG.md

- 2022-11-05 : 3.5.3

tweak readme
installer script change **list** to bash array **for** apps being installed. zero
impact
2022-11-04 update CHANGELOG.md

- 2022-11-04 : 3.5.2

PKGBUILD - duh - put back makedepends on poetry
update CHANGELOG.md

- 2022-11-04 : 3.5.1

Add package name to screen message
2022-11-03 update CHANGELOG.md

- 2022-11-03 : 3.5.0

bug fix incorrectly handling triggers pkg>xxx
update CHANGELOG.md

- 2022-11-03 : **3.4.0**

Better handling of PKGBUILD syntax errors
update CHANGELOG.md

- 2022-11-03 : **3.3.1**

unwind prev error check - needs more work
update CHANGELOG.md

- 2022-11-03 : **3.3.0**

2022-10-31 Additional check **for** errors when sourcing PKGBUILD
update CHANGELOG.md

- 2022-10-31 : **3.2.0**

typo - so sorry
update CHANGELOG.md

- 2022-10-31 : **3.1.0**

2022-10-30 Add more aliases of First_N **for** version comparisons (micro, serial)
Change build **from** poetry/pip to python -m build/installer
update CHANGELOG.md

- 2022-10-30 : **3.0.0**

2022-10-26 update CHANGELOG.md
Add epoch support - needs wider testing
update changelog

- 2022-10-26 : **2.5.0**

2022-10-24 bug fix **for** _mkpkg_depends_files - silly typo
CHANGELOG.md

- 2022-10-24 : **2.4.1**

update pyproject.toml vers
update changelog

- 2022-10-24 : **2.4.0**

oops - accidentally left debugger on!
update changelog

- 2022-10-24 : **2.3.6**

2022-10-23 Fix bug parsion <package> >= xxx. Greater than **is** fine.
update changelog

- 2022-10-23 : **2.3.5**


```
avoid all but tag in pkgver()
update pyproject.toml vers
update changelog
```

- 2022-10-23 : 2.3.4

```
PKGBUILD - remove tag= now that pkgver() is getting latest tag
```

- 2022-10-23 : 2.3.3

```
2022-10-14    PKGBUILD now builds latest release tag
              update changelog
              Add comment about being fast
              update changelog
```

- 2022-10-14 : 2.3.2

```
2022-10-13    Improve PKGBUILD for aur as per comments
              update pyproject.toml version
              Clean the dist directory before doing poetry build
              fix python depends version > 3.9
              Add makedepends packages in aur PKGBUILD
              fix comment
              add aur comment
              update changelog
```

- 2022-10-13 : 2.3.1

```
Update readme with link to AUR for mkpkg
Change PKGBUILD for AUR
little word smithing on readme
Clean up some comments
readme word smithing
update changelog
```

- 2022-10-13 : 2.3.0

```
In the event mkpkg_depends / mkpkg_depends_files are absent,
no longer fall back to use makedepends unless turned on with the --mkp-
use_makedepends option
update changelog
```

- 2022-10-13 : 2.2.1

```
Bug fix for _mkpkg_depends_files
better package description in PKGBUILD
readme markdown missed 2 spaces for newline
Readme - markdown requires escape for underscore
update CHANGELOG.md
```

- 2022-10-13 : 2.2.0

```
Change PKGBUILD variables to have leading "_" to follow arch packaging
guidelines
```

(continues on next page)

(continued from previous page)

Code **is** backward compatible **and** will work **with or** without the _
 New names are: `_mkpkg_depends` **and** `_mkpkg_depends_files`
 update changelog
 more readme tweaks
 update changelog

- 2022-10-13 : **2.1.1**

Provide sample PKGBUILD to build mkpkg
 update changelog
 typo **in** readme
 update changelog
 README tweak to explain "patch" being same **as** "First_3" **for** version triggers
 update CHANGELOG.md

- 2022-10-13 : **2.1.0**

2022-10-12 Enhance version triggers to handle version **with** more than 3 elements
 update changelog
 readme tweaks
 update CHANGELOG

- 2022-10-12 : **2.0.1**

update changelog
 remove unused **from** **do**-install
 update CHANGELOG
 tweak readme
 update changelog

- 2022-10-12 : **2.0.0**

Reorganize directory structure **and** use poetry **for** packaging.
 Add support **for** triggers now based on semantic versions.
 e.g python>3.12 **or** python>minor - where minor triggers build **if**
 major.minor version of dependency package **is** greater than that used when
 it was last built.
 Reorganize source tree
 2022-09-28 Update changelog
 tweak readme little more
 update Changelog
 Tweak README
 2022-09-22 tweak README

- 2022-09-22 : **1.3.1**

Update Changelog
 Add CVE-2022-36113 **as** example of build tool danger
 2022-09-18 Update Changelog
 Add Changelog

- 2022-09-07 : **1.3.0**

fix out of date comment **in** mkpkg.py
 fix little markdown issue
 2022-09-06 tweak readme **format**

- 2022-09-06 : **1.2.0**

Add support **for** trigger files : mkpkg_depends_files
 add README discssion comment
 2022-09-04 lint picking
 Add comment **in** README
 few more README tweaks

- 2022-09-04 : **1.1.1**

tidy message output
 typo
 Little tidy on README

- 2022-09-04 : **1.1.0**

Handle edge case when PKGBUILD hand edited
 Bug fix **for** case when override mkpkg_depends **set** to empty **set**

- 2022-09-03 : **1.0.5**

Now that we implemented mkpkg_depends, remove some readme comments
 typo
 minor README tweak
 Fix typo (resolves issue [#1](#)) *and tweak README*

- 2022-09-03 : **1.0.4**

fix section numbers **in** README

- 2022-09-03 : **1.0.3**

Support mkpkg_depends overriding makepends - gives full control to user

- 2022-09-03 : **1.0.2**

README use lower case **for** mkpkg

- 2022-09-03 : **1.0.1**

Tidy couple comments

- 2022-09-03 : **1.0.0**

Initial Revision of mkpkg.
 mkpkg builds Arch packages **and** rebuilds them whenever a make dependency **is**
 more recent than the last package

MIT LICENSE

Copyright © 2023 Gene C

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the “Software”), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED “AS IS”, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

HOW TO HELP WITH THIS PROJECT

Thank you for your interest in improving this project. This project is open-source under the MIT license.

7.1 Important resources

- [Git Repo](#)

7.2 Reporting Bugs or feature requests

Please report bugs on the issue tracker in the git repo. To make the report as useful as possible, please include

- operating system used
- version of python
- explanation of the problem or enhancement request.

7.3 Code Changes

If you make code changes, please update the documentation if it's appropriate.

CONTRIBUTOR COVENANT CODE OF CONDUCT

8.1 Our Pledge

In the interest of fostering an open and welcoming environment, we as contributors and maintainers pledge to making participation in our project and our community a harassment-free experience for everyone, regardless of age, body size, disability, ethnicity, sex characteristics, gender identity and expression, level of experience, education, socio-economic status, nationality, personal appearance, race, religion, or sexual identity and orientation.

8.2 Our Standards

Examples of behavior that contributes to creating a positive environment include:

- Using welcoming and inclusive language
- Being respectful of differing viewpoints and experiences
- Gracefully accepting constructive criticism
- Focusing on what is best for the community
- Showing empathy towards other community members

Examples of unacceptable behavior by participants include:

- The use of sexualized language or imagery and unwelcome sexual attention or advances
- Trolling, insulting/derogatory comments, and personal or political attacks
- Public or private harassment
- Publishing others' private information, such as a physical or electronic address, without explicit permission
- Other conduct which could reasonably be considered inappropriate in a professional setting

8.3 Our Responsibilities

Maintainers are responsible for clarifying the standards of acceptable behavior and are expected to take appropriate and fair corrective action in response to any instances of unacceptable behavior.

Maintainers have the right and responsibility to remove, edit, or reject comments, commits, code, wiki edits, issues, and other contributions that are not aligned to this Code of Conduct, or to ban temporarily or permanently any contributor for other behaviors that they deem inappropriate, threatening, offensive, or harmful.

8.4 Scope

This Code of Conduct applies both within project spaces and in public spaces when an individual is representing the project or its community. Examples of representing a project or community include using an official project e-mail address, posting via an official social media account, or acting as an appointed representative at an online or offline event. Representation of a project may be further defined and clarified by project maintainers.

8.5 Enforcement

Instances of abusive, harassing, or otherwise unacceptable behavior may be reported by contacting the project team at <arch@sapience.com>. All complaints will be reviewed and investigated and will result in a response that is deemed necessary and appropriate to the circumstances. The Code of Conduct Committee is obligated to maintain confidentiality with regard to the reporter of an incident. Further details of specific enforcement policies may be posted separately.

8.6 Attribution

This Code of Conduct is adapted from the Contributor Covenant, version 1.4, available at <https://www.contributor-covenant.org/version/1/4/code-of-conduct.html>

8.7 Interpretation

The interpretation of this document is at the discretion of the project team.

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`