
dmARC-report Documentation

Release 7.1.5

Gene C

Oct 08, 2026

DMARC AND TLS REPORT MANUAL

1	dmARC_report	1
1.1	Overview	1
1.2	Documentation	1
1.3	Getting Started	1
2	SMTP tls-rpt	5
2.1	Overview	5
2.2	Discussion	6
2.3	Using tls-rpt	7
3	Appendix	9
3.1	Dependencies	9
3.2	Available	9
3.3	Installation	9
3.4	License	9

DMARC_REPORT

1.1 Overview

Generate a human readable report from 1 or more standard DMARC and TLS-RPT xml email reports . DMARC reports are made using *dmARC-rpt* while TLS-RPTs use *tls-rpt*

Note:

All git tags are signed by <arch@sapience.com>. Public key is available via WKD or download from [sapience website](#). After key is on keyring use the PKGBUILD source line ending with *?signed* or manually verify using `git tag -v <tag-name>`

1.2 Documentation

The manual provides detailed information and is available in both HTML and PDF formats. Both are installed under `/usr/share/dmarc_report/docs`.

The manual is also available at: [readthedocs](#).

1.3 Getting Started

Save all DMARC or TLS-RPT reports into a directory. These are typically compressed xml/json files sent as email attachments. The saved reports can be :

- individual email files each with a compressed xml/json attachment. Thunderbird saves them this way. These are saved with a *.eml* extension.
- one single file with several emails, each with the attachment. Evolution saves this way. These are saved with *.mbox* extension.
- Individual compressed, or uncmompressed, xml reports created by saving the attachments from each email.

dmARC-rpt and *tls-rpt* will extract the actual **xml** (*dmARC*) or **json** (*tls-rpt*) data from all of the above.

1.3.1 Quick start

Save all emails with DMARC or TLS-RPT attachments to a directory, change into that directory and run either `dmARC-rpt` or `tls-rpt` as appropriate.

It is generally more convenient to use a config file explained below.

1.3.2 Config Files

Config files are read, in order, from directories:

```
/etc/dmARC_report/  
~/.config/dmARC_report/
```

with the settings in `~/.config/...` overriding any found in `/etc/...`. Command line options override config settings.

There are two config file formats supported. The older version 1 format uses 2 separate files:

- *config* - for `dmARC-rpt`
- *tls-config* - for `tls-rpt`

New version 2 format uses a single file, *config.v2*. Version 2 config will be used if its found. If only version 1 configs are found they will be automatically converted to version 2, which are used thereafter.

All config files use standard TOML format. Config files use 3 sections. A global section and one each for `dmARC` and `tls-rpt`.

Available config values are set using:

```
command_line_long_opt_name = xxx
```

e.g. to set data report dir use:

```
dir = "/foo/goo/dmARC_reports"
```

A sample config is available in the *conf.d* directory. A typical config might be of the form:

```
# comment  
[global]  
  theme = 'dark'  
  inp_files_disp = "save"  
  inp_files_save_dir = "../saved"  
  
[dmARC]  
  dom_ips = ['1.1.1.1', '1.2.2.0/24']  
  dir = "~/mail-reports/dmARC/xml"  
  
[tls]  
  dir = "~/mail-reports/tls/xml"
```

Variables set in *[dmARC]* or *[tls]* sections override any corresponding global ones.

This sample config says to read all the saved dmARC email reports from `~/mail-reports/dmARC/xml` and the TLS reports from `~/mail-reports/tls/xml`.

And to save the raw files after processing report by moving them to `~/mail-reports/dmarc/saved` or `~/mail-reports/tls/saved`.

For dmarc it says that ips listed in `dom_ips` are for your own domains.

Command line options override the corresponding config setting. See *Options* section for more detail.

1.3.3 dmarc-rpt

Change to the directory containing the one or more dmarc report files and simply run

```
dmarc-rpt
```

When using the `-dir` option (or config setting `dir`) it is not necessary to change directories before running the report.

Any email files, those ending with `.eml` will be processed first. These are assumed to contain the report as a mime attachment. The attachment is extracted from any such email files. Some mail clients save multiple emails as a single mbox file. Each email in the mbox file will be similarly processed and have the attached report extracted.

Then all remaining files are read and processed. The tool processes all xml and gzip/zip compressed xml dmarc report files and generates a human readable report.

We follow Postel's law and try to be liberal in what we accept as input. To that end we accept the dmarc XML report file, a gzip/zip compressed version of same or a saved email file text file with the report itself being a mime attachment.

Any file with extension `.eml` is treated as an email file.

To avoid line wrapping, the report should be viewed on wide enough terminal; roughly 112 or chars or more.

For convenience after report is generated, the input files can be automatically moved to a save direcorey, left where they are or removed. A typical sequents of events is to save the email reports, run dmarc-rpt. By auto moving (or removing) the input files, makes it simpler when doing the next batch of dmarc reports.

Then save all the raw `.eml` files into `~/dmarc/reports` and run the report.

All attachments from dmarc email reports would be saved into `~/dmarc/saved/2023-01` in this example.

1.3.4 tls-rpt

tls-rpt works in a similar way to dmarc-rpt, except it operates on TLS-RPT (compressed) xml inputs.

Command line options:

1.3.5 Common Options

These apply to both dmarc-rpt and tls-rpt:

-h, --help	show this help message and exit
-d, --dir DIR	Directory containing dmARC report files (xxx)
-ifd, --inp_files_disp WHAT	none, delete, save: disposition of input files. See -ifsd
↪ (save)	
-ifsd, --inp_files_save_dir DIR	When -ifd is save, input files moved here after report
↪ (./saved)	
-k, --keep	Keep .eml files extracted from attachment (False)
-thm, --theme THEME	Set color theme: dark, light, none (dark)
-v, --verb	Be more verbose

1.3.6 dmARC-rpt Additional Options

In addition to the common options:

-ips, --dom_ips NUM	Comma separated list of IPs / CIDRs for your own domains
-fdm, --dmARC_fails	DMARC Report - limit to failures
-fdk, --dkim_fails	DKIM Report - limit to failures
-fsp, --spf_fails	SPF Report - limit to failures

For example to have these IP addresses marked in the reports:

```
--dom-ips "1.1.1.0/24,2.2.2.16/29"
```

Or when used in the config file:

```
dom_ips = ['1.1.1.0/24', '2.2.2.16/29']
```

1.3.7 Saving Email Reports From Email Client

In most mail clients, such as thunderbird, one can select multiple email reports and then use *File -> Save* As to save the email files into a directory of your choosing. Each email gets saved with a .eml extension.

SMTP TLS-RPT

2.1 Overview

Generate a human readable tls report from one or more standard tls report files. These reports are used for a email domain with support for either DANE or MTA-STS or both.

2.1.1 Usage

Run from command line:

```
tls-rpt
```

Generates reports from one or more emailed tls reports. Similar to dmarc-rpt, the tool can consume email files (.eml) or the json attachments (plain or compressed) delivered as part of the usual mts-sts reports - and in directory specified by *inp_files_save_dir*.

tls-rpt is provided as part of the dmarc_report package

2.1.2 Background

TLS Reports are optionally generated for a mail domain when so requested by a TXT record in the domain's DNS. The tool parses and summarizes such email reports for human consumption.

SMTP TLS reporting is described by [RFC 8460]¹ where it summarizes:

A number of protocols exist for establishing encrypted channels between SMTP Mail Transfer Agents (MTAs), including STARTTLS, DNS-Based Authentication of Named Entities (DANE) TLSA, and MTA Strict Transport Security (MTA-STS).

MTA-STS, is explained by [RFC 8641]² where it is summarized:

SMTP MTA Strict Transport Security (MTA-STS) is a mechanism enabling mail service providers (SPs) to declare their ability to receive Transport Layer Security (TLS) secure SMTP connections and to specify whether sending SMTP servers should refuse to deliver to MX hosts that do not offer TLS with a trusted server certificate.

¹ TLS Report [RFC 8460] <https://www.rfc-editor.org/rfc/rfc8460.txt>

² MTA-STS [RFC 8641] <https://www.rfc-editor.org/rfc/rfc8641.txt>

while DANE is documented in [RFC 6698]³, [RFC 7671]⁴ and [RFC 7672]⁵

Encrypted communication on the Internet often uses Transport Layer Security (TLS), which depends on third parties to certify the keys used. This document improves on that situation by enabling the administrators of domain names to specify the keys used in that domain's TLS servers. This requires matching improvements in TLS client software, but no change in TLS server software

2.2 Discussion

To receive TLS reports requires a DNS record requesting a TLS report along with either a DANE TLSA record or MTA-STS. MTA-STS requires both a policy and and a DNS record.

2.2.1 TLS Report DNS Record

Example:

```
_smtp._tls.example.org IN TXT "v=TLSRPTv1; rua=mailto:tlsrpt@example.com"
```

The TLS reports will be sent to the email provided by the string following *rua*=. In this example reports would be sent to *tlsrpt@example.com*.

2.2.2 MTA-STS

Requires both a DNS record and a policy file available from the email's domain web server.

Policy file example to be provided by web server:

```
https://mta-sts.example.com/.well-known/mta-sts.txt
```

The policy mode can be set to *enforce* or *testing*. Example *mta-sts.txt* file:

```
version: STSv1
mode: enforce
mx: example.com
mx: *.example.com
max_age: 1296000
```

DNS TXT record example:

```
_mta-sts.example.org. IN TXT "v=STSv1; id=202301011200;"
```

2.2.3 DANE TLSA

DNS record example:

```
_25._tcp.example.com. TLSA 3 1 1 (xxx)
```

where xxx would be the appropriate public key hash.

³ DANE [RFC 6698] <https://www.rfc-editor.org/rfc/rfc6698.txt>

⁴ DANE [RFC 7671] <https://www.rfc-editor.org/rfc/rfc7671.txt>

⁵ DANE SMTP [RFC 7672] <https://www.rfc-editor.org/rfc/rfc7672.txt>

2.3 Using tls-rpt

Save all tls email reports into a directory. Change to the directory containing one or more dmarc report files and simply run

```
tls-rpt
```

Using the `-dir` option (or setting the config option *dir*) makes unnecessary to change directories before running the report.

Any email files, those ending with *.eml* will be processed first. These are assumed to contain the dmarc report as a mime attachment. The attachment is extracted from such email files.

Subsequently, all remaining files are read and processed. The tool processes all json and gzip/zip compressed json tls report files and produces a human readable report.

Any file with extension *.eml* is treated as an email file.

For convenience after report is generated, the input files can be automatically moved to a save direcorey, left where they are or removed. A typical sequents of eveents is to save the email reports, run dmarc-rpt. By auto moving (or removing) the input files, makes it simpler when doing the next batch of dmarc reports.

For example, you might save all *.eml* files in same directory and with config settings:

```
dir = "~/tlsrpt/reports"
inp_files_disp = "save"
inp_files_save_dir = "../saved"
```

Then save all the raw *.eml* files into `~/tlsrpt/reports` and run

```
tls-rpt
```

All attachments from email reports would be saved into `~/tlsrpt/saved/2023-01` in this example.

2.3.1 tls-rpt Options

Options are read first from config files then command line. Config files are read from `/etc/dmarc_report/config-tls` then `~/config/dmarc_report/config-tls`. Config files are in standard TOML format.

Config settings use corresponding command line option:

```
long-option = xxx.
```

e.g. to set data report dir in config use

```
dir = /foo/goo/other
```

The command line options:

<code>-h, --help</code>	show this help message and exit
<code>-d, --dir DIR</code>	Directory containing dmarc report files (xxx)
<code>-ifd, --inp_files_disp WHAT</code>	none, delete, save: disposition of input files. See <code>-ifsd</code>

(continues on next page)

(continued from previous page)

```
↪ (save)
-ifsd, --inp_files_save_dir DIR    When -ifd is save, input files moved here afer report
↪ (../saved)
-k, --keep                        Keep .eml files extracted from attachment (False)
-thm, --theme THEME               Set color theme: dark, light, none (dark)
-v, --verb                        Be more verbose
```

2.3.2 Saving Email Reports From Email Client

In most mail clients, such as thunderbird, one can select multiple email reports and then use *File -> Save As* to save the email files into a directory of your choosing. Each email gets saved with a *.eml* extension.

2.3.3 License

Created by Gene C. It is licensed under the terms of the GPL-2.0-or-later license.

- SPDX-License-Identifier: GPL-2.0-or-later
- Copyright (c) 2023, Gene C

3.1 Dependencies

- Run Time: * python (3.14 or later) * python-dateutil * python-lxml * py-cidr (2.7.0 or later) * tomli-w (for writing version 2 configs converted from version 1)
- Building Package: * git * meson * meson-python - rsync

3.2 Available

- On [Github](#)
- On [Archlinux AUR](#)

3.3 Installation

On Arch you can build using the PKGBUILD provided in packaging directory or from the AUR package. To build manually, clone the repo and then:

```
./scripts/do-build  
./scripts/do-install <destination-dir>
```

3.4 License

Created by Gene C. and licensed under the terms of the GPL-2.0-or-later license.

- SPDX-License-Identifier: GPL-2.0-or-later
- Copyright (c) 2023, Gene C