
kea-config Documentation

Release 6.5.1

Gene C

Sep 05, 2026

DNS-TOOLS MANUAL

1	kea-config	1
1.1	Overview	1
1.2	Latest Changes	2
1.3	Using kea-config	2
2	Appendix	7
2.1	Installation	7
2.2	Dependencies	7
2.3	Discussion and Next Steps	7
2.4	Older Changes	8
2.5	License	8

KEA-CONFIG

1.1 Overview

What is kea?

kea is a modern dhcp server from [ISC](#) which supercedes their older dhcp software.

kea offers a nice feature set including the ability to have a hot standby to pick up in case the primary is unavailable.

However, it's power lurks behind a complicated configuration suite that, at least for me, is not terribly human friendly.

Perhaps most notable is that each of the servers requires it's own separate configuration and keeping them all synchronized can be a bit of a chore and naturally is prone to human error unless a tool is used to ensure each server config is consistent.

What is kea-config?

kea-config provides the tool that has a single configuration input file from which it generates the native kea configuration files.

By using a single configuration we guarantee that the configs kea needs for the primary, standby and backup servers are always consistent with one other.

kea-config also has the convenience of doing DNS lookups for any host reservations, meaning the IP host reservations are specified by hostname and the IP, from DNS lookup, is then output for *kea-dhcp4* to use..

kea-config supports **kea-dhcp4** and its companion control agent.

Contents

- [Overview](#)
- [Latest Changes](#)
- [Using kea-config](#)
- [Configuration](#)
- [Appendix](#)

Please Note:

An Archlinux package can be built using the PKGBUILD from the packaging directory or from the AUR. All git tags are signed with arch@sapience.com key which is available via WKD or download from [sapience website](#). Add the key to your package builder gpg keyring. The key is included in the Arch package and the source= line with *?signed* at the end can be used to verify the git tag. You can also manually verify the signature

1.2 Latest Changes

6.5.1

- switch to meson/meson-python for build/package management
- add pytest checks and checkdepends on pytest

1.3 Using kea-config

kea-config depends on python, dnspython and ruamel-yaml.

To use it after installation, copy a sample config file from the *examples* dir and modify appropriately for your use case. When ready run it to generate the set of input files for *kea* to use:

```
kea-config -c <your-config.yaml>
```

It can also be run from the git source repo:

```
PYTHONPATH=src src/kea_config_mod/apps/kea-config.py -c <your-config.yaml>
```

The yaml config also specifies the directory where the outputs are to be written.

For each (active) server section (primary, standby and backup), it creates one configuration file to for use by *kea-dhcp4* and one for *kea-ctrl-agent* (the control agent).

The *primary* server must be provided in the input config file, while *standby* and *backup* servers are optional.

For example, the resulting kea configs for the primary server will be written to the directory specified by *conf_dir*:

```
kea-ctrl-agent-primary.conf
kea-dhcp4-primary.conf
```

Similarly for standby and/or backup servers if so requested. Each pair of files is to be used on the corresponding server. e.g The 2 primary files are for use on the *kea-dhcp4* primary server.

One simple way to manage these is to copy the entire *conf_dir* to each server */etc/kea/* and use symlinks */etc/kea/* pointing to appropriate primary, standby or backup config.

e.g. */etc/kea* on primary could have:

```
kea-dhcp4.conf -> <conf_dir>/kea-dhcp4-primary.conf
kea-ctrl-agent.conf -> <conf_dir>/kea-ctrl-agent-primary.conf
```

Note that if the input config, *xxx.conf*, passed to

```
kea-congig -c xxx.conf
```

is a pre-6.0 (*.conf*) file, then a *xxx.yaml* version will be written in the same directory.

The yaml file should be used thereafter. You may want to check it and/or add comments. Unfortunately any comments in the old config will be lost in the automatic conversion to yaml (my apologies).

1.3.1 Configuration

Config files are in YAML. Earlier versions used TOML. As mentioned above, version 6.0 of *kea-config* will automatically convert these to the new yaml format.

In yaml, comments begin with '#' and can be at for an entire line or part of a line.

Two example config files are provided in the *examples* directory and make a good starting template. The installer script puts these into `/usr/share/kea-config/examples`.

One of the examples has a primary server serving DHCP over a single network interface. It includes a high availability standby server as well as a backup server.

The second example expands on the first one, and introduces a second subnet that is on a separate network interface. This offers IPs out of pools belonging to the second subnet.

Each server configuration must have an *interfaces*: variable that is a list of (*interface*, *subnet*) pairs. That server is then able to offer DHCP for each subnet over its companion interface.

While the primary server is distinctive in being required, any server may provide 2 (or more) subnets. In the example, the primary server has 2 subnets.

For testing purposes, it can be useful to run:

```
kea-dhcp4 -t kea-dhcp4-xxx
# or
kea-dhcp4 -T kea-dhcp4-xxx
```

using the corresponding output *kea-dhcp4-xxx* file for the server the test is run on. Since *kea-dhcp4* validates not only the syntax, but also subnets and network interfaces, this test must be run on the actual server.

Please see the examples for full details. Below is a summary of the main parts of the *kea-config* input file.

```
---
# config snippet
title: Example 1 Config
conf_dir: Example-1
ctrl_agent_port: '8762'
socket_dir: /var/run/kea
global_options:
  domain_name_servers:
    - 10.1.0.10
    - 10.1.0.11
    - 10.1.0.12
  domain_name: sub1.example.com
  domain_search:
    - sub1.example.com
    - foo.com
  ntp_servers:
    - 10.1.0.10
    - 10.1.0.14
  min_valid_lifetime: 14400
  valid_lifetime: 28800
  max_valid_lifetime: 57600
servers:
  primary:
    hostname: server1.sub1.example.com
    port: '8761'
    auth_user: kea-ctrl
    auth_password: xxxSecretHotSauce
    stype: primary
    subdomain: sub1.example.com
    active: true
    interfaces:
```

(continues on next page)

(continued from previous page)

```
-
- eno1
- 10.1.0.0/24
standby:
  hostname: server2.sub1.example.com
  ...

backup:
  hostname: server3.sub1.example.com
  ...

nets:
  // first subnet
  10.1.0.0/24:
    pools:
      - 10.1.0.72 - 10.1.0.95
      - 10.1.0.193 - 10.1.0.250
    subnet: 10.1.0.0/24
    option_data:
      broadcast_address: 10.1.0.255
      routers: 10.1.0.1
      ntp_servers:
        - 10.1.0.10
        - 10.1.0.14
    reserved:
      ap0:
        hw_address: cc:aa:aa:aa:aa:01
      bob_laptop:
        hw_address: cc:aa:aa:aa:aa:02
      web_serv1:
        hw_address: cc:aa:aa:aa:aa:03
      subdomain: sub1.example.com
  // second subnet
  10.2.0.0/24:
    ...
```

It should be pretty self-explanatory.

- *title:*

For human use only - not used by kea-config.

- *conf_dir:*

Directory where generated kea configs reside. What I do is rsync this directory to /etc/kea/ on each kea server. Each server then has a soft link to its own specific config. For example on my primary server I have

- *global_options:*

This section provides common dhcp information to be shared with dhcp clients: It is generally better for each *net* section to have it's own.

- *servers:*

Provides the information needed for the each server. Primary is required while standby and backare are optional. Having a standby server is strongly recommended for high availability.

- *nets*

This section describes one or more networks to offer DHCP. Each section has the subnet, sub-domain, pool of IP addresses and so on for that network.

Any server offering a network, must have that subnet on one of it's network interfaces and every interface it will serve DHCP on, must be listed in the server's interface section.

Each subnet has it's own list of IP host reservations which are provided by short form *hostname* and it's MAC (hardware) address. Local DNS is used to lookup each host's IP address from it's hostname. Please be sure that any host in the reservation list can have it's IP retrieved via DNS

2.1 Installation

Available on * [Github](#) * [Archlinux AUR](#)

On Arch you can build using the PKGBUILD provided in packaging directory or from the AUR package.

Listing 1: Manual Install

```
./scripts/do-build  
./scripts/do-build <destination-directory>
```

2.2 Dependencies

- Run time
 - python
 - dnspython
 - ruamel-yaml
- Building Package:
 - git
 - meson
 - meson-python
 - rsync

2.3 Discussion and Next Steps

This version is for kea-dhcp4 (IPv4).

Most but not every available kea option is supported by kea-config. For example the high availability component of kea allows for either hot-standby or load balancing. At present we support hot standby only. Hot standby has one server at a time actively serving clients, whereas in load balancing case both servers are servicing clients at same time.

To create a version for kea-dhcp6, for example where a firewall is responsible for passing prefix delegation to the internal hosts, one needs an IPV6 internet connection; I am unable to work on this at the moment. It may also have significantly less utility than IPv4 dhcp.

kea-config is distro agnostic but I do maintain an Archlinux package on the AUR.

2.4 Older Changes

Please see the Changelog's in Docs directory for full history.

- Code Reorg
- Switch packaging from hatch to uv
- Testing to confirm all working on python 3.14.2
- License GPL-2.0-or-later
- Code re-org/cleanup.
- Code now complies with PEP-8, PEP-257 and PEP-484 style and type annotations
- Socket dir now defaults to `/var/run/kea`.

We prefer `/run/kea` per Linux FHS, but since kea version 2.7.9 requires the path to be `/var/run/kea/`. See [kea docs](#). There is a config option, `socket_dir`, to set this as well.

- Multiple gateway routers. option-data routers can now be a list of gateways.
- Add output option “calculate-tee-times” : true (replaces explicit renew-timer, rebind-timer)
- Add output option: “offer-lifetime”: 60
- Add global input options: “min-valid-lifetime”, “valid-lifetime”, “max-valid-lifetime”

These can be overridden at the subnet level

- If some lifetimes are set, missing ones are imputed using:
$$\text{min-valid-lifetime} = \text{valid-lifetime} / 2 \quad \text{max-valid-lifetime} = \text{valid-lifetime} * 2$$
- reservations : use FQDN for hostname. Hostname must be requested by client for kea to send it.
- kea has deprecated the option *reservation-mode* for versions of kea newer than 2.4. We have now removed this option from *kea-config* generated output.

2.5 License

Created by Gene C. and licensed under the terms of the GPL-2.0-or-later license.

- SPDX-License-Identifier: GPL-2.0-or-later
- SPDX-FileCopyrightText: © 2022-present Gene C <arch@sapience.com>