py-cidr Reference Documentation

Release 5.0.5

Gene C

Oct 05, 2026

API REFERENCE GUIDE:

1 py-cidr **1**
- 1.1 Overview . . . 1
- 1.2 Key features . . . 1
- 1.3 Manual . . . 2
- 1.4 Getting Started . . . 2
- 1.5 More Detail . . . 2

2 API Reference Guide **5**
- 2.1 PyCidr Class . . . 5
- 2.2 Cidr Class . . . 12
- 2.3 File Utilities . . . 22
- 2.4 Cidr Map . . . 24

3 Migrating from Cidr to PyCidr **27**

4 Appendix **29**
- 4.1 Installation . . . 29
- 4.2 Dependencies . . . 29
- 4.3 License . . . 30
- 4.4 AI Tooling . . . 30

Python Module Index **31**

Index **33**

CHAPTER

ONE

PY-CIDR

1.1 Overview

py-cidr is a python module with a variety of networking / CIDR tools.

1.2 Key features

- PyCidr (As of version 5.0) is now the preferred class.
  Very fast version that uses compiled C-code to do most of the work.
  Using compiled C-code is simple, clean, robust, very maintainable and is compiled with modern, restrictive compiler and linker flags.
  All CIDR and IP addresses are strings.
  Depends on two new packages:
  - cidrtools-cffi: github and AUR.
  - cidrtools: github and AUR.

  cidrtools-cffi has python bindings to the *cidrtools* compiled library.
- Cidr class is still upported.
  It uses Python's own *ipaddress* module.
  We decided to leave the Cidr class untouched. The primary reason is that this makes it straghtforward to compare with PyCidr.
  So, at least for now, the performance boost requires migrating from Cidr to PyCidr. At some point, we may update the Cidr class to take advantage of the very fast *cidrtools* library as well.
- *py_cidr* has four Classes : PyCidr, Cidr, CidrMap, CidrFile
  - PyCidr does everything Cidr class does just a lot faster.
    It is built on top of the compiled library *libcidrtools.so*. The API has changed a little from the *Cidr* class and is, hopefully, a little simpler and cleaner. One of the benefits (and drawbacks) of starting fresh.
  - PyCidr and Cidr offer a number of useful operations on IP addresses and network blocks.
    * Support for both IPv4 and IPv6
    * Compact a list of CIDRs to smallest set of CIDR blocks
    * Convert an range of IP addresses to a list of CIDRs
    * Exclude one list of cidr blocks from another list.
    * Split a CIDR block in a list of *smaller* CIDRs blocks with a larger prefix.
    * Identify and validate

        * more

- CidrFile reads and writes text files with lists of cidrs.
  - skips shell style comments when reading
  - Uses atomic file writes
- CidrMap is a way to map cidr strings to values.
  For example mapping IP prefixes (cidr blocks) to their ISO country codes.
  - File writes use locking to ensure multiple processes handle cached files correctly.
  - Built on Patricia trees using the patricia26 module. particia26 is extremely fast.

See API reference documentation for details.

1.3 Manual

There are pre-built versions of of the manual which comes as a PDF file as well as an HTML version. The manual includes the API reference guide for all classes.

The docs are in *src/data/docs* and the Arch PKGUILD installs them to */usr/share/py-cidr/docs*.

1.4 Getting Started

All git tags are signed with arch@sapience.com key which is available via WKD or download from https://www.sapience.com/tech. Add the key to your package builder gpg keyring. The key is included in the Arch package and the source= line with *?signed* at the end can be used to verify the git tag. You can also manually verify the signature

1.5 More Detail

The following are part of the module.

CidrMap Class

CidrMap provides an optimized tool to map a network-prefix to a value. The map may be saved to a (cache) file and reused.

To make use of the file cache, provide a *cache_directory* when instantiating the class.

Note that there are 2 typed of maps, non-compact and compact. The default and by far the most common is non-compact. Here, every (prefix, value) is added to the map.

If the data is available as a list of (prefix, value) tuples, then the best and fastest way is using very fast *bulk_insert* to get the data into the Patricia tree.

Bulk inserting is 2 - 3 times faster than inserting the data in a loop one at a time. For large maps it is hugely benficial to use bulk_intert().

For a compact map, effort is made to reduce redundant entries. For example if the map contains the (prefix, tuple) = ('10.0.0.0/22', 'net-1') and then a new tuple ('10.0.0.0/24', 'net-1') is added to the map, the

new one is considered redundent since the network is a subnet of *'10.0.0.0/22'* and the value, *'net-1'* is the same. If the value was different, then it is deemed not compactable. Note that bulk_insert() is not available with *compact* maps.

A *CidrMap* contains 2 separate maps one for each network family; one tree for IPv4 and separate one for IPv6.

Ths will create both an IPv4 and an IPv6 cache file in the given directory. The code is careful about reading and writing the cache files and uses locking and atomic writes to ensure the integrity of the data.

For example if application starts, reads cache, updates with new items and some time later saves the cache - the module will detect if the cache changed (by another process using same cache directory) since it was last read in, and merge its own changes with the changes in the cache file before writing out the updated cache. This should ensure nothing gets lost.

This was built this originally for our firewall tool, where part of the data gathering component creates maps of network prefixes (blocks of IP addresses) to geolocated country codes and other useful information such as the ASN(s) the prefix belongs to.

When looking up a CIDR, there are 2 methods available. The first, *lookup_lmp()* returns the (lmp_prefix, val) pair where *lmp_prefix* is the network with the longest matching cidr prefix. The longer the cidr prefix, the more specific the network. A */24* os more specific than a */22* for example.

The method *lookup_all()* returns every matching prefix and its associated value. the LMP is always the first element in returned in the list.

Since parallelizing often provides decent speedups, *CidrMap* provides a mechanism to do that. It allows each separate process or thread to work with private (thread local) cache. Each of the private data caches can then be merged together by the top level process or thread.

This avoids multiple threads/processes writing to the same in memory data at the same time. This is done using the *CidrMap::merge()* method.

Additional details are available in the API reference documentation.

Methods provided:

- CidrMap.add_prefix_val()
- CidrMap.add_prefix_vals()
- CidrMap.lookup_lmp()
- CidrMap.lookup_all()
- CidrMap.items()
- CidrMap.save_cache()
- CidrMap.merge()

Static functions: * CidrMap.create_private_cache()

PyCidr Class

See the API reference in the documentation for details. This class provides a suite of tools we found ourselves using often, so we encapsulated them in this class. All methods in the class are *@staticmethod* and thus no instance of the class is needed. Just call them as you would any function (*PyCidr.xxx()*).

IP addresses and networks are always represented as strings.

Here is a sample of some of the available functionality, see the API doc for complete documentation.

- PyCidr.compact()
- PyCidr.cidr_parts()
- PyCidr.exclude_cidrs()
- PyCidr.is_subnet()
- PyCidr.set_prefix()
- PyCidr.sort()
- PyCidr.get_host_bits(), format_host_bits()
- PyCidr.cidr_to_range(), range_to_cidrs()
- PyCidr.fix_host_bits()
- PyCidr.clean_cidr(), clean_cidrs()
- PyCidr.split_by_iptype()
- PyCidr.num_ips()
- PyCidr.ip_version()
- PyCidr.is_valid_ipv4(), is_valid_ipv6, is_valid_cidr()
- PyCidr.subnets_split()

CidrFile Class

This class provides a few reader/writer tools for files with lists of CIDR strings. Readers ignores comments. All methods are *@staticmethod* and thus no instance of the class is required. Simply use them as functions (*Cidr.xxx()*)

- Cidr.read_cidr_file(file:str, verb:bool=False) -> [str]:
- Cidr.read_cidr_files(targ_dir:str, file_list:[str]) -> [str]
- Cidr.write_cidr_file(cidrs:[str], pathname:str) -> bool
- Cidr.read_cidrs(fname:str|None, verb:bool=False) -> (ipv4:[str], ipv6:[str]):
- Cidr.copy_cidr_file(src_file:str, dst_file:str) -> None

Cidr Class

Quite similar to PyCidr but not identical. See the API Reference Guide for more details.

CHAPTER

TWO

API REFERENCE GUIDE

Cidr is the original class and over time it's API has grown in part to maintain backward compatibility and in part it has a dual personality. It is built on top of Python's native *ipaddress* class and ended up supporting network input/output in both string and *ipaddress* format.

PyCidr is designed for performance and simplicity. It only uses strings for IP address and CIDR blocks. The code is writein in Cython/C-code and is significantly faster than the Cidr class variants. For example, our tests show compacting a list of CIDRs to the smallest number runs 18 to 22 times faster.

We recommend migrating to PyCidr. This is completely optional. The Cidr class remains supported. If you choose to migrate then it means using strings only (no ipaddress). If code is already strings the migration is pretty straight forward and there is a quick guide how to do so.

The next section has the auto-generated API reference.

2.1 PyCidr Class

2.1.1 PyCidr: Overview

Before getting into detail, this is a brief summary of the member functions available. All member functions are *static* and therefore the member functions are called directly using PyCidr.xxx() - no need to instantiate the class.

- compact()
  Takes a list of cidrs and returns a new list with the smallest number of cidrs that span exactly the space as the original list.
- cidr_parts()
  Separates a cidr into the IP part and its prefix.
  Example:

```
cidr_parts("10.0.0.0/24")     -> ("10.0.0.0", 24)
cidr_parts("10.0.0.27/32")    -> ("10.0.0.27", 32)
cidr_parts("2001:db8::1/64")  -> ("2001:db8::", 64)
```

- exclude_cidrs()
  Exclude one list of cidrs from another.

```
smaller = PyCidr.exclude_cidrs(all_cidrs, excluded_cidrs)
```

- is_subnet()
  Determine if a cidr block is a subnet of any of a list of networks.

```
all_cidrs = ['10.0.0.0/24', ... ]
is_subnet = PyCidr.is_subnet('10.0.0.22/32', all_cidrs)
```

- set_prefix()
  Change the prefix (or add a prefix to an IP address).

```
cidr = '10.0.0.0/24'
new_cdr = PyCidr.set_prefix(cidr, 22)
```

- sort()
  Sorts a list of network blocks.

```
sorted_items = PyCidr.sort(all_cidrs)
```

- get_host_bits(), format_host_bits()
  Extracts the host bits of an IPv4 or IPv6 CIDR string and returns either an integer or human readable string from format_host_bits.

```
hbit_str = PyCidr.format_host_bits("10.0.0.22/24)")  # -> "0.0.0.22"
```

- cidr_to_range(), range_to_cidrs()
  cidr_to_range returns the first, last and middle ip address of a cidr, while range_to_cidrs() generates the list of network cidrs that span a range of IPs from first to last.
- fix_host_bits()
  Sometimes a cidr has host bits set, this 0's them out. For example "10.0.0.22/24" would return "10.0.0.0/24"
- clean_cidr(), clean_cidrs()
  Clean one cidr or a list of cidrs. A clean cidr is one that has 0 for host bits For example:
  10.1.2.3/24 -> 10.1.2.0/24
- split_by_iptype()
  Takes a list of cidrs, can be mixed IPv4 and IPv4 and separates the IPv4 from the IPv6 blocks. It returns a tuple of [ipv4_cidrs, ipv6_cidrs]
- num_ips()
  Returns the number of IPs in a cidr block.
- ip_version()
  If cidr is IPV4 then this returns the integer *4*. If an IPv6 then retutns *6*.
- is_valid_ipv4(), is_valid_ipv6, is_valid_cidr()
  They each return True or False as appropriate.
- subnets_split()
  Splits an IPv4 or IPv6 CIDR block into smaller subnets of a larger prefix size.
  Examples:

```
subnets_split("10.0.0.0/23", 24)    -> ["10.0.0.0/24", ""10.0.1.0/24")
```

PyCidr provides a suitr of common network CIDR utilities

- PyCidr works esclusively with strings. This contrasts with the older Cidr class which also supports Python's ipaddress.

class py_cidr.pycidr_class.**PyCidr**

Bases: object

Provides a suite of network CIDR tools using the cidrtools compiled library.

All mathods are static and are called without need to instantiate the class. For example:

new_cidrs = PyCidr.compact(cidrs)

It does not use or support any data types from ipaddress (far too slow)

static cidr_parts(*cidr: str*) → tuple[str, int]

Unified entry point splitting any valid IPv4 or IPv6 CIDR block into a clean base network address string and its integer prefix length.

Examples

cidr_parts("10.0.0.22/24") -> ("10.0.0.0", 24) cidr_parts("2001:db8::1/64") -> ("2001:db8::", 64)

Parameters
cidr – The cidr string to examine

Returns
Tuple of (ip-address, prefix)

static cidr_to_range(*cidr: str*) → tuple[str, str, str]

Cidr string to an IP Range : (First, Middle, Last) IPs

Parameters
cidr – The cidr string to examine.

Returns
A tuple (ip0, mid, ip1) First, Middle and Last IP address of the cidr block.

static cidrs_intersection(*cidrs1: list[str]*, *cidrs2: list[str]*) → list[str]

Returns the intersection subnets of 2 lists of cidrs.

Parameters

- **cidrs1** – First set of cidrs
- **cidrs2** – Second set of cidrs

Returns
List of the intersecting subnets (may be empty).

static clean_cidr(*cidr: str*) → str

Clean up a cidr address.

What it does:

- Ensures host bits are set to zero to match the prefix.
- Ensure the prefix is appropriate for the IP family, bounded by /32 or /128 for IPv4 or IPv6.
- Non-cidr (bad) strings are set to ‘’

Parameters
cidr – Cidr string to clean up.

Returns
cidr string if valid (empty if not valid)

static clean_cidrs(*cidrs: list[str]*) → list[str]

Takes a list of raw input CIDR strings, filters out any invalid items entirely, and returns a clean list of canonical networks with corrected host bits. Skips invalid entries completely instead of leaving them as empty strings.

Parameters
cidrs – List of cidr strings to be cleaned

Returns
New list of cidrs that are now clean. Bad cidrs are returned as empty strings.

static compact(*cidrs: list[str]*) → list[str]

Compact list of cidrs - can be mixed ipv4/ipv6. Returns 1 type, making type annotation simpler for caller.

Parameters
cidrs – Input list of cidr strings.

Returns
Compacted list of cidrs. If mixed ipv4 is before ipv6

static ct_version() → str

Returns
The cidrtools library version

static exclude_cidrs(*all_cidrs: list[str]*, *excluded_cidrs: list[str]*) → list[str]

Return new list of cidrs made by removing all excluded_cidrs from all_cidrs. Safely segregates mixed stacks to prevent invalid cross-version failures.

Parameters
all_cidrs – The full list of cidrs

Excluded_cidrs
The cidrs to be removed from the full list

Returns
Mew list of cidrs after the excluded_cidrs are removed.

static fix_host_bits(*cidr: str*) → str

Ensures that host bits in an IPv4 or IPv6 CIDR string are set to 0.

Examples

"10.0.0.22/32" -> "10.0.0.22/32" "10.0.0.22/24" -> "10.0.0.0/24"

A strictly valid cidr address must have host bits set to zero.

Parameters
cidr – The cidr to "fix" if needed.

Returns
The cidr with any non-zero host bits now zeroed out.

static format_host_bits(*cidr: str*) → str

Extracts the host bits of an IPv4 or IPv6 address by masking off the network bits defined by the prefix.

alias of get_host_bits().

Parameters
cidr – The cidr to examine.

Returns
String with network bits zero showing host bit.

static get_host_bits(*cidr: str*) → str

Extracts the host bits of an IPv4 or IPv6 address by masking off the network bits defined by the prefix.

Parameters
cidr – The cidr to examine.

Returns
String with network bits zero showing host bit.

static ip_type(*cidr: str*) → str

Determines if address string is valid ipv4 or ipv6 or not.

Parameters
cidr – ip address or cidr string

Returns
'ip4' or 'ip6' or empty string, '', if invalid address

static ip_version(*cidr: str*) → int

Determines the IP version number (4 or 6 or 0 if neither)

Parameters
cidr – IP addess or cidr string.

Returns
4 if IPv4, 6 if IPv6, 0 otherwise

static is_rfc_1918(*cidr: str*) → bool

Check if cidr is any RFC 1918.

Parameters
cidr – IP or Cidr to check if RFC 1918.

Returns
True if cidr is an RFC 1918 address, False if not.

static is_subnet(*cidr: str*, *cidrs: list[str]*) → bool
Check if cidr is a subnet of any of the list of IPvxNetworks .

Parameters

- **cidr** – Cidr string to check.
- **cidrs** – list of network blocks to check.

Returns
True if cidr is subnet of any of the cidrs list, else False.

static is_valid_cidr(*cidr: str*) → bool
Check if string is valid cidr or IP address (either IPv4 or IPv6) Equivalen to - is_valid_ipv4(cidr) or is_valid_ipv6(cidr)

Param
Address to check. Host bits set is permitted for a cidr network.

Returns
True/False if address is valid IPv4 or IPv6 address or network.

static is_valid_ipv4(*cidr: str*) → bool
Check if input is a valid IPv4 cidr or IP address

Parameters
cidr – Check if this cidr is valid.

Returns
True if valid IPv4 else False

static is_valid_ipv6(*cidr: str*) → bool
Check if input is a valid IPv6 cidr or IP address

Parameters
cidr – Check if this is a valid IPv6 address or cidr.

Returns
True if valid IPv6 else False

static num_ips(*cidr: str*) → int
Returns the number of IP addresses in the cidr block.

Parameters
cidr – The cidr to examine

Returns
The number of IP addresses in the range. For IPv6 This number is capped at 2^64 (pee cidrtools library)

static range_to_cidrs(*start_ip: str*, *end_ip: str*) → list[str]

Generate a list of cidrs from an IP range.

Parameters

- **start_ip** – First IP in range
- **end_ip** – Last IP in range

Returns

list of cidr network blocks representing the IP range.

static remove_rfc_1918(*cidrs: list[str]*) → list[str]

Given list of cidrs, return list without any rfc 1918.

Parameters

cidrs – list of cidr strings.

Returns

List of cidrs with any RFC 1918 addresses removed.

static rfc_1918_cidrs() → list[str]

Return list of rfc 1918 networks cidr strings

Returns

list of RFC 1918 networks as cidr strings

static set_prefix(*cidr: str*, *prefix: int*) → str

Set new prefix for cidr and return new cidr string.

Parameters

cidr – Cidr string to use

Prefix

The new prefix to use

Returns

Cidr string using the specified prefix

static sort(*cidrs: list[str]*) → list[str]

Sort the list of cidr strings.

Parameters

cidrs – list of cidrs.

Returns

Sorted copy of cidr list

static split_by_family(*cidrs: list[str]*) → tuple[list[str], list[str]]

Split a list of cidrs into ipv4 and ipv6 lists.

Parameters

cidrs – list of cidr strings

Returns

Tuple of an ipv4 cidr list and an ipv6 cidr list

static split_by_iptype(*cidrs: list[str]*) → tuple[list[str], list[str]]

Split a list of cidrs into ipv4 and ipv6 lists. Historical Alias of split_by_family()

Parameters
cidrs – list of cidr strings

Returns
Tuple of an ipv4 cidr list and an ipv6 cidr list

static subnets_split(*cidr: str*, *new_prefix: int*) → list[str]

Splits an IPv4 or IPv6 CIDR block into smaller subnets of a larger prefix size. If the new prefix is smaller or equal to the existing one, returns the original CIDR.

Examples

subnets_split("10.0.0.0/23", 24) -> ["10.0.0.0/24", ""10.0.1.0/24")

Parameters

- **cidr** – the cidr to work on
- **new_prefix** – the prefix to use to split cidr into smaller subnets

Returns
list of subnets - if compacted will be the input cidr block.

static version() → str

Returns
Returns the py-cidr Version

2.2 Cidr Class

Class providing some common CIDR utilities

class py_cidr.cidr_class.**Cidr**

Bases: object

Provides suite of CIDR tools.

All mathods are (static) and are thus called without need to instantiate the class. For example:

net = Cidr.cidr_to_net(cidr_string)

Notation:

- cidr means a string
- net means ipaddress network (IPv4Network or IPv6Network)
- ip means an IP address string
- addr means an ip address (IPv4Address or IPv6Address)
- address means either a IP address or a cidr network as a string

static address_iptype(*addr: IPvxAddress | IPvxNetwork*) → str

Identify address or net (IPvxNetwork) as ipv4, ipv6 or neither.

Parameters
addr – ipaddress IP or network .

Returns
'ip4', 'ip6' or ''

static address_to_net(*addr: IPAddress | IPvxNetwork*, *strict: bool = False*) → IPvxNetwork | None

Convert an address to IPvxNetwork.

Be flexible with input address. Can be IPAddress (includes string) or even IPvxNetwork.

Parameters

- **addr** – Input address.
- **strict** – If true then cidr is considered invalid if host bits are set. Defaults to False. (see ipaddress docs).

Returns
The IPvxNetwork derived from input "addr" or None if not an address/network.

static addresses_to_ips(*addresses: list[IPvxAddress]*) → list[str]

From list of IPs in ipaddress format, get list of ip strings.

Parameters
addresses – list of IP addresses in ipaddress format

Returns
list of IP strings

static cidr_exclude(*cidr1: str*, *cidrs2: list[str]*) → list[str]

Exclude cidr1 from any of networks in cidrs2.

Parameters

- **cidr1** – cidr to be excluded.
- **cidrs2** – list fo cidrs from which cidr1 will be excluded.

Returns
Resulting list of cidrs ("cidrs2" - "cidr1")

static cidr_iptype(*address: Any*) → str

Determines if address string is valid ipv4 or ipv6 or not.

Parameters
address – address or cidr string

Returns
'ip4' or 'ip6' or empty string, '', if address invalid. Note. Earlier versions returned None instead of empty string if unable to be converted.

static cidr_is_subnet(*cidr: str*, *ipa_nets: list[IPvxNetwork]*) → bool

Check if cidr is a subnet of any of the list of IPvxNetworks .

Parameters

- **cidr** – Cidr string to check.
- **ipa_nets** – list of IPvxNetworks to check.

Returns

True if cidr is subnet of any of the ipa_nets, else False.

static cidr_list_compact(*cidrs: list[str]*, *string: bool = True*) → list[str] | list[IPvxNetwork]

Compact list of cidr networks to smallest list possible. Deprecated - use compact_cidrs(cidrs, return_nets)) instead, it is the same with the boolean flag reversed.

Parameters

cidrs – list of cidr strings to compact.

String

If True (default), then return is a list of strings. If False, a list of IPvxNetworks.

Returns

Compressed list of cidrs as ipaddress networks (string=False) or list of strings when string=True

static cidr_range_split(*cidr: str*) → tuple[str, str, str]

Convert network to IP Range.

Parameters

- **net** – The network (IPvxNetwork) to examine.
- **string** – If True then returns cidr strings instead of IPvxAddress

Returns

strings of the first IP, middle IP and last IP in the cidr block

static cidr_set_prefix(*cidr: str*, *prefix: int*) → str

Set new prefix for cidr and return new cidr string.

Parameters

- **cidr** – Cidr string to use
- **prefix** – The new prefix to use

Returns

Cidr string using the specified prefix

static cidr_to_net(*cidr: str*, *strict: bool = False*) → IPvxNetwork | None

Convert cidr string to ipaddress network.

Parameters

- **cidr** – Input cidr string
- **strict** – If true then cidr is considered invalid if host bits are set. Defaults to False. (see ipaddress docs).

Returns

The ipaddress network derived from cidr string as IPvxNetwork = IPv4Network or IPv6Network or None if invalid.

static cidr_to_range(*cidr: str*, *string: bool = False*) → tuple[IPvxAddress | str | None, IPvxAddress | str | None]

Cidr string to an IP Range.

Parameters

- **cidr** – The cidr string to examine.
- **string** – If True then returns cidr strings instead of IPvxAddress

Returns

tuple (ip0, ip1) of first and last IP address in net (ip0, ip1) are IPvxAddress or str when string is True

static cidr_type_network(*cidr: str*) → tuple[str, type[IPvxNetwork]]

Cidr Network Type.

Parameters

cidr – Cidr string to examine

Returns

tuple('ip4' or 'ip6', IPv4Network or IPv6Network).

static cidrs2_minus_cidrs1(*cidrs1: list[str]*, *cidrs2: list[str]*) → list[str]

Exclude all of cidrs1 from cidrs2.

i.e. return "cidrs2" - "cidrs1".

Parameters

- **cidrs1** – list of cidr strings to be excluded.
- **cidrs2** – list of cidr strings from which cidrs1 are excluded.

Returns

Resulting list of cidr strings = "cidrs2" - "cidrs1".

static cidrs_exclude(*cidrs1: list[str]*, *cidrs2: list[str]*) → list[str]

Deprecated: replaced by cidrs2_minus_cidrs1()

static cidrs_split_type(*cidrs: list[str]*) → tuple[list[str], list[str], list[str]]

Split a list of cidrs into ipv4, ipv6 and other.

Parameters

cidrs – list of cidr strings

Returns
Tuple of lists of ipv4, ipv6 and unknown.

static cidrs_to_nets(*cidrs: list[str]*, *strict: bool = False*) → list[IPvxNetwork]

Convert list of cidr strings to list of IPvxNetwork.

Parameters

- **cidrs** – list of cidr strings
- **strict** – If true, cidr with host bits set is invalid. Defaults to false.

Returns
list of IPvxNetworks generated from cidrs.

static clean_cidr(*cidr: str*) → str | None

Clean up a cidr address.

Does:

- fix up host bits to match the prefix
- convert old class A,B,C style IPv4 addresses to cidr.

e.g.
a.b.c -> a.b.c.0/24 a.b.c.23/24 -> a.b.c.0/24

Parameters
cidr – Cidr string to clean up.

Returns

- cidr string if valid
- None if cidr is invalid.

static clean_cidrs(*cidrs: list[str]*) → list[str]

Clean list of cidrs.

Similar to clean_cidr() but for a list.

Parameters
cidrs – list of cidr strings to clean up.

Returns
list of cleaned cidrs. If input cidr is invalid then its returnded as None

static compact(*cidrs: list[str]*) → list[str]

Compact list of cidrs - can be mixed ipv4/ipv6. Returns 1 type, making type annotation simpler for caller.

Parameters
cidrs – Input list of cidr strings.

Returns
Compacted list of cidrs. If mixed ipv4 is before ipv6

Recommended methods are compact() or compact_nets(). Others are kept for backward compatibility.

static compact_cidrs(*cidrs: list[str]*, *nets: bool = False*) → list[str] | list[IPvxNetwork]

Compact a list of cidr networks as strings.

Parameters

- **cidrs** – list of cidrs to compact.
- **nets** – If False, the default, the result will be list of strings else a list of IPvxNetwork's.

Returns

A list of compacted networks whose elements are strings if return_nets is False or IPvxNetworks if True.

static compact_cidrs_to_cidrs(*cidrs: list[str]*) → list[str]

Compact list of cidr networks and return list of cidr strings

Same as compact_cidrs(cidrs, nets=False). With single return type this is helpful when using type annotation checkers.

static compact_nets(*nets: list[IPvxNetwork]*) → list[IPvxNetwork]

Compact list of IPvxNetwork.

Parameters

nets – Input list if networks to compact.

Returns

Compacted list of IPvxNetworks.

static fix_cidr_host_bits(*cidr: str*, *verb: bool = False*) → str

zero out any host bits.

A strictly valid cidr address must have host bits set to zero.

Parameters

cidr – The cidr to "fix" if needed.

Parm verb

Some info on stdout when set True. Defaults to False.

Returns

The cidr with any non-zero host bits now zeroed out.

static fix_cidrs_host_bits(*cidrs: list[str]*, *verb: bool = False*) → list[str]

zero any host bits for a list of cidrs.

Similar to fix_cidr_host_bits() but for a list of cidrs.

Parameters

- **cidrs** – list of cidrs to fix up.
- **verb** – Some info on stdout when set True. Defaults to False.

Returns
The list of cidrs each with any non-zero host bits now zeroed out.

static get_host_bits(*ip: str*, *pfx: int = 24*) → int

Gets the host bits from an IP address given the netmask.

Parameters

- **ip** – The IP to examine.
- **pfx** – The cidr prefix.

Returns
The host bits from the IP.

static ip_to_address(*ip: str*) → IPvxAddress | None

Return ipaddress of given ip.

If IP has prefix or host bits set, strip the prefix and keep host bits.

Parameters
ip – The IP string to convert

Rreturns
IPvxAddress derived from IP or None if not an IP address.

static ip_version(*addr_or_net: str | IPvxNetwork | IPvxAddress*) → int

Determines the IP version of an address or network:

Parameters
addr_or_net – Can be IP addess or network either a string or ip_address format.

Returns
4 if addr_or_net is IPv4Network or IPv4Address 6 if addr_or_net is IPv6Network or IPv5Address 0 otherwise

static ipaddr_cidr_from_string(*address: str*, *strict: bool = False*) → IPvxNetwork | None

Convert string of IP address or cidr net to IPvxNetwork

Parameters

- **address** – IP or CIDR network as a string.
- **strict** – If true, host bits are disallowed for cidr block.

Returns
An IPvxNetwork or None if invalid.

static ips_to_addresses(*ips: list[str]*) → list[IPvxAddress]

Convert list of IP strings to a list of ip addresses

Parameters
ips – list of IP strings to convert

Returns
list of IPvxAddress derived from input IPs.

static is_rfc_1918(*cidr: str*) → bool

Check if cidr is any RFC 1918.

Parameters
cidr – IP or Cidr to check if RFC 1918.

Returns
True if cidr is an RFC 1918 address. False if not.

static is_valid_cidr(*address: Any*) → bool

Check if address is a valid ip or cidr network.

Parram address
Address to check. Host bits set is permitted for a cidr network.

Returns
True/False if address is valid IPv4 or IPv6 address or network.

static is_valid_ip4(*address: Any*) → bool

check if valid IPv4 address or cidr.

Parameters
address – Check if this is a valid IPv4 address or cidr.

Returns
True if valid IPv4 else False

static is_valid_ip6(*address: Any*) → bool

check if valid IPv6 address or cidr.

Parameters
address – Check if this is a valid IPv6 address or cidr.

Returns
True if valid IPv6 else False

static net_exclude(*net1: IPvxNetwork*, *nets2: list[IPvxNetwork]*) → list[IPvxNetwork]

Exclude net1 from any of networks in net2 and return resulting list of nets (without net1).

Parameters

- **net1** – Network to be ecluded.
- **nets2** – list of networks from which net1 will be excluded from.

Returns
Resultant list of networks “nets2 - net1”.

static net_is_subnet(*net1: IPvxNetwork*, *net2: IPvxNetwork | list[IPvxNetwork]*) → bool

Determines if net1 is a subnet of any of net2.

Parameters

- **net1** – Network to check if is a subnet.
- **net2** – Network or list of networks to be checked.

Returns
True if net1 is a subnet of any of net2.

static net_range_split(*net: IPvxNetwork*) → tuple[IPvxAddress, IPvxAddress, IPvxAddress]

Convert network to IP Range.

Parameters

- **net** – The network (IPvxNetwork) to examine.
- **string** – If True then returns cidr strings instead of IPvxAddress

Returns
tuple of 3 IPvxAddress: (first IP, middle IP, last IP) in the cidr block

static net_to_cidr(*net: IPvxNetwork*) → str

Net to Cidr String
Convert an ipaddress network to a cidr string.

Parameters
net – Ipaddress Network to convert.

Returns
Cidr string from net. If unable to conver, then empty string is returned.

static net_to_range(*net: IPvxNetwork*, *string: bool = False*) → tuple[IPvxAddress | str | None, IPvxAddress | str | None]

Convert network to IP Range.

Parameters

- **net** – The network (IPvxNetwork) to examine.
- **string** – If True then returns cidr strings instead of IPvxAddress

Returns
tuple (ip0, ip1) of first and last IP address in net Each (ip0, ip1) is IPvxAddress or a string if “string” == True

static nets_exclude(*nets1: list[IPvxNetwork]*, *nets2: list[IPvxNetwork]*) → list[IPvxNetwork]

Exclude every nets1 network from from any networks in nets2.

Similar to net_exclude() except this version has a list to be excluded instead of a single network.

Parameters

- **nets1** – list of nets to be excluded.
- **nets2** – list of nets from which will exclude any of nets1.

Returns
list of resultant networks (“nets2” - “nets1”)

static nets_to_cidrs(*nets: list[IPvxNetwork]*) → list[str]

Convert list of ipaddress networks to list of cidr strings.

Parameters
nets – list of nets to convert.

Returns
list of cidr strings.

static range_to_cidrs(*addr_start: IPAddress*, *addr_end: IPAddress*, *string: bool = False*) → list[IPvxNetwork] | list[str]

Generate a list of cidr/nets from an IP range.

Parameters

- **addr_start** – Start of IP range
- **addr_end** – End of IP range

String
If True then returns list of cidr strings otherwise IPvxNetwork

Returns
list of cidr network blocks representing the IP range. list elements are IPvxAddress or str if parameter string=True

static remove_rfc_1918(*cidrs_in: str | list[str]*) → tuple[str | list[str], str | list[str]]

Given list of cidrs, return list without any rfc 1918

Parameters
cidrs_in – Cidr string or list of cidr strings.

Returns

Returns (tuple[cidrs_cleaned, rfc_1918_cidrs_found]): - cidrs_cleaned: list of cidrs with all rfc_1918 removed. - rfc_1918_cidrs_found: list of any rfc 1918 found in the input.

If input cidr(s) is a list, then items in output are a (possibly empty) list If not a list then returned items will be string or None.

static rfc_1918_cidrs() → list[str]

Return list of rfc 1918 networks cidr strings

Returns
list of RFC 1918 networks as cidr strings

static rfc_1918_nets() → list[IPvxNetwork]

Return list of rfc 1918 networks

Returns
list of RFC 1918 networks.

static sort_cidrs(*cidrs: list[str]*) → list[str]

Sort the list of cidr strings.

Parameters
cidrs – list of cidrs.

Returns
Sorted copy of cidr list

static sort_ips(*ips: list[str]*) → list[str]

Sort a list of IP addresses.

Parameters
ips – list of ips to be sorted.

Returns
Sorted copy of ips.

static sort_nets(*nets: list[IPvxNetwork]*) → list[IPvxNetwork]

Sort a list of networks.

Parameters
nets – list of networks to be sorted.

Returns
Sorted copy of networks.

static version() → str

Returns
Version of py-cidr

2.3 File Utilities

CidrFile class: Read/write a file with list of cidr blocks as strings For reading

- comments ignored
- pname = is path to the file.
- cidr are all in column 1

class py_cidr.cidr_file_class.**CidrFile**

Bases: object

Some CIDR string file read/writ tools.

All methods are static so no class instance variable needed.

static copy_cidr_file(*src_file: str*, *dst_file: str*) → bool

Copy one file to another.

Parameters

- **src_file** – Source file to copy.
- **dst_file** – Destination Where to save a copy

Returns

True if all okay else False

static read_cidr_file(*fname: str | None*, *verb: bool = False*) → list[str]

Read file of cidrs and return list of all IPv4 and IPv6.

See read_cidrs() to have the cidrs split by IP family.

Parameters

- **fname** – Path to file of cidrs to read. Stdin if set to None
- **verb** – More verbose output

Returns

list of all cidrs (ip4 and ip6) read from the file

static read_cidr_files(*targ_dir: str*, *file_list: list[str]*) → list[str]

Read files in a directory and return merged list of cidr strings.

Parameters

- **targ_dir** – Directory to find each file.
- **file_list** – read from this list of files found in in *targ_dir*

Returns

list of all cidrs found in the files.

static read_cidrs(*fname: str | None*, *verb: bool = False*) → tuple[list[str], list[str]]

Read file of cidrs and return tuple of separate lists (ip4, ip6).

- if fname is None or sys.stdin then data is read from stdin.
- only column 1 of file is used.
- comments are ignored

See also read_cidr_file() which returns all cidrs in one list.

Parameters

- **fname** – File name to read. If None, then reads from stdin.
- **verb** – More verbose output when set to True.

Returns
A tuple of lists (ipv4, ipv6) of cidrs separated into IPv4 and IPv6.

static write_cidr_file(*cidrs: list[str]*, *pname: str*) → bool

Write list of cidrs to a file.

Parameters

- **cidrs** – list of cidr strings to write.
- **pname** – Path to file where cidrs are to be written.

Returns
True if successful otherwise False.

2.4 Cidr Map

This tool uses Patricia Tree to maintain a map of cidr -> <value>. For example a map of all network prefixes where the <value> might be the country that network is located or registered in. Map cidr prefixes to some value.

Uses separate maps for ipv4 and ipv6

class py_cidr.cidr_map.**CidrMap**(*cache_dir: str = ''*, *compact: bool = False*)

Bases: object

Class provides map(cidr) -> some value.

- ipv4 and ipv6 are cached separately
- built on CidrCache and Cidr classes

Parameters

- **cache_dir** – Optional directory to keep cached copy of map
- **compact** – Optional flag to request a compact map. The standard map keeps every prefix added to map and this is the default. If compacting, then adjacent prefixes whose associated values are the same, will have the prefixed compacted to a single prefix.

add_cidr(*cidr: str*, *val: Any*, *priv_maps: PrefixMaps | None = None*)

Deprecated Legacy function - use add_prefix_val() instead.

add_cidrs(*prefixes: list[str]*, *vals: list[Any]*)

Deprecated Legacy function - use add_prefix_vals() instead.

add_prefix_val(*prefix_val: PrefixVal*, *priv_maps: PrefixMaps | None = None*)

Add cidr to the map..

Parameters

- **prefix_val** – The tuple of (prefix, value) to add to the map.

- **priv_map** – Optional private cache. If using multiple processes/threads then provide this object where changes are kept thread local to the private map instead of in the instance cache. This way the same instance (and its cache) can be used across multiple processes/threads. All the thread local caches can be merged ex post.
  Use CidrMap.create_private_cache() to create private_data

add_prefix_vals(*prefix_vals: list[PrefixVal]*)

Add list if (prefix, val) tuples.

Parameters
prefix_vals – Add a list of tuples of (prefix, value) to map.

static create_private_cache() → PrefixMaps

Create and Return private cache object to use with add_cidr().

This cache has no cache_dir set - memory only. Required if one CidrMap instance is used in multiple processes/threads Give each process/thread a private data cache and they can be merged into the CidrMap instance after they have all completed.

Returns
A private_cache_data object.

items(*v6: bool = False*) → Iterator[tuple[str, Any]]

Iterator that returns oen tuple element (prefix, value) at a time fomr the map.

Prefix v6
Default is false, and the elements are from IPv4 map If True, then elements are taken from the IPv6 map.

Returns
One tuple (prefix, value)]:

lookup(*cidr: str*) → Any | None

Return the value associated with the LPM (longest prefix match) of cidr. :param cidr: The cidr to lookup :returns: The value of the LPM of input cidr.

lookup_all(*cidr: str*) → list[tuple[str, Any]]

If cidr is in the map, return list of all (prefix, val) tuples. cidr is a subnet of each prefix. The first (prefix, val) returned is always the longest matching prefix (LMP) and it's value: (lmp, val)

The remaining elements will all have shorter prefix length (larger, less specific) network blocks.

Parameters
cidr – Cidr value to lookup.

Returns
A list of tuples (prefix, value]). where cidr is same as or subnet of each prefix. Empty list If no matching elements found

lookup_both(*cidr: str*) → tuple[str, Any]

Deprecated: Historical - same as lookup_lmp()

lookup_lmp(*cidr: str*) → tuple[str, Any]

Check if cidr is in the map. Similar to lookup() but returns the longest matching prefix (LMP) and it's value. cidr is then the same as or subnet of prefix. If not found then empty string for prefix.

See lookup_all() which returns list of (prefix, val) tuples where the first element is the (lmp, val) pair.

Parameters

cidr – Cidr value to lookup.

Returns

A tuple of (prefix, value) where cidr is same as or a asubnet of prefix and value is the assocated value. If not found then prefix is empty string.

merge(*priv_maps: PrefixMaps | None*)

Merge private maps back into into our instance map.

Parameters

priv_maps – The "private data" to add to the map. Merge the content of priv_maps into the current data. See CidrMap.create_private_cache()

print()

Print the cache data.

save_cache()

Write cache to files

CHAPTER

THREE

MIGRATING FROM CIDR TO PYCIDR

If existing code uses string representations, it is straightfoward. If using ipaddress format, then code will need to be migrated to strings to get the performance benefits. Cidr class is not going away, so migrating is optional.

Note that for any functions with an argument to choose the output in string or ipaddress format the PyCidr replacement has no such argument because strings are always the output form.

Some examples migrating:

- Compact list of cidrs.

```
Cidr.compact(cids)

PyCidr.compact(cidrs)

Cidr has some additional forms all of which are replaced as above
```

- Cidr to IP address range

```
(ip_start, ip_end) = Cidr.cidr_to_range(cidr)
(ip_start, ip_mid, ip_end) = Cidr.cidr_range_split(cidr)

(ip_start, ip_mid, ip_end) = PyCidr.cidr_to_range(cidr)
```

- Sorting
  While Cidr distinguished IP addresses from CIDR blocks and therefore provided separate functions for some tasks like sorting, PyCidr accepts an IP address (e.g. *10.0.0.22*) or a CIDR (e.g. *10.0.0.0/24* or *10.0.0.22/32*) everywhere.

```
x = Cidr.sort_cidrs(cidrs)
x = Cidr.sort_ips(ips)

x = PyCidr.sort(cidrs)
x = PyCidr.sort(ips)
```

However please note that PyCidr returns IP addresses with their prefix (/32 for IPv4 and /128 for IPv6). To recover just the IP part using cidr_parts()

```
(ip_part, pfx_part) = PyCidr.cidr_parts(cidr)
```

- Checking ip/cidr validity

```
Cidr.is_valid_ip4()
Cidr.is_valid_ip6()
Cidr.is_valid_cidr()

PyCidr.is_valid_ipv4()
PyCidr.is_valid_ipv6()
PyCidr.is_valid_cidr()
```

CHAPTER

FOUR

APPENDIX

4.1 Installation

Available on * Github * Archlinux AUR

On Arch you can build using the provided PKGBUILD in the packaging directory or from the AUR. To build manually, clone the repo and :

```
rm -f dist/*
./scripts/do-build
./scripts/do-install [destination]
```

The default destination is *build/pkg*.

4.2 Dependencies

Run Time :

- python (3.14 or later)
- lockmgr
- patricia26

Building Package :

- cython
- gcc
- git
- meson
- meson-python
- uv
- python-uv-build
- rsync
- python-pytest
- python-pytest-asyncio

4.3 License

Created by Gene C. and licensed under the terms of the GPL-2.0-or-later license.

- SPDX-License-Identifier: GPL-2.0-or-later
- SPDX-FileCopyrightText: © 2024-present Gene C <arch@sapience.com>

4.4 AI Tooling

Assistance from:

- Anthropic's Claude played a significant role updating and checking all C-code.
- Google's Gemini was especially helpful with Cython code.

PYTHON MODULE INDEX

p

py_cidr.cidr_class, 12
py_cidr.cidr_file_class, 22
py_cidr.cidr_map, 24
py_cidr.pycidr_class, 6

INDEX

A

add_cidr() (*py_cidr.cidr_map.CidrMap method*), 24
add_cidrs() (*py_cidr.cidr_map.CidrMap method*), 24
add_prefix_val() (*py_cidr.cidr_map.CidrMap method*), 24
add_prefix_vals() (*py_cidr.cidr_map.CidrMap method*), 25
address_iptype() (*py_cidr.cidr_class.Cidr static method*), 12
address_to_net() (*py_cidr.cidr_class.Cidr static method*), 13
addresses_to_ips() (*py_cidr.cidr_class.Cidr static method*), 13

C

Cidr (*class in py_cidr.cidr_class*), 12
cidr_exclude() (*py_cidr.cidr_class.Cidr static method*), 13
cidr_iptype() (*py_cidr.cidr_class.Cidr static method*), 13
cidr_is_subnet() (*py_cidr.cidr_class.Cidr static method*), 13
cidr_list_compact() (*py_cidr.cidr_class.Cidr static method*), 14
cidr_parts() (*py_cidr.pycidr_class.PyCidr static method*), 7
cidr_range_split() (*py_cidr.cidr_class.Cidr static method*), 14
cidr_set_prefix() (*py_cidr.cidr_class.Cidr static method*), 14
cidr_to_net() (*py_cidr.cidr_class.Cidr static method*), 14
cidr_to_range() (*py_cidr.cidr_class.Cidr static method*), 15
cidr_to_range() (*py_cidr.pycidr_class.PyCidr static method*), 7
cidr_type_network() (*py_cidr.cidr_class.Cidr static method*), 15
CidrFile (*class in py_cidr.cidr_file_class*), 22
CidrMap (*class in py_cidr.cidr_map*), 24
cidrs2_minus_cidrs1() (*py_cidr.cidr_class.Cidr static method*), 15
cidrs_exclude() (*py_cidr.cidr_class.Cidr static method*), 15
cidrs_intersection() (*py_cidr.pycidr_class.PyCidr static method*), 7
cidrs_split_type() (*py_cidr.cidr_class.Cidr static method*), 15
cidrs_to_nets() (*py_cidr.cidr_class.Cidr static method*), 16
clean_cidr() (*py_cidr.cidr_class.Cidr static method*), 16
clean_cidr() (*py_cidr.pycidr_class.PyCidr static method*), 7
clean_cidrs() (*py_cidr.cidr_class.Cidr static method*), 16
clean_cidrs() (*py_cidr.pycidr_class.PyCidr static method*), 8
compact() (*py_cidr.cidr_class.Cidr static method*), 16
compact() (*py_cidr.pycidr_class.PyCidr static method*), 8
compact_cidrs() (*py_cidr.cidr_class.Cidr static method*), 17
compact_cidrs_to_cidrs() (*py_cidr.cidr_class.Cidr static method*), 17
compact_nets() (*py_cidr.cidr_class.Cidr static method*), 17
copy_cidr_file() (*py_cidr.cidr_file_class.CidrFile static*

method), 22
create_private_cache() (*py_cidr.cidr_map.CidrMap static method*), 25
ct_version() (*py_cidr.pycidr_class.PyCidr static method*), 8

E

exclude_cidrs() (*py_cidr.pycidr_class.PyCidr static method*), 8

F

fix_cidr_host_bits() (*py_cidr.cidr_class.Cidr static method*), 17
fix_cidrs_host_bits() (*py_cidr.cidr_class.Cidr static method*), 17
fix_host_bits() (*py_cidr.pycidr_class.PyCidr static method*), 8
format_host_bits() (*py_cidr.pycidr_class.PyCidr static method*), 9

G

get_host_bits() (*py_cidr.cidr_class.Cidr static method*), 18
get_host_bits() (*py_cidr.pycidr_class.PyCidr static method*), 9

I

ip_to_address() (*py_cidr.cidr_class.Cidr static method*), 18
ip_type() (*py_cidr.pycidr_class.PyCidr static method*), 9
ip_version() (*py_cidr.cidr_class.Cidr static method*), 18
ip_version() (*py_cidr.pycidr_class.PyCidr static method*), 9
ipaddr_cidr_from_string() (*py_cidr.cidr_class.Cidr static method*), 18
ips_to_addresses() (*py_cidr.cidr_class.Cidr static method*), 18
is_rfc_1918() (*py_cidr.cidr_class.Cidr static method*), 19
is_rfc_1918() (*py_cidr.pycidr_class.PyCidr static method*), 9
is_subnet() (*py_cidr.pycidr_class.PyCidr static method*), 10
is_valid_cidr() (*py_cidr.cidr_class.Cidr static method*), 19
is_valid_cidr() (*py_cidr.pycidr_class.PyCidr static method*), 10
is_valid_ip4() (*py_cidr.cidr_class.Cidr static method*), 19
is_valid_ip6() (*py_cidr.cidr_class.Cidr static method*), 19
is_valid_ipv4() (*py_cidr.pycidr_class.PyCidr static method*), 10
is_valid_ipv6() (*py_cidr.pycidr_class.PyCidr static method*), 10
items() (*py_cidr.cidr_map.CidrMap method*), 25

L

lookup() (*py_cidr.cidr_map.CidrMap method*), 25
lookup_all() (*py_cidr.cidr_map.CidrMap method*), 25
lookup_both() (*py_cidr.cidr_map.CidrMap method*), 25
lookup_lmp() (*py_cidr.cidr_map.CidrMap method*), 25

M

merge() (*py_cidr.cidr_map.CidrMap method*), 26
module
    py_cidr.cidr_class, 12
    py_cidr.cidr_file_class, 22
    py_cidr.cidr_map, 24
    py_cidr.pycidr_class, 6

N

net_exclude() (*py_cidr.cidr_class.Cidr static method*), 19
net_is_subnet() (*py_cidr.cidr_class.Cidr static method*), 19
net_range_split() (*py_cidr.cidr_class.Cidr static method*), 20
net_to_cidr() (*py_cidr.cidr_class.Cidr static method*), 20
net_to_range() (*py_cidr.cidr_class.Cidr static method*), 20
nets_exclude() (*py_cidr.cidr_class.Cidr static method*), 20
nets_to_cidrs() (*py_cidr.cidr_class.Cidr static method*), 21

num_ips() (*py_cidr.pycidr_class.PyCidr static method*), 10

P

print() (*py_cidr.cidr_map.CidrMap method*), 26
py_cidr.cidr_class
    module, 12
py_cidr.cidr_file_class
    module, 22
py_cidr.cidr_map
    module, 24
py_cidr.pycidr_class
    module, 6
PyCidr (*class in py_cidr.pycidr_class*), 7

R

range_to_cidrs() (*py_cidr.cidr_class.Cidr static method*), 21
range_to_cidrs() (*py_cidr.pycidr_class.PyCidr static method*), 10
read_cidr_file() (*py_cidr.cidr_file_class.CidrFile static method*), 23
read_cidr_files() (*py_cidr.cidr_file_class.CidrFile static method*), 23
read_cidrs() (*py_cidr.cidr_file_class.CidrFile static method*), 23
remove_rfc_1918() (*py_cidr.cidr_class.Cidr static method*), 21
remove_rfc_1918() (*py_cidr.pycidr_class.PyCidr static method*), 11
rfc_1918_cidrs() (*py_cidr.cidr_class.Cidr static method*), 21
rfc_1918_cidrs() (*py_cidr.pycidr_class.PyCidr static method*), 11
rfc_1918_nets() (*py_cidr.cidr_class.Cidr static method*), 21

S

save_cache() (*py_cidr.cidr_map.CidrMap method*), 26
set_prefix() (*py_cidr.pycidr_class.PyCidr static method*), 11
sort() (*py_cidr.pycidr_class.PyCidr static method*), 11
sort_cidrs() (*py_cidr.cidr_class.Cidr static method*), 22
sort_ips() (*py_cidr.cidr_class.Cidr static method*), 22
sort_nets() (*py_cidr.cidr_class.Cidr static method*), 22
split_by_family() (*py_cidr.pycidr_class.PyCidr static method*), 11
split_by_iptype() (*py_cidr.pycidr_class.PyCidr static method*), 12
subnets_split() (*py_cidr.pycidr_class.PyCidr static method*), 12

V

version() (*py_cidr.cidr_class.Cidr static method*), 22
version() (*py_cidr.pycidr_class.PyCidr static method*), 12

W

write_cidr_file() (*py_cidr.cidr_file_class.CidrFile static method*), 24