

Probabilistic
Graphical
Models




Inference


Sampling Methods

Inference In Template Models

DBN Template Specification




Time slice 0




2TBA1

Ground Bayesian Network



Can unroll DBN for given trajectory
and run inference over ground network

Plate Model



Can unroll plate model for given set of objects
and run inference over ground network

Belief State Tracking

o^1, o^2, \dots, o^t


$$\sigma^{(t)}(S^{(t)}) = P(S^{(t)} \mid \mathbf{o}^{(1:t)})$$

$$\sigma^{(t+1)}(S^{(t+1)}) \triangleq P(S^{(t+1)} \mid \mathbf{o}^{(1:t+1)})$$

$$= \sum_{S^{(t)}} P(S^{(t+1)} \mid S^{(t)}, \mathbf{o}^{(1:t)}) P(S^{(t)} \mid \mathbf{o}^{(1:t)})$$

$$= \sum_{S^{(t)}} P(S^{(t+1)} \mid S^{(t)}) \sigma^{(t)}(S^{(t)})$$


transition model



Belief State Tracking

$$\sigma^{(t)}(S^{(t)}) = P(S^{(t)} \mid o^{(1:t)})$$

$$\sigma^{(\cdot, t+1)}(S^{(t+1)}) \triangleq P(S^{(t+1)} \mid o^{(1:t)})$$



$$\sigma^{(t+1)}(S^{(t+1)}) = P(S^{(t+1)} \mid o^{(1:t)}, o^{(t+1)})$$


$$\rightarrow \frac{P(o^{(t+1)} \mid S^{(t+1)}, o^{(1:t)}) P(S^{(t+1)} \mid o^{(1:t)})}{\text{normalization}}$$

$$= \frac{\text{observation } P(o^{(t+1)} \mid o^{(1:t)})}{\text{normalization}}$$


$$= \frac{P(o^{(t+1)} \mid S^{(t+1)}) \sigma^{(\cdot, t+1)}(S^{(t+1)})}{\text{normalization constant}}$$

normalization constant

Robot Localization



Robot Localization




robot true
position

Fox, Burgard, Thrun

Daphne Koller


Computational Issues




Minimal sepset must separate future from past


⇒ must involve at least all of the persistent variables

Entanglement




exact belief state is fully correlated in most cases
no conditional independence





Webbers (Mitchell) (Craven et al, Proc AAAI98; Tasker et al, UAI2002)

Collective Webpage Classification



Summary

- Inference in template and temporal models can be done by unrolling the ground network and using standard methods
- Temporal models also raise new inference tasks, such as real-time tracking, which require that we adapt our methods
- Moreover, ground network is often large and densely connected, requiring careful algorithm design and use of approximate methods