THE GEDCOM STANDARD

DRAFT Release 5.0

25 September 1991

Prepared by the
Family History Department
The Church of Jesus Christ of Latter-day Saints

Suggestions and Correspondence:
GEDCOM Coordinator - 3T
Family History Department
50 East North Temple
Salt Lake City, UT 84150
USA

Telephone (USA) 801-240-5225.

TABLE OF CONTENTS

Introduction....3
Purpose and Content of Document....3
Changes in Version 5.0....4
GEDCOM Product Registration....5
GEDCOM Software Library....5

Chapter 1
Data Representation Grammar....6
Concepts....6
Grammar....7

Chapter 2
Lineage-linked Grammar....14
Introduction....14
Lineage-linked Grammar Organization....14
Record Structures of the Lineage-linked Form....15
Substructures of the Lineage-linked Form....19
Primitive Elements of the Lineage-linked Form....22
Compatibility with previous GEDCOM versions....23

Chapter 3
GEDCOM Transmission File....34
Introduction....34
Headers and Trailers in the GEDCOM Transmission....34
Why Headers and Trailers are used....35
How to use a Header....35
How to use a Trailer....38
Naming your Transmission File....38

Chapter 4
GEDCOM Values....39
Introduction....39
Why Values are used....40
Guidelines for using Values....41
How to record Names of Individuals....41
How to record Dates....42
How to record Places....44
How to record Events....45
How to record Time....45
How to record Pointers....46
How to use other Values....47

Chapter 5
Using Character Sets in GEDCOM....48
Why various Character Sets are used....48
How to change Character Sets....49

Appendix A
Lineage-linked GEDCOM Tag Definition....52

INTRODUCTION

GEDCOM was developed by the Family History Department of the Church of Jesus Christ of Latter-day Saints to meet the data communication requirements of the Family History Department and other institutions wishing to exchange computerized genealogical data. GEDCOM is an acronym for GEnealogical Data Communication. GEDCOM is provided to foster the exchange of genealogical information and the development of a wide range of inter-operable software products to assist genealogists, historians, and other researchers in the exchange of genealogical information.

Purpose and Content of This Document

This technical document is written for computer programmers, system developers, and user specialists. It defines a flexible format for exchanging structured genealogical information between different computer systems.

The chapters in this document detail the following specifications:

- Data Representation Grammar
- Lineage-Linked GEDCOM Grammar
- GEDCOM Transmission File
- Values
- Character Sets

This document describes GEDCOM in two different levels. The lower level defines a general-purpose data representation language for representing any kind of structured information in a sequential media. This lower level is known as the GEDCOM data format. It deals with the syntax and identification of structured information in general, but does not deal with the semantic content of any particular kind of data.

The higher level defines specific content for a particular kind of data to be exchanged between a group of compatible systems. GEDCOM has been used for many different kinds of data. Each kind of data is referred to as a form of GEDCOM and has its own definition at this level. GEDCOM forms have been defined for lineage-linked, bibliographic, census, religious, and other kinds of data, including several that are not related to genealogy.

The first two chapters are presented as language grammars and are technically oriented. Chapter 1 presents basic GEDCOM concepts and then defines the lower-level GEDCOM format. This chapter will be useful to anyone using GEDCOM. Chapter 2 defines the higher-level, specific form of GEDCOM known as the lineage-linked form. The lineage-linked form is the form used by commercial genealogical software systems for exchanging compiled, linked information about individuals. The other forms of GEDCOM are not publicly exchanged at this time, and are not discussed in this document.

Chapters three and four discuss GEDCOM in a more tutorial fashion. If inconsistencies are present, they should be resolved in favor of the grammars presented in the first two chapters. The fifth chapter defines GEDCOM character sets. Appendix A defines tags used in the lineage-linked form of GEDCOM. Appendix B contains character tables that define the GEDCOM character set.

Changes in Version 5.0

Prior official versions of The GEDCOM Standard were released in October 1987 (3.0) and August 1989 (4.0). Versions prior to these were preliminary and were not established as a standard.

This GEDCOM release (5.0) includes the first standard definition of the lineage-linked form of GEDCOM, and also includes the first major expansion of the lineage-linked form since its initial use in GEDCOM 3.0. Products based on releases 3.0 and 4.0 versions should be upward-compatible. These existing registered GEDCOM-compatible systems should still be able to exchange data with newer systems that use this version, and will still be considered GEDCOM-compatible.

There are several purposes for the 5.0 release of GEDCOM:

- Re-define the GEDCOM data representation grammar in a shorter, more rigorous, and more precise format, for ease of understanding (see chapter 1). The GEDCOM format remains the same, even though the description of it is changed.

- Define the precise combinations of tags, values, and pointers allowed in the lineage-linked form (see chapter 2). This is the form of GEDCOM currently exchanged by commercial genealogical software systems, and it remains unchanged, other than adding new tags and the upward-compatible structural extensions listed below. (The lineage-linked form should not be confused with other forms of GEDCOM, which apply the basic GEDCOM data format with different tag, value, and pointer combinations for other purposes.)

- Define representations for supporting information such as source citations, submitter identification, and notes. (See chapter 2, <<SUPPORT_INFO>> structure in the lineage-linked grammar.)

- Define user-defined EVENts.

- Define user-defined ASSOciations with INDIviduals other than direct family relationships.

- Allow descriptive text to further qualify MARRiage, DIVorce, and other event structures.

- Require SOURce VERSion (product version) and GEDCom VERSion information.

- Define DATE modifier (ABT, BEF, AFT, etc.) and a more rigorous regular date format.

GEDCOM Product Registration

Developers of GEDCOM-compatible products using the lineage-linked form of GEDCOM (see chapter 2) should register their product by submitting the following information to the GEDCOM coordinator:

- A sharable, brief, representative sample of GEDCOM output from their product, on diskette, for registration review and for compatibility testing by other developers
- A proposed unique SOURce name to identify the product (not the company), up to 40 characters long, allowing mixed upper and lower case, with no embedded spaces (use underscore "_" instead), for inclusion in the product's GEDCOM output HEADer record
- An optional text file containing relevant technical documentation about the product's GEDCOM implementation.

GEDCOM Software Library

A library of public domain source code, in the C programming language, is available to help reduce the work required to achieve GEDCOM compatibility.

Chapter 1
DATA REPRESENTATION GRAMMAR

INTRODUCTION

This chapter describes the core GEDCOM data representation language, which provides a general purpose way to represent items of related information using a sequential stream of characters. At this generic level, GEDCOM may be used to represent any form of structured information, not just genealogical data.

CONCEPTS

A GEDCOM transmission represents a database in the form of a sequential stream of related records. A record is represented as a sequence of tagged, variable-length lines, arranged in a hierarchy. A line contains a hierarcical level number, a tag, and a value. The GEDCOM line is terminated by a carriage return and/or line feed character.

The tag identifies the value of a line in the same sense as a field name identifies a field in a database record. The data is self-defining. Tags allow a field to occur any number of times within a record, including zero, and allow the use of different or new fields without otherwise penalizing compatibility between different systems exchanging data.

The hierarchical relationships are indicated by a hierarchical level number. Subordinate lines have a higher level number. The hierarchy allows a line to have sub-lines, which in turn may have their own sub-lines, etc. A line and its sub-lines constitute a context or enclosure, that is, a cluster of information pertaining directly to the same thing. This hierarchical arrangement corresponds with the natural hierarchy found in most structured information.

The beginning of a record is indicated by a line whose level number is zero.

A GEDCOM receiver system scans the input for expected information by looking for specific tags and processing the associated values. Unrecognized tags (perhaps from a sending system whose database contains some different information) are handled by not processing the associated value nor its enclosed sub-lines, i.e, the entire context is ignored. These are treated as exceptions by printing them in an exception report or saving them in some generic way.

In addition to hierarchical relationships, GEDCOM defines inter-record references which allow a record to be logically related to other records, without introducing redundancy. These are represented by two additional, but optional, parts of a line: a cross-reference pointer and a cross-reference identifier. The cross-reference pointer "points at" a related record, identified by a required matching cross-reference identifier.

GRAMMAR

The GEDCOM data format, a data representation language, is defined in the grammar in this chapter. The grammar is a set of rules that specify what sequences of characters constitute valid GEDCOM expressions. The rules are expressed as a set of pattern definitions, where each pattern is defined in terms of more primitive patterns. Pattern definitions consist of the pattern name, a separator ":=", and a list of sub-patterns from which one alternative is selected. To read the grammar, components of the selected pattern are substituted recursively by other patterns or constants, continuing until all patterns are resolved into constants. Pattern names are in bold print. Constants are the actual symbols that appear in the complete expressions and are not bolded.

A GEDCOM transmission consists of a sequence of physical records, each of which consists of a sequence of gedcom_lines, all contained in a sequential file or stream of characters. The beginning of a new physical record is designated by a line whose level number is 0. Physical records are intended to be small enough to fit within available memory, though absolute limits are not established. A gedcom_line has the following syntax:

gedcom_line:=

level delimtr xref_id delimtr tag delimtr line_content terminator

- The gedcom_line represents one piece of information. One gedcom_line corresponds to one field in traditional database or file terminology, or to a grouping of fields as in a record or subrecord. The concepts of fields, records, and subrecords merge together in GEDCOM.

- The total length of a GEDCOM line does not exceed 255 characters.

- Leading white space (tabs, spaces) to a GEDCOM line should be ignored by the reading system. Systems outputing GEDCOM should not have any white space in front of the GEDCOM line (at least for the near future).

- The xref_id and line_content are optional.

The following are examples of valid (though unrelated) GEDCOM lines:

```
0 @1234@ INDI

1 AGE 13

1 CHIL @1234@
```

The first line has a level number 0, a xref_id of @1234@, an INDI tag, and no line_content.

The second line has a level number 1, no xref_id, an AGE tag, and a line_content value of 13.

The third line has a level number 1, no xref_id, a CHIL tag, and a line_content of a pointer to a xref_id named @1234@.

level:=

digit
digit level

The level number works the same way as the level of indentation in an indented outline, where indented lines provide detail about the item under which they are indented. A line at any level L is enclosed by and pertains directly to the nearest preceding line at level L-1. The Level L may only increase by at most 1.

The enclosed subordinate lines at level L are said to be in the context of the enclosing superior line at level L-1. The meaning of a tag (see tag below) is interpreted in the context of the tags of the enclosing line(s). Take the following record about an individual's birth and death dates, for example:

```
0 INDI
  1 BIRT
    2 DATE 12 MAY 1920
  1 DEAT
    2 DATE 1960
```

In this example, the expression DATE 12 MAY 1920 is interpreted within the INDI BIRTH context, representing the INDIvidual's BIRTh DATE. The second DATE is in the INDI DEAT (death) context. The complete meaning of DATE depends on the context. (Note: the above example is indented according to the level numbers to make the concept more obvious. In the actual GEDCOM data there is no indentation, just level numbers lined up vertically on the left margin.)

xref_id:=

@xref_text@

The xref_id (cross reference identifier) is the target for pointers, allowing physically separate records to reference each other logically. The at signs "@" delimit the xref_text. The xref_text is unique within a GEDCOM transmission, and is between 1 and 15 characters in length.

The purpose of the xref_text is to uniquely identify a record in the transmission. Receiving systems typically map xref_text into their own internal record identifiers, maintaining the relationships between records but not necessarily the xref_text values used in the transmission. The xref_text typically consists of some form of the internal record identifier from the database of the sending system.

A record with a matching xref_id must exist for every pointer in the transmission, unless the colon ":" character is present in the pointer, indicating a network reference (future) to a permanent record that might not be in the transmission. The colon ":" character is therefore reserved within xref_ids and pointers. The colon ":" character restriction does not apply to the other parts of a GEDCOM_line.

delimtr:=
space

The delimtr (delimiter), (a single space character), terminates both the variable-length level number and the tag. Note that space characters may also be present in a value.

tag:=
letter
tag letter
tag digit

A tag consists of a variable length sequence of letters and digits, beginning with a letter. The tag represents the meaning of the line_content within the context of the enclosing lines. Specific tags are defined in Appendix A.

Although existing tags are only three or four characters long, systems should prepare to handle tags from 1 to 15 characters in length, terminated by a delimtr.

Valid combinations of specific tags, values, xref_ids and pointers are further constrained by the GEDCOM form defined for representing a given kind of information (see Chapter 2 for the Lineage-Linked form grammar).

line_content:=
value
pointer
value pointer
escape_sequence
escape_sequence value

The line_content identifies an object within the domain of possible values allowed in the context of the tag. The combination of the tag, the line_content, and the line_content of the preceeding superior line (level N - 1) is a 3-tuple that defines an association between the two objects. A pointer stands in the place of the context identified by the matching xref_id. Theoretically, a receiving system should be prepared to follow a pointer to find any needed value in a manner that is transparent to the logic of the subsystem that is looking for specific tags. This highly-flexible facility will probably be used more in the future. For the time being, however, the use of pointers is explicitly defined within the GEDCOM form. The value pointer combination is used to indicate what kind of association or relationship exists between the current record and the record being pointed to. (See chapter 2). The escape_sequence grammar is used to

specify special processing, such as switching character sets or calendars for date interpretation, and for indicating an inclusion of a non_gedcom data form into the GEDCOM structure.

terminator:=
carriage_return
line_feed
carriage_return line_feed
line_feed carriage_return

The terminator delimits the variable-length line_content and signals the end of the line.

NOTE: Some existing systems provide an option to produce an indented GEDCOM output for user readability, using space or tab characters between the terminator and the level number of the next line to visibly show the hierarchy. Also, some have suggested allowing extra blank lines to visibly separate physical records. These features may be incorporated into the GEDCOM standard at some future time, but for now, such a change would render some existing systems incompatible. Therefore, we recommend that new systems be prepared to discard extra carriage returns, line feeds, spaces and tabs immediately preceeding the level number during input, though output for now should normally be constrained as specified above, without indentation or blank lines.

xref_text:=
letter
digit
punctuation
space
xref_text xref_text

The xref_text is any arbitrary combination of characters, except for the at-sign "@" and the terminator. The xref_text is not retained by the receiving system, and may therefore be formed from any convenient combination of identifiers from the sending system. No meaning is attributed by the receiver to any part of the xref_text, except for its unique association with the corresponding record. The use of the colon ":" character is reserved. To avoid confusion with the escape sequence prefix "@#", a xref_text must not begin with a pound sign "#".

value:=
letter
digit
punctuation
space
colon
value value

The value represents an object within the domain of the full context of the accompanying tag. This domain is defined by a specific grammar for representing a given GEDCOM form (see Chapters 2 for Lineage-Linked grammar).

Values are not encoded in binary or other schemes for reducing space requirements, and they are generally constrained to be understandable by a typical user without decoding. This is intended to reduce the decoding burden on the receiving software. A GEDCOM-optimized data compression standard will be defined in the future to reduce space requirements. Meanwhile, users may agree to compress GEDCOM files using any compression system available to both sender and receiver.

pointer:=

xref_text

The pointer represents the association between two objects that reside in different physical records. Complex logical records are divided into smaller physical records to accommodate memory constraints, many to many relationships, and independent record creation.

The pointer must match a corresponding xref_id within the transmission, unless the colon ":" character is present (future network reference to a permanent record). A pointer is given instead of duplicating the object identified in the value of the line pointed at, though the logical result is equivalent. An expanded traversal of a record tree includes following the pointers to related records to some depth, and splicing those records (logically) into the resultant expanded tree. Pointers may refer to either records which have not yet appeared in the transmission (forward reference) or to records that have already appeared earlier in the transmission (backward reference). This arrancement usually requires a preliminary pass to construct a lookup table to support random access by xref_id during subsequent passes.

A few GEDCOM structures allow the sending system to use either a pointer or a value within the same context (with the same tag and enclosing tags), and sometimes the line will contain both a value and pointer. In all cases, the pointer will be at either the beginning or the ending of the line_content, never in the middle. GEDCOM receiving systems should be prepared in certain cases to follow pointers recursively and "splice" either text or compound GEDCOM structures into the position occupied by the pointer. Assembling pointer-based structures into large segments of text may require staging the text in disk-based files to accommodate memory constraints. Specific requirements are defined in lower-level GEDCOM grammars for a particular form of GEDCOM data (see Chapter 2 for Lineage-Linked grammar).

letter:=

One of the letters A-Z, a-z, plus all diacritic and special characters from the GEDCOM character set.

digit:=

One of the digits 0 1 2 3 4 5 6 7 8 9

punctuation:=

One of the non-letter and non-digit characters from the GEDCOM character set, except the space and colon ":" characters. The colon ":" character may be used within a value.

The at sign "@" is used for an escape mechanism to identify pointers, xref_id, character set changes, calendar changes, or other shifts in representation rules. To include the at sign "@" as data in a value, two of them should be sent together "@@", which represent a single at sign "@" as data.

escape_sequence:=

@#Dcalendar_type@
@#Ccharacter_set@
@#Lescape_codes_with_length@ inclusion_data
@#Ffile_reference_escape_codes@

calendar_type :=

A reserved name indicating which calendar base should be used to interpret the associated date value (see section in chapter 4 on "How to Record Dates").

character_set :=

A reserved name indicating which character set should be used to interpret the codes contained in the associated value.

escape_codes_with_length :=

data_type_code delimtr data_length
This escape sequence indicates the inclusion of data of a non-gedcom structure is to be enclosed within the context of the GEDCOM structure. The data_length defines the length of the data being included (note: this length is not constrained by the 255 character line limit adopted for standard GEDCOM form and may be arbitrarily long). The data_type_code defines the form of the inclusion data. The specific rules and type codes have not yet been standardized. Reading systems should skip over the length of data indicated if they are not prepared to process the indicated data type.

data_type_code :=

A reserved one-letter code indicating what data form is contained in the inclusion data.

data_length :=

digit
digit digit
A decimal number in ASCII digits, indicating the count of characters contained in the inclusion_data.

inclusion_data :=

This data becomes the line content value whose type and size are defined by the associated escape sequence.

file_reference_escape_codes :=

file_type_code file_path_name

This escape sequence allows both GEDCOM and NON-GEDCOM data to be transmitted in a separate file for a logical inclusion within this GEDCOM context. Note: the data length of the file is not constrained by the 255 character line limit adopted for standard GEDCOM form. Systems not prepared to process the indicated type of file should skip past the filename to continue processing.

file_type_code :=

A reserved one letter code indicating what type of data is contained in the inclusion file. Specific types have not yet been standardized.

file_path_name :=

This is the path name required for accessing the inclusion file from within the current directory. In PC-DOS terms, this means either that a path must be fully specified, including the root directory and optional drive, or that a partial path refers to a file within the same directory as the GEDCOM transmission file or within a directory subordinate to the current directory.

Chapter 2
LINEAGE-LINKED GRAMMAR

INTRODUCTION

This chapter describes specific tag, value, and pointer combinations for exchanging lineage-linked information in the GEDCOM format. Lineage-linked data pertains to individuals linked in family relationships across multiple generations.

This lineage-linked grammar is based on the general framework of the GEDCOM data representation grammar defined in the previous chapter. These two layers define the GEDCOM format used by commercial genealogical software systems to exchange data. Other specialized GEDCOM-based grammars have been created for different purposes. Other uses of the general-purpose GEDCOM data representation should not be confused with this specific usage for lineage-linked genealogical data, as defined in this chapter, which is the only form of GEDCOM exchanged by commercial genealogical software systems at this time.

LINEAGE-LINKED GRAMMAR ORGANIZATION

This lineage-linked GEDCOM grammar is organized into three levels: structure components, substructure patterns, and primitive elements. Structures and substructures are indicated by enclosing the structure name within double angle <<brackets>>. Primitive element patterns are enclosed in single angle <brackets>. The definition of each structure consists of the structure name, a ":=" separator, and the structure's component pattern. This pattern is an enclosure of GEDCOM lines composed of primitive elements and/or substructure enclosures.

The record structures of the lineage-linked form are shown in the section 'RECORD STRUCTURES OF THE LINEAGE-LINKED FORM'. The supporting substructures contained that make up each of the record types are shown in alphabetic sequence in the section 'SUBSTRUCTURES OF THE LINEAGE-LINKED FORM'. The primitive elements are the lowest level (terminal) components that are not further divided and are shown in the section 'DEFINITION OF PRIMITIVE ELEMENTS' in alphabetic sequence.

Some elements have optional sub-pattern choices. These choices are shown by listing the alternative sub-patterns between opening and closing square brackets "[]" and separating each choice with a vertical bar "|", meaning that exactly one of the alternate substitutions must be selected.

The number of occurences of a sub-pattern allowed within a pattern is defined in an occurence definition in braces "{}" on each line. This number indicates the minimum and maximum number of occurrences allowed for a pattern component in the form {minimum:maximum}. Note that minimum and maximum occurrence limits are defined relative to the enclosing superior line. The enclosing line may prescribe zero, one, or many possible occurences, which, in effect, is multiplied by the occurences allowed for any of its subordinate lines. This means that a required line (minimum = 1) is not required if an optional enclosing line is not given. Similarly a line occurring only once (Maximum = 1) may occur multiple times as long as each occurs under its own multiple-occurring superior line.

The level numbers for any sub-structure are represented as "n", "+1", "+2", etc. so

that they may be used in more than one place at different starting level numbers. In these cases, "n" equals the same level number where the pattern first appears, and the "+1" means level n+1, "+2" means level n+2, etc.

Unless stated otherwise, the only ordering imposed on GEDCOM lines within an enclosure arises when multiple opinions or other items are presented for which only one may be expected by a receiving system. For example, a person may have been known by more than one name, or evidence may suggest either a birth in 1840 in New York or in 1837 in Pennsylvania. In this case, the most credible or preferred information is listed first, followed by less credible or less preferred items of conflicting or alternate information. Receiving systems that can only use one item of a given kind should use the first-listed value. The same is true for output documents that can only display one value, such as family group records, pedigree charts, and others.

Conflicting dates or places of an event should be represented in separate event structures to provide a place for the corresponding source citations, rather than place multiple dates or multiple places under the same enclosing event line.

Even though no other ordering is defined beyond the one described above, some GEDCOM programming tools optimize performance based on the assumption that tags generally appear in a typical order. Performance will be better in these circumstances when a common sequence is followed. Therefore, sending systems are encouraged to present GEDCOM structures in the same general order as the one given in these patterns, unless there is a sufficient reason to use a different sequence.

RECORD STRUCTURES OF THE LINEAGE-LINKED FORM

LINEAGE_LINKED_GEDCOM:=

This is a model of the Lineage-Linked Gedcom structure for submitting data to other lineaged-linked GEDCOM processing systems. A header and a trailer record are required and they enclose any number of data records. A data record is either a SUBMitter, INDIvidual, FAMily, NOTE, or SOURce record structure.

```
0   <<HEADER>>                                  {1:1}
0   <<RECORD>>                                  {0:M}
0 TRLR                                          {1:1}
```

NOTE:

There are certain subordinate structures that may occur under any tag, at any level. These structures are contained within a structure called SUPPORT_INFO. The SUPPORT_INFO structure should be considered as subordinate to any GEDCOM line, even though it is not shown (for readability). The SUPPORT_INFO structure may occur from zero to many times {0:M}. Each occurance of the SUPPORT_INFO structure contains exactly one logical choice of one of the subordinate SUPPORT_INFO structure components. This means that from none to all of the structures from SUPPORT_INFO could appear as subordinate to any GEDCOM line, however, some may not be locigal, for instance one would not expect to see a DATE tag as subordinate to another DATE tag.

HEADER:=

The header structure provides information for identifying the submitted data. Specific system names are reserved to identify which system sent the data and in some cases which system is intended to receive it. The DESTination system name "ANSTFILE" is required for submission to the Family History Department's Ancestral File system. For LDS temple ordinance submissions, the required DESTination name is "TempleReady". (See chapter 3, "How To Use A Header" for detail.)

```
n   HEAD
  +1 SOUR <SYSTEM_NAME>                          {1:1}
    +2 VERS <VERSION_NUMBER>                     {1:1}
    +2 DATA <NAME_OF_SOURCE_DATA>                {0:1}
      +3 DATE <PUBLICATION_DATE>                 {0:1}
  +1 DEST <SYSTEM_NAME>                          {0:1}
  +1 DATE <TRANSMISSION_DATE>                    {0:1}
      +2 TIME <TIME_VALUE>                       {0:1}
  +1 SUBM @XREF:SUBM@                            {1:1}
  +1 FILE <FILE_NAME>                            {0:M}
  +1 COPR <COPYRIGHT_STATEMENT>                  {0:1}
    +2 CONT <TEXT>                               {0:M}
  +1 GEDC                                        {1:1}
    +2 VERS <VERSION_NUMBER>                     {1:1}
            For this version of GEDCOM, the value should be "5.0"
    +2 FORM <GEDCOM_FORM>                        {1:1}
  +1 CHAR <CHARACTER_SET>                        {0:1}
  +1 LANG <LANGUAGE_OF_TEXT>                     {0:1}
```

RECORD:=

```
[
 n   <<FAMILY_RECORD>>
   +1 <<SUPPORT_INFO>>                           {0:M}
|
 n   <<INDIVIDUAL_RECORD>>                       {0:1}
   +1 <<SUPPORT_INFO>>                           {0:M}
|
 n   <<NOTE_RECORD>>                             {0:1}
   +1 <<SUPPORT_INFO>>                           {0:M}
|
 n   <<REPOSITORY_RECORD>>                       {0:1}
   +1 <<SUPPORT_INFO>>                           {0:M}
|
 n   <<SOURCE_EVENT_RECORD>>                     {0:1}
   +1 <<SUPPORT_INFO>>                           {0:M}
|
 n   <<SOURCE_RECORD>>                           {0:1}
   +1 <<SUPPORT_INFO>>                           {0:M}
|
 n   <<SUBMITTER_RECORD>>                        {0:1}
   +1 <<SUPPORT_INFO>>                           {0:M}
]
```

FAMILY_RECORD:=

```
n   @xref:FAM@ FAM
  +1 HUSB @XREF:INDI@                                    {0:M}
  +1 WIFE @XREF:INDI@                                    {0:M}
  +1 CHIL @XREF:INDI@                                    {0:M}
  +1 <MARR_EVENT_TAG> <MARRIAGE_DESCRIPTOR>              {0:M}
    +2 DATE <DATE_VALUE>                                 {0:1}
    +2 PLAC <PLACE_VALUE>                                {0:1}
  +1 <DIVORCE_EVENT_TAG> <DIVORCE_DESCRIPTOR>            {0:M}
    +2 DATE <DATE_VALUE>                                 {0:1}
    +2 PLAC <PLACE_VALUE>                                {0:1}
  +1 ASSO <ASSOCIATION_DESCRIPTOR> @XREF:INDI@           {0:M}
  +1   <<LDS_FAM_ORDINANCE_EVENT>>                       {0:M}
```

INDIVIDUAL_RECORD:=

```
n   @XREF:INDI@ INDI
  +1 RFN <PERMANENT_RECORD_FILE_NUMBER>                  {0:1}
  +1   <<INDIVIDUAL>>                                    {1:1}
  +1   <<LDS_INDI_ORDINANCE_EVENT>>                      {0:M}
  +1 ANCI @XREF:SUBM@                                    {0:M}
  +1 DECI @XREF:SUBM@                                    {0:M}
  +1 FAMC @XREF:FAM@                                     {0:M}
    +2   <<CHILD_FAMILY_EVENT>>                          {0:M}
  +1 ASSO <ASSOCIATION_DESCRIPTOR> @XREF:INDI@           {0:M}
  +1 ASSO <ASSOCIATION_DESCRIPTOR> @XREF:FAM@            {0:M}
  +1 ALIA @XREF:INDI@                                    {0:M}
  +1 FAMS @XREF:FAM@                                     {0:M}
  +1 NAMS @XREF:INDI@                                    {0:M}
    +2 REL <RELATIONSHIP_DESCRIPTOR>                     {0:M}
  +1 REFN <USER_REFERENCE_NUMBER>                        {0:M}
  +1 AFN <ANCESTRAL_FILE_NUMBER>                         {0:1}
```

NOTE_RECORD:=

```
n   @XREF:NOTE@ NOTE [<TEXT> | <NULL> ]
  +1   <<NOTE_STRUCTURE>>                                {0:1}
```

REPOSITORY_RECORD:=

```
n @XREF:REPO@ REPO
   +1   NAME <REPOSITORY_NAME>                           {0:1}
   +1   ADDR <ADDRESS_LINE>                              {0:1}
      +2 CONT <ADDRESS_LINE>                             {0:3}
```

SOURCE_EVENT_RECORD:=

This structure represents event-oriented information that may be used as evidence for submitter' opinions or conclusions expressed in INDIVIDUAL and FAMILY records.

```
n   @XREF:EVEN@ <EVENT_TAG> <EVENT_DESCRIPTOR>
  +1 DATE <DATE_VALUE>                                  {0:1}
  +1 PLAC <PLACE_VALUE>                                 {0:1}
  +1 <ROLE_TAG> <ROLE_DESCRIPTOR>                       {0:M}
    +2   <<INDIVIDUAL>> {0:1}
    +2 AGE <AGE_VALUE>                                  {0:1}
```

SOURCE_RECORD:=

```
n   @XREF:SOUR@ SOUR [<TEXT> | <NULL> ]
  +1   <<SOURCE_STRUCTURE>>                             {0:1}
```

SUBMITTER_RECORD:=

The submitter record identifies individuals or organizations that contributed the information contained within the GEDCOM transmission. All records are assumed to be submitted by the SUBMITTER referenced in the HEADer, unless a SUBMitter reference inside a specific record points at a different SUBMITTER.

```
n   @XREF:SUBM@ SUBM
  +1 NAME <NAME_VALUE>                                  {1:1}
  +1 ADDR <ADDRESS_LINE>                                {1:1}
    +2 CONT <ADDRESS_LINE>                              {0:3}
  +1 PHON <PHONE_NUMBER>                                {0:1}
  +1 CHAN                                               {0:1}
    +2 DATE <CHANGE_DATE>                               {1:1}
```

SUBSTRUCTURES OF THE LINEAGE-LINKED FORM

BURIAL_INFO:=

This structure is valid only if enclosed in the PLACe of a BURIal event.

```
 n   CEME <CEMETARY_NAME>                          {1:1}
    +1 ADDR <ADDRESS_LINE>                         {0:1}
      +2 CONT <ADDRESS_LINE>                       {0:3}
```

CHILD_FAMILY_EVENT:=

```
[
 n   ADOP <CHILD_FAMILY_EVENT_DESCRIPTOR>          {1:1}
    +1 DATE <DATE_VALUE>                           {0:1}
    +1 PLAC <PLACE_VALUE>                          {0:1}
|
 n    <<LDS_CHILD_SEALING_EVENT>>                  {0:1}
]
```

INDIVIDUAL:=

```
 n   NAME <NAME_VALUE>                             {0:M}
 n   NAMR <NAME_VALUE>                             {0:M}
 n   SEX <SEX_VALUE>                               {0:1}
 n   <INDIV_EVENT_TAG> <EVENT_DESCRIPTOR>          {0:M}
    +1 DATE <DATE_VALUE>                           {0:1}
    +1 PLAC <PLACE_VALUE>                          {0:1}
      +2   <<BURIAL_INFO>>                         {0:1}
 n   TITL <TITLE>                                  {0:M}
    +1 DATE <DATE_VALUE>                           {0:1}
    +1 PLAC <PLACE_VALUE>                          {0:1}
 n   RELI <RELIGIOUS_AFFILIATION>                  {0:M}
 n   OCCU <OCCUPATION>                             {0:M}
 n   PROP <POSSESSIONS>                            {0:M}
 n   DSCR <PHYSICAL_DESCRIPTION>                   {0:M}
    +1 CONT <PHYSICAL_DESCRIPTION>                 {0:M}
 n   SIGN <SIGNATURE_INFO>                         {0:M}
 n   NMR <COUNT_OF_MARRIAGES>                      {0:1}
 n   NCHI <COUNT_OF_CHILDREN>                      {0:1}
 n   NATI <NATIONALITY>                            {0:M}
 n   CAST <CASTE_NAME>                             {0:M}
 n   ADDR <ADDRESS_LINE>                           {0:M}
    +1 CONT <ADDRESS_LINE>                         {0:3}
    +1 DATE <DATE_VALUE>                           {0:1}
    +1 PHON <PHONE_NUMBER>                         {0:1}
```

LDS_CHILD_SEALING_EVENT:=

```
 n   SLGC                                          {1:1}
    +1 DATE <DATE_VALUE>                           {0:1}
    +1 TEMP <TEMPLE_VALUE>                         {0:1}
```

LDS_FAM_ORDINANCE_EVENT:=

```
n SLGS                                  {1:1}
  +1 DATE <DATE_VALUE>                  {0:1}
  +1 TEMP <TEMPLE_VALUE>                {0:1}
```

LDS_INDI_ORDINANCE_EVENT:=

```
n <LDS_INDI_ORD>                        {1:1}
  +1 DATE <DATE_VALUE>                  {0:1}
  +1 TEMP <TEMPLE_VALUE>                {0:1}
```

NOTE_STRUCTURE:=

This structure allows comments about the information originated by the submitter.

```
n CONT <SUBMITTERS_TEXT>                {1:M}
n NOTE @XREF:NOTE@                      {0:1}
```

REPOSITORY_STRUCTURE:=

```
n NAME <REPOSITORY_NAME>                {0:1}
n ADDR <ADDRESS_LINE>                   {0:1}
  +1 CONT <ADDRESS_LINE>                {0:3}
n PHON <PHONE_NUMBER>                   {0:1}
n CNTC <CONTACT_PERSON>                 {0:M}
```

SOURCE_STRUCTURE:=

```
n TYPE <SOURCE_CLASSIFICATION_CODE>     {0:1}
n EVEN <EVENT_CLASSIFICATION_CODE>      {0:1}
n NAME <DESCRIPTIVE_TITLE>              {0:1}
n PAGE <PAGE_DESCRIPTION>               {0:1}
n EDTR <EDITED_BY_NAME>                 {0:1}
n CPLR <COMPILED_BY_NAME>               {0:1}
n XLTR <TRANSLATED_BY_NAME>             {0:1}
n INFT <INFORMANTS_NAME>                {0:1}
n INTV <INTERVIEWERS_NAME>              {0:1}
[
n AUTH <AUTHOR_NAME>                    {0:M}
|
n AUTH @XREF:SUBM@                      {0:1}
]
n PERI <SOURCE_TIME_PERIOD>             {0:M}
n DATE <ENTRY_RECORDING_DATE>           {0:1}
n PLAC <SOURCE_JURISDICTION_PLACE>      {0:1}
n TEXT <SOURCE_TEXT>                    {0:1}
  +1 CONT <SOURCE_TEXT>                 {0:M}
n RECO <SOURCE_RECORDER_CODE>           {0:1}
n FIDE <SOURCE_FIDELITY_CODE>           {0:1}
n INDX <SOURCE_INDEXED_CODE>            {0:1}
n PUBL                                  {0:1}
  +1 NAME <PUBLICATION_NAME>            {0:1}
  +1 DATE <PUBLICATION_DATE>            {0:1}
  +1 PLAC <PUBLICATION_PLACE>           {0:1}
  +1 PUBR <PUBLISHER_NAME>              {0:1}
n SERS <SERIES_VOLUME_DESCRIPTION>      {0:1}
n LCCN <LIBRARY_CONGRESS_CALL_NUMBER>   {0:1}
```