```
  n  QUAY <QUALITY_OF_DATA>                          {0:1}
  n  REFS @XREF:SOUR@                                {0:M}
  n  SOUR @XREF:ANY@                                 {0:M}
  n  SUBM @XREF:SUBM@                                {0:M}
[
  n  NOTE <SUBMITTERS_TEXT>                          {1:1}
    +1 <<NOTE_STRUCTURE>>{0:1}
|
  n  NOTE @XREF:NOTE@                                {0:M}
]
[
  n  REPO                                            {0:1}
    +1 <<REPOSITORY_STRUCTURE>>                      {1:1}
|
  n  REPO @XREF:REPO@                                {0:1}
]
    +1 MEDI <MEDIA_TYPE_CODE>                        {0:M}
    +1 CALN <SOURCE_CALL_NUMBER>                     {0:1}
    +1 REFN <MANUAL_FILING_IDENTIFICATION>           {0:1}
    +1 FILM <SOURCE_FILM_NUMBER>                     {0:1}
      +2 ITEM <FILM_ITEM_IDENTIFICATION>             {0:1}
  [
    +1 NOTE @XREF:NOTE@                              {0:1}
  |
    +1 NOTE <SUBMITTERS_TEXT>                        {1:1}
      +2   <<NOTE_STRUCTURE>>                        {0:1}
  ]
  n  STAT <SEARCH_STATUS>                            {0:1}
    +1 DATE <SEARCH_STATUS_DATE>                     {1:1}
```

SUPPORT_INFO:=

This structure provides information pertaining to the enclosing item, i.e., information about the information. It may occur within any context.

```
[
  n  DATE <DATE_VALUE>                               {0:1}
|
  n  PLAC <PLACE_VALUE>                              {0:1}
|
  n  SOUR [<SOURCE_TEXT> | @XREF:SOUR@]
    +1   <<SOURCE_STRUCTURE>>                        {0:1}
|
  n  NOTE [ <SUBMITTERS_TEXT> | @XREF:SOUR@ ]        {0:1}
    +1   <<NOTE_STRUCTURE>>                          {1:1}
|
  n  SUBM @XREF:SUBM@                                {0:1}
|
  n  QUAY <QUALITY_OF_DATA>                          {0:1}
|
  n  CHAN                                            {0:M}
    +1 DATE <CHANGE_DATE>                            {1:1}
      +2 TIME <TIME_VALUE>                           {0:1}
]
```

PRIMITIVE ELEMENTS OF THE LINEAGE-LINKED FORM

ADDRESS_LINE:= {Size=1:40, Type=CHARACTERS}
Address information which, when combined with a NAME and CONTinuation lines, meets postal requirements for sending communications through the mail.

AGE_VALUE:= {Size=1:30, Type=CHARACTERS}
A number indicating the age in years, months, and/or days. Any labels must come after their corresponding number, i.e. 4 yr 8 mo 10 da. The year is required, listed first, even if 0 (zero).

ANCESTRAL_FILE_NUMBER:= {Size=1:8, Type=CHARACTERS}
This is a record number of an individual record contained in the Ancestral File maintained by the Family History Department. This number simplifies the matching process when submitting records that are intended to add additional data or to change data for a specific record contained in the Ancestral File.

ASSOCIATION_DESCRIPTOR:= {Size=1:90, Type=CHARACTERS}
This is a word or phrase that describes the association between this individual and the other individual in the context pointed to. (e.g., n ASSOC great grandfather @XREF:SUBM@ would be read, this person is a great grandfather of the individual found in submitter record.)

AUTHOR_NAME:= {Size=1:120, Type=CHARACTERS}
<NAME_VALUE>
This is the name of the person who authored or co-authored the referenced material.

CASTE_NAME:= {Size=1:90, Type=CHARACTERS}
A name assigned to a particular group that this person was associated with, such as a paticular racial group, religious group, or a group with an inherited status.

CEMETARY_NAME:= {Size=1:90, Type=CHARACTERS}
The name of the cemetary associated with a burial.

CHANGE_DATE:= {Size=10:11, Type=CHARACTERS}
<EXACT_DATE>
The date that this data was last changed.

CHARACTER_SET:= {Size=1:8, Type=CHARACTERS}
A code value representing the character set to be used in interpreting this data. The default character set is ANSEL. Other options are not defined.

CHILD_FAMILY_EVENT_DESCRIPTOR:= {Size=1:90, Type=CHARACTERS}
A word or phrase that describes or modifies the adoption event being reported. Systems that display data from the GEDCOM form should be able to display the descriptor value in their output, possibly inside of parenthesis ().

CALENDAR_ESCAPE_SEQUENCE:= {Size=4:15, Type=CHARACTERS}
[@#DHEBREW@ | @#DROMAN@ | @#DFRENCH_R@ | @D#GREGORIAN@ | @D#JULIAN@ | @D#UNKNOWN@]
An escape sequence which allows date from one of the indicated calendars to be represented. The default calendar is the Gregorian calendar.

COMPILED_BY_NAME:= {Size=1:120, Type=CHARACTERS}
The name of the person who compiled an information source.

CONTACT_PERSON:= {Size=1:120, Type=CHARACTERS}
<NAME_VALUE>
The name of the person to whom communications should be addressed.

COPYRIGHT_STATEMENT:= {Size=1:90, Type=CHARACTERS}
A copyright statement needed to protect the rights of the owner(s) of this data.

COUNT_OF_CHILDREN:= {Size=1:2, Type=NUMBER}
The number of children that this person (all marriages) or these parents were known to have been the parent(s) of.

COUNT_OF_MARRIAGES:= {Size=1:2, Type=NUMBER}
The number of times that this person was known to have been married.

DATE_MODIFIER :=
[ABT | AFT | BEF | BET | EST | <CALENDAR_ESCAPE_SEQUENCE>]

DATE_PHRASE:= {Size=1:90, Type=TEXT}
<text>
Any date statement which adds understanding to when an event occurred. Does not include a numerical year equivalent.

DATE_RANGE:=
[BET <REGULAR_DATE> AND <REGULAR_DATE>]

DATE_VALUE:= {Size=1:90, Type=TEXT}
[<REGULAR_DATE> | <DATE_PHRASE> | <DATE_RANGE> | <DATE_WITH_BC> | <DATE_MODIFIER> <REGULAR_DATE>]
(See Chapter 4 on "How To Record Dates".)

DATE_WITH_BC:= {Size=1:90, Type=TEXT}
[<DATE_PHRASE> <YEAR> B.C.]
This represents a B.C. date.

DAY:= {Size=1:2, Type=DIGIT}
dd
This field represents the day of the month where dd is a numeric digit whose value is within the valid range of the days for the particular month in which this day is for. A leading zero is optional.

DESCRIPTIVE_TITLE:= {Size=1:247, Type=CHARACTERS}

A descriptive title of the information source, such as a description of:

- A title of an article published in a periodical.
- A letter, showing who sent the letter to whom, and when.
- A transaction between a buyer and seller, naming them, and when.
- A Family Bible containing genealogical information, who owned it, and some additional description of the book.
- A description of a personal interview.

DIVORCE_DESCRIPTOR:= {Size=1:90, Type=CHARACTERS}

A word or phrase that commonly describes the type of separation that took place between husband and wife. The separation descriptor should use the same word or phrase and in the same language, whenever possible, that was used by the recorder of the event. Systems that display data from the GEDCOM form should be able to display the descriptor value in their output, possibly inside of parenthesis ().

DIVORCE_EVENT_TAG:= {Size=3:4, Type=CHARACTER}

[ANUL | DIV | DIVF]

A family event tag. The preferred usage is to use the DIV tag with the <DIVORCE_DESCRIPTOR> value which describes the separation event. For example, use DIV Annullment rather than ANUL. The separation event tags shown above were defined in The GEDCOM Standard 4.0 and are included here for the sake of compatibility.

ENTRY_RECORDING_DATE:= {Size=1:90, Type=CHARACTERS}

<DATE_VALUE>

The date that the entry was entered into the source record by the recorder.

EVENT_CLASSIFICATION_CODE:= {Size=1:90, Type=CHARACTERS}

[<INDIV_EVENT_TAG> | <EVENT_DESCRIPTOR>]

This code classifies the source as to the primary event that caused this source record to be created.

EVENT_DESCRIPTOR:= {Size=1:90, Type=CHARACTERS}

This primitive must be used whenever the EVEN tag is used in order to define the event being cited. For example, if the event was a purchase of a primary residence, one would show this by using the EVEN tag followed by the phrase "Purchased Residence". When the event descriptor primitive is used with any of the defined event tags, it is to modify the basic definition of the associated tag. For example the BIRT tag could be used in connection with an EVENT_DESCRIPTOR of 'Stillborn' to modify the birth event as a stillborn birth. The event descriptor should use the same word or phrase and in the same language, when possible, that was used by the recorder of the event. Systems that display data from the GEDCOM form should be able to display the descriptor value in their output, possibly inside of parenthesis ().

EVENT_TAG:= {Size=3:4, Type=CHARACTERS}

[<INDIV_EVENT_TAG> | <MARRIAGE_EVENT_TAG>]

An event tag that chosen from the tags which comprise those identifying individual events or from those identifying marriage type events, including EVEN and MARR with event descriptors.

EXACT_DATE:= {Size=10:11, Type=CHARACTERS}
<DAY> <MONTH> <YEAR>
A formatted date with one space between the date parts.

FILE_NAME:= {Size=1:90, Type=CHARACTERS}
The source file name as specified on the source operating system. It must include the path, file name, and file extention.

FILM_ITEM_IDENTIFICATION:= {Size=1:90, Type=CHARACTERS}
This identifies a particular book or unit of material which may have been filmed with other books or units on the same microform. The convention used in the Family History Department microfilms is to include a separator frame with an item number to separate multiple books on a film.

GEDCOM_FORM:= {Size=1:15, Type=CHARACTERS}
[LINEAGE-LINKED | (others to be registered)]
Identifies the GEDCOM form used to construct this transmission.

INDIV_EVENT_TAG:= {Size=3:4, Type=CHARACTERS}
[BIRT | BAPM | BARM | BASM | BLES | BURI | CENS | CHR | CHRA | CONF | DEAT | EVEN | GRAD | NATU | ORDN | RETI | PROB | WILL]
The EVEN tag must be followed by an <EVENT_DESCRIPTOR> which describes the event. The <EVENT_DESCRIPTOR> is optional for the other types of events.

INTERVIEWERS_NAME:= {Size=1:90, Type=CHARACTERS}
The name of the person who conducted the interview for information.

INFORMANTS_NAME:=
A persons name that contributed information during an interview.

LANGUAGE_OF_TEXT:= {Size=1:25, Type=CHARACTERS}
[<LANGUAGE_TABLE>]
This indicates the language used in describing the data about an event or person. It is placed in the header indicating that the values contained in the transmission are generally written in the indicated language.

LANGUAGE_TABLE:= {Size=1:25, Type=CHARACTERS}
The valid values must be selected from the table of languages shown in the Encylopaedia Britannica 1989 Britannica Book of the Year.

LDS_INDI_ORD:= {Size=3:4, Type=CHARACTERS}
[BAPL | CONL | WAC | ENDL]
This field is a choice of religious events associated with The Church of Jesus Christ of Latter-day Saints. (See Appendix A for a definition of these tags.)

LIBRARY_CONGRESS_CALL_NUMBER:= {Size=1:20, Type=CHARACTERS}
Call number assigned to this item by the U.S. Library of Congress.

MANUAL_FILING_IDENTIFICATION:= {Size=1:90, Type=CHARACTERS}

A description of where the source is manually filed at this repository. Personal genealogical archives should be organized and filed so that items can be specifically identified and retrieved. This field allows the entry of a filing number or description of where the genealogical source material is located within the private or public archives. i.e. "Probate file Drawer 83, File D, Number 18".

MARR_EVENT_TAG:= {Size=3:4, Type=CHARACTERS}

[MARR | MARB | MARC | MARL | MARL | MARS | ENGA | EVEN]
The preferred usage is to use the MARR tag with the <MARRIAGE_DESCRIPTOR> value which describes the family event. For example, use MARR License rather than MARL. These marriage event tags shown above were defined in The GEDCOM Standard 4.0 and are included here for the sake of compatibility.

MARRIAGE_DESCRIPTOR:= {Size=1:90, Type=CHARACTERS}

A word or phrase that best describes the event that created this family. The marriage descriptor should use the same word or phrase and in the same language, when possible, that was used by the recorder of the event. Possible descriptors include "Childbirth-unmarried", "Common Law", "Tribal Custom", etc. Systems that display data from the GEDCOM form should be able to display the descriptor value in their output, possibly inside of parenthesis ().

MEDIA_TYPE_CODE:= {Size=1:15, Type=CHARACTERS}

[AUDIO | BOOK | ELECTRONIC | FICHE | FILM | VIDEO | MANUSCRIPT]
This code is selected from one of the media classifications above. The code selected is based on the type of media that the referenced source is stored on.

MONTH:= {Size=3:3, Type=CHARACTERS}

[JAN | FEB | MAR | APR | MAY | JUN |
JUL | AUG | SEP | OCT | NOV | DEC]

NAME_OF_SOURCE_DATA:= {Size=1:90, Type=CHARACTERS}

The name of the data source that was used to obtain the data in this transmission. For example, the data may have been obtained from a CD-ROM disc that was named "CD-ROM U.S. 1880 CENSUS vol. 13".

NAME_VALUE:= {Size=1:120, Type=CHARACTERS}

```
[
 <TEXT> |
 <TEXT>/<TEXT>/ |
/<TEXT>/<TEXT> |
 <TEXT>/<TEXT>/<TEXT>
]
```

The surname of an individual, if known, should be between two slash / characters. The order of the pieces of the name should be the order which the person would customarily have used the name when giving it to a recorder. (See Chapter 4, "How To Record Names Of Individuals" section)

NATIONALITY:= {Size=1:90, Type=CHARACTERS}

Indicates the common national origin of this person and his or her grandparents.

OCCUPATION:= {Size=1:90, Type=CHARACTERS}

The kind of activity or vocation that one does to earn a living.

PAGE_DESCRIPTION:= {Size=1:90, Type=CHARACTERS}

Identifies the page within the source. This may be a page number range, a specific page number, or another way of defining how to find the specified information within the source.

PERMANENT_RECORD_FILE_NUMBER:= {Size=1:18, Type=CHARACTERS}

<REGISTERED_RESOURCE_IDENTIFIER>:<RECORD_IDENTIFIER>

The record number that uniquely identifies this record within a registered network resource (future). The number will be usable as a cross reference pointer. The use of the colon ":" is reserved to indicate the separation of the 'registered resource identifier' which precedes the colon and the unique 'record identifier' within that resource which follows the colon.

PHONE_NUMBER:= {Size=1:25, Type=CHARACTERS}

A phone number formatted to provide international phone access.

PHYSICAL_DESCRIPTION:= {Size=1:247, Type=CHARACTERS}

An unstructured list of the attributes which describes the physical characteristics of a person, place, or object.

PLACE_VALUE:= {Size=1:120, Type=CHARACTERS}

[
<TEXT> |
<TEXT>, <PLACE_VALUE>
]

The jurisdictional name of the place where the event took place. Jurisdictions are separated by commas. ie. town, county, state or village, parish, country. Receiving systems cannot assume that the nth locality position is necessarily a specific level of jurisdiction. Missing intermediate jurisdictions, if known to exist, should be represented by adjacent placeholder commas.

POSSESSIONS:= {Size=1:247, Type=CHARACTERS}

A list of possessions (real estate or other property) belonging to this individual, separated by commas.

PUBLICATION_DATE:= {Size=10:11, Type=CHARACTERS}

<DATE_VALUE>

The date this source was published or compiled.

PUBLICATION_NAME:= {Size=1:120, Type=CHARACTERS}

The name of a publication such as a book, pamphlet, periodical, newspaper, or other monographic publication.

PUBLICATION_PLACE:= {Size=1:120, Type=CHARACTERS}
The name of the place (City, State) where an item was published or the location of the main office of the publisher.

PUBLISHER_NAME:= {Size=1:120, Type=CHARACTERS}
The name of the publisher of the referenced publication.

QUALITY_OF_DATA:= {Size=1:1, Type=DIGIT}
[0 | 1 | 2 | 3]
Submitter's assessment of of the reliability of the information:
0 = Unreliable evidence or data was estimated.
1 = Direct or primary evidence with some question of reliability or potential for bias (e.g., an autobiography).
2 = Secondary evidence.
3 = Direct and primary evidence used, or a preponderance of evidence.

REGULAR_DATE:= {Size=1:90, Type=TEXT}
[<DATE_MODIFIER>] [<EXACT_DATE> | <MONTH> <YEAR> | <YEAR]

RELATIONSHIP_DESCRIPTOR: {Size=1:90, Type=CHARACTERS}
An English word or phrase that describes the relationship between this individual and the individual pointed to. Systems that display data from the GEDCOM form should be able to display the descriptor value in their output, possibly inside of parenthesis ().

RELIGIOUS_AFFILIATION:= {Size=1:90, Type=CHARACTERS}
A name of the religion that this person or record was affiliated with.

REPOSITORY_NAME:= {Size=1:90, Type=CHARACTERS}
The official name of the archive in which the stated source material is stored.

ROLE_DESCRIPTOR:= {Size=1:90, Type=CHARACTERS}
Used in connection with the ROLE tag, this descriptor is a word or phrase that identifies the role of each peron in the event being described. This should be the same word or phrase, and in the same language, that the recorder used to define the role in the actual record. Systems that display data from the GEDCOM form should be able to display the descriptor value in their output, possibly inside of parenthesis ().

ROLE_TAG:= {Size=1:90, Type=CHARACTERS}
[BUYR | CHIL | FATH | HDOH | HEIR | HUSB | INFT | MOTH | OFFI | RECO | REL | ROLE | SELR | TXPY | WIFE | WITN]
These tags indicate the various roles of individuals mentioned in a source event record. If the role being cited is different than one of the above defined roles then use the ROLE tag followed by a <ROLE_DESCRIPTOR> to define the role.

SEARCH_STATUS:= {Size=1:90, Type=CHARACTERS}

[ACTIVE | INFO_FOUND | INFO_NOT_FOUND | ON_ORDER | PLANNED | RECONCILLED]

This status field shows the status of using the specified source for the enclosing information where:

ACTIVE	=	This source is currently being searched.
INFO_FOUND	=	Part or all of the expected information was found.
INFO_NOT_FOUND	=	Indicates that this source is no longer in use because this information could not be found.
ON_ORDER	=	Request for source has been sent to the Repository.
PLANNED	=	Source recommended for examination.
RECONCILLED	=	The data in this record has been reconcilled with the indicated resource data record.

SEARCH_STATUS_DATE:= {Size=1:90, Type=CHARACTERS}

<EXACT_DATE>

The date on which a SEARCH_STATUS was set.

SERIES_VOLUME_DESCRIPTION:= {Size=1:247, Type=CHARACTERS}

A description of a successive publication. The description should include an identification of timing of the publication such as Spring, Summer, Fall, Winter, etc. Volume numbers of periodicals or of multivolume books are also stated.

SEX_VALUE:= {Size=1:7, Type=CHARACTERS}

The following code indicates the sex of the individual:

M = Male

F = Female

SIGNATURE_INFO:=

[YES | NO | SYMBOL_NAME]

Identifies the type of signature used by this person.

YES	=	This person knew how to sign his or her name.
NO	=	This person did not use a signature or know how to sign.
SYMBOL_NAME	=	The descriptive name of the sybol used as a signature by this person.

SOURCE_CALL_NUMBER:= {Size=1:90, Type=CHARACTERS}

An identification number used to file and retrieve items from the holdings of a repository.

SOURCE_CLASSIFICATION_CODE:= {Size=7:90, Type=CHARACTERS}

[<INDIV_EVENT_TAG> | <MARR_EVENT_TAG> | <DIV_EVENT_TAG> | GENEALOGY | ORAL_GENEALOGY | NEWSPAPER | PERIODICAL | CORRESPONDENCE | INTERVIEW | CIVIL_REC | CENSUS | MILITARY | BIOGRAPHY | HISTORY | FAMILY_REC | TRADITION | PERSONAL_KNOWLEDGE | JOURNAL | <SOURCE_CLASS_DESCRIPTOR>]

This classifies the source citation as to whether it is citing a document of a primary event or citing events from:

<INDIV_EVENT_TAG>	=	A source documenting an individual type event.
<MARR_EVENT_TAG>	=	A source documenting a marriage type event.
<DIV_EVENT_TAG>	=	A source documenting a divorce type event.
GENEALOGY	=	A compiled genealogical work.

ORAL_GENEALOGY	=	A recited genealogy, such as a tribal or clan genealogy.
NEWSPAPER	=	A newspaper account.
PERIODICAL	=	An account published in a periodical.
CORRESPONDENCE	=	A letter or other written communication.
INTERVIEW	=	An interview with another person.
CIVIL_REC	=	A record from a court or other government organization.
CENSUS	=	A official census.
MILITARY	=	A military record.
BIOGRAPHY	=	A published biographical compilation.
HISTORY	=	A published historical account.
TRADITION	=	A source that was compiled from accounts handed down by word of mouth from one generation to another.
KNOWLEDGE	=	An accounting by a person having personal memory of an event.
JOURNAL	=	A personal record or diary.

Systems that display data from the GEDCOM form should be able to display the descriptor value in their output, possibly inside of parenthesis ().

SOURCE_CLASS_DESCRIPTOR:= {Size=1:25, Type=CHARACTERS}

A descriptive word or phrase that helps to classify the type of source that is being cited. This descriptor is used only after examining the controlled descriptors as defined under <SOURCE_CLASSIFICATION_CODE> and finding that none of the classifications fit this source type. Systems that display data from the GEDCOM form should be able to display the descriptor value in their output, possibly inside of parenthesis ().

SOURCE_FIDELITY_CODE:= {Size=7:17, Type=CHARACTERS}

[ORIGINAL | PHOTOCOPY | TRANSCRIPT | EXTRACT]

This code is a selection of one of the above choices designed to provide an assessment of the fidelity (the exactness) of this source material.

ORIGINAL	=	This source is the original record being cited.
PHOTOCOPY	=	This source is a photocopy of the cited record.
TRANSCRIPT	=	This source is a transcribed record of the original record.
EXTRACT	=	This source is an abridgement and/or interpretation of the original record.

SOURCE_FILM_NUMBER:= {Size=1:15, Type=CHARACTERS}

A unique number assigned to by the repository to identify the specific microfilm containing information about the event of interest recognized by the repository.

SOURCE_INDEXED_CODE:= {Size=1:1, Type=CHARACTERS}

[Y | N]

An indication of whether this source has been indexed by names.

Y = This source contains an index.

N = This source does not contain an index.

SOURCE_JURISDICTION_PLACE:=
<PLACE_VALUE>
The highest level place name that covers all of the event places contained as in this information source. For example, "United States of America" would be used when referencing the U.S. 1880 Census.

SOURCE_RECORDER_CODE:= {Size=1:25, Type=CHARACTERS}
[PERSONAL | CIVIL | CHURCH | COMMERCIAL | INSTITUTIONAL]
A classification of the type of authority the person or institution responsible for making the record possessed.

PERSONAL	=	Recorder of record was acting as an individual or family record keeper.
CIVIL	=	Recorder of record was acting as a civil officer or clerk.
CHURCH	=	Recorder of record was acting as a church officer or clerk.
COMMERCIAL	=	This record was produced by a business enterprise.
INSTITUTIONAL	=	This record was produced by an institution such as a genealogical society, school, prison, or other institution.

SOURCE_TEXT:= {Size=1:247, Type=CHARACTERS}
<TEXT>
A verbatim copy of any description or verbage contained within the source. This indicates notes that are actually contained in the source document, not someones opinion notes about the source.

SOURCE_TIME_PERIOD:= {Size=1:25, Type=CHARACTERS}
<DATE_VALUE> - <DATE_VALUE>
The time period covered by this source. Either end of the date range may be missing, indicating an indefinite past or future.

SUBMITTERS_TEXT:= {Size=1:247, Type=CHARACTERS}
Comments or opinions originated by the submitter.

SYSTEM_NAME:= {Size=1:40, Type=CHARACTERS}
Identifiifies the product that sent or will receive the GEDCOM output. The system name was obtained when the product was registered as a GEDCOM-compatible product. All GEDCOM transmissions must be so identified.

TEMPLE_VALUE:= {Size=5:5, Type=CHARACTERS}
A 5 character abbreviation of the temple in which LDS temple ordinances are performed. (See LDS Church publication, 'Come unto Christ through Temple Ordinances and Covenants' for a table of valid abbreviations.)

TEXT:= {Size=1:247, Type=CHARACTERS}
A string composed of any valid character or string of characters in the GEDCOM character set.

TIME_VALUE:= {Size=1:10, Type=CHARACTERS}

[hh:mm:ss.fs]

The time of a specific event, usually a computer timed event where:
hh = hours on a 24 hour clock
mm = minutes
ss = seconds
fs = decimal fraction of a second, 2 digits.

TIME_PERIOD:=

[FROM <REGULAR_DATE> TO <REGULAR_DATE> | FROM <REGULAR_DATE> | TO <REGULAR_DATE>]

The choice "FROM <REGULAR_DATE>" indicates a range from a beginning date to an indifinite future date. The choice "TO <REGULAR_DATE>" indicates from an indefinite beginning to a specified date.

TITLE:= {Size=1:90, Type=CHARACTERS}

A descriptive, general name or formal designation used by an individual.

TRANSLATED_BY_NAME:= {Size=1:120, Type=CHARACTERS}

The name of the person that translated someone else's words into the language as it appears in the source being cited.

TRANSMISSION_DATE:= {Size=10:11, Type=CHARACTERS}

<EXACT_DATE>

The date that this transmission was created.

USER_REFERENCE_NUMBER:= {Size=1:20, Type=CHARACTERS}

A user-defined number or text that the submitter uses to identify this record. For instance it may be a record number within the submitter's automated or manual system, or a page and position number on a pedigree chart.

VERSION_NUMBER:= {Size=1:15, Type=CHARACTERS}

An identifier which represents the version level assigned to the associated product. It is defined and changed by the creators of the product.

XREF:= {Size=1:15, Type=CHARACTERS}

A XREF is either of type pointer or of type cross reference identifier. If the enclosed value appears before the tag in a GEDCOM-line, then it is a cross reference identifier type. If it appears after the tag in a GEDCOM-line, then it is a pointer type. The method of delimiting a pointer or cross reference identifiers in a GEDCOM-line is to enclose the pointer or cross reference identifier within at-signs "@", i.e. @I123@. A XREF may not begin with a pound sign "#". This is to avoid confusion with an escape sequence prefix "@#". The colon ":" is reserved for future network reference.

XREF:ANY:= {Size=1:15, Type=CHARACTERS}

<XREF>

This pointer is a universal pointer meaning that it may point to any other cross reference identifier type.

XREF:EVEN:= {Size=1:15, Type=CHARACTERS}
<XREF>
A pointer to, or a cross reference identifier of, a source event record.

XREF:FAM:= {Size=1:15, Type=CHARACTERS}
<XREF>
A pointer to, or a cross reference identifier of, a family record.

XREF:INDI:= {Size=1:15, Type=CHARACTERS}
<XREF>
A pointer to, or a cross reference identifier of, an individual record.

XREF:NOTE:= {Size=1:15, Type=CHARACTERS}
<XREF>
A pointer to, or a cross reference identifier of, a note record.

XREF:REPO:= {Size=1:15, Type=CHARACTERS}
<XREF>
A pointer to a REPOsitory, a SUBMitter, or an INDIvidual record, or a cross reference identifier of a repository record.

XREF:SOUR:= {Size=1:15, Type=CHARACTERS}
<XREF>
A pointer to a SOURce, a SUBMitter, or an INDIvidual record, or a cross reference identifier of a source record.

XREF:SUBM:= {Size=1:15, Type=CHARACTERS}
<XREF>
A pointer to a SUBMitter, or an INDIvidual record, or a cross reference identifier of a submitter record.

YEAR:= {Size=3:4, Type=NUMBER}
A numeric representation of the calendar year in which an event occurred. Years less than 3 digits long will be treated as a number in a phrase.

COMPATIBILITY WITH PREVIOUS GEDCOM VERSIONS

Roots III and GRIOT Alternative products implemented a source citation structure prior to GEDCOM release 5.0 which is slightly incompatible. Compatibility with these products may be maintained by doing the following:

1. Treat a TITL tag as if it were a SOUR tag.
2. Treat the text value of a TITL tag at level 0 as if it were the value of the NAME tag within the SOURce enclosure.

Chapter 3
GEDCOM TRANSMISSION FILE

INTRODUCTION

This chapter contains information you need to implement GEDCOM transmissions. This includes examples for creating header and trailer records, and for the conventions in naming your transmission file.

HEADERS AND TRAILERS IN THE GEDCOM TRANSMISSION

An example of how the header and trailer records appear in GEDCOM lineage-linked format is shown below:

Level	Cross-Ref. ldentifier	Tag	Value
0		HEAD	
1		SOUR	PAF
2		VERS	2.1
1		GEDC	
2		VERS	5.0
2		FORM	LINEAGE-LINKED
1		DEST	ANSTFILE
1		SUBM	@R1@
0	@1@	INDI	
1		NAME	John Ouentin/Doe/
1		SEX	Male
1		BIRT	
2		DATE	1836
2		PLAC	Illinois
1		DEAT	
2		DATE	24 Oct 1905
2		PLAC	Idaho Falls, Bonneville, Idaho
1		FAMS	@4@
0	@2@	INDI	
1		NAME	Mary Ann/Wilson/
1		SEX	Female
1		BIRT	
2		DATE	1838
1		FAMS	@4@
0	@3@	INDI	
1		NAME	Joe /Doe/
1		SEX	Male
1		BIRT	
2		DATE	11 June 1861
2		PLAC	Idaho Falls, Bonneville, Idaho
1		FAMC	@4@
0	@4@	FAM	
1		HUSB	@1@
1		WIFE	@2@
1		MARR	License
2		DATE	Dec 1881
1		CHIL	@3@
0		TRLR	

The example on the preceding page is a sample transmission of genealogical information about three individuals who are members of the same family (lineage)--husband, wife, and child. The lines making up the information appear between the header (HEAD) and trailer (TRLR) records.

WHY HEADERS AND TRAILERS ARE USED

GEDCOM data format is used to transfer a wide variety of data to a wide variety of computer systems. The Family History Department's Receiving and Routing System uses header and trailer records to route the information in each GEDCOM transmission to the right place. In the sample at the beginning of this chapter, PAF (SOUR) 2.1 (VERS)--the sending system name and version--is routing the information to ANSTFILE (Ancestral File)--the destination (DEST). To enable processing of GEDCOM transmission at any family history centers, the SOUR system name must be registered with the Family History Department GEDCOM coordinator. Destination system names will depend on the purpose for the transmission and can also be obtained from the GEDCOM coordinator. (See GEDCOM Coordinator's address on the title page.)

Header and trailer records also include other information to help an application software system process the data in the transmission. For example, a character set default for the entire transmission is set in the header using the appropriate escape sequence for selecting the desired character set (see chapter 5). The header and trailer are separate from any other protocols attached to the transmission by an electronic communications network.

HOW TO USE A HEADER

Use a header to begin every GEDCOM transmission. A header has both required and optional GEDCOM lines. Each line begins with a level number and a tag (in capital letters) and may be followed by a value.

Required Lines

The following are the lines required in all GEDCOM transmission headers.

Example:

Level	Tag	Value	
0	HEAD		
1	SOUR	PAF	
2	VERS	2.1	
1	DEST	ANSTFILE	
1	SUBM	@R1@	note: @R1@ is a pointer to a submitter record.
1	GEDC		
2	VERS	5.0	

- HEAD
  The first line of a transmission always has the level number 0 and contains the tag HEAD. No value is specified. All other lines in the header are at subordinate levels--level 1 in the example above.

- SOUR
  At level 1 a transmission always contains the tag SOUR. The value for the SOURce line is the resource identifier (the name of the system or file that sends the transmission) A source resource identifier can be in upper and lower case with a length of from 1 to 40 characters. At level 2 below SOUR is a VERS tag to specify the version level of the source system. (A resource identifier is a single string of alphanumeric characters that identify any system, file, etc. that may participate in a GEDCOM transmission as either a sender or a receiver.) The value (name of the sending file) for the sample SOURce line above is PAF 2.1 (Personal Ancestral File, release 2.1).

  The receiving and routing function of the Family History Department associates the resource identifier with the actual locations of sender and receiver. This permits relocation of systems and files without modification of the systems that initiate transmissions, or of data containing pointers to records in other systems. The resource identifier is assigned by the Data Administration section of the Family History Department.
  - VERS
    Under SOURce, VERSion is a short phrase identifying which release of the product generated the transmission. The phrase is defined by the creator of the product. i.e., VERS 2.1.

- DEST
  The value for the DESTination line is required when sending data to the Family History Department for adding records to the ancestral file or for submitting records to TempleReady processing. This tag value is the resource identifier (the name of the system or file to which the transmission is being sent). A source resource identifier can be in upper and lower case with a length of from 1 to 40 characters.For example, the value (name of the receiving file) for the sample DESTination line in the preceding examples is ANSTFLE, indicating that this transmission is destined for the Ancestral File. The value for submitting data to the TempleReady system is "TempleReady".

- SUBM
  This tag is required and points to a submitter record that is included in the transmission. The submitter record should be in the form as prescribed by the Submitter structure in chapter 2.

- GEDC
  - VERS
    VERSion under the GEDC tag is a short phrase identifying which release of the GEDCOM Standard document was used for the specification for the product's GEDCOM implementation. For this release the VERS line is "VERS 5.0".

Optional Header Lines

You may include optional lines in GEDCOM transmission headers, depending on your need or preference for additional information. One or more optional lines would immediately follow the DEST line. The four optional lines shown below are possible optional lines for the sample transmission on page 3-1. They can occur in any order.

Example:

Level	Tag	Value
1	DATE	3 APR 1989
1	TIME	13:01
1	CHAR	@#ANSEL@
1	FILE	YOUNG.GED

- DATE
  This line contains the date the sender generated the GEDCOM transmission. (For more information about the date value, see chapter 4, "How To Record Dates".

- TIME
  This line contains the time the sender generated the GEDCOM transmission. The value is the time (military time) the file was created. (For more information about the time value, see chapter 4 "How To Designate Time" section.)

- CHAR
  This line is used to change the default character set of an entire transmission to another character set.

  Example:

Lvl	Tag	Value
0	HEAD	
1	SOUR	PAF 2.1
1	DEST	ANSTFILE
1	CHAR	ANSEL

  The value is the name of the character set. The designation ANSEL is the name (value) for the GEDCOM default character set "8-Bit ANSEL". (See chapter 5 for more information about character sets.)

  If you use the default character set, the required lines of your GEDCOM transmission (the header and trailer) will be coded in 8-Bit ANSEL characters restricted to decimal codes 10 (line feed), 13 (carriage return), and 32 through 126 (printable characters). The characters specified will be identical to those in the 7-Bit ASCII (USA version) character set.

  If the computer you are using to send the transmission cannot accommodate the default character set, you must convert all required header lines to it (8-Bit ANSEL) before sending the transmission to a computer that can accommodate the default character set.

A change of character sets, whether in the header or in the body of the data, is effective only for a single transmission. All subsequent transmissions will be in the default character set unless it is changed.

- FILE
  This line contains the name of the GEDCOM transmission file generated by the sender. The value is the name of the file.

HOW TO USE A TRAILER

Use a trailer to end your transmission. A GEDCOM transmission must always be terminated by one line containing the tag TRLR (trailer) with the level 0. No value is specified for this line.

NAMING YOUR TRANSMISSION FILE

The GEDCOM transmission data are normally created on DOS compatible diskettes. By convention the filename extention (the 3 characters after the period ".") is "GED". Macintosh filenames does not use any file extention in their naming.

MULTIPLE DISKETTE FILE NAMES

When the GEDCOM file is too large to fit on a single diskette, the file is divided after any whole-line (last character is the terminator), and the filename extension is changed from "GED" to "G##" where "##" is "00" for the second disk, "01" for the third, etc. (See example below.) This allows the receiving software to ensure that disks are read in the correct sequence.

By convention, Macintosh filenames use parens "()" to set apart each diskette with a different consecutive filename. Therefore, Macintosh filenames consist of just the user-supplied name for the first disk, then the user-supplied name concatenated with "(##)" for subsequent disks where "##" is "00" for the second disk, "01" for the third disk, etc. (See example below.)

Given that the user- supplied portion of the file name is "SMITH", complete filenames for a three-disk transmission would be:

Disk	DOS Filename	Macintosh Filename
1	SMITH.GED	SMITH
2	SMITH.G00	SMITH(00)
3	SMITH.G01	SMITH(01)

The GEDCOM TRLR (trailer) record appears only on the final disk (see Chapter 2).

Chapter 4
GEDCOM VALUES

INTRODUCTION

This chapter contains information you need to implement GEDCOM values. You will find an explanation about the purpose of these values and how to use them when creating a transmission. An example of how they appear in GEDCOM lineage-linked format is shown here.

Example:

Level	Cross-Ref. Identifier	Tag	Value*
0		HEAD	
1		SOUR	PAF
2		VERS	2.1
1		DEST	ANSTFILE
0	@1@	INDI	
1		NAME	John Quentin/Doe/
1		SEX	Male
1		BIRT	
2		DATE	1836
2		PLAC	Illinois
1		DEAT	
2		DATE	24 Oct 1905
2		PLAC	Idaho Falls, Bonneville, Idaho
1		FAMS	@4@
0	@2@	lNDI	
1		NAME	Mary Ann/Wilson/
1		SEX	Female
1		BIRT	
2		DATE	1838
2		PLAC	Iowa
1		FAMS	@4@
0	@3@	INDI	
1		NAME	Joe/Doe/
1		SEX	Male
1		BIRT	
2		DATE	11 June 1861
2		PLAC	Idaho Falls, Bonneville, Idaho
1		FAMC	@4@
0	@4@	FAM	
1		HUSB	@1@
1		WIFE	@2@
1		MARR	
2		DATE	Dec 1881
1		CHIL	@3@
0		TRLR	

The preceding example is a sample transmission of genealogical information about three individuals who are members of the same family (lineage)--husband, wife, and child.

WHY VALUES ARE USED

Values provide the actual raw data that is put in context by the proper use of the GEDCOM-tags so that the data can be properly represented. In the example on the preceding page, "Joe/Doe/" is the value specified by the tag NAME under the INDI tag which is identified as "@3@". Other values in other lines, such as the birth date and place, provide additional information about Joe Doe. The values "@4@" specified by the FAMC tag is a pointer to the FAMily record identified by "@4@" of which Joe Doe is a child.

The following value types have been defined so as to represent information about individuals, families, events, and relationships in a standard way: (Other value types will be defined as the need develops.)

- Names Values
  - Enclosed by the NAME tag.
- Dates Values
  - Enclosed by the DATE tag.
- Places Values
  - Enclosed by the PLAC tag.
- Events Values
  - Enclosed by the DEAT, BURI, BIRT, CHR, MARR, EVEN, and other event tags.
- Descriptor
  - Event Values
    - Used to further define the kind of event.
  - Relationship Values
    - Used to define a relationship.
  - Association Values
    - Used to define an association.
  - Systems designed to display data from a GEDCOM format should display the descriptor values as well as the subordinate context values.

- Information Values
  - Text values enclosed by SOURce and NOTE enclosures to provide supporting facts about the enclosing information or values enclosed by tags that were defined to provide additional facts pertaining to an individual, i.e. RELIgion and OCCUpation tag values.
- Pointers Values
  - A marker within a value field which points to other enclosures (structures) of the same value time.
- Miscellaneous Values
  - Used to support routing, processing, and routing.
- Resource Identifier Values
  - Uniquely identifies SOURce or DESTination systems or products. Resource identifiers are recommended by the systems creator and registered by the GEDCOM coordinator.

This chapter explains how to record these different value types in a lineage-linked format, to preserve the relationship of the individuals and to properly format the support information included in the GEDCOM transmission.