GUIDELINES FOR USING VALUES

Values are optional and of variable length upto a maximum GEDCOM-line length of 255 (this includes the length of the non-value components of a line). Place each value in the line with its tag. The value must appear after the space following the tag. End each value by using a terminator as described later in this chapter.

The value component may consist of any alpha, numeric, or other characters, except the escape-sequence prefix symbol "@#" or the escape-delimiter "@". These symbols have reserved meanings to the GEDCOM processor defined in the "ESCAPE SEQUENCES" section below. The at sign "@" is used for an escape mechanism to identify pointers, character set changes, calendar changes, or other shifts in representation rules. To include the at sign "@" as data, two of them should be sent together "@@", which represent a single at sign "@" as data.

Corresponding structures or lines (same tag structure) are used to record information that contains different opinions about the same item. The preferred data is listed first so that systems or reports that only accomodate a single value will show the preferred occurance. The existence of other possible values may be indicated in system output with a leading plus "+" sign, if desired.

ESCAPE SEQUENCES

The escape-sequence symbol "@#" allows for special processing including the inclusion of non-GEDCOM data. Currently four classes of escape sequences have been defined (see chapter 1 for exact grammar):

- "@#C....." for character-set changes.
- "@#D....." for calendar date changes.
- "@#L..XXX" for indicating a non-GEDCOM inclusion of XXX bytes.
- "@#F..file name" for indicating a inclusion of data from a file.

HOW TO RECORD NAMES OF INDIVIDUALS

Use the name value with the NAME tag to provide the actual name of an individual. The following example shows how name values provide the information indicated by the tag. These values can appear with varying level numbers.

Example:

Lvl	Tag	Value
1	NAME	John Quentin/Doe/

A name consists of a string of one or more name parts, separated by spaces, or by a slash "/" in the case of the surname. Capitalize the name of a person or place in the conventional manner--capitalize the first letter of each part and lowercase the other letters, unless conventional usage is otherwise. For example: McMurray.

Record the name pieces in the order they are spoken; the surname follows the given name(s), unless the name is traditionally spoken in some other order. The surname is Immediately preceded and followed by a slash "/". In cultures where there is no distiction between surnames and given names, slashes "/" should not be used.

Examples:

William Lee/Parry/	(Parry is surname)
William/Parry/Lee	(Surname Parry spoken in middle)
/Parry/	(No given names)
William	(No surname)
William/Lee Parry/	(Lee Parry is surname)

If diacritics or special characters are present in a name, preserve them in the manner referred to in chapter 5, "GEDCOM Character Sets."

Use ellipses--three periods "..."--to indicate missing or illegible name pieces.

Examples:

William Lee/Pa.../	(Part of surname is illegible)
William .../Parry	(Second given name is illegible)

Names of individuals who were known by different names should be recorded in the manner shown below:

Example:

Lvl	Tag	Value
0	INDI	
1	NAME	George/Lowther/
1	NAME	Geoff/Louder/

HOW TO RECORD DATES

Calendar

You specify a calendar for a date by following these three steps:

1. Start with the escape sequence indicator "@#" and a "D".
2. Type the name of the calendar.
3. End the designation with the terminator "@".

Example:

@#DARABIC@	Arabic calendar
@#DHEBREW@	Hebrew calendar
@#DFRENCH R@	French Republic calendar
@#DGREGORIAN@	Gregorian calendar
@#DJULIAN@	Julian calendar
@#DROMAN@	Roman calendar
@#DUNKNOWN@	date from unknown calendar

For further information about approved calendars, contact the GEDCOM coordinator, see GEDCOM Coordinator's address on the title page.

DATES

Place the date in the same line as the DATE tag, immediately after the space following the tag. Dates are of two kinds: regular and irregular.

Regular dates are bonafide dates in a controlled format from the conventional Gregorian calendar. Follow this procedure to record these dates:

29 FEB 1960 10 JAN 1802
1 JUN 1802 1802

Type the day (one or two characters) first, then the month (capitalize the first three letters of the English name of the month; do not use a period at the end), and then the year (four-character numeric year). The day and month may be omitted if unknown.

Irregular dates or dates that cannot fit the controlled date format. Irregular dates are typically treated as unformatted strings of characters. Record them exactly as they appear in the source. The following are some of the irregular date types and examples:

- A date from a calendar other than the conventional Gregorian calendar. Identify this date with "@#D" and the name of the calendar.
  Examples:
  @#DRoman@MDCCCXV
  @#DHebrew@26TAM5742

- Pre-1752 English calendar
  Examples:
  4/5 January 1751/52
  24 7ber 1725

- Partial date (except where only the year is known; a year alone constitutes a regular date)
  Example:
  5 June (year missing)

- Illegible date.
  Example:
  5 June... (year present but illegible)

- Ambiguous date
  Example:
  7-12-84 (July 12th or December 7th?; 1984 or 1884?)

- Approximate date
  Examples:
  ABT 1850
  BEF 3 MAR 1913
  BET 1904 AND 1905

- Date range
  Example:
  FROM 1904 TO 1905
  FROM 1904 (indefinite future)

TO 1905 (indefinite beginning)

- Feast date

  Example:
  2 days after Easter, 1690

- Dates for eras B.C. (before Christ) are recorded with the indicator B.C. appended after the date. A.D. (anno domini) dates are assumed if the B.C. indicator is missing.

  Example:
  600 B.C.

HOW TO RECORD PLACES (Localities)

A place name consists of one or more jurisdiction names (indicating one or more units In a political, ecclesiastical, or geographical hierarchy). Each jurisdiction name may consist of one or more name pieces (separated by spaces, such as Idaho Falls). Each name making up the full name is separated from the other by a comma (a space following each comma is optional).

The following examples show how place names appear in a GEDCOM transmission.

Examples:

Lvl	Tag	Value
2	PLAC	Illinois
2	PLAC	Idaho Falls,Bonneville,Idaho
2	PLAC	Chicago, Illinois
2	PLAC	Iowa

Follow these three steps to record the names of places:

1. Place the actual name of the place or locality in the same line as the PLAC tag, after the space that Immediately follows the tag.

2. List the jurisdictions in order of increasing size, smallest first. The number of jurisdictions varies, depending on the source.

   - If an intermediate jurisdiction is known to exist, but its name cannot be determined, indicate its absence by using adjacent commas. For example, a city and state may be given, but not a county.

     Example:
     Green,, New York

   - If the country referred to in the data, and the countries in which the data is prepared or used, are different, be sure the place name includes the country jurisdiction or an internationally recognized abbreviation, without periods.

     Example:
     Salt Lake City, Salt Lake, Utah, USA

3. Spell the name Pieces exactly as they appear in the source.

- Use the capitalization that appears in the source.
- If a name listed on the original record appears to be misspelled, be sure to preserve this spelling. Do not change it.

  Example:
  Green, Chenango County, Now York
  (Do not change Now to New; leave it Now.)
- If part or all of a place name is illegible, use ellipses--three periods "..."--to indicate exactly what part of the name is illegible.

  Example:
  Green, ...ango County, New York

HOW TO RECORD EVENTS

Use the tag that is the name of the event you want to record, if the tag for that event is in the appendix. For example, use BIRT for birth. If the tag is not in the appendix, use the event tag--EVEN. Then specify the name of the event as the value. Dates and places of events are usually recorded as related GEDCOM lines. Here is an example of an event and related Information:

Example:

Lvl	Tag	Value
1	BIRT	
2	DATE	1836
2	PLAC	Illinois
1	EVEN	Service in World War II
2	DATE	12 Oct 1942 to 5 Aug 1945

HOW TO DESIGNATE TIME

Use the time value to identify when a request was sent or when the event occurred. Use this value with the TIME tag. Time information is part of the header record (see chapter 3 for more information about the header). Follow these steps to designate time:

1. Place the time value--the time local to the event--in the same line as the TIME tag, after the space immediately following the tag.

2. Be sure to use 24-hour clock (military time) notation. Put the hour of the day first, then the number of minutes into the hour, and optionally the number of seconds into the minute. Separate each level with a colon ":" character.

   Examples:

Lvl	Tag	Value
0	HEAD	
1	SOUR	PAF
1	TIME	13:25:10
0	INDI	
1	BIRT	
2	DATE	12 June 1950
3	TIME	14:53

HOW TO USE POINTERS

Use pointers to show how information in one or more lines of a GEDCOM transmission is related to information in another line of the same transmission. Each pointer must contain exactly the same characters as its corresponding cross-reference identifier (which occurs only once in the cross-reference identifier component in order to "point" to the desired relationship. Multiple (identical) pointers can appear in any record to point to the same cross-reference identifier.

- Use each pointer with the tag and level number that corresponds to the appropriate line of information.

- Be sure that the pointer follows the tag in the same line and that it appears after the space Immediately following the tag.

- Begin and end each pointer with the delimiter symbol "@".

Examples:

```
@121@      @DE@
@X-x@      @F1-1@
```

In the example below the pointer "@1@" in the HUSBAND tag in the second line of the family record refers to the individual whose name is John Quentin Doe in the first individual record. The pointer "@1@" points to the cross-reference identifier "@1@" to show this relationship. The characters for the pointer and the corresponding cross-reference identifier are identical.

Example:

Lvl	Identifer	Tag	Value
0	@1@	INDI	
1		NAME	John Quentin/Doe/
0	@4@	FAM	
1		HUSB	@1@

You can use most alpha, numeric, or other characters to create pointers--including your computer's own native keys, or record numbers from its internal data base structure. You cannot, however, use the following three characters:

- "@" (the delimiter symbol)
- "#" (the number sign, also known as the U.S. pound sign, which is ASCII code 35)
- The terminator symbol (see the Terminator section later in this chapter.)
- The colon character ":" usage within pointers is reserved (See the syntax for xref_id and pointer in chapter 1).

HOW TO USE OTHER VALUES

Character Set

Two standard character sets are used most often for GEDCOM transmissions': 8-Bit ANSEL and ASClI. The default character set is 8-Bit ANSEL--Extended Latin Alphabet Coded Character Set for Bibliographic Use (American National Standards [ANSI] Z39.47-1985)--because it handles a wider variety of diacritics and special characters than any other character set.

If your transmission does not require diacritics, you may wish to use ASCII (USA version--ANSI 8 Bit), if your computer already supports it. In the future, you will be able to use the binary character set to facilitate transmission of photographs and other bit-mapped graphics. Other character sets can also be used for the transmissions. You will find more information about character sets in chapter 5, "Using Character Sets in GEDCOM".

You can change the character set any time in any system associated with any data. To change the character set, follow the procedure outlined in chapter 5.

A GEDCOM line must contain a terminator which cannot occur as data in a value.

Terminator

The terminator marks the end of a GEDCOM line--it separates one line from another. A terminator (not visible on the screen) produces a line feed. In ANSEL, the terminator symbol is the line feed (decimal code 10 or hex code 0A) or carriage return (decimal code 13 or hex code 0D), or a combination of the two. The terminator is an invisible carriage-return character in the examples used in this document.

Chapter 5
USING CHARACTER SETS IN GEDCOM

INTRODUCTION

This chapter lists and explains the character sets that can be used with GEDCOM. It also provides the escape sequences and conventions required to change from one character set to another during a transmission.

This specification does not include implementation methods for multilingual processing, such as keyboard arrangements, sorting sequences, or character and graphic representations (font styles, proportional spacing, etc.) on the CRT or Printers.

WHY VARIOUS CHARACTER SETS ARE USED

GEDCOM accommodates several standard character sets to facilitate the sharing of diverse genealogical data in many different languages, and to meet different user needs. These character sets are listed and explained below.

8-Bit ANSEL--The Default Character Set

The 8-Bit ANSEL (American National Standard for Extended Latin Alphabet Coded Character Set for Bibliographic Use, Z39.47, 1985 copyright) is the default character set for GEDCOM. It is used for all transmissions of information, unless another character set is specified.

The 8-Bit ANSEL is a standard of the American National Standards Institute (ANSI). It is the only character set that will handle a wide variety of diacritics and special characters for Romanized languages. (A diacritic is a graphic mark, Point, or sign used with alphabetic graphic characters to distinguish them by form or sound.) GEDCOM accommodates all diacritics that are included in Family History Department computer systems text and bibliographic information. Use the 8-Bit ANSEL character set when your transmission must preserve the full integrity of original Roman-alphabetic
languages, including diacritics and special characters.

The 8-Bit ANSEL is also known by two other names: (1) the American National Standard for Extended Latin Alphabet Coded Character Set for Bibliographic Use (American National Standards [ANSI] Z39.47-1985) and (2) the American Library Association character set, widely used in library systems, including the MARC (Machine-Readable Catalog) format.

You will find the standard for 8-Bit ANSEL on the last five pages of this chapter. It is reproduced with permission from the American National Standards Institute. Copies of this character set may be purchased from the American National Standards Institute at 1430 Broadway, New York, N.Y. 10018.

The standard 8-Bit ANSEL includes the following which is shown in table form in Appendix B of this document:

- An 8-Bit Code Table consisting of ANSEL and ASCII codes, page B-1
- An explanation of the codes, page B-2
- ANSEL Nonspacing Graphic Characters, page B-3
- ASCII Control Characters, page B-4
- ASCII Graphic Characters, page B-5

Character-set codes 0 through 127 are the same for 8-Bit ANSEL and 8-Bit ASCII (USA version--ANSI 8 Bit). Character-set codes 128 through 255 are unique to the ANSEL character set.

ASCII (USA version) (ANSI 8 Bit)

If you have no need for diacritics or special characters, and if you are not transmitting binary data, you will find it convenient to use ASCII (USA version--ANSI 8 Bit) if your computer already supports it. This is a standard of the American National Standards Institute (ANSI). Most of the normal printable characters of ANSEL and ASClI (USA version--ANSI 8 Bit) are identical.

Binary and Other Character Sets

When requested, binary formats for transmission of photographs and other bit-mapped graphics will be defined or adopted.

How to Change Character Sets

The procedure for changing character sets depends on whether you wish to change the character set for an entire transmission, or for just part of a transmission.

For an Entire Transmission

To change the character set for an entire transmission, do two things:

1. Specify the new character set in the character set line of the header record. (For more information about the header record, see chapter 3.)

2. Use the one-word name of the character set you want, following the CHAR tag in the same line.

The example below shows the specification in the header record.

Example:

Lvl	Tag	Value
0	HEAD	
1	SOUR	PAF
2	VERS	2.1
1	DEST	ANSTFILE
1	CHAR	ASCII

For Part of a Transmission

To change the character set for part of a transmission, follow this procedure:

1. Select the registered one-word name approved for the character set you want for your transmission. GEDCOM transmissions are automatically sent in 8-Bit ANSEL, unless you specify another character set. Following are the one-word names already registered for this designation the character set being used:

   - ANSEL. 8-Bit ANSEL character set (default)
   - ASCII. ASCII (USA version--ANSI 8 Bit)
   - BINARY. Binary data (future use)

2. Make sure the character set appears on the same line as the rest of the data for the character set.

   Example:
   @#CASCII@. This is the designation for the character set for ASCIl (USA version--ANSI 8 Bit) with the symbols that begin and end it.

3. Designate the character set. Begin with the escape-sequence symbol followed by "C" (C for character set). The escape-sequence symbol is a combination of a "C", an "@" and a "#" to form "@#C". Then type the name of the character set. End the designation with a "@" (the terminator for the escape-sequence), as shown in the examples below:

   Examples:
   @#CANSEL@ 8-Bit ANSEL character set (default)
   @#CASCII@ ASCII (USA version) (ANSI 8 Bit)
   @#CBINARY@ Binary data (future use)

The first three characters "@#C" alert the computer that information will be sent or received in a new character set. The actual change in character set starts with the first character that follows the closing "@". This change is in effect until the length indicated has been reached, the end-of-transmission symbol (TRLR) has been encountered, or another change in character set is specified.

If you are using the default character set (8-Bit ANSEL), make sure that all diacritic and special characters immediately precede the character they are to be associated with. If you are using a character set other than ANSEL, or if the data must change from one character set to another, indicate the change by using a character-set change escape sequence.

Example:
(space)@#CASCII@

The escape sequence is context insensitive and may appear anywhere, as many times as needed.

For more information about character sets, see the following:

- Genealogical Department Internal Memorandum, from GIS Administrative Council to GIS User's Committee Regarding Diacritics and the Genealogical Information System. 13 January 1986.

- Extended Latin Alphabet Coded Character Set for Bibliographic Use. American National Standards (ANSI) Z39.47, 1985.

- 8-Bit ASCII--Structure and Rules." American National Standards (ANSI)X3.134.1-198x.

- "7-Bit and 8-Bit ASCII Supplemental Multilingual Graphic Character Set (ASCII Multilingual Set)" (manuscript). American National Standards (ANSI), X3.134.2-198x.

Appendix A
LINEAGE-LINKED GEDCOM TAG DEFINITION

Introduction

Appendix A is a glossary of the tags approved for use with Lineage-Linked GEDCOM. (See chapter 2 for an example of the tags in context that describes the Lineage-Linked structure.) Every tag must be used within the context shown to ensure uniformity in the identification of all information transmitted by means of GEDCOM.

The tags are of various types, depending on their role or use in a transmission. They are used to identify individuals, families, names, dates, places, events, roles, sex, sources, relationships, control codes and other kinds of data for computers, computer programs, and computer systems.

The definition for each tag is generally broad enough to cover all uses of the tag. Other tags have been defined for structures other than those used in the Lineage-Linked Grammar. These tags were not included in Appendix A. For a list of these, contact the GEDCOM Coordinator.

Any new tag needed to enhance the Lineage_Linked form for system specific purposes may be used and will not violate the Lineage-Linked GEDCOM standard as long as the approved standard Lineage-Linked GEDCOM grammar context is not violated. System builders should register these tags and their definitions with the GEDCOM Coordinator at the address listed on the title page of this document. The Coordinator will evaluate the feasibility of including them as a part of the next release of the standard. Suggestions and proposed additions are welcome. Use the form "GEDCOM New Tag Proposal" (PFGS3709) provided at the end of the appendix. Be sure to check the appendix carefully first--the tag in question may already be defined.

Lineage-Linked GEDCOM Tag Definitions

In this section the standardized GEDCOM tag and its longer name appear prior to the delimiter ":=". The long name of the tag is shown inside of the braces "{}". The definition of the GEDCOM tag is shown on a new line following the delimiter ":=".

ADDR {ADDRESS} :=

The contemporary place, usually for postal purposes, of an individual, a submitter of information, a repository, a business, a school, or a company.

ADOP {ADOPTION} :=

The event of a legal creation of the child-parent relationship that does not biologiclly exist.

AFN {AFN} :=

A unique permanent record file number of an individual record stored in the Ancestral File.

AGE {AGE} :=
The age of the individual at the time an event occured, or the age listed in the document.

ALIA {ALIAS} :=
Indicates, by a cross reference pointer, that another record is suspected of being the same person. When the suspicions are confirmed drop the alias line, combine all data into one record, and delete the other record.

ANCI {ANCES_INTEREST} :=
Indicates the submitter that has interest in research to identify additional ancestors of this individual. (See also DECI.)

ANUL {ANNULMENT} :=
An event declaring a marriage void from the beginning (never existed).

ASSO {ASSOCIATES} :=
Identifies friends, neighbors, or associates of an individual.

AUTH {AUTHOR} :=
The name of the individual who created or compiled information.

BAPL {BAPTISM-LDS} :=
The event of baptism performed at age eight or later by priesthood authority of The Church of Jesus Christ of Latter-day Saints. (See also BAPM.)

BAPM {BAPTISM} :=
The event of baptism (not LDS), performed in infancy or later. (See also BAPL and CHR.

BARM {BAR_MITZVAH} :=
The ceremonial event held when a Jewish boy reaches age 13.

BASM {BAS_MITZVAH} :=
The ceremonial event held when a Jewish girl reaches age 13, also known as "Bat Mitzvah".

BIRT {BIRTH} :=
The event of entering into life.

BLES {BLESSING} :=
A religious event of bestowing divine care, intercession, etc.

BURI {BURIAL} :=
The event of the proper disposing of the mortal remains of a deceased person.

BUYR {BUYER} :=
A person who purchased or purchases from another.

CALN {CALL_NUMBER} :=
The number used by a repository to identify the specific items in its collections.

CAST {CASTE} :=
The name of an individual's rank or status in society, based on racial or religious differences, or differences in wealth, inherited rank, profession, occupation, etc.

CEME {CEMETARY} :=
The name of the cemetery or other resting place where an individual is buried.

CENS {CENSUS} :=
The event of the periodic count of the population for a designated locality, such as national or state Census.

CHAN {CHANGE} :=
Indicates a change, correction, or modification. Typically used in connection with a DATE to specify when a change occured.

CHAR {CHARACTER} :=
An indicator of the character set used in writing this automated information.

CHIL {CHILD} :=
The natural, adopted, or sealed offspring of a father and a mother.

CHR {CHRISTENING} :=
The religious event (not LDS) of baptising and/or naming a child.

CHRA {ADULT_CHRISTNG} :=
The religious event (not LDS) of baptizing and/or naming an adult person.

CNTC {CONTACT_PERSON} :=
The name of a person that is listed as the contact person at an institution such as a repository, college, business, etc.

CONF {CONFIRMATION} :=
The religious event (not LDS) of conferring the gift of the Holy Ghost and, among protestants, full church membership.

CONL {CONFIRMATION_L} :=
The religious event by which a person receives the gift of the Holy Ghost and becomes a member of The Church of Jesus Christ of Latter-day Saints.

CONT {CONTINUED} :=
An indicator that additional value information follows and is to be concatenated with the value of the superior tag.

COPR {COPYRIGHT} :=
A statement that accompanies data to protect it from unlawful duplication and distribution.

CPLR {COMPILER} :=
The name of the person that compiled writings of others.

DATA {DATA} :=
Stored automated information.

DATE {DATE} :=
The time of an event.

DEAT {DEATH} :=
The event when mortal life terminated.

DECI {DESC_INTEREST} :=
Indicates the submitter that has interest in research to identify additional decendants of this individual. (See also ANCI.)

DESR {PHY_DESCRIPTION} :=
The physical characteristics of a person, place, or thing.

DEST {DESTINATION} :=
A place or system receiving data, material, or a person.

DIV {DIVORCE} :=
An event of dissolving a marriage through civil action.

DIVF {DIVORCE_FILED} :=
An event of filing for a divorce by a spouse.

EDTR {EDITOR} :=
The name of a person who edited information.

ENDL {ENDOWMENT} :=
A religious event where an ordinance for an individual was performed by priesthood authority in a LDS Temple.

ENGA {ENGAGEMENT} :=
An event of recording or announcing an agreement between two people to become married.

EVEN {EVENT} :=
A noteworthy happening related to an individual, a group, or an organization.

FAM {FAMILY} :=
Identifies a relationship of husband and wife and their children, if any.

FAMC {FAMILY_CHILD} :=
Identifies the family in which an individual appears as a child.

FAMS {FAMILY_SPOUSE} :=
Identifies the family in which an individual appears as a spouse.

FATH {FATHER} :=
Identifies the male parent in a family.

FIDE {FIDELITY} :=
An assessment of the exactness or trustworthiness of information. (An oppion of how close this information is to the original.)

FILE {FILE} :=
A storage place that is ordered and arranged for preservation and reference.

FILM {FILM_NUMBER} :=
An assigned, unique number used to identify film.

FORM {FORMAT} :=
An assigned name given to a consistent format in which information can be understood.

GEDC {GEDCOM} :=
A collection of records and fields tagged with standardized labels that provides the context and meaning of the enclosed data.

GRAD {GRADUATION} :=
An event of awarding an educational diplomas or degrees to individuals.

HDOH {HEAD_HOUSEHOLD} :=
Identifies a person whose role was recorded as "head of household" for an event such as a census.

HEAD {HEADER} :=
Identifies beginning information for the recognition and processing of data within a transmission.

HEIR {HEIR} :=
An individual who inherited or is entitled to inherit an estate.

HUSB {HUSBAND} :=
An individual in the family role of a married man.

INDI {INDIVIDUAL} :=
A person.

INDX {INDEXED} :=
Specifies information about an index.

INFT {INFORMANT} :=
An individual who reported facts concerning an event.

INTV {INTERVIEWER} :=
The person who facilitated, recorded, and obtained information during an interview.

ITEM {ITEM} :=
Refers to a unit within a set of things that belong together. The unit itself may be made up of other objects but collectively they are referred to as an unit (item) of the set. Such as a group of papers filmed together under one header page is referred to as an item on a film.

LANG {LANGUAGE} :=
The name of the language used in a communication or transmission of information.

LCCN {LIB_CONGRS_CALL} :=
The number assigned by the U.S. Library of Congress to a holding.

MARB {MARRIAGE_BANN} :=
An event of an official public notice given that two people intend to marry.

MARC {MARR_CONTRACT} :=
An event of recording a formal agreement of marriage, including the prenuptial agreement in which marriage partners reach agreement about the property rights of one or both, securing property to their children.

MARL {MARR_LICENSE} :=
An event of obtaining a legal license to marry.

MARR {MARRIAGE} :=
An event of creating a family unit of a man and a woman as husband and wife.

MEDI {MEDIA} :=
The medium used to store or transmit information.

MOTH {MOTHER} :=
Identifies the female parent in a family.

NAME {NAME} :=
A word or combination of words used to help identify an individual, title, or other item.

NAMR {NAME_RELIGIOUS } :=
A name given to an individual to be used in association with one's religious obligations.

NAMS {NAME SAKE} :=
Identifies the person that an individual is named after to perpetuate the person's name.

NATI {NATIONALITY} :=
The national heritage of an individual.

NATU {NATURALIZATION } :=
The event of obtaining citizenship.

NCHI {CHILDREN_COUNT } :=
The number of children that this person is known to be the parent of.

NMR {MARRIAGE_COUNT } :=
The number of times this person has been married.

NOTE {NOTE} :=
Additional information provided for understanding the enclosing data. This information is either submitter opinion or other information foreign to the context of the enclosing data.

OCCU {OCCUPATION} :=
The type of work or profession of an individual.

OFFI {OFFICIATOR} :=
A person acting in an authorized capacity as voice in performing an ordinance or ceremony.

ORDN {ORDINATION} :=
A religious event of receiving authority to act in religious matters.

PAGE {PAGE} :=
A number or description to show the relationship of a specific data view (page) has in relationship to the beginning of a document.

PERI {PERIOD} :=
Indicates the range of time within which events that happened over time took place.

PHON {PHONE} :=
A unique set of numbers assigned to a given telephone.

PLAC {PLACE} :=
A jurisdictional name to identify the place or location of an event.

PROB {PROBATE} :=
An event of judicial determination of the validity of a will.

PROP {PROPERTY} :=
The name of land and/or other properties possessed by this individual.

PUBL {PUBLICATION} :=
A published work.

PUBR {PUBLISHER} :=
The name of the company or individual who published a work.

QUAY {QUALITY_OF_DATA} :=
An assessment of the reliability of information.

RECO {RECORDER} :=
A person responsible for recording identifying data about an event, place, or person.

REFN {REFERENCE} :=
A description or number used to identify an item for filing, storage, or other reference purposes.

REFS {REFERENCED_SOUR} :=
A source that was referenced by the cited source but was not examined by the submitter. Examined sources are listed using a SOUR tag.

REL {RELATION} :=
A name of a relationship indicating the kinship.

RELI {RELIGION} :=
A religious denomination to which a person is affiliated or for which a record applies.

REPO {REPOSITORY} :=
An institution that has the specified item as part of its collection(s).

RETI {RETIREMENT} :=
An event of exiting an occupational relationship with an employer after a qualifying time period.

RFN {REC_FILE_NUMBER} :=
A permanent number assigned to a record that uniquely identifies it within a known file.

ROLE {ROLE} :=
A name given to a role played by an individual in connection with an event.

SELR {SELLER} :=
A person who sold or sells to another.

SERS {SERIES} :=
Designates the volume within a series in which a given work is a part.

SEX {SEX} :=
Indicates the sex of an individual--male or female.

SIGN {SIGNATURE} :=
[YES | N0 | SYMBOL_NAME]
Used to identify information about an individual: the type of signature this person used.
YES = This person knew how to sign his or her name.
NO = This person did not sign name or use a symbol.
SYMBOL_NAME = The name of the symbol this person used as a signature.

SLGC {SEALING_CHILD} :=
A religious event pertaining to the sealing of a child to his or her parents in an LDS temple ceremony.

SLGS {SEALING_SPOUSE } :=
A religious event pertaining to the sealing of a husband and wife in an LDS temple ceremony.

SOUR {SOURCE} :=
The initial or original material from which data originated or was obtained.

STAT {STATUS} :=
An assesment of the state of affairs.

STIL {STILLBORN} :=
An event of birth delivery of a child who was dead.

SUBM {SUBMITTER} :=
An individual or organization who contributes genealogical data to a file or transfers it from one file to another.

SUBN {SUBMISSION} :=
Refers to processing information pertaining to the data that was submitted within a transmission.

TEMP {TEMPLE} :=
The name or code that represents the name of a temple of The Church of Jesus Christ of Latter-day Saints.

TEXT {TEXT} :=
The exact wording of comments found in an original source document.

TIME {TIME} :=
A time value in a 24-hour clock format, including hours, minutes, and optional seconds, separated by a colon ":", fractions of seconds are shown in decimal notation.

TITL {TITLE} :=
A descriptive, general name or formal designation used for an individual, in addition to the individual's given and surnames.

TRLR {TRAILER} :=
At level 0, specifies the end of a GEDCOM transmission.

TXPY {TAX_PAYER} :=
A person who has been assessed a tax.

TYPE {TYPE} :=
A classification name given to identify a group of people or objects because they posses a set of similar attributes or characteristics.

VERS {VERSION} :=
Indicates which variation of an item, publication, or product is being used or referenced.

WIFE {WIFE} :=
An individual in the family role of a married woman.

WILL {WILL} :=
A legal document by which a person disposes of his or her estate, to take effect after death.

WITN {WITNESS} :=
An individual who attested that he or she saw an event take place.

XLTR {TRANSLATOR} :=
The name of a person who translated words from one language to another.