Tag	Name URI	Description
`CREM`	cremation `g7:CREM` (p.68)	The act of reducing a dead body to ashes by fire.
`DEAT`	death `g7:DEAT` (p.70)	Mortal life terminates.
`EMIG`	emigration `g7:EMIG` (p.71)	Leaving one's homeland with the intent of residing elsewhere.
`FCOM`	first communion `g7:FCOM` (p.73)	The first act of sharing in the Lord's supper as part of church worship.
`GRAD`	graduation `g7:GRAD` (p.74)	Awarding educational diplomas or degrees to individuals.
`IMMI`	immigration `g7:IMMI` (p.75)	Entering into a new locality with the intent of residing there.
`NATU`	naturalization `g7:NATU` (p.79)	Obtaining citizenship.
`ORDN`	ordination `g7:ORDN` (p.80)	Receiving authority to act in religious matters.
`PROB`	probate `g7:PROB` (p.82)	Judicial determination of the validity of a will. It may indicate several related court activities over several dates.
`RETI`	retirement `g7:RETI` (p.84)	Exiting an occupational relationship with an employer after a qualifying time period.
`WILL`	will `g7:WILL` (p.92)	A legal document treated as an event, by which a person disposes of his or her estate. It takes effect after death. The event date is the date the will was signed while the person was alive. (See also `PROB`)

In addition, `INDI.EVEN` (p.71) is a structure for a generic individual event. It must have a `TYPE` (p.90) substructure to define what kind of event is being provided.

3.3.1.2. Family Events

Tag	Name URI	Description
`ANUL`	annulment `g7:ANUL` (p.66)	Declaring a marriage void from the beginning (never existed).
`CENS`	census `g7:FAM-CENS` (p.67)	Periodic count of the population for a designated locality, such as a national or state census.

Tag	Name URI	Description
`DIV`	divorce `g7:DIV` (p.70)	Dissolving a marriage through civil action.
`DIVF`	divorce filed `g7:DIVF` (p.70)	Filing for a divorce by a spouse.
`ENGA`	engagement `g7:ENGA` (p.71)	Recording or announcing an agreement between 2 people to become married.
`MARB`	marriage bann `g7:MARB` (p.77)	Official public notice given that 2 people intend to marry.
`MARC`	marriage contract `g7:MARC` (p.77)	Recording a formal agreement of marriage, including the prenuptial agreement in which marriage partners reach agreement about the property rights of 1 or both, securing property to their children.
`MARL`	marriage license `g7:MARL` (p.77)	Obtaining a legal license to marry.
`MARR`	marriage `g7:MARR` (p.77)	A legal, common-law, or customary event such as a wedding or marriage ceremony that joins 2 partners to create or extend a family unit.
`MARS`	marriage settlement `g7:MARS` (p.77)	Creating an agreement between 2 people contemplating marriage, at which time they agree to release or modify property rights that would otherwise arise from the marriage.

In addition, `FAM.EVEN` (p.71) is a structure for a generic family event. It must have a `TYPE` substructure to define what kind of event is being provided.

3.3.2. Attributes

Unlike events, the presence of an attribute is sufficient to assert the attribute applied to the individual, regardless of the attribute's substructures and payload.

3.3.2.1. Individual Attributes

Tag	Name URI	Description
`CAST`	caste `g7:CAST` (p.67)	The name of an individual's rank or status in society which is sometimes based on racial or religious differences, or differences in wealth, inherited rank, profession, or occupation.

Tag	Name URI	Description
`DSCR`	physical description `g7:DSCR` (p.70)	The physical characteristics of a person.
`EDUC`	education `g7:EDUC` (p.71)	Indicator of a level of education attained.
`IDNO`	identifying number `g7:IDNO` (p.75)	A number or other string assigned to identify a person within some significant external system. It must have a `TYPE` substructure to define what kind of identification number is being provided.
`NATI`	nationality `g7:NATI` (p.79)	An individual's national heritage or origin, or other folk, house, kindred, lineage, or tribal interest.
`NCHI`	number of children `g7:INDI-NCHI` (p.79)	The number of children that this person is known to be the parent of (all marriages).
`NMR`	number of marriages `g7:NMR` (p.79)	The number of times this person has participated in a family as a spouse or parent.
`OCCU`	occupation `g7:OCCU` (p.80)	The type of work or profession of an individual.
`PROP`	property `g7:PROP` (p.82)	Pertaining to possessions such as real estate or other property of interest.
`RELI`	religion `g7:INDI-RELI` (p.83)	A religious denomination to which a person is affiliated or for which a record applies.
`RESI`	residence `g7:INDI-RESI` (p.84)	An address or place of residence where an individual resided.
`SSN`	social security number `g7:SSN` (p.86)	A number assigned by the United States Social Security Administration, used for tax identification purposes. It is a type of `IDNO`.
`TITL`	title `g7:INDI-TITL` (p.87)	A formal designation used by an individual in connection with positions of royalty or other social status, such as Grand Duke.

In addition, `INDI`.`FACT` (p.73) is a structure for a generic individual attribute. It must have a `TYPE` (p.90) substructure to define what kind of attribute is being provided.

3.3.2.2. Family Attributes

Tag	Name URI	Description
NCHI	number of children g7:FAM-NCHI (p.79)	The number of children that belong to this family.
RESI	residence g7:FAM-RESI (p.83)	An address or place of residence where a family resided.

In addition, FAM.FACT (p.72) is a structure for a generic family attribute. It must have a TYPE substructure to define what kind of attribute is being provided.

3.3.3. Latter-day Saint Ordinances

The structures describing ordinances performed by The Church of Jesus Christ of Latter-day Saints are unlike regular events in that they might either be performed during life or by proxy on the behalf of a deceased individual.

Proxy ordinances on behalf of deceased persons were once requested and officially recorded using an earlier version of GEDCOM. This is no longer the case, but when it was the case the following principles held:

- PLAC (p.82) was used only for ordinances that were performed by the recipient in life.
- TEMP (p.87) was used with all ENDL (p.71), SLGC (p.85), and SLGS (p.85), but only with posthumous proxy BAPL (p.66) and CONL (p.68).

Tag	Name URI	Description
BAPL	baptism g7:BAPL	The event of baptism performed at age 8 or later by priesthood authority of The Church of Jesus Christ of Latter-day Saints. (See also BAPM (p.60))
CONL	confirmation g7:CONL	The religious event by which a person receives membership in The Church of Jesus Christ of Latter-day Saints. (See also CONF (p.60))
INIL	initiatory g7:INIL (p.75)	A religious event where an initiatory ordinance for an individual was performed by priesthood authority in a temple of The Church of Jesus Christ of Latter-day Saints.
ENDL	endowment g7:ENDL	A religious event where an endowment ordinance for an individual was performed by priesthood authority in a temple of The Church of Jesus Christ of Latter-day Saints.

Tag	Name URI	Description
`SLGC`	sealing child `g7:SLGC`	A religious event pertaining to the sealing of a child to his or her parents in a temple ceremony of The Church of Jesus Christ of Latter-day Saints.
`SLGS`	sealing spouse `g7:SLGS`	A religious event pertaining to the sealing of a husband and wife in a temple ceremony of The Church of Jesus Christ of Latter-day Saints. (See also `MARR` (p.61))

3.3.4. Structure types

Structure types are listed in this section alphabetically by tag. When the same tag is used for different structure types in different contexts, they may be distinguished by their URI.

`ABBR` (Abbreviation) <g7:ABBR>

A short name of a title, description, or name used for sorting, filing, and retrieving records.

`ADDR` (Address) <g7:ADDR>

The location of, or most relevant to, the subject of the superstructure. See `ADDRESS_STRUCTURE` (p. 43) for more details.

`ADOP` (Adoption) <g7:ADOP>

An Individual Event (p.60). See also `INDIVIDUAL_EVENT_STRUCTURE` (p.50).

`ADOP` (Adoption) <g7:FAMC-ADOP>

An enumerated value from set `g7:enumset-ADOP` (p.92) indicating which parent(s) in the family adopted this individual.

`ADR1` (Address Line 1) <g7:ADR1>

The first line of the address, used for indexing. This structure's payload should be a single line of text equal to the first line of the corresponding `ADDR`. See `ADDRESS_STRUCTURE` for more details.

> *Deprecation Note* — `ADR1` should not be added to new files; see `ADDRESS_STRUCTURE` for more details.

`ADR2` (Address Line 2) <g7:ADR2>

The second line of the address, used for indexing. This structure's payload should be a single line of text equal to the second line of the corresponding `ADDR`. See `ADDRESS_STRUCTURE` for more details.

> *Deprecation Note* — `ADR2` should not be added to new files; see `ADDRESS_STRUCTURE` for more details.

`ADR3` (Address Line 3) `<g7:ADR3>`

The third line of the address, used for indexing. This structure's payload should be a single line of text equal to the third line of the corresponding `ADDR`. See `ADDRESS_STRUCTURE` for more details.

> *Deprecation Note* — `ADR3` should not be added to new files; see `ADDRESS_STRUCTURE` for more details.

`AGE` (Age at event) `<g7:AGE>`

The age of the individual at the time an event occurred, or the age listed in the document.

`AGNC` (Responsible agency) `<g7:AGNC>`

The organization, institution, corporation, person, or other entity that has responsibility for the associated context. Examples are an employer of a person of an associated occupation, or a church that administered rites or events, or an organization responsible for creating or archiving records.

`ALIA` (Alias) `<g7:ALIA>`

A single individual may have facts distributed across multiple individual records, connected by `ALIA` pointers (named after "alias" in the computing sense, not the pseudonym sense).

> *Note* — This specification does not define how to connect `INDI` records with `ALIA`. Some systems organize `ALIA` pointers to create a tree structure, with the root `INDI` record containing the composite view of all facts in the leaf `INDI` records. Others distribute events and attributes between `INDI` records mutually linked by symmetric pairs of `ALIA` pointers. A future version of this specification may adjust the definition of `ALIA`.

`ANCI` (Ancestor interest) `<g7:ANCI>`

Indicates an interest in additional research for ancestors of this individual. (See also `DESI` (p.70)).

`ANUL` (Annulment) `<g7:ANUL>`

A Family Event (p.61). See also `FAMILY_EVENT_STRUCTURE` (p.46).

`ASSO` (Associates) `<g7:ASSO>`

A pointer to an associated individual. See `ASSOCIATION_STRUCTURE` (p.44) for more details.

`AUTH` (Author) `<g7:AUTH>`

The person, agency, or entity who created the record. For a published work, this could be the author, compiler, transcriber, abstractor, or editor. For an unpublished source, this may be an individual, a government agency, church organization, or private organization.

`BAPL` (Baptism, Latter-Day Saint) `<g7:BAPL>`

A Latter-Day Saint Ordinance (p.64). See also `LDS_INDIVIDUAL_ORDINANCE` (p.53).

BAPM (Baptism) <g7:BAPM>

An Individual Event (p.60). See also INDIVIDUAL_EVENT_STRUCTURE (p.50).

BARM (Bar Mitzvah) <g7:BARM>

An Individual Event (p.60). See also INDIVIDUAL_EVENT_STRUCTURE.

BASM (Bas Mitzvah) <g7:BASM>

An Individual Event (p.60). See also INDIVIDUAL_EVENT_STRUCTURE.

BIRT (Birth) <g7:BIRT>

An Individual Event (p.60). See also INDIVIDUAL_EVENT_STRUCTURE.

BLES (Blessing) <g7:BLES>

An Individual Event (p.60). See also INDIVIDUAL_EVENT_STRUCTURE.

BURI (Depositing remains) <g7:BURI>

An Individual Event (p.60). See also INDIVIDUAL_EVENT_STRUCTURE.

Although defined as any depositing of remains since it was introduced in the first version of GEDCOM, this tag is a shortened form of the English word “burial” and has been interpreted to mean “depositing of remains by burial” by some applications and users. In the absence of a clarifying TYPE (p.90) substructure it is likely, but not guaranteed, that a BURI structure refers to a burial rather than another form of depositing remains.

CALN (Call number) <g7:CALN>

An identification or reference description used to file and retrieve items from the holdings of a repository. Despite the word “number” in the name, may contain any character, not just digits.

CAST (Caste) <g7:CAST>

An Individual Attribute (p.62). See also INDIVIDUAL_ATTRIBUTE_STRUCTURE (p.48).

CAUS (Cause) <g7:CAUS>

The reasons which precipitated an event. It is often used subordinate to a death event to show cause of death, such as might be listed on a death certificate.

CENS (Census) <g7:FAM-CENS>

An Family Event (p.61).

CENS (Census) <g7:INDI-CENS>

An Individual Event (p.60). See also INDIVIDUAL_EVENT_STRUCTURE (p.50).

`CHAN` (Change) `<g7:CHAN>`

The most recent change to the superstructure. This is metadata about the structure itself, not data about its subject. See `CHANGE_DATE` (p.44) for more details.

`CHIL` (Child) `<g7:CHIL>`

The child in a family, whether biological, adopted, foster, sealed, or other relationship.

`CHRA` (Christening, adult) `<g7:CHRA>`

An Individual Event (p.60). See also `INDIVIDUAL_EVENT_STRUCTURE`.

`CHR` (Christening) `<g7:CHR>`

An Individual Event (p.60). See also `INDIVIDUAL_EVENT_STRUCTURE`.

`CITY` (City) `<g7:CITY>`

The name of the city used in the address. See `ADDRESS_STRUCTURE` (p.43) for more details.

`CONF` (Confirmation) `<g7:CONF>`

An Individual Event (p.60). See also `INDIVIDUAL_EVENT_STRUCTURE`.

`CONL` (Confirmation, Latter-Day Saint) `<g7:CONL>`

A Latter-Day Saint Ordinance (p.64). See also `LDS_INDIVIDUAL_ORDINANCE` (p.53).

`CONT` (Continued) `<g7:CONT>`

A pseudo-structure to indicate a line break. The `CONT` tag is generated during serialization and is never present in parsed datasets. See Lines (p.11) for more details.

`COPR` (Copyright) `<g7:COPR>`

A copyright statement, as appropriate for the copyright laws applicable to this data.

`CORP` (Corporate name) `<g7:CORP>`

The name of the business, corporation, or person that produced or commissioned the product.

`CREA` (Creation) `<g7:CREA>`

The initial creation of the superstructure. This is metadata about the structure itself, not data about its subject. See `CREATION_DATE` (p.45) for more details.

`CREM` (Cremation) `<g7:CREM>`

An Individual Event (p.60). See also `INDIVIDUAL_EVENT_STRUCTURE` (p.50).

CROP (Crop) <g7:CROP>

A subregion of an image to display. It is only valid when the superstructure links to a MULTIMEDIA_RECORD (p.40) with at least 1 FILE (p.73) substructure that refers to an external file with a defined pixel unit.

LEFT (p.77) and TOP (p.87) indicate the top-left corner of the region to display. WIDTH (p.91) and HEIGHT (p.74) indicate how many pixels wide and tall the region to display is. If omitted, LEFT and TOP each default to 0; WIDTH defaults to the image width minus LEFT; and HEIGHT defaults to the image height minus TOP.

If the superstructure links to a MULTIMEDIA_RECORD that includes multiple FILE substructures, the CROP applies to the first FILE to which it can apply, namely the first external file with a defined pixel unit.

It is recommended that CROP be used only with a single-FILE MULTIMEDIA_RECORD.

The following are errors:

- LEFT or LEFT + WIDTH exceed the image width.
- TOP or TOP + HEIGHT exceed the image height.
- CROP applied to a non-image or image without a defined pixel unit.

CTRY (Country) <g7:CTRY>

The name of the country that pertains to the associated address. See ADDRESS_STRUCTURE (p.43) for more details.

DATA (Data) <g7:DATA>

A structure with no payload used to distinguish a description of something from metadata about it. For example, SOUR (p.85) and its other substructures describe a source itself, while SOUR.DATA describes the content of the source.

DATA (Data) <g7:SOUR-DATA>

See g7:DATA.

DATA (Data) <g7:HEAD-SOUR-DATA>

The database, electronic data source, or digital repository from which this dataset was exported. The payload is the name of the database, electronic data source, or digital repository, with substructures providing additional details about it (not about the export).

DATE (Date) <g7:DATE>

The principal date of the subject of the superstructure. The payload is a DateValue (p.25).

When the superstructure is an event, the principal date indicates when the event took place.

When the superstructure is an attribute, the principal date indicates when the attribute was observed, asserted, or applied. A date period might put bounds on the attributes applicability, but other date forms assume that the attribute may have also applied on other dates too.

When the superstructure is a `g7:SOUR-DATA` (p.69), the principal date indicates when the data was entered into the source; or, for a source like a website that changes over time, a date on which the source contained the data.

See `DATE_VALUE` (p.45) for more details.

`DATE` (Date) `<g7:DATE-exact>`

The principal date of the subject of the superstructure. The payload is a `DateExact`.

`DATE` (Date) `<g7:HEAD-DATE>`

The `DateExact` that this document was created.

`DATE` (Date) `<g7:NO-DATE>`

The `DatePeriod` during which the event did not occur or the attribute did not apply.

`DATE` (Date) `<g7:DATA-EVEN-DATE>`

The `DatePeriod` covered by the entire source; the period during which this source recorded events.

`DEAT` (Death) `<g7:DEAT>`

An Individual Event (p.60). See also `INDIVIDUAL_EVENT_STRUCTURE` (p.50).

`DESI` (Descendant Interest) `<g7:DESI>`

Indicates an interest in research to identify additional descendants of this individual. See also `ANCI` (p. 66).

`DEST` (Destination) `<g7:DEST>`

An identifier for the system expected to receive this document. See `HEAD.SOUR` (p.86) for guidance on choosing identifiers.

`DIVF` (Divorce filing) `<g7:DIVF>`

A Family Event (p.61). See also `FAMILY_EVENT_STRUCTURE` (p.46).

`DIV` (Divorce) `<g7:DIV>`

A Family Event (p.61). See also `FAMILY_EVENT_STRUCTURE`.

`DSCR` (Description) `<g7:DSCR>`

An Individual Attribute (p.62). See also `INDIVIDUAL_ATTRIBUTE_STRUCTURE` (p.48).

`EDUC` (Education) `<g7:EDUC>`

An Individual Attribute (p.62). See also `INDIVIDUAL_ATTRIBUTE_STRUCTURE`.

`EMAIL` (Email) `<g7:EMAIL>`

An electronic mail address, as defined by any relevant standard such as RFC 3696, RFC 5321, or RFC 5322.

If an invalid email address is present upon import, it should be preserved as-is on export.

> *Note* — The version 5.5.1 specification contained a typo where this tag was sometimes written `EMAI` and sometimes written `EMAIL`. `EMAIL` should be used in version 7.0 and later.

`EMIG` (Emigration) `<g7:EMIG>`

An Individual Event (p.60). See also `INDIVIDUAL_EVENT_STRUCTURE` (p.50).

`ENDL` (Endowment, Latter-Day Saint) `<g7:ENDL>`

A Latter-Day Saint Ordinance (p.64). See also `LDS_INDIVIDUAL_ORDINANCE` (p.53).

`ENGA` (Engagement) `<g7:ENGA>`

A Family Event (p.61). See also `FAMILY_EVENT_STRUCTURE` (p.46).

`EVEN` (Event) `<g7:FAM-EVEN>`

See `g7:INDI-EVEN`.

`EVEN` (Event) `<g7:INDI-EVEN>`

An event: a noteworthy happening related to an individual or family. If a specific event type exists, it should be used instead of a generic `EVEN` structure. Each `EVEN` must be classified by a subordinate use of the `TYPE` (p.90) tag and may be further described in the structure's payload.

> *Example* — A person that signed a lease for land dated October 2, 1837 and a lease for mining equipment dated November 4, 1837 would be written as:
>
> ```
> 0 @I1@ INDI
> 1 EVEN
> 2 TYPE Land Lease
> 2 DATE 2 OCT 1837
> 1 EVEN Mining equipment
> 2 TYPE Equipment Lease
> 2 DATE 4 NOV 1837
> ```

EVEN (Event) <g7:DATA-EVEN>

A list of enumerated values from set g7:enumset-EVENATTR (p.93) indicating the types of events that were recorded in a particular source. Each event type is separated by a comma and space. For example, a parish register of births, deaths, and marriages would be BIRT, DEAT, MARR.

EVEN (Event) <g7:SOUR-EVEN>

An enumerated value from set g7:enumset-EVENATTR indicating the type of event or attribute which was responsible for the source entry being recorded. For example, if the entry was created to record a birth of a child, then the type would be BIRT (p.67) regardless of the assertions made from that record, such as the mother's name or mother's birth date.

EXID (External Identifier) <g7:EXID>

An identifier for the subject of the superstructure. The identifier is maintained by some external authority; the authority owning the identifier is provided in the TYPE substructure; see EXID.TYPE (p.90) for more details.

Depending on the maintaining authority, an EXID may be a unique identifier for the subject, an identifier for 1 of several views of the subject, or an identifier for the externally-maintained copy of the same information as is contained in this structure. However, unlike UID (p.91) and REFN (p.83), EXID does not identify a structure; structures with the same EXID may have originated independently rather than by edits from the same starting point.

EXID identifiers are expected to be unique. Once assigned, an EXID identifier should never be reused for any other purpose.

FAM (Family record) <g7:record-FAM>

See FAMILY_RECORD (p.37)

> *Note* — The common case is that each couple has one FAM record, but that is not always the case.
>
> A couple that separates and then gets together again can be represented either as a single FAM with multiple events (MARR (p.77), DIV (p.70), etc.) or as a separate FAM for each time together. Some user interfaces may display these two in different ways and the two admit different semantics in sourcing. A single FAM with two MARR with distinct dates might also represent uncertainty about dates and a pair of FAM with same spouses might also be the result of merging multiple files.
>
> Implementers should support both representations, and should choose between them based on user input or other context beyond that provided in the datasets themselves.

FACT (Fact) <g7:FAM-FACT>

See g7:INDI-FACT.

FACT (Fact) <g7:INDI-FACT>

A noteworthy attribute or fact concerning an individual or family. If a specific attribute type exists, it should be used instead of a generic FACT structure. Each FACT must be classified by a subordinate use of the TYPE (p.90) tag and may be further described in the structure's payload.

> *Example* — If the attribute being defined was 1 of the person's skills, such as woodworking, the FACT tag would have the value of "Woodworking", followed by a subordinate TYPE tag with the value "Skills".
>
> ```
> 0 @I1@ INDI
> 1 FACT Woodworking
> 2 TYPE Skills
> ```

FAMC (Family child) <g7:INDI-FAMC>

The family in which an individual appears as a child. It is also used with a g7:FAMC-STAT (p.86) substructure to show individuals who are not children of the family. See FAMILY_RECORD (p.37) for more details.

FAMC (Family child) <g7:FAMC>

The family with which this individual event is associated.

FAMC (Family child) <g7:ADOP-FAMC>

The individual or couple that adopted this individual.

Adoption by an individual, rather than a couple, may be represented either by pointing to a FAM where that individual is a HUSB (p.75) or WIFE (p.91) and using a g7:FAMC-ADOP (p.65) substructure to indicate which 1 performed the adoption; or by using a FAM where the adopting individual is the only HUSB/WIFE.

FAMS (Family spouse) <g7:FAMS>

The family in which an individual appears as a partner. See FAMILY_RECORD for more details.

FAX (Facsimile) <g7:FAX>

A fax telephone number appropriate for sending data facsimiles. See PHON (p.81) for additional comments on telephone numbers.

FCOM (First communion) <g7:FCOM>

An Individual Event (p.60). See also INDIVIDUAL_EVENT_STRUCTURE (p.50).

FILE (File reference) <g7:FILE>

A reference to an external file. See the File Path datatype (p.31) for more details.

FORM (Format) <g7:FORM>

The media type (p.30) of the file referenced by the superstructure.

FORM (Format) <g7:PLAC-FORM>

A comma-separated list of jurisdictional titles, which has the same number of elements and in the same order as the PLAC (p.82) structure. As with PLAC, this shall be ordered from lowest to highest jurisdiction.

> *Example* — The following represents Baltimore, a city that is not within a county.
>
> ```
> 2 PLAC Baltimore, , Maryland, USA
> 3 FORM City, County, State, Country
> ```

FORM (Format) <g7:HEAD-PLAC-FORM>

Any PLAC with no FORM (p.74) shall be treated as if it has this FORM (p.74).

GEDC (GEDCOM) <g7:GEDC>

A container for information about the entire document.

It is recommended that applications write GEDC with its required substructure g7:GEDC-VERS (p.91) as the first substructure of HEAD.

GIVN (Given name) <g7:GIVN>

A given or earned name used for official identification of a person.

GRAD (Graduation) <g7:GRAD>

An Individual Event (p.60). See also INDIVIDUAL_EVENT_STRUCTURE (p.50).

HEAD (Header) <g7:HEAD>

A pseudo-structure for storing metadata about the document. See The Header and Trailer (p.15) for more details.

HEIGHT (Height in pixels) <g7:HEIGHT>

How many pixels to display vertically for the image. See CROP (p.69) for more details.

> *Note* — HEIGHT is a number of pixels. The correct tag for the height of an individual is the DSCR (p.70) attribute.
>
> > *Example* —
> >
> > ```
> > 0 @I45@ INDI
> > 1 DSCR brown eyes, 5ft 10in, 198 pounds
> > ```

HUSB (Husband) <g7:HUSB>

A container for information relevant to the subject of the superstructure specific to the individual described by the associated FAM's HUSB substructure.

HUSB (Husband) <g7:FAM-HUSB>

This is a partner in a FAM record. See FAMILY_RECORD (p.37) for more details.

IDNO (Identification number) <g7:IDNO>

An Individual Attribute (p.62). See also INDIVIDUAL_ATTRIBUTE_STRUCTURE.

IMMI (Immigration) <g7:IMMI>

An Individual Event (p.60). See also INDIVIDUAL_EVENT_STRUCTURE (p.50).

INDI (Individual) <g7:record-INDI>

See INDIVIDUAL_RECORD (p.38).

INIL (Initiatory, Latter-Day Saint) <g7:INIL>

A Latter-Day Saint Ordinance (p.64). See also LDS_INDIVIDUAL_ORDINANCE (p.53). Previously, GEDCOM versions 3.0 through 5.3 called this WAC; it was not part of 5.4 through 5.5.1. FamilySearch GEDCOM 7.0 reintroduced it with the name INIL for consistency with BAPL (p.66), CONL (p.68), and ENDL (p.71).

LANG (Language) <g7:LANG>

The primary human language of the superstructure. The primary language in which the Text (p.24)-typed payloads of the superstructure and its substructures appear.

The payload of the LANG structure is a language tag, as defined by BCP 47. A registry of component subtags is maintained publicly by the IANA.

In the absence of a LANG structure, the language is assumed to be unspecified; that may also be recorded explicitly with language tag und (meaning "undetermined"). See g7:HEAD-LANG (p.76) for information about applying language-specific algorithms to text in an unspecified language.

If the text is primarily in one language with a few parts in a different language, it is recommended that a language tag identifying the primary language be used. If no one language is primary, the language tag mul (meaning "multiple") may be used, but most language-specific algorithms will treat mul the same way they do und.

> *Note* — Conversations are ongoing about adding part-of-payload language tagging in a future version of the specification to provide more fidelity for multilingual text.

If the text is not in any human language and should not be treated as lingual content, the language tag zxx (meaning "no linguistic content" or "not applicable") may be used. An example of zxx text might be a diagram approximated using characters for their shape, not their meaning.

> *Note* — This specification does not permit `LANG` in every place where human language text might appear. Conversations are ongoing about adding it in more places in a future version of the specification. Using the current specification, additional language tagging can be accomplished using a documented extension tag (p.19) by including the following in the header:
>
> ```
> 1 SCHEMA
> 2 TAG _LANG https://gedcom.io/terms/v7/LANG
> ```
>
> and using the extension tag like so:
>
> ```
> 2 DATE 31 AUG 2018
> 3 PHRASE 2018年8月31日
> 4 _LANG cmn
> ```

`LANG` (Language) `<g7:HEAD-LANG>`

A default language which may be used to interpret any `Text` (p.24)-typed payloads that lack a specific language tag from a `g7:LANG` (p.75) structure. An application may choose to use a different default based on its knowledge of the language preferences of the user.

The payload of the `LANG` structure is a language tag, as defined by BCP 47.

> *Note* — Some algorithms on text are language-specific. Examples include sorting sequences, name comparison and phonetic name matching algorithms, spell-checking, computer-synthesized speech, Braille transcription, and language translation. When the language of the text is given through a `g7:LANG`, that should be used. When `g7:LANG` is not available, `g7:HEAD-LANG` provides the file creator's suggested default language. For some language-specific algorithms, the user's preferred language may be a more appropriate default than the file's default language. User language preferences can be found in a variety of platform-specific places, such as the default language from operating system settings, user locales, Input Method Editors (IMEs), etc.

`LANG` (Language) `<g7:SUBM-LANG>`

A language the subject of that record understands.

The payload of the `LANG` structure is a language tag, as defined by BCP 47.

`LATI` (Latitude) `<g7:LATI>`

A latitudinal coordinate. The payload is either `N` (for a coordinate north of the equator) or `S` (for a coordinate south of the equator) followed by a decimal number of degrees. Minutes and seconds are not used and should be converted to fractional degrees prior to encoding.

> *Example* — 18 degrees, 9 minutes, and 3.4 seconds North would be formatted as `N18.150944`.

`LEFT` (Left crop width) `<g7:LEFT>`

Left is a number of pixels to not display from the left side of the image. See `CROP` (p.69) for more details.

`LONG` (Longitude) `<g7:LONG>`

A longitudinal coordinate. The payload is either `E` (for a coordinate east of the prime meridian) or `W` (for a coordinate west of the prime meridian) followed by a decimal number of degrees. Minutes and seconds are not used and should be converted to fractional degrees prior to encoding.

> *Example* — 168 degrees, 9 minutes, and 3.4 seconds East would be formatted as `E168.150944`.

`MAP` (Map) `<g7:MAP>`

A representative point for a location, as defined by `LATI` (p.76) and `LONG` substructures.

Note that `MAP` provides neither a notion of accuracy (for example, the `MAP` for a birth event may be some distance from the point where the birth occurred) nor a notion of region size (for example, the `MAP` for a place "Belarus" may be anywhere within that nation's 200,000 square kilometer area).

`MARB` (Marriage banns) `<g7:MARB>`

A Family Event (p.61). See also `FAMILY_EVENT_STRUCTURE` (p.46).

`MARC` (Marriage contract) `<g7:MARC>`

A Family Event (p.61). See also `FAMILY_EVENT_STRUCTURE`.

`MARL` (Marriage license) `<g7:MARL>`

A Family Event (p.61). See also `FAMILY_EVENT_STRUCTURE`.

`MARR` (Marriage) `<g7:MARR>`

A Family Event (p.61). See also `FAMILY_EVENT_STRUCTURE`.

`MARS` (Marriage settlement) `<g7:MARS>`

A Family Event (p.61). See also `FAMILY_EVENT_STRUCTURE`.

`MEDI` (Medium) `<g7:MEDI>`

An enumerated value from set `g7:enumset-MEDI` (p.93) providing information about the media or the medium in which information is stored.

When `MEDI` is a substructure of a `g7:CALN` (p.67), it is recommended that its payload describes the medium directly found at that call number rather than a medium from which it was derived.

> *Example* — Consider an asset in a repository that is a digital scan of a book of compiled newspapers; for this asset, the `CALN.MEDI` is recommended to be `ELECTRONIC` rather than `BOOK` or `NEWSPAPER`.

When `MEDI` is a substructure of a `g7:FORM` (p.74), it is recommended that its payload describes the medium from which it was derived.

> *Example* — Consider a digital photo in a multimedia record; for this asset, the `FORM.MEDI` is recommended to be `PHOTO` rather than `ELECTRONIC`.

`MIME` (Media type) `<g7:MIME>`

Indicates the media type (p.30) of the payload of the superstructure.

As of version 7.0, only 2 media types are supported by this structure:

- `text/plain` shall be presented to the user as-is, preserving all spacing, line breaks, and so forth.
- `text/html` uses HTML tags to provide presentation information. Applications should support at least the following:
  - `p` and `br` elements for paragraphing and line breaks.
  - `b`, `i`, `u`, and `s` elements for bold, italic, underlined, and strike-through text (or corresponding display in other locales; see HTML §4.5 for more).
  - `sup` and `sub` elements for super- and sub-script.
  - The 3 XML entities that appear in text: `&`, `<` `>`. Note that `&quote;` and `'` are only needed in attributes. Other entities should be represented as their respective Unicode characters instead.

  Supporting more of HTML is encouraged. Unsupported tags should be ignored during display.

> *Note* — Applications are welcome to support more XML entities or HTML character references in their user interface. However, exporting must only use the core XML entities, translating any other entities into their corresponding Unicode characters.

> *Note* — Applications are welcome to support additional HTML elements, but they should ensure that content is meaningful if those extra elements are ignored and only their content text is displayed.

> *Note* — Media types are also used by external files, as described under `FORM` (p.74). External file media types are not limited to `text/plain` and `text/html`.

If needed, `text/html` can be converted to `text/plain` using the following steps:

1. Replace any sequence of 1 or more spaces, tabs, and line breaks with a single space
2. Case-insensitively replace each `<p…>`, `</p…>`, and `<br…>` with a line break
3. Remove all other `<…>` tags
4. Replace each `<` with `<` and `>` with `>`

5. Replace each `&` with `&`

`NAME` (Name) `<g7:NAME>`

The name of the superstructure's subject, represented as a simple string.

`NAME` (Name) `<g7:INDI-NAME>`

A `PERSONAL_NAME_STRUCTURE` (p.56) with parts, translations, sources, and so forth.

`NATI` (Nationality) `<g7:NATI>`

An Individual Attribute (p.62). See also `INDIVIDUAL_ATTRIBUTE_STRUCTURE` (p.48).

`NATU` (Naturalization) `<g7:NATU>`

An Individual Event (p.60). See also `INDIVIDUAL_EVENT_STRUCTURE` (p.50).

`NCHI` (Number of children) `<g7:FAM-NCHI>`

A Family Attribute (p.64). See also `FAMILY_ATTRIBUTE_STRUCTURE` (p.46).

`NCHI` (Number of children) `<g7:INDI-NCHI>`

An Individual Attribute (p.62). See also `INDIVIDUAL_ATTRIBUTE_STRUCTURE`.

`NICK` (Nickname) `<g7:NICK>`

A descriptive or familiar name that is used instead of, or in addition to, one's official or legal name.

> *Note* — The label "nickname" and description text of this structure were introduced with version 5.5 in 1996, but are understood differently by different users. Some use `NICK` only for names that would be inappropriate in formal settings. Some use it for pseudonyms regardless of where they are used. Some use it for any variant of a name that is not the one used on legal documents. Because all of these uses, and likely others as well, are common in existing data, no further clarification of the meaning of the `NICK` structure is possible without contradicting some existing data.

`NMR` (Number of marriages) `<g7:NMR>`

An Individual Attribute (p.62). See also `INDIVIDUAL_ATTRIBUTE_STRUCTURE`.

`NO` (Did not happen) `<g7:NO>`

An enumerated value from set `g7:enumset-EVEN` (p.92) identifying an event type which did not occur to the superstructure's subject. A specific payload `NO XYZ` should only appear where `XYZ` would be legal.

See `NON_EVENT_STRUCTURE` (p.54) for more details.

NOTE (Note) <g7:NOTE>

A NOTE_STRUCTURE (p.55), containing additional information provided by the submitter for understanding the enclosing data.

When a substructure of HEAD (p.74), it should describe the contents of the document in terms of "ancestors or descendants of" so that the person receiving the data knows what genealogical information the document contains.

NPFX (Name prefix) <g7:NPFX>

Text that appears on a name line before the given and surname parts of a name.

NSFX (Name suffix) <g7:NSFX>

Text which appears on a name line after or behind the given and surname parts of a name.

OBJE (Object) <g7:OBJE>

See MULTIMEDIA_LINK.

OBJE (Object) <g7:record-OBJE>

See MULTIMEDIA_RECORD (p.40).

OCCU (Occupation) <g7:OCCU>

An Individual Attribute (p.62). See also INDIVIDUAL_ATTRIBUTE_STRUCTURE (p.48).

ORDN (Ordination) <g7:ORDN>

An Individual Event (p.60). See also INDIVIDUAL_EVENT_STRUCTURE (p.50).

PAGE (Page) <g7:PAGE>

A specific location within the information referenced. For a published work, this could include the volume of a multi-volume work and the page number or numbers. For a periodical, it could include volume, issue, and page numbers. For a newspaper, it could include a date, page number, and column number. For an unpublished source or microfilmed works, this could be a film or sheet number, page number, or frame number. A census record might have an enumerating district, page number, line number, dwelling number, and family number.

It is recommended that the data in this field be formatted comma-separated with label: value pairs

Example —

```
2 SOUR @S1@
3 PAGE Film: 1234567, Frame: 344, Line: 28
```

If the superstructure's pointer is @VOID@ then there is no information referenced and the PAGE may describe the entire source.