Example —

```
1 DSCR Tall enough his head touched the ceiling
2 SOUR @VOID@
3 PAGE His grand-daughter Lydia told me this in 1980
```

PEDI (Pedigree) <g7:PEDI>

An enumerated value from set `g7:enumset-PEDI` (p.94) indicating the type of child-to-family relationship represented by the superstructure.

PHON (Phone) <g7:PHON>

A telephone number. Telephone numbers have many regional variations and can contain non-digit characters. Users should be encouraged to use internationalized telephone numbers rather than local versions. As a starting point for this recommendation, there are international standards that use a "'+'" shorthand for the international prefix (for example, in place of "011" in the US or "00" in the UK). Examples are `+1 (555) 555-1234` (US) or `+44 20 1234 1234` (UK).

See ITU standards E.123 and E.164 for more information.

PHRASE (Phrase) <g7:PHRASE>

Textual information that cannot be expressed in the superstructure due to the limitations of its data type. A `PHRASE` may restate information contained in the superstructure, but doing so is not recommended unless it is needed for clarity.

Example — A date interpreted from the phrase "The Feast of St John" might be

```
2 DATE 24 JUN 1852
3 PHRASE During the feast of St John
```

Example — A record using `1648/9` to indicate a change in new year might become

```
2 DATE 30 JAN 1649
3 PHRASE 30th of January, 1648/9
```

Example — A record using `1648/9` to indicate uncertainty in the year might become

```
2 DATE BET 1648 AND 1649
3 PHRASE 1648/9
```

Example — A record using `Q1 1867` to indicate an event occurred sometime within the first quarter of 1867 might become

```
2 DATE BET 1 JAN 1867 AND 31 MAR 1867
3 PHRASE Q1 1867
```

Example — A record defining the Maid of Honor in a marriage might become

```
1 MARR
2 ASSO @I2@
3 ROLE OTHER
4 PHRASE Maid of Honor
```

Example — A name given to a foundling orphan might be

```
1 NAME Mary //
2 GIVN Mary
2 TYPE OTHER
3 PHRASE given by orphanage
```

`PLAC` (Place) <g7:PLAC>

The principal place in which the superstructure's subject occurred, represented as a List (p.29) of jurisdictional entities in a sequence from the lowest to the highest jurisdiction, where "jurisdiction" includes units in a political, ecclesiastical, and geographical hierarchies and may include units of any size, such as a continent, "at sea", or a specific building, farm, or cemetery. As with other lists, the jurisdictions are separated by commas. Any jurisdiction's name that is missing is still accounted for by an empty string in the list.

The type of each jurisdiction is given in the `PLAC.FORM` (p.74) substructure, if present, or in the `HEAD.PLAC.FORM` structure. If neither is present, the jurisdictional types are unspecified beyond the lowest-to-highest order noted above.

`PLAC` (Place) <g7:HEAD-PLAC>

This is a placeholder for providing a default `PLAC.FORM`, and must not have a payload.

`POST` (Postal code) <g7:POST>

A code used by a postal service to identify an area to facilitate mail handling. See `ADDRESS_STRUCTURE` (p.43) for more details.

`PROB` (Probate) <g7:PROB>

An Individual Event (p.60). See also `INDIVIDUAL_EVENT_STRUCTURE` (p.50).

`PROP` (Property) <g7:PROP>

An Individual Attribute (p.62). See also `INDIVIDUAL_ATTRIBUTE_STRUCTURE` (p.48).

`PUBL` (Publication) <g7:PUBL>

When and where the record was created. For published works, this includes information such as the city of publication, name of the publisher, and year of publication.

For an unpublished work, it includes the date the record was created and the place where it was created, such as the county and state of residence of a person making a declaration for a pension or the city and state of residence of the writer of a letter.

`QUAY` (Quality of data) `<g7:QUAY>`

An enumerated value from set `g7:enumset-QUAY` (p.94) indicating the credibility of a piece of information, based on its supporting evidence. Some systems use this feature to rank multiple conflicting opinions for display of most likely information first. It is not intended to eliminate the receivers' need to evaluate the evidence for themselves.

`REFN` (Reference) `<g7:REFN>`

A user-defined number or text that the submitter uses to identify the superstructure. For instance, it may be a record number within the submitter's automated or manual system, or it may be a page and position number on a pedigree chart.

This is metadata about the structure itself, not data about its subject. Multiple structures describing different aspects of the same subject must not have the same `REFN` value.

`RELI` (Religion) `<g7:RELI>`

A religious denomination associated with the event or attribute described by the superstructure.

`RELI` (Religion) `<g7:INDI-RELI>`

An Individual Attribute (p.62). See also `INDIVIDUAL_ATTRIBUTE_STRUCTURE` (p.48).

`RESN` (Restriction) `<g7:RESN>`

A List (p.29) of enumerated values from set `g7:enumset-RESN` (p.94) signifying access to information may be denied or otherwise restricted.

The `RESN` structure is provided to assist software in filtering data that should not be exported or otherwise used in a particular context. It is recommended that tools provide an interface to allow users to filter data on export such that certain `RESN` structure payload entries result in the `RESN` structure and its superstructure being removed from the export. Such removal must abide by some constraints: see Removing data (p.23) for more details.

This is metadata about the structure itself, not data about its subject.

`REPO` (Repository) `<g7:REPO>`

See `SOURCE_REPOSITORY_CITATION` (p.58).

`REPO` (Repository) `<g7:record-REPO>`

See `REPOSITORY_RECORD` (p.40).

`RESI` (Residence) `<g7:FAM-RESI>`

A Family Attribute (p.64). See also `FAMILY_ATTRIBUTE_STRUCTURE` (p.46).

See `g7:INDI-RESI` for comments on the use of payload strings in `RESI` (p.64) structures.

`RESI` (Residence) `<g7:INDI-RESI>`

An Individual Attribute (p.62). See also `INDIVIDUAL_ATTRIBUTE_STRUCTURE` (p.48).

Where possible, the residence should be identified in `PLAC` (p.82) and/or `ADDR` (p.65) substructures of the `RESI` structure. The payload text should not duplicate `PLAC` or `ADDR` information, but may be used for residence information that cannot be expressed by those structures.

> *Example* — The following two examples show situations where a `RESI` payload may be appropriate:
>
> ```
> 1 RESI living with an aunt
> 2 DATE ABT MAR 1894
> ```
>
> ```
> 1 RESI in a mobile caravan
> 2 PLAC , , Austro-Hungarian Empire
> 3 FORM City, County, Country
> ```

`RETI` (Retirement) `<g7:RETI>`

An Individual Event (p.60). See also `INDIVIDUAL_EVENT_STRUCTURE` (p.50).

`ROLE` (Role) `<g7:ROLE>`

An enumerated value from set `g7:enumset-ROLE` (p.95) indicating what role this person played in an event or person's life.

> *Example* — The following indicates a child's birth record as the source of the mother's name:
>
> ```
> 0 @I1@ INDI
> 1 NAME Mary //
> 2 SOUR @S1@
> 3 EVEN BIRT
> 4 ROLE MOTH
> ```

> *Example* — The following indicates that a person's best friend was a witness at their baptism:
>
> ```
> 0 @I2@ INDI
> 1 ASSO @I3@
> 2 ROLE FRIEND
> 3 PHRASE best friend
> 1 BAPM
> 2 ASSO @I3@
> 3 ROLE WITN
> ```

SCHMA (Extension schema) <g7:SCHMA>

A container for storing meta-information about the extension tags used in this document. See Extensions (p.16) for more details.

SDATE (Sort date) <g7:SDATE>

A date to be used as a sorting hint. It is intended for use when the actual date is unknown, but the display order may be dependent on date.

If both a DATE (p.69) and SDATE are present in the same structure, the SDATE should be used for sorting and positioning while the DATE should be displayed as the date of the structure.

SDATE and its substructures (including PHRASE (p.81), TIME (p.87), and any extension structures) should be used only as sorting hints, not to convey historical meaning.

It is recommended to use a payload that matches `[[day D] month D] year [D epoch]`. Other DateValue forms may have unreliable effects on sorting. Including a month and day is encouraged to help different applications sort dates the same way, as the relative ordering of dates with different levels of precision is not well defined.

SEX (Sex) <g7:SEX>

An enumerated value from set g7:enumset-SEX (p.96) that indicates the sex of the individual at birth.

SLGC (Sealing, child) <g7:SLGC>

A Latter-Day Saint Ordinance (p.64). See also LDS_INDIVIDUAL_ORDINANCE (p.53).

SLGS (Sealing, spouse) <g7:SLGS>

A Latter-Day Saint Ordinance (p.64). See also LDS_SPOUSE_SEALING (p.53).

SNOTE (Shared note) <g7:SNOTE>

A pointer to a note that is shared by multiple structures. See NOTE_STRUCTURE (p.55) for more details.

SNOTE (Shared note) <g7:record-SNOTE>

A note that is shared by multiple structures. See SHARED_NOTE_RECORD (p.41) for more details.

SOUR (Source) <g7:SOUR>

A description of the relevant part of a source to support the superstructure's data. See SOURCE_CITATION (p.58) for more details.

SOUR (Source) <g7:record-SOUR>

A description of an entire source. See SOURCE_RECORD (p.42) for more details.

`SOUR` (Source) `<g7:HEAD-SOUR>`

An identifier for the product producing this dataset. A registration process for these identifiers existed for a time, but no longer does. If an existing identifier is known, it should be used. Otherwise, a URI owned by the product should be used instead.

`SPFX` (Surname prefix) `<g7:SPFX>`

A name piece used as a non-indexing pre-part of a surname.

`SSN` (Social security number) `<g7:SSN>`

An Individual Attribute (p.62). See also `INDIVIDUAL_ATTRIBUTE_STRUCTURE` (p.48).

`STAE` (State) `<g7:STAE>`

A geographical division of a larger jurisdictional area, such as a state within the United States of America. See `ADDRESS_STRUCTURE` (p.43) for more details.

`STAT` (Status) `<g7:ord-STAT>`

An enumerated value from set `g7:enumset-ord-STAT` (p.97) assessing of the state or condition of an ordinance.

`STAT` (Status) `<g7:FAMC-STAT>`

An enumerated value from set `g7:enumset-FAMC-STAT` (p.96) assessing of the state or condition of a researcher's belief in a family connection.

`SUBM` (Submitter) `<g7:SUBM>`

A contributor of information in the substructure. This is metadata about the structure itself, not data about its subject.

`SUBM` (Submitter) `<g7:record-SUBM>`

A description of a contributor of information to the document. See `SUBMITTER_RECORD` (p.43) for more details.

`SURN` (Surname) `<g7:SURN>`

A family name passed on or used by members of a family.

`TAG` (Extension tag) `<g7:TAG>`

Information relating to a single extension tag as used in this document. See Extensions (p.16) for more details.

`TEMP` (Temple) `<g7:TEMP>`

The name of a temple of The Church of Jesus Christ of Latter-day Saints. Previous versions recommended using a set of abbreviations for temple names, but the list of abbreviations is no longer published by the Church and using abbreviations is no longer recommended.

`TEXT` (Text from Source) `<g7:TEXT>`

A verbatim copy of any description contained within the source. This indicates notes or text that are actually contained in the source document, not the submitter's opinion about the source. This should be, from the evidence point of view, "what the original record keeper said" as opposed to the researcher's interpretation.

`TIME` (Time) `<g7:TIME>`

A `Time` (p.27) value in a 24-hour clock format.

`TITL` (Title) `<g7:TITL>`

The title, formal or informal, of the superstructure.

A published work, such as a book, might have a title plus the title of the series of which the book is a part. A magazine article would have a title plus the title of the magazine that published the article.

For an unpublished work, including most digital files, titles should be descriptive and appropriate to the work.

> *Example —*
>
> - The `TITL` of a letter might include the date, the sender, and the receiver.
> - The `TITL` of a transaction between a buyer and seller might have their names and the transaction date.
> - The `TITL` of a family Bible containing genealogical information might have past and present owners and a physical description of the book.
> - The `TITL` of a personal interview would cite the informant and interviewer.

Some sources may have a citation text that cannot readily be represented using the `SOURCE_RECORD` (p.42) substructures `AUTH` (p.66), `PUBL` (p.82), `REPO` (p.83), and so on. In such cases, the entire citation text may be presented as the payload of the `SOUR.TITL`.

`TITL` (Title) `<g7:INDI-TITL>`

An Individual Attribute (p.62). See also `INDIVIDUAL_ATTRIBUTE_STRUCTURE` (p.48).

`TOP` (Top crop width) `<g7:TOP>`

A number of pixels to not display from the top side of the image. See `CROP` (p.69) for more details.

`TRAN` (Translation)

A representation of the superstructure's data in a different format.

In some situations it is desirable to provide the same semantic content in multiple formats. Where this is desirable, a `TRAN` substructure is used, where the specific format is given in its language tag substructure, media type substructure, or both.

Different `TRAN` structures are used in different contexts to fully capture the structure of the information being presented in multiple formats. In all cases, a `TRAN` structure's payload and substructures should provide only information also contained in the `TRAN` structures' superstructure, but provide it in a new language, script, or media type.

Each `TRAN` substructure must have either a language tag or a media type or both. Each `TRAN` structure must differ from its superstructure and from every other `TRAN` substructure of its superstructure in either its language tag or its media type or both.

`TRAN` (Translation) `<g7:NAME-TRAN>`

A type of `TRAN` substructure specific to Personal Names (p.30). Each `NAME.TRAN` must have a `LANG` (p.75) substructure. See also `INDI.NAME` (p.79).

Example — The following presents a name in Mandarin, transliterated using Pinyin

```
1 NAME /孔/德成
2 GIVN 德成
2 SURN 孔
2 TRAN /Kǒng/ Déyōng
3 GIVN Déyōng
3 SURN Kǒng
3 LANG zh-pinyin
```

`TRAN` (Translation) `<g7:PLAC-TRAN>`

A type of `TRAN` (p.87) substructure specific to places. Each `PLAC.TRAN` must have a `LANG` (p.75) substructure. See also `PLAC` (p.82).

Example — The following presents a place in Japanese with a romaji transliteration and English translation

```
2 PLAC 千代田, 東京, 日本
3 FORM 千, 京, 本
3 LANG ja
3 TRAN Chiyoda, Tokyo, Nihon
4 LANG ja-Latn
3 TRAN Chiyoda, Tokyo, Japan
4 LANG en
```

TRAN (Translation) <g7:NOTE-TRAN>

A type of TRAN (p.87) for unstructured human-readable text, such as is found in NOTE (p.80) and SNOTE (p.85) payloads. Each g7:NOTE-TRAN must have either a LANG (p.75) substructure or a MIME (p.78) substructure or both. If either is missing, it is assumed to have the same value as the superstructure. See also NOTE and SNOTE.

> *Example* — The following presents the same note in HTML-format English; in plain-text with the same language as the superstructure (English); and in Spanish with the same media type as the superstructure (HTML).

```
1 NAME Arete /Hernandez/
2 NOTE Named after Arete from <i>The Odyssey</i>
3 LANG en
3 MIME text/html
3 TRAN Named after Arete from "The Odyssey"
4 MIME text/plain
3 TRAN Nombrada en honor a Arete de <i>La Odisea</i>
4 LANG es
```

It is recommended that text given in text/html should only be translated into text/plain if the resulting text is different from the text created by the HTML-to-text conversion process defined in g7:MIME (p.78).

TRAN (Translation) <g7:FILE-TRAN>

A type of TRAN (p.87) for external media files. Each g7:NOTE-TRAN (p.89) must have a FORM (p.74) substructure. See also FILE (p.73) and the File Path datatype (p.31).

> *Example* — If an mp3 audio file has been transcoded as an ogg file and a timestamped transcript has been extracted as a WebVTT file, the resulting set of files might be presented as follows:

```
0 @EX@ OBJE
1 FILE media/original.mp3
2 FORM audio/mp3
2 TRAN media/derived.oga
3 FORM audio/ogg
2 TRAN media/transcript.vtt
3 FORM text/vtt
```

Note that FILE.TRAN (p.89) refers to translation to a different digital format, not to translation to a different human language. Files that differ in the human language of their content should each be given their own FILE (p.73) structure.

`TRLR` (Trailer) <g7:TRLR>

A pseudo-structure marking the end of a dataset. See The Header and Trailer (p.15) for more details.

`TYPE` (Type) <g7:TYPE>

A descriptive word or phrase used to further classify the superstructure.

When both a `NOTE` (p.80) and free-text `TYPE` are permitted as substructures of the same structure, the displaying systems should always display the `TYPE` value when they display the data from the associated structure; `NOTE` will typically be visible only in a detailed view.

`TYPE` must be used whenever the generic `EVEN`, `FACT` and `IDNO` (p.75) tags are used. It may also be used for any other event or attribute.

Using the subordinate `TYPE` classification method provides a further classification of the superstructure but does not change its basic meaning.

> *Example* — A `ORDN` (p.80) with a `TYPE` could clarify what kind of ordination was performed:
>
> ```
> 0 @I1@ INDI
> 1 ORDN
> 2 TYPE Bishop
> ```
>
> This classifies the entry as an ordination as a bishop, which is still a ordination event. The event could be further clarified with `RELI` (p.83), `DATE` (p.69), and other substructures.
>
> Other descriptor values might include, for example,
>
> - “Stillborn” as a qualifier to `BIRT` (p.67) (birth)
> - “Civil” as a qualifier to `MARR` (p.77) (marriage)
> - “College” as a qualifier to `GRAD` (p.74) (graduation)
> - “Oral” as a qualifier to `WILL` (p.92)
>
> See also `FACT` and `EVEN` for additional examples.

`TYPE` (Type) <g7:NAME-TYPE>

An enumerated value from set `g7:enumset-NAME-TYPE` (p.98) indicating the type of the name.

`TYPE` (Type) <g7:EXID-TYPE>

The authority issuing the `EXID` (p.72), represented as a URI. It is recommended that this be a URL.

If the authority maintains stable URLs for each identifier it issues, it is recommended that the `TYPE` (p.90) payload be selected such that appending the `EXID` payload to it yields that URL. However, this is not required and a different URI for the set of issued identifiers may be used instead.

Registered URIs are listed in the exid-types registry, where fields are defined using the YAML file format.

Additional type URIs can be registered by filing a GitHub pull request.

`UID` (Unique Identifier) `<g7:UID>`

A globally-unique identifier of the superstructure, to be preserved across edits. If a globally-unique identifier for the record already exists, it should be used without modification, not even whitespace or letter case normalization. New globally unique identifiers should be created and formatted as described in RFC 4122.

This is metadata about the structure itself, not data about its subject. Multiple structures describing different aspects of the same subject would have different `UID` values.

Because the `UID` identifies a structure, it can facilitate inter-tool collaboration by distinguishing between a structure being edited and a new structure being created. If an application allows structures to be edited in a way that completely changes their meaning (e.g., changing all the contents of an `INDI` record to have it describe a completely different person) then any `UID`s should also be changed.

> *Note* — Some systems used a 16-byte UUID with a custom 2-byte checksum for a total of 18 bytes:
>
> - checksum byte 1 = (sum of (byte_i) for i 1 through 16) mod 256
> - checksum byte 2 = (sum of ($(16 - i) \times (\text{byte}_i)$) for i 1 through 16) mod 256
>
> Use of checksums for UIDs is discouraged except in cases where error-prone input is expected and an appropriate action to take in case of an error is known.

`VERS` (Version) `<g7:VERS>`

An identifier that represents the version level assigned to the associated product. It is defined and changed by the creators of the product.

`VERS` (Version) `<g7:GEDC-VERS>`

The version number of the official specification that this document's data conforms to. This must include the major and minor version (for example, "`7.0`"); it may include the patch as well (for example, "`7.0.1`"), but doing so is not required. See A Guide to Version Numbers (p.7) for more details about version numbers.

`WIDTH` (Width in pixels) `<g7:WIDTH>`

How many pixels to display horizontally for the image. See `CROP` (p.69) for more details.

`WIFE` (Wife) `<g7:WIFE>`

A container for information relevant to the subject of the superstructure specific to the individual described by the associated `FAM`'s `WIFE` substructure.

`WIFE` (Wife) `<g7:FAM-WIFE>`

A partner in a `FAM` record. See `FAMILY_RECORD` (p.37) for more details.

`WILL` (Will) `<g7:WILL>`

An Individual Event (p.60). See also `INDIVIDUAL_EVENT_STRUCTURE` (p.50).

`WWW` (Web address) `<g7:WWW>`

A URL or other locator for a World Wide Web page of the subject of the superstructure, as defined by any relevant standard such as whatwg/url, RFC 3986, RFC 3987, and so forth.

Like other substructures, the `WWW` structure provides details about the subject of its superstructure. For example, a `MARR` (p.61). `WWW` is a world wide web page of the marriage event, not the personal website of the couple or an entry in an online database serving as a source documenting the marriage. However, the meaning of `WWW` was only implicit when it was introduced in version 5.5.1 and many files were created that use `WWW` to store a more tangentially-related web address, so applications are recommended to interpret the `WWW` structure's meaning cautiously.

If an invalid or no longer existing web address is present upon import, it should be preserved as-is on export.

3.4. Enumeration Values

Unless otherwise specified in the enumeration description in this section, each enumeration value defined in this section has a URI constructed by concatenating `g7:enum-` to the enumeration value; for example, the `HUSB` (p.75) enumeration value has the URI `http://gedcom.io/terms/v7/enum-HUSB`.

Each set of enumeration values has its own URI.

`<g7:enumset-ADOP>`

Value	Meaning
`HUSB`	Adopted by the `HUSB` of the `FAM` pointed to by `FAMC`. The URI of this value is `g7:enum-ADOP-HUSB`
`WIFE`	Adopted by the `WIFE` of the `FAM` pointed to by `FAMC`. The URI of this value is `g7:enum-ADOP-WIFE`
`BOTH`	Adopted by both `HUSB` and `WIFE` of the `FAM` pointed to by `FAMC`

`<g7:enumset-EVEN>`

An event-type tag name, but not the generic `EVEN` tag. See Events (p.59).

Most values in this enumeration set use the same tag and URI as the corresponding event, except for tags used with different URIs for `FAM` vs `INDI`; these are given generic definitions with URIs constructed by concatenating `g7:enum-` to the enumeration value:

Value	Meaning
CENS	A census event; either g7:INDI-CENS (p.67) or g7:FAM-CENS (p.67)

<g7:enumset-EVENATTR>

An event- or attribute-type tag name. See Events (p.59) and Attributes (p.62).

Most values in this enumeration set use the same tag and URI as the corresponding event or attribute, except for tags used with different URIs for FAM vs INDI; these are given generic definitions with URIs constructed by concatenating g7:enum- to the enumeration value:

Value	Meaning
CENS	A census event; either g7:INDI-CENS or g7:FAM-CENS
NCHI	A count of children; either g7:INDI-NCHI (p.79) or g7:FAM-NCHI (p.79)
RESI	A residence attribute; either g7:INDI-RESI (p.84) or g7:FAM-RESI (p.83)
FACT	A generic attribute; either g7:INDI-FACT (p.73) or g7:FAM-FACT (p.72)
EVEN	A generic event; either g7:INDI-EVEN (p.71) or g7:FAM-EVEN (p.71)

<g7:enumset-MEDI>

Value	Meaning
AUDIO	An audio recording
BOOK	A bound book
CARD	A card or file entry
ELECTRONIC	A digital artifact
FICHE	Microfiche
FILM	Microfilm
MAGAZINE	Printed periodical
MANUSCRIPT	Written pages
MAP	Cartographic map
NEWSPAPER	Printed newspaper
PHOTO	Photograph
TOMBSTONE	Burial marker or related memorial
VIDEO	Motion picture recording
OTHER	A value not listed here; should have a PHRASE substructure

<g7:enumset-PEDI>

Value	Meaning
`ADOPTED`	Adoptive parents
`BIRTH`	Family structure at time of birth
`FOSTER`	The child was included in a foster or guardian family
`SEALING`	The child was sealed to parents other than birth parents
`OTHER`	A value not listed here; should have a `PHRASE` substructure

> *Note* — It is known that some users have interpreted `BIRTH` to mean "genetic parent" and others to mean "social parent at time of birth". Definitions differ in many circumstances (infidelity, surrogacy, sperm donation, and so on). Hence, applications should refrain from asserting it has either meaning in imported data.

> *Note* — The structures for foster children in particular, and family relationships in general, are known to have undesirable limitations and are likely to change in a future version of this specification.

> *Note* — `SEALING` implies that a `SLGC` (p.85) event was performed, and it is recommended that this enumeration value only be used when the `SLGC` event is present in the GEDCOM file. `ADOPTED`, on the other hand, only implies a social relationship which may or may not have any associated `ADOP` event.

<g7:enumset-QUAY>

Value	Meaning
`0`	Unreliable evidence or estimated data
`1`	Questionable reliability of evidence (interviews, census, oral genealogies, or potential for bias, such as an autobiography)
`2`	Secondary evidence, data officially recorded sometime after the event
`3`	Direct and primary evidence used, or by dominance of the evidence

Although the values look like integers, they do not have numeric meaning.

> *Note* — The structures for representing the strength of and confidence in various claims are known to be inadequate and are likely to change in a future version of this specification.

<g7:enumset-RESN>

Value	Meaning
`CONFIDENTIAL`	This data was marked as confidential by the user.

Value	Meaning
`LOCKED`	Some systems may ignore changes to this data.
`PRIVACY`	This data is not to be shared outside of a trusted circle, generally because it contains information about living individuals. This definition is known to admit multiple interpretations, so use of the `PRIVACY` restriction notice is not recommended.

It is recommended that applications allow users to chose how `CONFIDENTIAL` and/or `PRIVACY` data is handled when interfacing with other users or applications, for example by allowing them to exclude such data when exporting.

When a List (p.29) of `RESN` (p.83) enumeration values are present, all apply.

> *Example* — The line `1 RESN CONFIDENTIAL, LOCKED` means the superstructure's data is both considered confidential *and* read-only.

Since `RESN` was introduced in version 5.5 the intent of the `PRIVACY` value has been interpreted differently by different applications. Known interpretations include

- Some assign `PRIVACY` by algorithm or policy, unlike the user-assigned `CONFIDENTIAL`
- Some use `PRIVACY` to mark records that have already had private data removed
- Some use the English definitions of "privacy" and "confidential" to inform different restrictions for each

There may also be applications using `PRIVACY` with interpretations not listed above.

Because these different interpretations became widespread before they were identified, determining which one is meant generally requires knowledge of which application applied the `PRIVACY` restriction notice. It is anticipated that a future version will deprecate the `PRIVACY` option and introduce new values for each of its current use cases.

`<g7:enumset-ROLE>`

Value	Meaning
`CHIL`	Child
`CLERGY`	Religious official in event; implies `OFFICIATOR`
`FATH`	Father; implies `PARENT`
`FRIEND`	Friend
`GODP`	Godparent or related role in other religions
`HUSB`	Husband; implies `SPOU`
`MOTH`	Mother; implies `PARENT`
`MULTIPLE`	A sibling from the same pregnancy (twin, triplet, quadruplet, and so on). A `PHRASE` can be used to specify the kind of multiple birth.

Value	Meaning
`NGHBR`	Neighbor
`OFFICIATOR`	Officiator of the event
`PARENT`	Parent
`SPOU`	Spouse
`WIFE`	Wife; implies `SPOU`
`WITN`	Witness
`OTHER`	A value not listed here; should have a `PHRASE` substructure

These should be interpreted in the context of the recorded event and its primary participants. For example, if you cite a child's birth record as the source of the mother's name, the value for this field is "`MOTH`." If you describe the groom of a marriage, the role is "`HUSB` (p.75)."

`<g7:enumset-SEX>`

Value	Meaning
`M`	Male
`F`	Female
`X`	Does not fit the typical definition of only Male or only Female
`U`	Cannot be determined from available sources

This can describe an individual's reproductive or sexual anatomy at birth. Related concepts of gender identity or sexual preference are not currently given their own tag. Cultural or personal gender preference may be indicated using the `FACT` tag.

`<g7:enumset-FAMC-STAT>`

Value	Meaning
`CHALLENGED`	Linking this child to this family is suspect, but the linkage has been neither proven nor disproven.
`DISPROVEN`	There has been a claim by some that this child belongs to this family, but the linkage has been disproven.
`PROVEN`	Linking this child to this family has been proven.

When these enumeration values were introduced in version 5.5.1 it was assumed, but never specified, that "proven" referred to the definition provided by the Board for Certification of Genealogists. Because that meaning was not specified and other definitions of "proven" exist, existing files might use these values in other ways.

> *Note* — The structures for representing the strength of and confidence in various claims are known to be inadequate and are likely to change in a future version of this specification.

`<g7:enumset-ord-STAT>`

These values were formerly used by The Church of Jesus Christ of Latter-day Saints for coordinating between temples and members. They are no longer used in that way, meaning their interpretation is subject to individual user interpretation

The definition of some of these values combined with the official policies of the church mean that some values only make sense under a subset of ordinance structures (p.64). These contexts are identified in the "applies to" column below, and it is recommended that applications follow those guidelines. These recommendations were not present when these enumeration values were first introduced in version 5.3 so uses that do not conform to the "applies to" guidelines may be encountered; if so, they should be treated by applications like any other user-specified but semantically-strange data.

The definition of some of these values combined with the official policies of the church and the move of the church away from using GEDCOM for handling ordinance requests make them redundant and/or no longer relevant. If so, that is indicated in the "status" column below. Like the "applies to" column, the "status" column is a recommendation, not a requirement, and applications should be prepared to encounter non-current values.

Value	Applies to	Meaning	Status
`BIC`	`SLGC`	Born in the covenant, so child to parent sealing ordinance is not required.	Current
`CANCELED`	`SLGS`	Canceled and considered invalid.	Current
`CHILD`	All but `SLGC`	Died before 8 years old, so ordinances other than child to parent sealing are not required.	Current
`COMPLETED`	All	Completed, but the date is not known.	Deprecated, use `DATE BEF date` instead. This status was defined for use with TempleReady which is no longer in use.
`EXCLUDED`	All	Patron excluded this ordinance from being cleared in this submission.	Deprecated. This status was defined for use with TempleReady which is no longer in use.

Value	Applies to	Meaning	Status
`DNS`	`SLGC`, `SLGS`	This ordinance is not authorized.	Current
`DNS_CAN`	`SLGS`	This ordinance is not authorized, and the previous ordinance is cancelled.	Current
`INFANT`	All but `SLGC`	Died before less than 1 year old, baptism or endowment not required.	Deprecated. Use `CHILD` instead.
`PRE_1970`	All	Ordinance was likely completed because an ordinance for this person was converted from temple records of work completed before 1970.	Deprecated. Use `DATE BEF 1970` instead.
`STILLBORN`	All	Born dead, so no ordinances are required.	Current
`SUBMITTED`	All	Ordinance was previously submitted.	Deprecated. This status was defined for use with TempleReady which is no longer in use.
`UNCLEARED`	All	Data for clearing the ordinance request was insufficient.	Deprecated. This status was defined for use with TempleReady which is no longer in use.

`<g7:enumset-NAME-TYPE>`

Value	Meaning
`AKA`	Also known as, alias, etc.
`BIRTH`	Name given at or near birth.
`IMMIGRANT`	Name assumed at the time of immigration.
`MAIDEN`	Maiden name, name before first marriage.
`MARRIED`	Married name, assumed as part of marriage.
`PROFESSIONAL`	Name used professionally (pen, screen, stage name).

Value	Meaning
`OTHER`	A value not listed here; should have a `PHRASE` substructure

4. The FamilySearch GEDZIP file format

It is often useful to transmit a dataset together with a set of external files. The FamilySearch GEDZIP 7.0 file format is provided for this purpose. Version 7.0 was the first version of GEDZIP released; the version number of a GEDZIP file is the same as the version number of the dataset it contains.

A GEDZIP file is a zip archive, as defined by the .ZIP File Format Specification and standardized by ISO/IEC 21320-1:2015.

Each GEDZIP file contains the following entries:

- An entry with name `gedcom.ged` containing a data stream.
- An entry for each *local file* `g7:type-FilePath` payload in `gedcom.ged`, with the same zip *file name* as the payload. If there is a local file named `gedcom.ged`, it must be renamed to a new unused filename with the same extension prior to constructing the GEDZIP.

All file names inside a GEDZIP are case-sensitive.

Many other zip-based file formats (such as jar, epub, docx, GEDCOM-X) assign special meaning to the zip directory `META-INF` and the zip file names `MANIFEST.MF` and `META-INF/MANIFEST.MF`. These have no special meaning in GEDZIP and it is recommended that they not be used in a GEDZIP file, both to avoid confusing systems that look inside zip archives to determine their file type, and to leave open the possibility of their addition in a future version of this specification.

When saved as a file, a GEDZIP should use the filename extension `.gdz`.

> *Note* — A few details about the zip archive format are useful to fully understand GEDZIP:
>
> - An archive can contain 1 or more files.
> - Files within an archive can be added, removed, or updated individually without needing to re-process the rest of the archive. Libraries such as libzip allow applications to operate directly on the zip archive as if it were a normal directory tree.
> - What the zip specification calls a “file name” is actually a local path and may contain directories.
> - Directory separators are `/` internally and are converted to the appropriate form by the zip processing tool during zipping and unzipping. Because of this, unzipping a GEDZIP in any local directory results in all GEDZIP file paths working as-is for the resulting `gedcom.ged` without the need for any additional processing.