

ComBat Documentation

Module name: ComBat

Description: Performs batch correction on a dataset containing multiple

batches

Author: Marc-Danie Nazaire (Broad Institute), qp-help@broad.mit.edu

Date: 05/8/2008

Release: 1.0

Summary: This module runs the ComBat (<u>Com</u>bining <u>Bat</u>ches) R script on a microarray dataset. The ComBat R script uses an Empirical Bayes method to adjust for potential batch effects in the dataset.

References:

• Johnson, WE, Rabinovic, A, and Li, C (2007). Adjusting batch effects in microarray expression data using Empirical Bayes methods. Biostatistics 8(1):118-127.

Parameters:

Name Description input file: input file – res, gct

sample info file: A file containing information about the samples.

The first three columns in the sample info file must be

Array, Sample, and Batch.

covariate columns: The covariate columns to use in analysis.

This is a list specifying additional columns from sample info file

to use in analysis (i.e, 4, 5, 7, ...).

absent calls filter: The filter to apply to genes with absent calls. Filters genes with

absent calls in 1 - (absent calls filter) of the samples. This value must be between 0 and 1. Ignored if input file is not a .res file.

create prior plots: Whether to generate prior probability distribution plots

prior method: Empirical Bayes priors distribution estimation method to use.

Either a parametric or non-parametric method can be applied. If unsure of which method to use try the parametric method first

since it is faster.

output.file: Name of batch adjusted output file

Return Value:

1. <output.file>.<res, gct>, A file containing the batch effect adjusted dataset in the same file format as the input file

If "create prior plots" is yes:

2. <output.file>.plot.<pdf, jpeg>, A file containing the prior plots in jpeg format if this format is supported, otherwise in pdf format.

Platform dependencies:

GenePattern

Preprocess & Utility

Task type: CPU type: OS: any

any R (v. 2.5.0) Language: