DSCI 552 Homework 6

Jun Jiang · GitHub: `generalisjj-hub`

```
from pathlib import Path
import warnings
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from IPython.display import display, Markdown
from sklearn.impute import SimpleImputer
from sklearn.preprocessing import StandardScaler
from sklearn.ensemble import RandomForestClassifier
from sklearn.metrics import confusion_matrix, roc_auc_score, roc_curve, accuracy_s
core
from sklearn.model_selection import StratifiedKFold
from imblearn.over_sampling import SMOTE
from xgboost import XGBClassifier

warnings.filterwarnings('ignore', category=UserWarning)
DATA = Path('data') if Path('data').exists() else Path('../data')
SEED = 552
train = pd.read_csv(DATA / 'aps_failure_training_set.csv', skiprows=20, na_values=
'na')
test = pd.read_csv(DATA / 'aps_failure_test_set.csv', skiprows=20, na_values='na')
X_raw = train.drop(columns='class')
T_raw = test.drop(columns='class')
y = (train['class'] == 'pos').astype(int).to_numpy()
yt = (test['class'] == 'pos').astype(int).to_numpy()
# The assignment explicitly requires test-set statistics for test imputation.
train_imputer = SimpleImputer(strategy='median')
test_imputer = SimpleImputer(strategy='median')
X = train_imputer.fit_transform(X_raw).astype(np.float32)
T = test_imputer.fit_transform(T_raw).astype(np.float32)
features = X_raw.columns
print(f'Train: {X.shape}, test: {T.shape}; missing entries: {X_raw.isna().sum().su
m():,} / {T_raw.isna().sum().sum():,}.')
```

```
Train: (60000, 170), test: (16000, 170); missing entries: 850,015 / 228,680.
```

1(a)–(b) Data preparation

Missing values can be addressed by deleting incomplete observations, mean/median imputation, or multivariate methods such as k-nearest-neighbor or iterative imputation. Since missing entries are common and the minority class is small, we use the median separately for each feature. As requested in the assignment, test medians come from the test set; training medians come from training data. Within cross-validation each fold's medians are fitted on that fold's training portion only. Sources: scikit-learn imputation guide, UCI data.

The correlation-matrix indices follow the original 170 feature columns in dataset order (starting at 0).

```
counts = pd.DataFrame({'training': np.bincount(y, minlength=2), 'test': np.bincoun
t(yt, minlength=2)}, index=['negative', 'positive'])
display(counts)
print(f"Training: {counts.loc['negative','training'] / counts.loc['positive','trai
ning']:.0f}:1 negative to positive; this is strongly imbalanced.")
filled = pd.DataFrame(X, columns=features)
```

```
cv = (filled.std(ddof=1) / filled.mean()).sort_values(ascending=False)
# Show all 170 coefficients in five side-by-side groups.
parts = []
for idx in np.array_split(np.arange(len(cv)), 5):
    parts.append(pd.DataFrame({'feature': cv.index[idx], 'CV': cv.iloc[idx].to_num
py()}).reset_index(drop=True))
display(pd.concat(parts, axis=1).round(3))
print('Top 13 features:', ', '.join(cv.head(13).index))
```


	training	test
negative	59000	15625
positive	1000	375

```
Training: 59:1 negative to positive; this is strongly imbalanced.
```

	feature	CV	feature	CV	feature	CV	feature	CV	feature	CV
0	cf_000	244.888000	ay_003	28.735001	be_000	6.847	cs_003	3.132	bb_000	2.405
1	co_000	244.507004	cn_000	26.336000	ba_008	6.831	ap_000	3.081	bv_000	2.405
2	ad_000	244.322998	ae_000	24.200001	cn_002	6.707	dd_000	3.057	bu_000	2.405
3	cs_009	237.931000	at_000	23.708000	cu_000	6.673	ck_000	3.056	cq_000	2.405
4	dh_000	123.216003	az_008	22.680000	cn_007	6.335	ay_006	3.053	ci_000	2.400
5	dj_000	117.494003	dq_000	22.030001	bz_000	6.314	az_005	3.035	ed_000	2.394
6	ag_000	92.917999	af_000	19.471001	db_000	6.259	ba_006	3.031	ag_006	2.357
7	as_000	87.333000	ai_000	18.204000	ag_008	6.221	bi_000	3.022	cn_005	2.345
8	ay_009	84.734001	ag_002	17.566000	av_000	6.006	ag_005	2.956	ds_000	2.320
9	ak_000	80.425003	az_007	16.229000	ee_009	5.692	du_000	2.918	ah_000	2.312
10	az_009	77.838997	cl_000	14.971000	ag_004	5.463	ba_002	2.898	ac_000	2.310
11	ch_000	77.454002	cz_000	14.506000	cs_007	5.425	dn_000	2.888	bg_000	2.309
12	au_000	68.883003	cp_000	13.933000	cm_000	5.392	ag_007	2.859	ce_000	2.271
13	cr_000	58.077999	az_002	13.272000	dx_000	5.374	aq_000	2.857	ao_000	2.271
14	ay_001	52.825001	ay_005	12.525000	bd_000	5.352	az_004	2.849	an_000	2.250
15	df_000	52.292999	di_000	11.826000	cs_002	5.115	ee_005	2.847	dt_000	2.192
16	dz_000	51.332001	ar_000	11.354000	ee_007	5.013	ba_007	2.844	do_000	2.166
17	ef_000	49.367001	cn_001	11.263000	cx_000	4.749	ba_003	2.733	cs_006	2.143
18	cs_008	48.102001	cj_000	11.070000	cs_004	4.685	ba_000	2.700	dp_000	2.022
19	aj_000	44.265999	ab_000	10.383000	eb_000	4.540	ba_005	2.698	cs_000	1.881
20	eg_000	42.481998	cn_008	9.734000	de_000	4.528	ba_004	2.632	cv_000	1.837
21	dl_000	39.738998	ba_009	9.430000	cn_003	4.192	bh_000	2.629	dc_000	1.725
22	ay_002	39.249001	az_000	9.406000	cg_000	4.025	ba_001	2.624	bs_000	1.051
23	dg_000	38.486000	al_000	9.173000	ax_000	4.019	ee_004	2.622	ca_000	0.932
24	ay_000	37.428001	am_0	9.155000	ay_008	3.816	cn_004	2.621	cb_000	0.909
25	dk_000	37.039001	az_006	8.881000	cs_001	3.663	ee_002	2.594	bl_000	0.871
26	cy_000	36.601002	ag_003	8.647000	dv_000	3.587	ec_00	2.581	bm_000	0.849
27	dm_000	36.261002	ct_000	7.850000	bj_000	3.576	ee_003	2.573	bn_000	0.836
28	ag_001	35.249001	dy_000	7.797000	ay_007	3.314	cc_000	2.524	bk_000	0.820
29	ea_000	34.946999	az_001	7.721000	ee_000	3.300	bx_000	2.512	bo_000	0.792
30	cn_009	34.271999	az_003	7.527000	ee_001	3.281	cs_005	2.510	bp_000	0.753
31	ay_004	33.751999	bf_000	7.454000	ee_008	3.259	aa_000	2.451	bq_000	0.719
32	ag_009	33.358002	bc_000	7.264000	ee_006	3.219	by_000	2.450	br_000	0.689
33	da_000	29.368000	dr_000	6.865000	cn_006	3.163	bt_000	2.448	cd_000	0.000


```
Top 13 features: cf_000, co_000, ad_000, cs_009, dh_000, dj_000, ag_000, as_000, a
y_009, ak_000, az_009, ch_000, au_000
```


```
fig, ax = plt.subplots(figsize=(6.5, 5.5))
im = ax.imshow(filled.corr(), cmap='coolwarm', vmin=-1, vmax=1, interpolation='nea
rest')
ax.set(title='Correlation matrix: all 170 features', xlabel='Feature index', ylabe
l='Feature index')
fig.colorbar(im, ax=ax, fraction=.045, label='Pearson correlation')
plt.tight_layout(); plt.show()
```





```
# Show every pair among the top 13 CV features in two labeled triangular panels.
# Keep all positives and a reproducible sample of negatives for visual clarity.
rng = np.random.default_rng(SEED)
show_idx = np.r_[np.flatnonzero(y == 1), rng.choice(np.flatnonzero(y == 0), 4000,
replace=False)]
top = cv.head(13).index.tolist()
plot_data = filled.iloc[show_idx][top]
for group in [range(0, 7), range(7, 13)]:
    fig, axes = plt.subplots(13, len(group), figsize=(8.5, 10), squeeze=False)
    fig.subplots_adjust(left=.13, right=.99, top=.90, bottom=.03, hspace=.12, wspa
ce=.12)
    for i in range(13):
        for col, j in enumerate(group):
            ax = axes[i, col]
```

```
            if i > j:
                for label, color in [(0, 'tab:blue'), (1, 'tab:orange')]:
                    mask = y[show_idx] == label
                    ax.scatter(plot_data.iloc[mask, j], plot_data.iloc[mask, i], c
=color, s=1, alpha=.25, rasterized=True)
                ax.set_xscale('symlog', linthresh=1); ax.set_yscale('symlog', lint
hresh=1)
            else:
                ax.set_axis_off()
            ax.set_xticks([]); ax.set_yticks([])
    for col, j in enumerate(group):
        fig.text(.13+(col+.5)*.86/len(group), .915, top[j], ha='center', va='botto
m', fontsize=9, rotation=45)
    for i, name in enumerate(top):
        fig.text(.12, .90-(i+.5)*.87/13, name, ha='right', va='center', fontsize=9
)
    fig.suptitle('Top 13 CV features: pairwise scatter (blue negative, orange posi
tive)', fontsize=10, y=.99)
    plt.show()
fig, axes = plt.subplots(4, 4, figsize=(8, 7))
for i, name in enumerate(top):
    ax = axes.flat[i]
    ax.boxplot([filled.loc[y == 0, name], filled.loc[y == 1, name]], showfliers=Fa
lse, tick_labels=['neg', 'pos'])
    ax.set_title(name, fontsize=9)
    ax.tick_params(labelsize=8)
for ax in axes.flat[13:]: ax.axis('off')
fig.suptitle('Top 13 CV features by class (box plots omit outlier markers)')
plt.tight_layout(); plt.show()
display(Markdown('For example, `cs_009` is zero for 56,148/59,000 negatives (95.17
%) and 948/1,000 positives (94.8%) after imputation, so those observations overlap
 on that feature. Scatter plots can reveal separation but cannot establish statist
ical significance without uncertainty or a formal test. They show all 1,000 positi
ves and 4,000 sampled negatives; models use all data.'))
```


Top 13 CV features: pairwise scatter (blue negative, orange positive)
cf_000
co_000
ad_000
cs_009
dh_000
dj_000
ag_000
as_000
ay_009
ak_000
az_009
ch_000
au_000


Top 13 CV features: pairwise scatter (blue negative, orange positive)
as_000
ay_009
ak_000
az_009
ch_000
au_000
cf_000
co_000
ad_000
cs_009
dh_000
dj_000
ag_000
as_000
ay_009
ak_000
az_009
ch_000
au_000



For example, `cs_009` is zero for 56,148/59,000 negatives (95.17%) and 948/1,000 positives (94.8%) after imputation, so those observations overlap on that feature. Scatter plots can reveal separation but cannot establish statistical significance without uncertainty or a formal test. They show all 1,000 positives and 4,000 sampled negatives; models use all data.

1(c)–(d) Random forests

A class-weighted forest gives minority-class classification errors greater weight in each split. We use `class_weight="balanced"`, which weights each class inversely to its training frequency. Both forests use the same 50 trees and all observations; out-of-bag (OOB) error uses predictions from trees that did not bootstrap the observation. scikit-learn RandomForestClassifier documentation.

```
models = {}
for name, weight in [('RF', None), ('Weighted RF', 'balanced')]:
    model = RandomForestClassifier(n_estimators=50, n_jobs=4, random_state=SEED,
                                   oob_score=True, class_weight=weight)
    model.fit(X, y)
```

```
    models[name] = model
    print(f'{name}: OOB error = {1-model.oob_score_:.5f}')
```

```
RF: OOB error = 0.00615
Weighted RF: OOB error = 0.01990
```

1(e)–(f) XGBoost and SMOTE

We select `reg_alpha` from {0, 1, 10} using five-fold stratified CV and misclassification error. XGBoost's `gbtree` is the tree-based alternative specified in 1(e); its L1 penalty applies to leaf weights, so it is not a logistic regression model at each node. For SMOTE, interpolation is done **only on the training part of each fold** before fitting; validation observations are never oversampled. Features are standardized using each training fold before SMOTE distance calculations, then returned to their original units. Resampling the full data before CV would leak synthetic information across folds. The final SMOTE model uses the entire 60,000-row training set. References: XGBoost parameters, imbalanced-learn common pitfalls.

```
alphas = [0, 1, 10]
folds = StratifiedKFold(n_splits=5, shuffle=True, random_state=SEED)
cv_errors = {'XGB': {a: [] for a in alphas}, 'SMOTE XGB': {a: [] for a in alphas}}

def xgb(alpha):
    return XGBClassifier(n_estimators=50, max_depth=4, learning_rate=.1,
                         reg_alpha=alpha, objective='binary:logistic',
                         eval_metric='logloss', tree_method='hist',
                         random_state=SEED, n_jobs=4)
for fold, (itr, iva) in enumerate(folds.split(X_raw, y), 1):
    imp = SimpleImputer(strategy='median')
    xf = imp.fit_transform(X_raw.iloc[itr]).astype(np.float32)
    xv = imp.transform(X_raw.iloc[iva]).astype(np.float32)
    yf, yv = y[itr], y[iva]
    scaler = StandardScaler().fit(xf)
    xs, ys = SMOTE(random_state=SEED).fit_resample(scaler.transform(xf), yf)
    xs = scaler.inverse_transform(xs)
    for a in alphas:
        for name, xx, yy in [('XGB', xf, yf), ('SMOTE XGB', xs, ys)]:
            model = xgb(a); model.fit(xx, yy)
            cv_errors[name][a].append(1 - accuracy_score(yv, model.predict(xv)))
    print(f'Completed CV fold {fold}/5', flush=True)
    del xs, ys, xf, xv
cv_table = pd.DataFrame({name: {a: np.mean(v) for a, v in row.items()} for name, r
ow in cv_errors.items()})
cv_table.index.name = 'alpha'
display(cv_table.round(5))
selected = cv_table.idxmin()
print('Selected alpha:', selected.to_dict())
models['XGB'] = xgb(float(selected['XGB'])); models['XGB'].fit(X, y)
scaler = StandardScaler().fit(X)
Xs, ys = SMOTE(random_state=SEED).fit_resample(scaler.transform(X), y)
Xs = scaler.inverse_transform(Xs)
print('Full SMOTE training counts:', dict(zip(*np.unique(ys, return_counts=True)))
)
models['SMOTE XGB'] = xgb(float(selected['SMOTE XGB'])); models['SMOTE XGB'].fit(X
s, ys)
del Xs, ys
```


```
Completed CV fold 1/5
Completed CV fold 2/5
Completed CV fold 3/5
```

```
Completed CV fold 4/5
Completed CV fold 5/5
```

	XGB	SMOTE XGB
alpha		
0	0.00777	0.02558
1	0.00773	0.02582
10	0.00882	0.02663

```
Selected alpha: {'XGB': 1, 'SMOTE XGB': 0}
Full SMOTE training counts: {np.int64(0): np.int64(59000), np.int64(1): np.int64(5
9000)}
```

```
results = []
fig, axes = plt.subplots(1, 2, figsize=(10, 4.2))
for name, model in models.items():
    for split, values, target, ax in [('Train', X, y, axes[0]), ('Test', T, yt, ax
es[1])]:
        pred = model.predict(values)
        prob = model.predict_proba(values)[:,1]
        tn, fp, fn, tp = confusion_matrix(target, pred, labels=[0,1]).ravel()
        auc = roc_auc_score(target, prob)
        error = 1-accuracy_score(target, pred)
        results.append([name, split, tn, fp, fn, tp, auc, error])
        fpr, tpr, _ = roc_curve(target, prob)
        ax.plot(fpr, tpr, label=f'{name} (AUC {auc:.3f})')
for ax, title in zip(axes, ['Training ROC', 'Test ROC']):
    ax.plot([0,1], [0,1], 'k--', lw=.6); ax.set(xlabel='False positive rate', ylab
el='True positive rate', title=title)
    ax.legend(fontsize=7)
plt.tight_layout(); plt.show()
metrics = pd.DataFrame(results, columns=['Model','Split','TN','FP','FN','TP','AUC'
,'Error']).set_index(['Model','Split'])
display(metrics.round(5))
print('Each confusion matrix is [[TN, FP], [FN, TP]]; error is (FP + FN)/total.')
r = metrics.loc[('RF','Test')]; w = metrics.loc[('Weighted RF','Test')]
display(Markdown(f"**1(c)–(d).** RF OOB error {1-models['RF'].oob_score_:.4f} vs t
est error {r.Error:.4f}; weighted RF OOB error {1-models['Weighted RF'].oob_score_
:.4f} vs test error {w.Error:.4f}. The weighted forest has {int(w.FN)} false negat
ives and {int(w.FP)} false positives, versus {int(r.FN)} and {int(r.FP)} for the u
nweighted forest; its test AUC is {w.AUC:.4f} versus {r.AUC:.4f}."))
a = metrics.loc[('XGB','Test')]; b = metrics.loc[('SMOTE XGB','Test')]
display(Markdown(f"**1(e)–(f).** Uncompensated XGBoost selected alpha {selected['X
GB']} with CV error {cv_table.loc[selected['XGB'],'XGB']:.4f} and test error {a.Er
ror:.4f}; SMOTE XGBoost selected alpha {selected['SMOTE XGB']} with CV error {cv_t
able.loc[selected['SMOTE XGB'],'SMOTE XGB']:.4f} and test error {b.Error:.4f}. On
test data, SMOTE changes false negatives from {int(a.FN)} to {int(b.FN)}, false po
sitives from {int(a.FP)} to {int(b.FP)}, and AUC from {a.AUC:.4f} to {b.AUC:.4f}."
))
```



		TN	FP	FN	TP	AUC	Error
Model	**Split**						
RF	**Train**	59000	0	4	996	1.00000	0.00007
	Test	15609	16	112	263	0.99062	0.00800
Weighted RF	**Train**	58980	20	0	1000	1.00000	0.00033
	Test	15569	56	100	275	0.99267	0.00975
XGB	**Train**	58938	62	238	762	0.99552	0.00500
	Test	15602	23	120	255	0.99481	0.00894
SMOTE XGB	**Train**	57506	1494	44	956	0.99311	0.02563
	Test	15188	437	19	356	0.99157	0.02850

`Each confusion matrix is [[TN, FP], [FN, TP]]; error is (FP + FN)/total.`

1(c)–(d). RF OOB error 0.0061 vs test error 0.0080; weighted RF OOB error 0.0199 vs test error 0.0098. The weighted forest has 100 false negatives and 56 false positives, versus 112 and 16 for the unweighted forest; its test AUC is 0.9927 versus 0.9906.

1(e)–(f). Uncompensated XGBoost selected alpha 1 with CV error 0.0077 and test error 0.0089; SMOTE XGBoost selected alpha 0 with CV error 0.0256 and test error 0.0285. On test data, SMOTE changes false negatives from 120 to 19, false positives from 23 to 437, and AUC from 0.9948 to 0.9916.

2. ISLR 6.6.3

(a) **iv**: training RSS is nonincreasing as the L1 constraint expands. (b) **ii**: test RSS typically falls then rises as bias decreases and variance increases. (c) **iii**: variance generally increases. (d) **iv**: squared bias generally decreases. (e) **v**: irreducible error remains constant. These describe the usual bias–variance pattern, not a guaranteed test curve for every dataset.

3. ISLR 6.6.5

Let $X_{11} = X_{12} = a$, $X_{21} = X_{22} = -a$, $y_1 = b$, and $y_2 = -b$, with zero intercept.

(a) Ridge minimizes $2[b - a(\beta_1 + \beta_2)]^2 + \lambda(\beta_1^2 + \beta_2^2)$.

(b) For a fixed sum $t = \beta_1 + \beta_2$, the penalty equals $t^2/2 + (\beta_1 - \beta_2)^2/2$, so for $\lambda > 0$ it is uniquely minimized at $\beta_1 = \beta_2$.

(c) Lasso minimizes $2[b - a(\beta_1 + \beta_2)]^2 + \lambda(|\beta_1| + |\beta_2|)$.

(d) For a nonzero optimal sum t^*, every same-sign split summing to t^* has the same RSS and minimum penalty $|t^*|$, yielding infinitely many solutions. If $t^* = 0$ and $\lambda > 0$, only $(0, 0)$ minimizes the penalty.

4. ISLR 8.4.5


Six of ten probabilities exceed 0.5, so majority vote predicts **Red** (6–4). The mean probability is $4.5/10 = 0.45$, so averaging probabilities predicts **Green**.

5. ISLR 9.7.3

(a) The observations are plotted below. (b) The maximum-margin separator is $x_2 = x_1 - 0.5$. (c) Predict Red if $0.5 - x_1 + x_2 > 0$, Blue otherwise; $(\beta_0, \beta_1, \beta_2) = (0.5, -1, 1)$. (d) The margins are $x_2 = x_1$ and $x_2 = x_1 - 1$, at distance $1/(2\sqrt{2})$ from the separator. (e) Support vectors are Red $(2, 2), (4, 4)$ and Blue $(2, 1), (4, 3)$.

(f) The Blue point $(4, 1)$ lies strictly outside the margin, so a sufficiently small movement does not change the separator. (g) $x_2 = x_1 - 0.25$ also separates the data but has a smaller margin. (h) A new Blue point $(3, 3)$ lies on the segment between the Red points $(2, 2)$ and $(4, 4)$, making linear separation impossible.

```
red = np.array([[3,4],[2,2],[4,4],[1,4]])
blue = np.array([[2,1],[4,3],[4,1]])
xline = np.linspace(.5, 4.5, 100)
fig, ax = plt.subplots(figsize=(5.5, 4.5))
ax.scatter(*red.T, color='red', label='Red'); ax.scatter(*blue.T, color='blue', la
bel='Blue')
ax.plot(xline, xline-.5, 'k-', label='Maximum-margin boundary')
ax.plot(xline, xline, 'k--', lw=.8, label='Margins')
ax.plot(xline, xline-1, 'k--', lw=.8)
ax.plot(xline, xline-.25, color='green', ls=':', label='Alternative boundary')
ax.scatter([3], [3], marker='x', color='blue', s=65, label='Added blue point (h)')
ax.set(xlim=(.5,4.5), ylim=(.5,4.5), xlabel='$X_1$', ylabel='$X_2$', title='ISLR 9
.7.3'); ax.set_aspect('equal'); ax.legend(fontsize=7)
plt.tight_layout(); plt.show()
```


ISLR 9.7.3
Red
Blue
Maximum-margin boundary
Margins
Alternative boundary
Added blue point (h)
4.5
4.0
3.5
3.0
2.5
2.0
1.5
1.0
0.5
X_2
0.5
1.0
1.5
2.0
2.5
3.0
3.5
4.0
4.5
X_1