

Turing Machines

Prof. Shrisha Rao
IIIT Bangalore

srao@iiitb.ac.in

2025-09-09

TURING MACHINES

- We have seen that DFAs/NFAs accept regular languages, and PDAs accept context-free languages. We can thus wonder what type of machine can accept context-sensitive and other languages.
- The difference between finite automata and pushdown automata is only in the stack, which is a limited form of storage. By replacing this with a better form of storage, we get a more powerful type of machine.
- In place of a stack, consider an infinite read-write tape divided into cells, each of which can contain a single symbol.
- A machine of this type is known as a *Turing machine*, named after Alan Turing.

CHURCH-TURING THESIS AND TURING COMPLETENESS

- A Turing machine (TM) is the ultimate type of computing device that anyone has been able to describe. (There is no known type of computing abstraction beyond it.)
- The *Church-Turing Thesis* (due to Alonzo Church) is the accepted thesis (belief) that a TM is the ultimate computing device; our intuitive notion of “computability” is the same as saying that something is computable by a TM.
- Any other computing abstraction (e.g., two-stack PDA, partial recursive functions, λ calculus) that can be designed is at best as good as a TM.
- A computing abstraction (or even a programming language) is called *Turing complete* if it has the full expressive power of a TM.


FORMAL DEFINITION OF A TURING MACHINE

- A Turing machine is a 6-tuple $\langle Q, \Sigma, \Gamma, \delta, q_0, F \rangle$, where $Q, \Sigma, \delta, q_0, F$ are all as before, and Γ is a special *tape alphabet* of symbols written on the tape.
- Instead of a stack push/pop as with a PDA, a TM has a R/W head that can read a symbol from the tape at the current position, write a symbol on to the tape at the current position, or move one cell to the left or right.
- The tape alphabet Γ is a superset of the input alphabet Σ , especially containing the blank tape symbol Δ . (A cell on the tape is blank if it contains Δ .)
- The transition function $\delta : Q \times \Gamma \longrightarrow Q \times \Gamma \times \{L, R, S\}$ indicates the state change and possible tape head movement.

TRANSITION FUNCTION OF A TM

All inputs to a TM are written on the tape, which also is how the TM provides its output. At each step, a TM:

- Reads a symbol from the current tape cell.
- Writes a symbol on to the current tape cell.
- Moves left or right one cell, or stays in the same cell.
- Updates its state.




Schematic of a TM tape and head

DRAWING A TM

As previously, a TM can be shown by a bubble diagram, but the labels on the arrows have three values:

oldSymbol newSymbol moveDirection



A TM TO ACCEPT $\{0^n 1^n\}$


If $0^k 1^k$ is written on the tape for some k , then the idea is for the TM to successively erase the first 0 and the last 1, and keep doing this. If this ends with the tape blank, the TM accepts, else it rejects.

Exercise: give a pseudocode description of this approach.

PSEUDOCODE FOR $\{0^n 1^n\}$

- (i) If symbol read is 0, then write Δ (erase), else reject.
- (ii) Move head right until symbol read is Δ .
- (iii) Move head one step left. If symbol read is 1, write Δ , else reject.
- (iv) Move head left until symbol read is Δ . Move head one step right. If symbol read is Δ then accept.
- (v) Goto step (i).

TM FOR $\{0^n 1^n\}$



EXERCISES

Come up with TMs for the following languages:

- (1) The language $\{0^n 1^{2^n} \mid n \geq 0\}$. Show the operation of the TM for the strings 001111 and 00011.
- (2) The language of all balanced brackets over the alphabet $(,.)$. Show the operation of the TM for the strings $((()))$ and $((()))(($.
- (3) All strings of the form $\{0^n 1^n 2^n \mid n \geq 0\}$. Show the operation of the TM for $0^2 1^2 2^2$ and $0^2 1^3 2^2$.

For these exercises, come up with the TM logic and pseudocode first, and then only draw the diagram.

TURING MACHINES AS CALCULATORS

- So far we have looked at machines only as *language acceptors*, i.e., as devices that can accept or reject particular languages.
- A TM can also function as a *calculator* that processes numerical inputs and produces an output.
- By the Church-Turing thesis, any computable function that can be processed on any device in any manner whatsoever can be handled by a TM.

GIVING INPUTS TO A TURING MACHINE

- As before, inputs to a Turing Machine are written on the tape at the outset.
- A TM can only accept natural numbers (zero and the positive integers) as inputs. (NB. This restriction applies in the natural setting to electronic calculators, CPUs, etc., also.)
- In case of multiple inputs to be given (e.g., two numbers), the same are written on the TM tape in sequence with a Δ in between.
- As before, it is presumed that the TM head starts its execution at the leftmost nonblank symbol on the tape.

UNARY ALPHABET

- To represent natural numbers on the tape, we use a *unary* (not binary) alphabet, with 1 being the only symbol.
- In this alphabet, a single 1 stands for the natural number 0, 11 stands for 1, and a natural number $n > 1$ is represented by 1^{n+1} , i.e., a sequence of $n + 1$ 1s.

THE SIMPLEST POSSIBLE TM CALCULATION

- Problem: Create a TM which adds 1 to a number it is given as input.
- Solution: Assume that 1^k is written on the tape, for some $k > 0$. The TM should add a single 1 to the string, to leave 1^{k+1} on the tape.

MORE REALISTIC ADDITION

- Problem: Consider a TM that is given natural numbers m and n . It is to add them to get the natural number $m + n$.
- Solution: Note that m is given in unary alphabet by 1^{m+1} and n is given by 1^{n+1} . Therefore the tape reads $1^{m+1}\Delta 1^{n+1}$ at the outset. The TM should leave the tape with 1^{m+n+1} at the end of its execution.
- It can do this by overwriting the Δ in the middle with a 1, and then deleting two 1s from either the beginning or the end of the combined string.
- Example: If starting with $111\Delta 111$ on the tape (representing 2, 2, the numbers to be added), overwrite the Δ with 1 first to get 1111111 , then remove two 1s to get 11111 , the final answer (representing 4).
- Addition of three or more numbers is handled in the same way, sequentially.

MULTIPLICATION BY 2 IS ADDITION WITH ITSELF

- Once we are able to get TMs to add two or more numbers, we can take on the next step of getting a TM to multiply two natural numbers.
- Problem: Given a number m in unary alphabet on the tape, compute $2m$.
- Solution: The tape reads 1^{m+1} to start with. It should be left with 1^{2m+1} . The best approach is to first repeat the first number m on the tape leaving a blank in between (change the tape to $1^{m+1}\Delta 1^{m+1}$), and then add up as previously.

EXERCISES

- (4) Give a TM that adds 3 to any number given to it as input.
- (5) Prove that the function $\lfloor \frac{x}{2} \rfloor$ is Turing computable, by giving a TM that computes it.