


Q1: In this direct mapped cache, each block contains 64 bytes or 16 words.  
How many bits does the following contain:

- Byte offset
- Index
- Tag



Address

Tag	Index	Offset
-----	-------	--------

Direct mapped cache

	V	Tag	Data0	Data1	Data2	Data3
0	1	0x000004	0x412C1232	0x41111234	0x11241239	0x412C1111
1	1	0xCC3003	0x002C12AB	0x00111235	0x00011238	0x412C1000
2	0	0xAA4004	0x41AC1200	0x41100237	0x115411255	0x412C1133
3	1	0x500001	0x002AAA38	0x001112AA	0x00011222	0x412C1000
4	1	0xA57000	0xAAAC1232	0x41111234	0x11111230	0x412C1BB
5	1	0x000200	0xCA1C1238	0xCC111235	0x030100234	0x412C10A4
15						

32  
↓

32  
↓

32  
↓

32  
↓

Q2 Consider a direct mapped cache which uses 4-word blocks, 32-bit data words (4 bytes) and 32-bit addresses.

Say you are trying to read data from memory location 0x00020013. Assume you are reading the bytes individually. What would be the:

Tag field value

Offset value

The cache line or block in which the data should be found

Is it a cache hit? If yes, what is the data that is read assuming a byte read?

Address

Tag	Index	Offset
-----	-------	--------

Direct mapped cache

	V	Tag	Data0	Data1	Data2	Data3
0	1	0x000004	0x412C1232	0x41111234	0x11241239	0x412C1111
1	1	0xCC3003	0x002C12AB	0x00111235	0x00011238	0x412C1000
2	0	0xAA4004	0x41AC1200	0x41100237	0x115411255	0x412C1133
3	1	0x500001	0x002AAA38	0x001112AA	0x00011222	0x412C1000
4	1	0xA57000	0xAAAC1232	0x41111234	0x11111230	0x412C1BB
5	1	0x000200	0xCA1C1238	0xCC111235	0x030100234	0x412C10A4
15						

32  
↓

32  
↓

32  
↓

32  
↓

Q3 Consider a direct mapped cache which uses 4-word blocks, 32-bit data words (4 bytes) and 32-bit addresses.

Say you are trying to read data from memory location 0x00020053. Assume you are reading the bytes individually. What would be the:

Is it a cache hit? If yes, what is the data that is read assuming a byte read?

Address

Tag	Index	Offset
-----	-------	--------

Direct mapped cache

	V	Tag	Data0	Data1	Data2	Data3
0	1	0x000004	0x412C1232	0x41111234	0x11241239	0x412C1111
1	1	0xCC3003	0x002C12AB	0x00111235	0x00011238	0x412C1000
2	0	0xAA4004	0x41AC1200	0x41100237	0x115411255	0x412C1133
3	1	0x500001	0x002AAA38	0x001112AA	0x00011222	0x412C1000
4	1	0xA57000	0xAAAC1232	0x41111234	0x11111230	0x412C1BB
5	1	0x000200	0xCA1C1238	0xCC111235	0x030100234	0x412C10A4
15						

32  
↓

32  
↓

32  
↓

32  
↓

Q4

Consider a direct mapped cache which uses 4-word blocks, 32-bit data words (4 bytes) and 32-bit addresses.

Can data from locations 0x00012329 and 0x00322FF9 be present in the cache at the same time? Explain.

Q5: This is a 2 way set associative cache whose index number, tag and data are shown in the following table.

The address we obtain is:

1010 1010 0100 11 0111 0000

Assume no byte offset. What is the data fetched, if it is a cache hit?

Tag (14 bits)	Index or Set ID	Data
10100001001001	01101101	00 <sub>16</sub>
11100001100100	01101101	10 <sub>16</sub>
11001011010110	01101110	20 <sub>16</sub>
11100101101011	01101110	30 <sub>16</sub>
11110110110100	01101111	40 <sub>16</sub>
10100111010101	01101111	50 <sub>16</sub>
10101010111110	01110000	84 <sub>16</sub>
10101010010011	01110000	94 <sub>16</sub>
01110001001000	01110001	A4 <sub>16</sub>
00001101101101	01110001	B4 <sub>16</sub>
01011010010010	01110010	C4 <sub>16</sub>
10101111001011	01110010	D4 <sub>16</sub>

## Q6

- Show the hits and misses and final cache contents for a fully associative cache with four-word blocks and a total size of 8 words. Assume LRU replacement.
  - Assume the sequence: 2,3,10,11,16,21,0